MenpoFit Documentation

Release 0.5.0

Joan Alabort-i-Medina, Epameinondas Antonakos, James Booth,

May 05, 2017

Contents

1	User	Guide	3
	1.1	Quick Start	3
	1.2	Introduction	4
	1.3	Building Models	5
	1.4	Fitting Models	6
	1.5	Fitting Result	7
	1.6	Visualizing Objects	8
	1.7	References	9
2	The N	MenpoFit API	11
	2.1	Deformable Models	11
	2.2	Internal API) 1

Welcome to the MenpoFit documentation!

MenpoFit is a Python package for building, fitting and manipulating deformable models. It includes state-of-the-art deformable modelling techniques implemented on top of the **Menpo** project. Currently, the techniques that have been implemented include:

- Active Appearance Model (AAM)
 - Holistic, Patch-based, Masked, Linear, Linear Masked
 - Lucas-Kanade Optimisation
 - Cascaded-Regression Optimisation
- Active Pictorial Structures (APS)
 - Weighted Gauss-Newton Optimisation with fixed Jacobian and Hessian
- Active Template Model (ATM)
 - Holistic, Patch-based, Masked, Linear, Linear Masked
 - Lucas-Kanade Optimisation
- Lucas-Kanade Image Alignment (LK)
 - Forward Additive, Forward Compositional, Inverse Compositional
 - Residuals: SSD, Fourier SSD, ECC, Gradient Correlation, Gradient Images
- Unified Active Appearance Model and Constrained Local Model (Unified AAM-CLM)
 - Alternating/Project Out with Regularised Landmark Mean Shift
- Constrained Local Model (CLM)
 - Active Shape Model
 - Regularised Landmark Mean Shift
- Ensemble of Regression Trees (ERT) [provided by DLib]
- Supervised Descent Method (SDM)
 - Non Parametric
 - Parametric Shape
 - Parametric Appearance
 - Fully Parametric

Please see the to *References* for an indicative list of papers that are relevant to the methods implemented in MenpoFit.

CHAPTER 1

User Guide

The User Guide is designed to give you an overview of the key concepts within MenpoFit. In particular, we want to try and explain some of the design decisions that we made and demonstrate why we think they are powerful concepts for building, fitting and analysing deformable models.

Quick Start

Here we give a very quick rundown of the basic links and information sources for the project.

Basic Installation

In the Menpo Team, we **strongly** advocate the usage of conda for scientific Python, as it makes installation of compiled binaries much more simple. In particular, if you wish to use any of the related Menpo projects such as *menpofit*, *menpo3d* or *menpodetect*, you will not be able to easily do so without using conda. The installation of MenpoFit using conda is as easy as

\$ conda install -c menpo menpofit

Conda is able to work out all the requirements/dependencies of MenpoFit. You may for example notice that *menpo* is one of them. Please see the thorough installation instructions for each platform on the Menpo website.

API Documentation

Visit API Documentation

MenpoFit is extensively documented on a per-method/class level and much of this documentation is reflected in the API Documentation. If any functions or classes are missing, please bring it to the attention of the developers on Github.

Notebooks

Explore the Menpo and MenpoFit Notebooks

For a more thorough set of examples, we provide a set of Jupyter notebooks that demonstrate common use cases of MenpoFit. The notebooks include extensive examples regarding all the state-of-the-art deformable models that we provide. You may need to have a look at the Menpo notebooks in order to get an overview of the basic functionalities required by MenpoFit.

User Group and Issues

If you wish to get in contact with the Menpo developers, you can do so via various channels. If you have found a bug, or if any part of MenpoFit behaves in a way you do not expect, please raise an issue on Github.

If you want to ask a theoretical question, or are having problems installing or setting up MenpoFit, please visit the user group.

Introduction

This user guide is a general introduction to MenpoFit, aiming to provide a bird's eye of MenpoFit's design. After reading this guide you should be able to go explore MenpoFit's extensive Notebooks and not be too surprised by what you see.

What makes MenpoFit better?

The vast majority of **existing deformable modeling software** suffers from one or more of the following important issues:

- It is released in binary closed-source format
- It does not come with training code; only pre-trained models
- It is not well-structured which makes it very difficult to tweak and alter
- It only focuses on a single method/model

MenpoFit overcomes the above issues by providing open-source *training* and *fitting* code for multiple state-of-the-art deformable models under a unified protocol. We **strongly** believe that this is the only way towards reproducable and high-quality research.

Core Interfaces

MenpoFit is an object oriented framework for building and fitting deformable models. It makes some basic assumptions that are common for all the implemented methods. For example, all deformable models are trained in *multiple scales* and the fitting procedure is, in most cases, *iterative*. MenpoFit's key interfaces are:

- MultiScaleNonParametricFitter multi-scale fitting class
- *MultiScaleParametricFitter* multi-scale fitting class that uses a parametric shape model
- MultiScaleNonParametricIterativeResult multi-scale result of an iterative fitting
- *MultiScaleParametricIterativeResult* multi-scale result of an iterative fitting using a parametric shape model

Deformable Models

- AAM, LucasKanadeAAMFitter, SupervisedDescentAAMFitter Active Appearance Model builder and fitters
- ATM, LucasKanadeATMFitter Active Template Model builder and fitter
- GenerativeAPS, GaussNewtonAPSFitter Active Pictorial Structures builder and fitter
- CLM, GradientDescentCLMFitter Constrained Local Model builder and fitter
- LucasKanadeFitter Lucas-Kanade Image Alignment
- SupervisedDescentFitter Supervised Descent Method builder and fitter
- DlibERT Ensemble of Regression Trees builder and fitter

Building Models

All MenpoFit's models are built in a **multi-scale** manner, i.e. in multiple resolutions. In all our core classes, this is controlled using the following three parameters:

- **reference_shape** (*PointCloud*) First, the size of the training images is normalized by rescaling them so that the scale of their ground truth shapes matches the scale of this reference shape. In case no reference shape is provided, then the mean of the ground shapes is used. This step is essential in order to ensure consistency between the extracted features of the images.
- **diagonal** (*int*) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. This rescaling takes place before normalizing the training images' size. Thus, *diagonal* controls the size of the model at the highest scale.
- **scales** (*tuple* of *float*) A *tuple* with the scale value at each level, provided in ascending order, i.e. from lowest to highest scale. These values are proportional to the final resolution achieved through the reference shape normalization.

Additionally, all models have a **holistic_features** argument which expects the *callable* that will be used for extracting features from the training images.

Given the above assumptions, an example of a typical call for building a deformable model using HolisticAAM is:

Information about any kind of model can be retrieved by:

print (aam)

The next section (*Fitting*) explains the basics of fitting such a deformable model.

Fitting Models

Fitter Objects

MenpoFit has specialised classes for performing a fitting process that are called *Fitters*. All *Fitter* objects are subclasses of *MultiScaleNonParametricFitter* and *MultiScaleParametricFitter*. The main difference between those two is that a *MultiScaleParametricFitter* optimises over the parameters of a statistical shape model, whereas *MultiScaleNonParametricFitter* optimises directly the coordinates of a shape.

Their behaviour can differ depending on the deformable model. For example, a Lucas-Kanade AAM fitter (*LucasKanadeAAMFitter*) assumes that you have trained an AAM model (assume the *aam* we trained in the *Building* section) and can be created as:

The constructor of the *Fitter* will set the active shape and appearance components based on *n_shape* and *n_appearance* respectively, and will also perform all the necessary pre-computations based on the selected algorithm.

However, there are deformable models that are directly defined through a *Fitter* object, which is responsible for training the model as well. *SupervisedDescentFitter* is a good example. The reason for that is that the fitting process is utilised during the building procedure, thus the functionality of a *Fitter* is required. Such models can be built as:

Information about a Fitter can be retrieved by:

print (fitter)

Fitting Methods

All the deformable models that are currently implemented in MenpoFit, which are the state-of-the-art approaches in current literature, aim to find a *local optimum* of the cost function that they try to optimise, given an initialisation. The initialisation can be seen as an initial estimation of the target shape. MenpoFit's *Fitter* objects provide two functions for fitting the model to an image:

or

They only differ on the type of initialisation. fit_from_shape expects a *PointCloud* as the *initial_shape*. On the other hand, the *bounding_box* argument of fit_from_bb is a *PointDirectedGraph* of 4 vertices that represents the initial bounding box. The bounding box is used in order to align the model's reference shape and use the resulting

PointCloud as the initial shape. Such a bounding box can be retrieved using the detection methods of **menpodetect**. The rest of the options are:

- max_iters (*int* or *list* of *int*) Defines the maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then it specifies the maximum number of iterations per scale. Note that this does not apply on all deformable models. For example, it can control the number of iterations of a Lucas-Kanade optimisation algorithm, but it does not affect the fitting of a cascaded-regression method (e.g. SDM) which has a predefined number of cascades (iterations).
- **gt_shape** (*PointCloud* or *None*) The ground truth shape associated to the image. This is *only* useful to compute the final fitting error. It is *not* used, of course, at any internal stage of the optimisation.
- **return_costs** (*bool*) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned *fitting_result*. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Thus, this option should only be used for research purposes. Finally, this argument does not apply to all deformable models.

kwargs (dict) Additional keyword arguments that can be passed to specific models.

The next section (*Result*) presents the basics of the fitting result.

Fitting Result

Objects

The fitting methods of the *Fitters* presented in the previous section return a result object. MenpoFit has three basic fitting result objects:

- *Result* : Basic fitting result object that holds the final shape, and optionally, the initial shape, ground truth shape and the image.
- *MultiScaleNonParametricIterativeResult*: The result of a multi-scale iterative fitting procedure. Apart from the final shape, it also stores the shapes acquired at each fitting iteration.
- *MultiScaleParametricIterativeResult*: The same as *MultiScaleNonParametricIterativeResult* with the difference that the optimisation was performed over the parameters of a statistical parametric shape model. Thus, apart from the actual shapes, it also stores the shape parameters acquired per iteration. *Note that in this case, the initial shape that was provided by the user gets reconstructed using the shape model, i.e. it first gets projected in order to get the initial estimation of the shape parameters, and then gets reconstructed with those*. The resulting shape is then used as initialisation for the iterative fitting process.

Attributes

The above result objects can provide some very useful information regarding the fitting procedure. For example, the various shapes can be retrieved as:

result.final_shape The final shape of the fitting procedure.

result.initial_shape The initial shape of the fitting procedure that was provided by the user.

result.reconstructed_initial_shape The reconstruction of the initial shape that was used to initialise the fitting procedure. It only applies for *MultiScaleParametricIterativeResult*.

result.image The image on which the fitting procedure was applied.

result.gt_shape The ground truth shape associated to the image.

result.shapes The shapes acquired fitting iteration. It list of at each applies only on MultiScaleNonParametricIterativeResult and MultiScaleParametricIterativeResult.

result.costs() The cost values per iteration, if they were computed during fitting.

Also, a result can compute some error metrics, in case the *gt_shape* of the image exists:

result.final_error() The final fitting error.

result.initial_error() The initial fitting error.

result.errors() The list of errors acquired each fitting iteration. It at and MultiScaleNonParametricIterativeResult only applies on MultiScaleParametricIterativeResult.

Visualizing Objects

In Menpo, we take an opinionated stance that visualization is a key part of generating research on deformable models. Therefore, we tried to make the mental overhead of visualizing objects as low as possible.

We also took a strong step towards simple visualization by integrating some of our objects with visualization widgets for the Jupyter notebook. Remember that our widgets live on their own repository, called **menpowidgets**.

Visualizing Models

Without further ado, a quick example of visualising the AAM trained in the *Building* section with an interactive widget:

```
%matplotlib inline # This is only needed if viewing in a Jupyter notebook
aam.view_aam_widget()
```

Fig. 1.1: Figure 1: Example of visualizing an AAM using an interactive widget.

One can visualize the only the multi-scale shape models:

```
%matplotlib inline
aam.view_shape_models_widget()
```

or the appearance models:

```
%matplotlib inline
import menpo.io as mio
aam.view_appearance_models_widget()
```

The same visualization widgets can be found in other models, such as ATM, CLM etc.

Visualizing Fitting Result

The fitting result objects shown in *Building* can be easily visualized. Specifically, the initial and final shapes can be rendered as:

```
%matplotlib inline
result.view(render_initial_shape=True)
```

Similarly, the shapes acquired at each iteration can be visualized as:

%matplotlib inline
fr.view_iterations()

and the corresponding errors as:

```
%matplotlib inline
fr.plot_errors()
```

Finally, a fitting result can also be analysed through an interactive widget as:

```
%matplotlib inline
fr.view_widget()
```

Fig. 1.2: Figure 2: Example of visualizing the iterations of a fitting procedure using an interactive widget.

References

This is an indicative list of papers relevant to the methods that are implemented in MenpoFit. They are listed in alphabetical order of the first author's surname.

- 1. J. Alabort-i-Medina, and S. Zafeiriou. "A Unified Framework for Compositional Fitting of Active Appearance Models", arXiv:1601.00199.
- J. Alabort-i-Medina, and S. Zafeiriou. "Bayesian Active Appearance Models", IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2014.
- J. Alabort-i-Medina, and S. Zafeiriou. "Unifying Holistic and Parts-Based Deformable Model Fitting", IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2015.
- 4. E. Antonakos, J. Alabort-i-Medina, G. Tzimiropoulos, and S. Zafeiriou. *"Feature-based Lucas-Kanade and Active Appearance Models"*, IEEE Transactions on Image Processing, vol. 24, no. 9, pp. 2617-2632, 2015.
- 5. E. Antonakos, J. Alabort-i-Medina, G. Tzimiropoulos, and S. Zafeiriou. "HOG Active Appearance Models", IEEE International Conference on Image Processing (ICIP), 2014.
- E. Antonakos, J. Alabort-i-Medina, and S. Zafeiriou. "Active Pictorial Structures", IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2015.
- 7. A.B. Ashraf, S. Lucey, and T. Chen. "Fast Image Alignment in the Fourier Domain", IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2010.
- 8. A. Asthana, S. Zafeiriou, S. Cheng, and M. Pantic. "*Robust discriminative response map fitting with constrained local models*", IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2013.
- S. Baker, and I. Matthews. "Lucas-Kanade 20 years on: A unifying framework", International Journal of Computer Vision, vol. 56, no. 3, pp. 221-255, 2004.
- P.N. Belhumeur, D.W. Jacobs, D.J. Kriegman, and N. Kumar. "Localizing parts of faces using a consensus of exemplars", IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 35, no. 12, pp. 2930-2940, 2013.
- 11. D.S. Bolme, J.R. Beveridge, B.A. Draper, and Y.M. Lui. "Visual Object Tracking using Adaptive Correlation Filters", IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2010.
- T.F. Cootes, G.J. Edwards, and C.J. Taylor. "Active Appearance Models", IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 23, no. 6, pp. 681–685, 2001.

- 13. T.F. Cootes, and C.J. Taylor. "Active shape models-'smart snakes", British Machine Vision Conference (BMVC), 1992.
- 14. T.F. Cootes, C.J. Taylor, D.H. Cooper, and J. Graham. "Active Shape Models their training and application", Computer Vision and Image Understanding, vol. 61, no. 1, pp. 38-59, 1995.
- 15. D. Cristinacce, and T.F. Cootes. "Feature Detection and Tracking with Constrained Local Models", British Machine Vision Conference (BMVC), 2006.
- G.D. Evangelidis, and E.Z. Psarakis. "Parametric Image Alignment Using Enhanced Correlation Coefficient Maximization", IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 30, no. 10, pp. 1858-1865, 2008.
- 17. R. Gross, I. Matthews, and S. Baker. "Generic vs. person specific Active Appearance Models", Image and Vision Computing, vol. 23, no. 12, pp. 1080-1093, 2005.
- 18. V. Kazemi, and J. Sullivan. "One millisecond face alignment with an ' 'ensemble of regression trees", IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2014.
- 19. B.D. Lucas, and T. Kanade, "An iterative image registration technique with an application to stereo vision", International Joint Conference on Artificial Intelligence, 1981.
- 20. I. Matthews, and S. Baker. "Active Appearance Models Revisited", International Journal of Computer Vision, 60(2): 135-164, 2004.
- 21. G. Papandreou, and P. Maragos. "Adaptive and constrained algorithms for ' inverse compositional active appearance model fitting", IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2008.
- D. Ross, J. Lim, R.S. Lin, and M.H. Yang. "Incremental Learning for Robust Visual Tracking". International Journal on Computer Vision, vol. 77, no. 1-3, pp. 125-141, 2007.
- 23. J.M. Saragih, S. Lucey, and J.F. Cohn. "Deformable model fitting by regularized landmark mean-shift", International Journal of Computer Vision, vol. 91, no. 2, pp. 200–215, 2011.
- J.M. Saragih, and R. Goecke. "Learning AAM fitting through simulation", Pattern Recognition, vol. 42, no. 11, pp. 2628–2636, 2009.
- G. Tzimiropoulos, J. Alabort-i-Medina, S. Zafeiriou, and M. Pantic. "Active Orientation Models for Face Alignment in-the-wild", IEEE Transactions on Information Forensics and Security, Special Issue on Facial Biometrics in-the-wild, vol. 9, no. 12, pp. 2024-2034, 2014.
- 26. G. Tzimiropoulos, and M. Pantic. "Gauss-Newton Deformable Part Models for Face Alignment In-the-Wild", IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2014.
- 27. G. Tzimiropoulos, J. Alabort-i-Medina, S. Zafeiriou, and M. Pantic. "Generic Active Appearance Models Revisited", Asian Conference on Computer Vision, Springer, 2012.
- 28. G. Tzimiropoulos, M. Pantic. "Optimization problems for fast AAM fitting in-the-wild", IEEE International Conference on Computer Vision (ICCV), 2013.
- 29. G. Tzimiropoulos, S. Zafeiriou, and M. Pantic. "*Robust and efficient parametric face alignment*", IEEE International Conference on Computer Vision (ICCV), 2011.
- 30. G. Tzimiropoulos, S. Zafeiriou, and M. Pantic. "Subspace Learning from Image Gradient Orientations", IEEE Transactions on Pattern Analysis and Machine Intelligence. vol. 34, no. 12, pp. 2454-2466, 2012.
- 31. X. Xiong, and F. De la Torre. "Supervised descent method and its applications to face alignment", IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2013.

CHAPTER 2

The MenpoFit API

This section attempts to provide a simple browsing experience for the MenpoFit documentation. In MenpoFit, we use legible docstrings, and therefore, all documentation should be easily accessible in any sensible IDE (or IPython) via tab completion. However, this section should make most of the core classes available for viewing online.

Deformable Models

menpofit.aam

Active Appearance Model

AAM is a generative model that consists of a statistical parametric model of the shape and the appearance of an object. MenpoFit has several AAMs which differ in the manner that they compute the warp (thus represent the appearance features).

AAM

Bases: object

Class for training a multi-scale holistic Active Appearance Model. Please see the references for a basic list of relevant papers.

Parameters

•images (list of menpo.image.Image) – The list of training images.

- •group (*str* or None, optional) The landmark group that will be used to train the AAM. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.
- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •reference_shape (menpo.shape.PointCloud or None, optional) The reference shape that will be used for building the AAM. The purpose of the reference shape is to normalise the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.
- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •transform (subclass of DL and DX, optional) A differential warp transform object, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •max_shape_components (*int*, *float*, *list* of those or None, optional) The number of shape components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •max_appearance_components (*int*, *float*, *list* of those or None, optional) The number of appearance components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •verbose (bool, optional) If True, then the progress of building the AAM will be printed.
- •batch_size (*int* or None, optional) If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

References

appearance_reconstructions (*appearance_parameters*, *n_iters_per_scale*)

Method that generates the appearance reconstructions given a set of appearance parameters. This is to be combined with a *AAMResult* object, in order to generate the appearance reconstructions of a fitting procedure.

Parameters

- •appearance_parameters (*list* of (n_params,) *ndarray*) A set of appearance parameters per fitting iteration. It can be retrieved as a property of an *AAMResult* object.
- •n_iters_per_scale (*list* of *int*) The number of iterations per scale. This is necessary in order to figure out which appearance parameters correspond to the model of each scale. It can be retrieved as a property of a *AAMResult* object.
- **Returnsappearance_reconstructions** (*list* of *menpo.image.Image*) *List* of the appearance reconstructions that correspond to the provided parameters.

build_fitter_interfaces (sampling)

Method that builds the correct Lucas-Kanade fitting interface. It only applies in case you wish to fit the AAM with a Lucas-Kanade algorithm (i.e. *LucasKanadeAAMFitter*).

Parameterssampling (*list* of *int* or *ndarray* or None) – It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.

Returnsfitter_interfaces (*list*) – The *list* of Lucas-Kanade interface per scale.

increment (images, group=None, shape_forgetting_factor=1.0, appearance_forgetting_factor=1.0, verbose=False, batch_size=None)

Method to increment the trained AAM with a new set of training images.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •group (*str* or None, optional) The landmark group that will be used to train the AAM. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.
- •**shape_forgetting_factor** ([0.0, 1.0] *float*, optional) Forgetting factor that weights the relative contribution of new samples vs old samples for the shape model. If 1. 0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.
- •appearance_forgetting_factor ([0.0, 1.0] *float*, optional) Forgetting factor that weights the relative contribution of new samples vs old samples for the appearance model. If 1.0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.
- •verbose (*bool*, optional) If True, then the progress of building the AAM will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

instance (*shape_weights=None*, *appearance_weights=None*, *scale_index=-1*)

Generates a novel AAM instance given a set of shape and appearance weights. If no weights are provided, then the mean AAM instance is returned.

Parameters

•**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.

•appearance_weights ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the appearance model that will be used to create a novel appearance instance. If None, the weights are assumed to be zero, thus the mean appearance is used.

•scale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The AAM instance.

random_instance(scale_index=-1)

Generates a random instance of the AAM.

Parametersscale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The AAM instance.

view_aam_widget (n_shape_parameters=5, n_appearance_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure_size=(7, 7))

Visualizes the AAM using an interactive widget.

Parameters

•n_shape_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•n_appearance_parameters (*int* or *list* of *int* or None, optional) – The number of appearance principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

Visualizes the appearance models of the AAM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of appearance principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

view_shape_models_widget (n_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure_size=(7, 7))

Visualizes the shape models of the AAM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) – If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

n_scales

Returns the number of scales.

Type*int*

HolisticAAM

menpofit.aam.HolisticAAM alias of AAM

MaskedAAM

```
holistic_features=<function
class menpofit.aam.MaskedAAM (images,
                                               group=None,
                                                                                             no ob>.
                                    reference_shape=None,
                                                              diagonal=None,
                                                                                 scales = (0.5, 
                                                                                                1.0).
                                                                   shape_model_cls=<class</pre>
                                    patch_shape=(17,
                                                          17),
                                                                                                'men-
                                    pofit.modelinstance.OrthoPDM'>,
                                                                       max_shape_components=None,
                                                                                       verbose=False,
                                    max_appearance_components=None,
                                    batch size=None)
```

Bases: AAM

Class for training a multi-scale patch-based Masked Active Appearance Model. The appearance of this model is formulated by simply masking an image with a patch-based mask.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•group (*str* or None, optional) – The landmark group that will be used to train the AAM. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.

•holistic_features (*closure* or *list* of *closure*, optional) – The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.

•**reference_shape** (*menpo.shape.PointCloud* or None, optional) – The reference shape that will be used for building the AAM. The purpose of the reference shape is to normalise

the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.

- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •**patch_shape** ((*int*, *int*), optional) The size of the patches of the mask that is used to sample the appearance vectors.
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •max_shape_components (*int*, *float*, *list* of those or None, optional) The number of shape components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •max_appearance_components (*int*, *float*, *list* of those or None, optional) The number of appearance components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •verbose (bool, optional) If True, then the progress of building the AAM will be printed.
- •**batch_size** (*int* or None, optional) If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

appearance_reconstructions (*appearance_parameters*, *n_iters_per_scale*)

Method that generates the appearance reconstructions given a set of appearance parameters. This is to be combined with a *AAMResult* object, in order to generate the appearance reconstructions of a fitting procedure.

Parameters

•appearance_parameters (*list* of (n_params,) *ndarray*) – A set of appearance parameters per fitting iteration. It can be retrieved as a property of an *AAMResult* object.

•n_iters_per_scale (*list* of *int*) – The number of iterations per scale. This is necessary in order to figure out which appearance parameters correspond to the model of each scale. It can be retrieved as a property of a *AAMResult* object.

Returnsappearance_reconstructions (*list* of *menpo.image.Image*) – *List* of the appearance reconstructions that correspond to the provided parameters.

build_fitter_interfaces(sampling)

Method that builds the correct Lucas-Kanade fitting interface. It only applies in case you wish to fit the AAM with a Lucas-Kanade algorithm (i.e. *LucasKanadeAAMFitter*).

Parameterssampling (*list* of *int* or *ndarray* or None) – It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly

defines the sampling mask. If None, then no sub-sampling is applied.

Returnsfitter_interfaces (*list*) – The *list* of Lucas-Kanade interface per scale.

increment (images, group=None, shape_forgetting_factor=1.0, appearance_forgetting_factor=1.0, verbose=False, batch_size=None)

Method to increment the trained AAM with a new set of training images.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •group (*str* or None, optional) The landmark group that will be used to train the AAM. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.
- •**shape_forgetting_factor** ([0.0, 1.0] *float*, optional) Forgetting factor that weights the relative contribution of new samples vs old samples for the shape model. If 1. 0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.
- •appearance_forgetting_factor ([0.0, 1.0] *float*, optional) Forgetting factor that weights the relative contribution of new samples vs old samples for the appearance model. If 1.0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.

•verbose (*bool*, optional) – If True, then the progress of building the AAM will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

```
instance (shape_weights=None, appearance_weights=None, scale_index=-1)
```

Generates a novel AAM instance given a set of shape and appearance weights. If no weights are provided, then the mean AAM instance is returned.

Parameters

•**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.

•appearance_weights ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the appearance model that will be used to create a novel appearance instance. If None, the weights are assumed to be zero, thus the mean appearance is used.

•scale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The AAM instance.

random_instance(scale_index=-1)

Generates a random instance of the AAM.

Parametersscale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The AAM instance.

view_aam_widget (n_shape_parameters=5, n_appearance_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure_size=(7, 7)) Visualizes the AAM using an interactive widget.

8

Parameters

•n_shape_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•n_appearance_parameters (*int* or *list* of *int* or None, optional) – The number of appearance principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

Visualizes the appearance models of the AAM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of appearance principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•**parameters_bounds** ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) – If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

Visualizes the shape models of the AAM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•**parameters_bounds** ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter. •figure_size ((*int*, *int*), optional) – The size of the rendered figure.

n_scales

Returns the number of scales.

Typeint

LinearAAM

Bases: AAM

Class for training a multi-scale Linear Active Appearance Model.

Parameters

•images (list of menpo.image.Image) – The list of training images.

- •group (*str* or None, optional) The landmark group that will be used to train the AAM. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.
- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •reference_shape (*menpo.shape.PointCloud* or None, optional) The reference shape that will be used for building the AAM. The purpose of the reference shape is to normalise the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.
- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •transform (subclass of DL and DX, optional) A differential warp transform object, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •max_shape_components (*int*, *float*, *list* of those or None, optional) The number of shape components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value

per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.

•max_appearance_components (*int*, *float*, *list* of those or None, optional) – The number of appearance components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.

•verbose (bool, optional) – If True, then the progress of building the AAM will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

appearance_reconstructions (*appearance_parameters*, *n_iters_per_scale*)

Method that generates the appearance reconstructions given a set of appearance parameters. This is to be combined with a *AAMResult* object, in order to generate the appearance reconstructions of a fitting procedure.

Parameters

•appearance_parameters (*list* of (n_params,) *ndarray*) – A set of appearance parameters per fitting iteration. It can be retrieved as a property of an *AAMResult* object.

•n_iters_per_scale (*list* of *int*) – The number of iterations per scale. This is necessary in order to figure out which appearance parameters correspond to the model of each scale. It can be retrieved as a property of a *AAMResult* object.

Returnsappearance_reconstructions (*list* of *menpo.image.Image*) – *List* of the appearance reconstructions that correspond to the provided parameters.

build_fitter_interfaces (sampling)

Method that builds the correct Lucas-Kanade fitting interface. It only applies in case you wish to fit the AAM with a Lucas-Kanade algorithm (i.e. LucasKanadeAAMFitter).

Parameterssampling (*list* of *int* or *ndarray* or None) – It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.

Returnsfitter_interfaces (list) – The list of Lucas-Kanade interface per scale.

Method to increment the trained AAM with a new set of training images.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•group (*str* or None, optional) – The landmark group that will be used to train the AAM. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.

•**shape_forgetting_factor** ([0.0, 1.0] *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples for the shape model. If 1. 0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.

•appearance_forgetting_factor ([0.0, 1.0] *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples for the appearance model. If 1.0, all samples are weighted equally and, hence, the result is the

exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.

•verbose (*bool*, optional) – If True, then the progress of building the AAM will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

instance (*shape_weights=None*, *appearance_weights=None*, *scale_index=-1*)

Generates a novel AAM instance given a set of shape and appearance weights. If no weights are provided, then the mean AAM instance is returned.

Parameters

•**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.

•appearance_weights ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the appearance model that will be used to create a novel appearance instance. If None, the weights are assumed to be zero, thus the mean appearance is used.

•scale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The AAM instance.

random_instance(scale_index=-1)

Generates a random instance of the AAM.

Parametersscale_index (*int*, optional) – The scale to be used.

Returnsimage (menpo.image.Image) - The AAM instance.

view_shape_models_widget (n_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure_size=(7, 7))

Visualizes the shape models of the \overline{AAM} object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

n_scales

Returns the number of scales.

Typeint

LinearMaskedAAM

Bases: AAM

Class for training a multi-scale Linear Masked Active Appearance Model.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •group (*str* or None, optional) The landmark group that will be used to train the AAM. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.
- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •reference_shape (menpo.shape.PointCloud or None, optional) The reference shape that will be used for building the AAM. The purpose of the reference shape is to normalise the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.
- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •**patch_shape** ((*int*, *int*), optional) The size of the patches of the mask that is used to sample the appearance vectors.
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •max_shape_components (*int*, *float*, *list* of those or None, optional) The number of shape components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •max_appearance_components (*int*, *float*, *list* of those or None, optional) The number of appearance components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.

•verbose (bool, optional) – If True, then the progress of building the AAM will be printed.

•batch_size (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

appearance_reconstructions (*appearance_parameters*, *n_iters_per_scale*)

Method that generates the appearance reconstructions given a set of appearance parameters. This is to be combined with a *AAMResult* object, in order to generate the appearance reconstructions of a fitting procedure.

Parameters

•appearance_parameters (*list* of (n_params,) *ndarray*) – A set of appearance parameters per fitting iteration. It can be retrieved as a property of an *AAMResult* object.

•n_iters_per_scale (*list* of *int*) – The number of iterations per scale. This is necessary in order to figure out which appearance parameters correspond to the model of each scale. It can be retrieved as a property of a *AAMResult* object.

Returnsappearance_reconstructions (*list* of *menpo.image.Image*) – *List* of the appearance reconstructions that correspond to the provided parameters.

build_fitter_interfaces(sampling)

Method that builds the correct Lucas-Kanade fitting interface. It only applies in case you wish to fit the AAM with a Lucas-Kanade algorithm (i.e. *LucasKanadeAAMFitter*).

Parameterssampling (*list* of *int* or *ndarray* or None) – It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.

Returnsfitter_interfaces (list) – The list of Lucas-Kanade interface per scale.

increment (images, group=None, shape_forgetting_factor=1.0, appearance_forgetting_factor=1.0, verbose=False, batch_size=None)

Method to increment the trained AAM with a new set of training images.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•group (*str* or None, optional) – The landmark group that will be used to train the AAM. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.

•**shape_forgetting_factor** ([0.0, 1.0] *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples for the shape model. If 1. 0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.

•appearance_forgetting_factor ([0.0, 1.0] *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples for the appearance model. If 1.0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.

•verbose (*bool*, optional) – If True, then the progress of building the AAM will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

instance (shape_weights=None, appearance_weights=None, scale_index=-1)

Generates a novel AAM instance given a set of shape and appearance weights. If no weights are provided, then the mean AAM instance is returned.

Parameters

- •**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.
- •appearance_weights ((n_weights,) *ndarray* or *list* or None, optional) The weights of the appearance model that will be used to create a novel appearance instance. If None, the weights are assumed to be zero, thus the mean appearance is used.

•scale_index (int, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The AAM instance.

random_instance(scale_index=-1)

Generates a random instance of the AAM.

Parametersscale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The AAM instance.

Visualizes the shape models of the AAM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

n_scales

Returns the number of scales.

Type*int*

PatchAAM

Bases: AAM

Class for training a multi-scale Patch-Based Active Appearance Model. The appearance of this model is formulated by simply sampling patches around the image's landmarks.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •group (*str* or None, optional) The landmark group that will be used to train the AAM. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.
- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •reference_shape (menpo.shape.PointCloud or None, optional) The reference shape that will be used for building the AAM. The purpose of the reference shape is to normalise the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.
- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •**patch_shape** ((*int*, *int*) or *list* of (*int*, *int*), optional) The shape of the patches to be extracted. If a *list* is provided, then it defines a patch shape per scale.
- •**patch_normalisation** (*list* of *callable* or a single *callable*, optional) The normalisation function to be applied on the extracted patches. If *list*, then it must have length equal to the number of scales. If a single patch normalization *callable*, then this is the one applied to all scales.
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •max_shape_components (*int*, *float*, *list* of those or None, optional) The number of shape components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •max_appearance_components (*int*, *float*, *list* of those or None, optional) The number of appearance components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •verbose (bool, optional) If True, then the progress of building the AAM will be printed.
- •**batch_size** (*int* or None, optional) If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

appearance_reconstructions (*appearance_parameters*, *n_iters_per_scale*)

Method that generates the appearance reconstructions given a set of appearance parameters. This is to be combined with a *AAMResult* object, in order to generate the appearance reconstructions of a fitting procedure.

Parameters

•appearance_parameters (*list* of *ndarray*) – A set of appearance parameters per fitting iteration. It can be retrieved as a property of a *AAMResult* object.

•n_iters_per_scale (*list* of *int*) – The number of iterations per scale. This is necessary in order to figure out which appearance parameters correspond to the model of each scale. It can be retrieved as a property of a *AAMResult* object.

Returnsappearance_reconstructions (*list* of *ndarray*) – List of the appearance reconstructions that correspond to the provided parameters.

build_fitter_interfaces (sampling)

Method that builds the correct Lucas-Kanade fitting interface. It only applies in case you wish to fit the AAM with a Lucas-Kanade algorithm (i.e. *LucasKanadeAAMFitter*).

Parameterssampling (*list* of *int* or *ndarray* or None) – It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.

Returnsfitter_interfaces (*list*) – The *list* of Lucas-Kanade interface per scale.

Method to increment the trained AAM with a new set of training images.

Parameters

•images (list of menpo.image.Image) – The list of training images.

- •group (*str* or None, optional) The landmark group that will be used to train the AAM. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.
- •**shape_forgetting_factor** ([0.0, 1.0] *float*, optional) Forgetting factor that weights the relative contribution of new samples vs old samples for the shape model. If 1. 0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.
- •appearance_forgetting_factor ([0.0, 1.0] *float*, optional) Forgetting factor that weights the relative contribution of new samples vs old samples for the appearance model. If 1.0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.
- •verbose (*bool*, optional) If True, then the progress of building the AAM will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

instance (*shape_weights=None*, *appearance_weights=None*, *scale_index=-1*)

Generates a novel AAM instance given a set of shape and appearance weights. If no weights are provided, then the mean AAM instance is returned.

Parameters

•**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.

•appearance_weights ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the appearance model that will be used to create a novel appearance instance. If None, the weights are assumed to be zero, thus the mean appearance is used.

•scale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The AAM instance.

```
random_instance(scale_index=-1)
```

Generates a random instance of the AAM.

Parametersscale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The AAM instance.

Visualizes the AAM using an interactive widget.

Parameters

•n_shape_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•n_appearance_parameters (*int* or *list* of *int* or None, optional) – The number of appearance principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•**parameters_bounds** ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

Visualizes the appearance models of the AAM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of appearance principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

Visualizes the shape models of the AAM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

n_scales

Returns the number of scales.

Type*int*

Fitters

An AAM can be optimised either in a gradient descent manner (Lucas-Kanade) or using cascaded regression (Supervised Descent).

LucasKanadeAAMFitter

= 0 =	men
algorithm.lk.WibergInverseCompositio	onal'>,
None, n_appearance=None,	sam-
ne)	
l n	algorithm.lk.WibergInverseCompositio None, n_appearance=None, ne)

Bases: AAMFitter

Class for defining an AAM fitter using the Lucas-Kanade optimisation.

Note: When using a method with a parametric shape model, the first step is to **reconstruct the initial shape** using the shape model. The generated reconstructed shape is then used as initialisation for the iterative optimisation. This step takes place at each scale and it is not considered as an iteration, thus it is not counted for the provided *max_iters*.

Parameters

•aam (AAM or subclass) – The trained AAM model.

Class	Method
AlternatingForwardCompositional	Alternating
AlternatingInverseCompositional	
ModifiedAlternatingForwardCompositional	Modified Alternating
ModifiedAlternatingInverseCompositional	
ProjectOutForwardCompositional	Project-Out
ProjectOutInverseCompositional	
SimultaneousForwardCompositional	Simultaneous
SimultaneousInverseCompositional	
WibergForwardCompositional	Wiberg
WibergInverseCompositional	

•**lk_algorithm_cls** (*class*, optional) – The Lukas-Kanade optimisation algorithm that will get applied. The possible algorithms are:

•**n_shape** (*int* or *float* or *list* of those or None, optional) – The number of shape components that will be used. If *int*, then it defines the exact number of active components. If *float*, then it defines the percentage of variance to keep. If *int* or *float*, then the provided value will be applied for all scales. If *list*, then it defines a value per scale. If None, then all the available components will be used. Note that this simply sets the active components without trimming the unused ones. Also, the available components may have already been trimmed to *max_shape_components* during training.

- •n_appearance (*int* or *float* or *list* of those or None, optional) The number of appearance components that will be used. If *int*, then it defines the exact number of active components. If *float*, then it defines the percentage of variance to keep. If *int* or *float*, then the provided value will be applied for all scales. If *list*, then it defines a value per scale. If None, then all the available components will be used. Note that this simply sets the active components without trimming the unused ones. Also, the available components may have already been trimmed to *max_appearance_components* during training.
- •sampling (*list* of *int* or *ndarray* or None) It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.

appearance_reconstructions (*appearance_parameters*, *n_iters_per_scale*)

Method that generates the appearance reconstructions given a set of appearance parameters. This is to be combined with a *AAMResult* object, in order to generate the appearance reconstructions of a fitting procedure.

Parameters

•appearance_parameters (*list* of (n_params,) *ndarray*) – A set of appearance parameters per fitting iteration. It can be retrieved as a property of an *AAMResult* object.

•n_iters_per_scale (*list* of *int*) – The number of iterations per scale. This is necessary in order to figure out which appearance parameters correspond to the model of each scale. It can be retrieved as a property of a *AAMResult* object.

Returnsappearance_reconstructions (*list* of *menpo.image.Image*) – *List* of the appearance reconstructions that correspond to the provided parameters.

fit_from_bb (*image*, *bounding_box*, *max_iters=20*, *gt_shape=None*, *return_costs=False*, ***kwargs*) Fits the multi-scale fitter to an image given an initial bounding box.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•bounding_box (*menpo.shape.PointDirectedGraph*) – The initial bounding box from which the fitting procedure will start. Note that the bounding box is used in order to align the model's reference shape.

•max_iters (*int* or *list* of *int*, optional) – The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

Fits the multi-scale fitter to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape estimate from which the fitting procedure will start.

•max_iters (*int* or *list* of *int*, optional) – The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

warped_images (image, shapes)

Given an input test image and a list of shapes, it warps the image into the shapes. This is useful for generating the warped images of a fitting procedure stored within an *AAMResult*.

Parameters

•image (menpo.image.Image or subclass) – The input image to be warped.

•**shapes** (*list* of *menpo.shape.PointCloud*) – The list of shapes in which the image will be warped. The shapes are obtained during the iterations of a fitting procedure.

Returnswarped_images (*list* of *menpo.image.MaskedImage* or *ndarray*) – The warped images.

aam

The trained AAM model.

TypeAAM or subclass

holistic_features

The features that are extracted from the input image at each scale in ascending order, i.e. from lowest to highest scale.

Typelist of closure

n_scales

Returns the number of scales.

Type*int*

reference_shape

The reference shape that is used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of this reference shape.

Typemenpo.shape.PointCloud

scales

The scale value of each scale in ascending order, i.e. from lowest to highest scale.

Typelist of int or float

SupervisedDescentAAMFitter

class menpofit.aam.SupervisedDescentAAMFitter	(images,	aam,	group=None	, bound-
	ing_box_g	roup_gl	ob=None, n_sh	hape=None,
	n_appeara	nce=Na	one, samp	ling=None,
	sd_algorith	hm_cls=	<class< th=""><th>'men-</th></class<>	'men-
	pofit.aam.a	algorith	m.sd.ProjectOu	tNewton'>,
	n_iteration	ıs=6, i	n_perturbations	s=30, per-
	turb_from_	_gt_bou	nding_box= <fu< th=""><th>inction</th></fu<>	inction
	noisy_shap	pe_from	_bounding_box	>,
	batch_size	=None,	verbose = False)

Bases: SupervisedDescentFitter

Class for training a multi-scale cascaded-regression Supervised Descent AAM fitter.

Parameters

•images (list of menpo.image.Image) – The list of training images.

- •aam (AAM or subclass) The trained AAM model.
- •group (*str* or None, optional) The landmark group that will be used to train the fitter. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.
- •bounding_box_group_glob (*glob* or None, optional) Glob that defines the bounding boxes to be used for training. If None, then the bounding boxes of the ground truth shapes are used.
- •n_shape (*int* or *float* or *list* of those or None, optional) The number of shape components that will be used. If *int*, then it defines the exact number of active components. If *float*, then it defines the percentage of variance to keep. If *int* or *float*, then the provided value will be applied for all scales. If *list*, then it defines a value per scale. If None, then all the

available components will be used. Note that this simply sets the active components without trimming the unused ones. Also, the available components may have already been trimmed to *max_shape_components* during training.

- •n_appearance (*int* or *float* or *list* of those or None, optional) The number of appearance components that will be used. If *int*, then it defines the exact number of active components. If *float*, then it defines the percentage of variance to keep. If *int* or *float*, then the provided value will be applied for all scales. If *list*, then it defines a value per scale. If None, then all the available components will be used. Note that this simply sets the active components without trimming the unused ones. Also, the available components may have already been trimmed to *max_appearance_components* during training.
- •**sampling** (*list* of *int* or *ndarray* or None) It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.
- •sd_algorithm_cls (*class*, optional) The Supervised Descent algorithm to be used. The possible algorithms are:

Class	Features	Regression
MeanTemplateNewton	Mean Template	IRLRegression
MeanTemplateGaussNewton		IIRLRegression
ProjectOutNewton	Project-Out	IRLRegression
<i>ProjectOutGaussNewton</i>		IIRLRegression
AppearanceWeightsNewton	App. Weights	IRLRegression
AppearanceWeightsGaussNewton		IIRLRegression

- •**n_iterations** (*int* or *list* of *int*, optional) The number of iterations (cascades) of each level. If *list*, it must specify a value per scale. If *int*, then it defines the total number of iterations (cascades) over all scales.
- •**n_perturbations** (*int* or None, optional) The number of perturbations to be generated from the provided bounding boxes.
- •**perturb_from_gt_bounding_box** (*callable*, optional) The function that will be used to generate the perturbations.
- •**batch_size** (*int* or None, optional) If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.
- •verbose (bool, optional) If True, then the progress of training will be printed.
- fit_from_bb (*image*, *bounding_box*, *max_iters=20*, *gt_shape=None*, *return_costs=False*, ***kwargs*) Fits the multi-scale fitter to an image given an initial bounding box.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •bounding_box (*menpo.shape.PointDirectedGraph*) The initial bounding box from which the fitting procedure will start. Note that the bounding box is used in order to align the model's reference shape.
- •max_iters (*int* or *list* of *int*, optional) The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.
- •gt_shape (*menpo.shape.PointCloud*, optional) The ground truth shape associated to the image.
•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

Fits the multi-scale fitter to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape estimate from which the fitting procedure will start.

•max_iters (*int* or *list* of *int*, optional) – The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

Method to increment the trained SDM with a new set of training images.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•group (*str* or None, optional) – The landmark group that corresponds to the ground truth shape of each image. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.

•bounding_box_group_glob (*glob* or None, optional) – Glob that defines the bounding boxes to be used for training. If None, then the bounding boxes of the ground truth shapes are used.

•verbose (bool, optional) – If True, then the progress of training will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

warped_images (image, shapes)

Given an input test image and a list of shapes, it warps the image into the shapes. This is useful for generating the warped images of a fitting procedure stored within a *MultiScaleParametricIterativeResult*.

Parameters

•image (menpo.image.Image or subclass) – The input image to be warped.

•**shapes** (*list* of *menpo.shape.PointCloud*) – The list of shapes in which the image will be warped. The shapes are obtained during the iterations of a fitting procedure.

Returnswarped_images (*list* of *menpo.image.MaskedImage* or *ndarray*) – The warped images.

holistic_features

The features that are extracted from the input image at each scale in ascending order, i.e. from lowest to highest scale.

Typelist of closure

n_scales

Returns the number of scales.

Type*int*

reference_shape

The reference shape that is used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of this reference shape.

Typemenpo.shape.PointCloud

scales

The scale value of each scale in ascending order, i.e. from lowest to highest scale.

Typelist of int or float

Lucas-Kanade Optimisation Algorithms

AlternatingForwardCompositional

class menpofit.aam.AlternatingForwardCompositional (*aam_interface*, *eps=1e-05*)

Bases: Alternating

Alternating Forward Compositional (AFC) Gauss-Newton algorithm.

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

•image (*menpo.image.Image*) – The input test image.

•**initial_shape** (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•map_inference (*bool*, optional) – If True, then the solution will be given after performing MAP inference.

Returnsfitting_result (AAMAlgorithmResult) – The parametric iterative fitting result.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

template

Returns the template of the AAM (usually the mean of the appearance model).

Typemenpo.image.Image or subclass

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

AlternatingInverseCompositional

class menpofit.aam.AlternatingInverseCompositional (aam_interface, eps=1e-05)
Bases: Alternating

Alternating Inverse Compositional (AIC) Gauss-Newton algorithm.

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

•image (menpo.image.Image) – The input test image.

•**initial_shape** (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•map_inference (*bool*, optional) – If True, then the solution will be given after performing MAP inference.

Returnsfitting_result (AAMAlgorithmResult) – The parametric iterative fitting result.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

template

Returns the template of the AAM (usually the mean of the appearance model).

Typemenpo.image.Image or subclass

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

ModifiedAlternatingForwardCompositional

class menpofit.aam.ModifiedAlternatingForwardCompositional (*aam_interface*, *eps=le-*05)

Bases: ModifiedAlternating

Modified Alternating Forward Compositional (MAFC) Gauss-Newton algorithm

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

•image (*menpo.image.Image*) – The input test image.

- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the optimization will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.
- •max_iters (*int*, optional) The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•map_inference (*bool*, optional) – If True, then the solution will be given after performing MAP inference.

Returnsfitting_result (AAMAlgorithmResult) – The parametric iterative fitting result.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

template

Returns the template of the AAM (usually the mean of the appearance model).

Typemenpo.image.Image or subclass

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

ModifiedAlternatingInverseCompositional

class menpofit.aam.ModifiedAlternatingInverseCompositional (aam_interface, eps=le-05)
Bases: ModifiedAlternating

Modified Alternating Inverse Compositional (MAIC) Gauss-Newton algorithm

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

•image (*menpo.image.Image*) – The input test image.

- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the optimization will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.
- •max_iters (*int*, optional) The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.
- •map_inference (*bool*, optional) If True, then the solution will be given after performing MAP inference.

Returnsfitting_result (AAMAlgorithmResult) - The parametric iterative fitting result.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

template

Returns the template of the AAM (usually the mean of the appearance model).

Typemenpo.image.Image or subclass

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

ProjectOutForwardCompositional

class menpofit.aam.ProjectOutForwardCompositional(aam_interface, eps=1e-05)
Bases: ProjectOut

Project-out Forward Compositional (POFC) Gauss-Newton algorithm.

$project_out(J)$

Projects-out the appearance subspace from a given vector or matrix.

Typendarray

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

•**image** (*menpo.image.Image*) – The input test image.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•map_inference (*bool*, optional) – If True, then the solution will be given after performing MAP inference.

Returnsfitting_result (AAMAlgorithmResult) – The parametric iterative fitting result.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

template

Returns the template of the AAM (usually the mean of the appearance model).

Typemenpo.image.Image or subclass

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

ProjectOutInverseCompositional

class menpofit.aam.ProjectOutInverseCompositional (aam_interface, eps=1e-05)
Bases: ProjectOut

Project-out Inverse Compositional (POIC) Gauss-Newton algorithm.

$project_out(J)$

Projects-out the appearance subspace from a given vector or matrix.

Typendarray

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

•image (menpo.image.Image) – The input test image.

•**initial_shape** (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•map_inference (*bool*, optional) – If True, then the solution will be given after performing MAP inference.

Returnsfitting_result (AAMAlgorithmResult) – The parametric iterative fitting result.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

template

Returns the template of the AAM (usually the mean of the appearance model).

Typemenpo.image.Image or subclass

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

SimultaneousForwardCompositional

class menpofit.aam.SimultaneousForwardCompositional(aam_interface, eps=1e-05)
Bases: Simultaneous

Simultaneous Forward Compositional (SFC) Gauss-Newton algorithm.

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

•image (*menpo.image.Image*) – The input test image.

•**initial_shape** (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•map_inference (*bool*, optional) – If True, then the solution will be given after performing MAP inference.

Returnsfitting_result (AAMAlgorithmResult) – The parametric iterative fitting result.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

template

Returns the template of the AAM (usually the mean of the appearance model).

Typemenpo.image.Image or subclass

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

SimultaneousInverseCompositional

```
class menpofit.aam.SimultaneousInverseCompositional(aam_interface, eps=1e-05)
Bases: Simultaneous
```

Simultaneous Inverse Compositional (SIC) Gauss-Newton algorithm.

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

•image (menpo.image.Image) – The input test image.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•map_inference (*bool*, optional) – If True, then the solution will be given after performing MAP inference.

Returnsfitting_result (AAMAlgorithmResult) - The parametric iterative fitting result.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

template

Returns the template of the AAM (usually the mean of the appearance model).

Typemenpo.image.Image or subclass

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of DL and DX

WibergForwardCompositional

class menpofit.aam.WibergForwardCompositional (aam_interface, eps=1e-05)

Bases: Wiberg

Wiberg Forward Compositional (WFC) Gauss-Newton algorithm.

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

- •image (menpo.image.Image) The input test image.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the optimization will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.
- •max_iters (*int*, optional) The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•map_inference (*bool*, optional) – If True, then the solution will be given after performing MAP inference.

Returnsfitting_result (*AAMAlgorithmResult*) – The parametric iterative fitting result.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

template

Returns the template of the AAM (usually the mean of the appearance model).

Typemenpo.image.Image or subclass

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

WibergInverseCompositional

class menpofit.aam.WibergInverseCompositional(aam_interface, eps=1e-05)
Bases: Wiberg

Wiberg Inverse Compositional (WIC) Gauss-Newton algorithm.

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

•image (menpo.image.Image) – The input test image.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•map_inference (*bool*, optional) – If True, then the solution will be given after performing MAP inference.

Returnsfitting_result (AAMAlgorithmResult) – The parametric iterative fitting result.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

template

Returns the template of the AAM (usually the mean of the appearance model).

Typemenpo.image.Image or subclass

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

Supervised Descent Optimisation Algorithms

AppearanceWeightsNewton

class menpofit.aam.AppearanceWeightsNewton(aam	ı_interface,	n_iterations=3,
com	ipute_error= <function< td=""><td>eu-</td></function<>	eu-
clid	ean_bb_normalised_error>,	alpha=0,
bias	s=True)	

Bases: AppearanceWeights

Class for training a cascaded-regression Newton algorithm using Incremental Regularized Linear Regression (*IRLRegression*) given a trained AAM model. The algorithm uses the projection weights of the appearance vectors as features in the regression.

Parameters

•**aam_interface** (The AAM interface class from *menpofit.aam.algorithm.lk.*) – Existing interfaces include:

'LucasKanadeStandardInterface'	Suitable for holistic AAMs
'LucasKanadeLinearInterface'	Suitable for linear AAMs
'LucasKanadePatchInterface'	Suitable for patch-based AAMs

- •n_iterations (*int*, optional) The number of iterations (cascades).
- •compute_error (*callable*, optional) The function to be used for computing the fitting error when training each cascade.
- •alpha (*float*, optional) The regularization parameter.
- •bias (bool, optional) Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False) Method to increment the model with the set of current shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •prefix (str, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

project(J)

Projects a given vector or matrix onto the appearance subspace.

Typendarray

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the fitting procedure will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to 'True''. This is because it is not possible to evaluate the cost function of this algorithm.

Returnsfitting_result (*AAMAlgorithmResult*) – The parametric iterative fitting result.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•prefix (*str*, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

AppearanceWeightsGaussNewton

<pre>class menpofit.aam.AppearanceWeightsGaussNewton</pre>	(aam_interface,	n_iterations=3,
	compute_error= <function< th=""><th>on eu-</th></function<>	on eu-
	clidean_bb_normalised_	_error>, alpha=0,
	alpha2=0, bias=True)	

Bases: AppearanceWeights

Class for training a cascaded-regression Gauss-Newton algorithm using Indirect Incremental Regularized Linear Regression (*IIRLRegression*) given a trained AAM model. The algorithm uses the projection weights of the appearance vectors as features in the regression.

Parameters

•aam_interface (The AAM interface class from *menpofit.aam.algorithm.lk.*) – Existing interfaces include:

'LucasKanadeStandardInterface'	Suitable for holistic AAMs
'LucasKanadeLinearInterface'	Suitable for linear AAMs
'LucasKanadePatchInterface'	Suitable for patch-based AAMs

•n_iterations (*int*, optional) – The number of iterations (cascades).

•compute_error (*callable*, optional) – The function to be used for computing the fitting error when training each cascade.

- •alpha (*float*, optional) The regularization parameter.
- •alpha2 (*float*, optional) The regularization parameter of the Hessian matrix.

•bias (bool, optional) – Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

project(J)

Projects a given vector or matrix onto the appearance subspace.

Typendarray

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the fitting procedure will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to ''True''. This is because it is not possible to evaluate the cost function of this algorithm.

Returnsfitting_result (AAMAlgorithmResult) – The parametric iterative fitting result.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=``*, *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

MeanTemplateNewton

```
class menpofit.aam.MeanTemplateNewton (aam_interface, n_iterations=3, com-
pute_error=<function euclidean_bb_normalised_error>,
alpha=0, bias=True)
```

Bases: MeanTemplate

Class for training a cascaded-regression Newton algorithm using Incremental Regularized Linear Regression (*IRLRegression*) given a trained AAM model. The algorithm uses the centered appearance vectors as features in the regression.

Parameters

•aam_interface (The AAM interface class from *menpofit.aam.algorithm.lk.*) – Existing interfaces include:

'LucasKanadeStandardInterface'	Suitable for holistic AAMs
'LucasKanadeLinearInterface'	Suitable for linear AAMs
'LucasKanadePatchInterface'	Suitable for patch-based AAMs

•n_iterations (*int*, optional) – The number of iterations (cascades).

•compute_error (*callable*, optional) – The function to be used for computing the fitting error when training each cascade.

•alpha (*float*, optional) – The regularization parameter.

•bias (bool, optional) – Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •prefix (str, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- **run** (*image*, *initial_shape*, *gt_shape=None*, *return_costs=False*, ***kwargs*) Run the algorithm to an image given an initial shape.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to ''True''. This is because it is not possible to evaluate the cost function of this algorithm.

Returnsfitting_result (AAMAlgorithmResult) - The parametric iterative fitting result.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images, which will be used as initial shapes.
- •prefix (str, optional) The prefix to use when printing information.
- •verbose (*bool*, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

MeanTemplateGaussNewton

class menpofit.aam.MeanTemplateGaussNewton (aam_interface,	<i>n_iterations=3</i> ,
	compute_error= <function< td=""><td>eu-</td></function<>	eu-
	<pre>clidean_bb_normalised_error>,</pre>	alpha=0,
	alpha2=0, bias=True)	

Bases: MeanTemplate

Class for training a cascaded-regression Gauss-Newton algorithm using Indirect Incremental Regularized Linear Regression (*IIRLRegression*) given a trained AAM model. The algorithm uses the centered appearance vectors as features in the regression.

Parameters

•**aam_interface** (The AAM interface class from *menpofit.aam.algorithm.lk.*) – Existing interfaces include:

'LucasKanadeStandardInterface'	Suitable for holistic AAMs
'LucasKanadeLinearInterface'	Suitable for linear AAMs
'LucasKanadePatchInterface'	Suitable for patch-based AAMs

•n_iterations (int, optional) – The number of iterations (cascades).

•compute_error (*callable*, optional) – The function to be used for computing the fitting error when training each cascade.

•alpha (float, optional) – The regularization parameter.

•alpha2 (*float*, optional) – The regularization parameter of the Hessian matrix.

•bias (bool, optional) – Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the fitting procedure will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.

Returnsfitting_result (AAMAlgorithmResult) - The parametric iterative fitting result.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=''*, *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of DL and DX

ProjectOutNewton

Bases: ProjectOut

Class for training a cascaded-regression Newton algorithm using Incremental Regularized Linear Regression (*IRLRegression*) given a trained AAM model. The algorithm uses the projected-out appearance vectors as features in the regression.

Parameters

•aam_interface (The AAM interface class from *menpofit.aam.algorithm.lk.*) – Existing interfaces include:

Class	AAM
'LucasKanadeStandardInterface'	Suitable for holistic AAMs
'LucasKanadeLinearInterface'	Suitable for linear AAMs
'LucasKanadePatchInterface'	Suitable for patch-based AAMs

•n_iterations (*int*, optional) – The number of iterations (cascades).

•compute_error (*callable*, optional) – The function to be used for computing the fitting error when training each cascade.

•alpha (*float*, optional) – The regularization parameter.

•bias (bool, optional) – Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

•images (*list* of *menpo.image.Image*) – The *list* of training images.

- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •prefix (*str*, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

$project_out(J)$

Projects-out the appearance subspace from a given vector or matrix.

Typendarray

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to ''True''. This is because it is not possible to evaluate the cost function of this algorithm.

Returnsfitting_result (AAMAlgorithmResult) - The parametric iterative fitting result.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=``*, *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (*bool*, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of DL and DX

ProjectOutGaussNewton

<pre>class menpofit.aam.ProjectOutGaussNewton(aam_interface,</pre>		1s=3,
compute_error= <function< td=""><td></td><td>eu-</td></function<>		eu-
clidean_bb_normalised_error>,	alpha=0,	al-
pha2=0, bias=True)		

Bases: ProjectOut

Class for training a cascaded-regression Gauss-Newton algorithm using Indirect Incremental Regularized Linear Regression (*IIRLRegression*) given a trained AAM model. The algorithm uses the projected-out appearance vectors as features in the regression.

Parameters

•aam_interface (The AAM interface class from *menpofit.aam.algorithm.lk.*) – Existing interfaces include:

'LucasKanadeStandardInterface'	Suitable for holistic AAMs
'LucasKanadeLinearInterface'	Suitable for linear AAMs
'LucasKanadePatchInterface'	Suitable for patch-based AAMs

•n_iterations (*int*, optional) – The number of iterations (cascades).

•compute_error (*callable*, optional) – The function to be used for computing the fitting error when training each cascade.

•alpha (*float*, optional) – The regularization parameter.

•alpha2 (*float*, optional) – The regularization parameter of the Hessian matrix.

•bias (*bool*, optional) – Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

$project_out(J)$

Projects-out the appearance subspace from a given vector or matrix.

Typendarray

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) - The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the fitting procedure will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.

Returnsfitting_result (AAMAlgorithmResult) - The parametric iterative fitting result.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=``*, *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•**prefix** (*str*, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

appearance_model

Returns the appearance model of the AAM.

Typemenpo.model.PCAModel

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

Fitting Result

AAMResult

Class for storing the multi-scale iterative fitting result of an AAM. It holds the shapes, shape parameters, appearance parameters and costs per iteration.

Note: When using a method with a parametric shape model, the first step is to **reconstruct the initial shape** using the shape model. The generated reconstructed shape is then used as initialisation for the iterative optimisation. This step is not counted in the number of iterations.

Parameters

- •results (*list* of AAMA1gorithmResult) The *list* of optimization results per scale.
- •scales (*list* or *tuple*) The *list* of scale values per scale (low to high).
- •affine_transforms (*list* of *menpo.transform.Affine*) The list of affine transforms per scale that transform the shapes into the original image space.
- •scale_transforms (*list* of *menpo.shape.Scale*) The list of scaling transforms per scale.
- •**image** (*menpo.image.Image* or *subclass* or None, optional) The image on which the fitting process was applied. Note that a copy of the image will be assigned as an attribute. If None, then no image is assigned.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated with the image. If None, then no ground truth shape is assigned.

displacements()

A list containing the displacement between the shape of each iteration and the shape of the previous one.

Typelist of ndarray

displacements_stats (stat_type='mean')

A list containing a statistical metric on the displacements between the shape of each iteration and the shape of the previous one.

- **Parametersstat_type** ({'mean', 'median', 'min', 'max'}, optional) Specifies a statistic metric to be extracted from the displacements.
- **Returnsdisplacements_stat** (*list* of *float*) The statistical metric on the points displacements for each iteration.

RaisesValueError - type must be 'mean', 'median', 'min' or 'max'

errors (compute_error=None)

Returns a list containing the error at each fitting iteration, if the ground truth shape exists.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

Returnserrors (*list* of *float*) – The error at each iteration of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

final_error (compute_error=None)

Returns the final error of the fitting process, if the ground truth shape exists. This is the error computed based on the *final_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the fitted and ground truth shapes.

Returnsfinal_error (*float*) – The final error at the end of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

initial_error(compute_error=None)

Returns the initial error of the fitting process, if the ground truth shape and initial shape exist. This is the error computed based on the *initial_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the initial and ground truth shapes.

Returnsinitial_error (*float*) – The initial error at the beginning of the fitting process.

Raises

•ValueError – Initial shape has not been set, so the initial error cannot be computed

•ValueError – Ground truth shape has not been set, so the initial error cannot be computed

plot_costs (figure_id=None, new_figure=False, render_lines=True, line_colour='b', line_style='', line_width=2, render_markers=True, marker_style='o', marker_size=4,
marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0,
render_axes=True, axes_font_name='sans-serif', axes_font_size=10,
axes_font_style='normal', axes_font_weight='normal', axes_r_limits=0.0,
axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6),
render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the cost function evolution at each fitting iteration.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None, optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•line_style ({ '-', '--', '-.', ':'}, optional) – The style of the lines.

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (marker, optional) – The style of the markers. Example marker options

{'.', ',', 'o', 'v', '^', '<', '>', '+', 'x', 'D', 'd', 's', 'p', '*', 'h', 'H', '1', '2', '3', '4', '8'}

•marker_size (*int*, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) - The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (See below, optional) - The font of the axes. Example options

{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({'normal', 'italic', 'oblique'}, optional) - The font style of the axes.

•axes_font_weight (See below, optional) - The font weight of the axes. Example options

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

Plot of a statistical metric of the displacement between the shape of each iteration and the shape of the previous one.

Parameters

•**stat_type** ({mean, median, min, max}, optional) – Specifies a statistic metric to be extracted from the displacements (see also *displacements_stats()* method).

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) - If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

```
\{-, --, -, :\}
```

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (*bool*, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (menpo.visualize.GraphPlotter) – The renderer object.

plot_errors (compute_error=None, figure_id=None, new_figure=False, render lines=True, line_colour='b', line_style='-', line width=2, render markers=True, marker_style='o', marker_size=4, marker_face_colour='b', marker_edge_colour='k', axes_font_name='sans-serif', marker_edge_width=1.0, render_axes=True, axes_font_size=10, axes_font_style='normal', axes_font_weight='normal', axes_x_limits=0.0, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6), render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the error evolution at each fitting iteration.

Parameters

•compute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

```
{-, --, -., :}
```

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves'

width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

- •axes_y_limits (*float* or (*float*, *float*) or None, optional) The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.
- •axes_x_ticks (list or tuple or None, optional) The ticks of the x axis.
- •axes_y_ticks (list or tuple or None, optional) The ticks of the y axis.
- •figure_size ((float, float) or None, optional) The size of the figure in inches.
- •render_grid (*bool*, optional) If True, the grid will be rendered.
- •grid_line_style ({ '-', '--', '-.', ':'}, optional) The style of the grid lines.

•grid_line_width (float, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

reconstructed_initial_error(compute_error=None)

Returns the error of the reconstructed initial shape of the fitting process, if the ground truth shape exists. This is the error computed based on the *reconstructed_initial_shapes[0]*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the reconstructed initial and ground truth shapes.
- **Returnsreconstructed_initial_error** (*float*) The error that corresponds to the initial shape's reconstruction.

RaisesValueError – Ground truth shape has not been set, so the reconstructed initial error cannot be computed

to_result (*pass_image=True*, *pass_initial_shape=True*, *pass_gt_shape=True*)

Returns a *Result* instance of the object, i.e. a fitting result object that does not store the iterations. This can be useful for reducing the size of saved fitting results.

Parameters

•pass_image (bool, optional) – If True, then the image will get passed (if it exists).

•**pass_initial_shape** (*bool*, optional) – If True, then the initial shape will get passed (if it exists).

•**pass_gt_shape** (*bool*, optional) – If True, then the ground truth shape will get passed (if it exists).

Returnsresult (*Result*) – The final "lightweight" fitting result.

view (figure id=None, new figure=False, render image=True, render final shape=True, render_initial_shape=False, subplots enabled=True, *render_gt_shape=False*, channels=None, interpolation='bilinear', cmap name=None, alpha=1.0, masked=True, final_marker_face_colour='r', final_marker_edge_colour='k', final_line_colour='r', initial marker face colour='b', initial marker edge colour='k', initial line colour='b', gt marker face colour='y', gt marker edge colour='k', gt line colour='y', render lines=True, line style='-', line width=2, render markers=True, marker style='o', marker edge width=1.0, marker_size=4, render numbering=False, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers_font_name='sansserif', numbers_font_size=10, numbers_font_style='normal', numbers_font_weight='normal', numbers_font_colour='k', render_legend=True, legend_title='', legend_font_name='sans*legend_font_style='normal', legend_font_size=10,* legend_font_weight='normal', serif', legend_marker_scale=None, legend_location=2, legend_bbox_to_anchor=(1.05, 1.0), legend_border_axes_pad=None, *legend_horizontal_spacing=None*, *legend_n_columns=1*, *legend_vertical_spacing=None*, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sansaxes_font_size=10, axes_font_style='normal', axes_font_weight='normal', serif', axes x limits=None, axes y limits=None, axes x ticks=None, axes v ticks=None, figure size=(7, 7))

Visualize the fitting result. The method renders the final fitted shape and optionally the initial shape, ground truth shape and the image, id they were provided.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

- •render_final_shape (*bool*, optional) If True, then the final fitting shape gets rendered.
- •render_initial_shape (*bool*, optional) If True and the initial fitting shape exists, then it gets rendered.
- •**render_gt_shape** (*bool*, optional) If True and the ground truth shape exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

- •channels (*int* or *list* of *int* or all or None) If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.
- •interpolation (See Below, optional) The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

{none, nearest, bilinear, bicubic, spline16, spline36, hanning, hamming, hermite, kaiser, quadric, catrom, gaussian, bessel, mitchell, sinc, lanczos}

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•final_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_marker_edge_colour (See Below, optional) – The edge colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_line_colour (See Below, optional) – The line colour of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_edge_colour (See Below, optional) - The edge colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_line_colour (See Below, optional) – The line colour of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_edge_colour (See Below, optional) – The edge colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_line_colour (See Below, optional) – The line colour of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_lines (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•line_style (*str* or *list* of *str*, optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{'-', '--', '-.', ':'}

•line_width (*float* or *list* of *float*, optional) – The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•marker_style (*str* or *list* of *str*, optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align ({center, right, left}, optional) - The horizontal alignment of the numbers' texts.

•numbers_vertical_align ({center, top, bottom, baseline}, optional) – The vertical alignment of the numbers' texts.

•numbers_font_name (See Below, optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (See Below, optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style ({normal, italic, oblique}, optional) - The font style of the legend.

•legend_font_size (*int*, optional) – The font size of the legend.

•legend_font_weight (See Below, optional) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (*int*, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

- •legend_border (bool, optional) If True, a frame will be drawn around the legend.
- •legend_border_padding (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.
- •legend_rounded_corners (*bool*, optional) If True, the frame's corners will be rounded (fancybox).
- •render_axes (bool, optional) If True, the axes will be rendered.
- •axes_font_name (See Below, optional) The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- •axes_font_size (*int*, optional) The font size of the axes.
- •axes_font_style ({normal, italic, oblique}, optional) The font style of the axes.
- •axes_font_weight (See Below, optional) The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

- •axes_x_limits (float or (float, float) or None, optional) The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.
- •axes_y_limits ((*float*, *float*) tuple or None, optional) The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.
- •axes_x_ticks (list or tuple or None, optional) The ticks of the x axis.
- •axes_y_ticks (list or tuple or None, optional) The ticks of the y axis.
- •figure_size ((float, float) tuple or None optional) The size of the figure in inches.

Returnsrenderer (*class*) – The renderer object.

view iterations (figure id=None, new figure=False, iters=None, render image=True, subplots_enabled=False, channels=None. interpolation='bilinear', render lines=True, cmap name=None, alpha=1.0, masked=True. *line_style='-'*, line width=2, *line_colour=None*, render_markers=True, marker edge colour=None, marker face colour=None, marker_style='o', marker_size=4. marker_edge_width=1.0, render numbering=False, numbers horizontal align='center'. numbers vertical align='bottom', numbers font name='sans-serif', numbers font size=10, numbers font style='normal', numbers font weight='normal', numrender_legend=True, *bers_font_colour='k'*, legend_title='', legend_font_name='sans-serif', legend_font_style='normal', legend_font_size=10, legend_font_weight='normal', legend_marker_scale=None, *legend location=2*, legend_bbox_to_anchor=(1.05, 1.0). legend_border_axes_pad=None, *legend_n_columns=1*, legend_horizontal_spacing=None, *legend_vertical_spacing=None*, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sans-serif', axes font size=10, axes font style='normal', axes font weight='normal', axes x limits=None, axes y limits=None, axes x ticks=None, axes y ticks=None, figure size=(7, 7))

Visualize the iterations of the fitting process.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•iters (*int* or *list* of *int* or None, optional) – The iterations to be visualized. If None, then all the iterations are rendered.

No.	Visualised shape	Description
0	self.initial_shape	Initial shape
1	self.reconstructed_initial_shape	Reconstructed initial
2	self.shapes[2]	Iteration 1
i	self.shapes[i]	Iteration i-1
n_iters+1	self.final_shape	Final shape

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

•channels (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (*str* (See Below), optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

{none, nearest, bilinear, bicubic, spline16, spline36, hanning, hamming, hermite, kaiser, quadric, catrom, gaussian, bessel, mitchell, sinc, lanczos}

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•**render_lines** (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•line_style (*str* or *list* of *str* (See below), optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options:

{-, --, -., :}

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_colour (*colour* or *list* of *colour* (See Below), optional) The colour of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_style (*str or 'list* of *str* (See below), optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_edge_colour (*colour* or *list* of *colour* (See Below), optional) – The edge colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_face_colour (*colour* or *list* of *colour* (See Below), optional) – The face (filling) colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align (*str* (See below), optional) – The horizontal alignment of the numbers' texts. Example options

```
{center, right, left}
```

•numbers_vertical_align (*str* (See below), optional) – The vertical alignment of the numbers' texts. Example options

{center, top, bottom, baseline}

•numbers_font_name (*str* (See below), optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (*str* (See below), optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) - If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style (*str* (See below), optional) – The font style of the legend. Example options

{normal, italic, oblique}

•legend_font_size (*int*, optional) – The font size of the legend.

•legend_font_weight (*str* (See below), optional) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (*int*, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

•legend_border (bool, optional) – If True, a frame will be drawn around the legend.

• **legend_border_padding** (*float*, optional) – The fractional whitespace inside the legend border.

•legend_shadow (bool, optional) – If True, a shadow will be drawn behind legend.

•legend_rounded_corners (*bool*, optional) – If True, the frame's corners will be rounded (fancybox).

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.
•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((*float*, *float*) *tuple* or None optional) – The size of the figure in inches.

Returnsrenderer (class) – The renderer object.

view_widget (figure_size=(7, 7))

Visualizes the result object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

appearance_parameters

Returns the *list* of appearance parameters obtained at each iteration of the fitting process. The *list* includes the parameters of the *initial_shape* (if it exists) and *final_shape*.

Type*list* of (n_params,) *ndarray*

costs

Returns a *list* with the cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

final_shape

Returns the final shape of the fitting process.

Typemenpo.shape.PointCloud

gt_shape

Returns the ground truth shape associated with the image. In case there is not an attached ground truth shape, then None is returned.

Typemenpo.shape.PointCloud or None

image

Returns the image that the fitting was applied on, if it was provided. Otherwise, it returns None.

Typemenpo.shape.Image or subclass or None

initial_shape

Returns the initial shape that was provided to the fitting method to initialise the fitting process. In case the initial shape does not exist, then None is returned.

Typemenpo.shape.PointCloud or None

is_iterative

Flag whether the object is an iterative fitting result.

Typebool

n_iters

Returns the total number of iterations of the fitting process.

Type*int*

n_iters_per_scale

Returns the number of iterations per scale of the fitting process.

Typelist of int

n_scales

Returns the number of scales used during the fitting process.

Type*int*

reconstructed_initial_shapes

Returns the result of the reconstruction step that takes place at each scale before applying the iterative optimisation.

Typelist of menpo.shape.PointCloud

shape_parameters

Returns the *list* of shape parameters obtained at each iteration of the fitting process. The *list* includes the parameters of the *initial_shape* (if it exists) and *final_shape*.

Typelist of (n_params,) ndarray

shapes

Returns the *list* of shapes obtained at each iteration of the fitting process. The *list* includes the *initial_shape* (if it exists) and *final_shape*.

Typelist of menpo.shape.PointCloud

AAMAlgorithmResult

class menpofit.aam.result.AAMAlgorithmResult(shapes, shape_parameters, appearance_parameters, initial_shape=None, image=None, gt_shape=None, costs=None)

Bases: ParametricIterativeResult

Class for storing the iterative result of an AAM optimisation algorithm.

Note: When using a method with a parametric shape model, the first step is to **reconstruct the initial shape** using the shape model. The generated reconstructed shape is then used as initialisation for the iterative optimisation. This step is not counted in the number of iterations.

Parameters

- •**shapes** (*list* of *menpo.shape.PointCloud*) The *list* of shapes per iteration. The first and last members correspond to the initial and final shapes, respectively.
- •**shape_parameters** (*list* of (n_shape_parameters,) *ndarray*) The *list* of shape parameters per iteration. The first and last members correspond to the initial and final shapes, respectively.
- •appearance_parameters (*list* of (n_appearance_parameters,) *ndarray*) The *list* of appearance parameters per iteration. The first and last members correspond to the initial and final shapes, respectively.
- •initial_shape (*menpo.shape.PointCloud* or None, optional) The initial shape from which the fitting process started. If None, then no initial shape is assigned.
- •**image** (*menpo.image.Image* or *subclass* or None, optional) The image on which the fitting process was applied. Note that a copy of the image will be assigned as an attribute. If None, then no image is assigned.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated with the image. If None, then no ground truth shape is assigned.

•costs (*list* of *float* or None, optional) – The *list* of cost per iteration. If None, then it is assumed that the cost function cannot be computed for the specific algorithm.

displacements()

A list containing the displacement between the shape of each iteration and the shape of the previous one.

Type*list* of *ndarray*

displacements_stats (stat_type='mean')

A list containing a statistical metric on the displacements between the shape of each iteration and the shape of the previous one.

Parametersstat_type ({'mean', 'median', 'min', 'max'}, optional) – Specifies a statistic metric to be extracted from the displacements.

Returnsdisplacements_stat (*list* of *float*) – The statistical metric on the points displacements for each iteration.

RaisesValueError - type must be 'mean', 'median', 'min' or 'max'

errors (compute_error=None)

Returns a list containing the error at each fitting iteration, if the ground truth shape exists.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

Returnserrors (*list* of *float*) – The error at each iteration of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

final_error(compute_error=None)

Returns the final error of the fitting process, if the ground truth shape exists. This is the error computed based on the *final_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the fitted and ground truth shapes.

Returnsfinal_error (*float*) – The final error at the end of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

initial_error(compute_error=None)

Returns the initial error of the fitting process, if the ground truth shape and initial shape exist. This is the error computed based on the *initial_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the initial and ground truth shapes.

Returnsinitial_error (*float*) – The initial error at the beginning of the fitting process.

Raises

•ValueError - Initial shape has not been set, so the initial error cannot be computed

•ValueError – Ground truth shape has not been set, so the initial error cannot be computed plot_costs (figure_id=None, new_figure=False, render_lines=True, line_colour='b', line_style='', line_width=2, render_markers=True, marker_style='o', marker_size=4,
marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0,
render_axes=True, axes_font_name='sans-serif', axes_font_size=10,
axes_font_style='normal', axes_font_weight='normal', axes_x_limits=0.0,
axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6),
render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the cost function evolution at each fitting iteration.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None, optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3,) ndarray

•line_style ({ '-', '--', '-.', ':'}, optional) – The style of the lines.

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (marker, optional) – The style of the markers. Example marker options

{'.', ',', 'o', 'v', '^', '<', '>', '+', 'x', 'D', 'd', 's', 'p', '*', 'h', 'H', '1', '2', '3', '4', '8'}

•marker_size (*int*, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_width (*float*, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (See below, optional) - The font of the axes. Example options

{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({'normal', 'italic', 'oblique'}, optional) - The font style of the axes.

•axes_font_weight (See below, optional) - The font weight of the axes. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
    'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
    'extra bold', 'black'}
```

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

- •axes_y_limits (*float* or (*float*, *float*) or None, optional) The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.
- •axes_x_ticks (list or tuple or None, optional) The ticks of the x axis.
- •axes_y_ticks (*list* or *tuple* or None, optional) The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (float, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

Plot of a statistical metric of the displacement between the shape of each iteration and the shape of the previous one.

Parameters

•**stat_type** ({mean, median, min, max}, optional) – Specifies a statistic metric to be extracted from the displacements (see also *displacements_stats()* method).

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

```
\{-, --, -., :\}
```

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (str (See below), optional) – The style of the markers. Example marker
options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int*, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

{r, g, b, c, m, k, w}
or
(3,) ndarray

•marker_edge_width (*float*, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (menpo.visualize.GraphPlotter) – The renderer object.

plot errors (compute error=None, figure_id=None, new figure=False, render lines=True, *line_colour='b'*, line_style='-', *line_width=2*, render_markers=True, marker_style='o', marker_size=4, marker_face_colour='b', marker_edge_colour='k', *marker_edge_width=1.0*, render_axes=True, axes_font_name='sans-serif', axes_font_style='normal', axes_font_size=10, axes_font_weight='normal', axes_x_limits=0.0, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure size=(10, 6), render grid=True, grid line style='-', grid line width=0.5)

Plot of the error evolution at each fitting iteration.

Parameters

•compute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

{r, g, b, c, m, k, w}
or
(3,) ndarray

•line_style (*str* (See below), optional) – The style of the lines. Example options:

{-, --, -., :}

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (float, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

reconstructed_initial_error(compute_error=None)

Returns the error of the reconstructed initial shape of the fitting process, if the ground truth shape exists. This is the error computed based on the *reconstructed_initial_shape*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the reconstructed initial and ground truth shapes.
- **Returnsreconstructed_initial_error** (*float*) The error that corresponds to the initial shape's reconstruction.
- **Raises**ValueError Ground truth shape has not been set, so the reconstructed initial error cannot be computed

to_result (*pass_image=True*, *pass_initial_shape=True*, *pass_gt_shape=True*)

Returns a *Result* instance of the object, i.e. a fitting result object that does not store the iterations. This can be useful for reducing the size of saved fitting results.

Parameters

•pass_image (bool, optional) - If True, then the image will get passed (if it exists).

•**pass_initial_shape** (*bool*, optional) – If True, then the initial shape will get passed (if it exists).

•**pass_gt_shape** (*bool*, optional) – If True, then the ground truth shape will get passed (if it exists).

Returnsresult (Result) – The final "lightweight" fitting result.

view (figure id=None, render_image=True, render_final_shape=True, new figure=False, subplots enabled=True, render initial shape=False, render_gt_shape=False, channels=None, interpolation='bilinear', cmap name=None, alpha=1.0, masked=True, final marker face colour='r', final marker edge colour='k', final line colour='r', initial marker face colour='b', initial marker edge colour='k', initial line colour='b', gt_marker_face_colour='y', gt_marker_edge_colour='k', gt_line_colour='y', render_lines=True, line_style='-', line_width=2, render_markers=True, marker_style='o', marker_size=4, marker_edge_width=1.0, render_numbering=False, numbers horizontal align='center', numbers vertical align='bottom', numbers font name='sansserif', numbers_font_size=10, numbers_font_style='normal', numbers_font_weight='normal', numbers_font_colour='k', render_legend=True, legend_title='', legend_font_name='sans*legend_font_style='normal'*, legend_font_size=10, legend_font_weight='normal', serif', legend_marker_scale=None, legend_location=2, legend_bbox_to_anchor=(1.05, 1.0), legend_border_axes_pad=None, *legend_n_columns=1*, *legend_horizontal_spacing=None*, *legend vertical spacing=None*, legend border=True, legend border padding=None, legend shadow=False, legend rounded corners=False, render axes=False, axes font name='sansaxes font size=10, axes font style='normal', serif', axes font weight='normal', axes_x_limits=None, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure size=(7, 7))

Visualize the fitting result. The method renders the final fitted shape and optionally the initial shape, ground truth shape and the image, id they were provided.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•render_final_shape (*bool*, optional) – If True, then the final fitting shape gets rendered.

•render_initial_shape (*bool*, optional) – If True and the initial fitting shape exists, then it gets rendered.

•**render_gt_shape** (*bool*, optional) – If True and the ground truth shape exists, then it gets rendered.

- •**subplots_enabled** (*bool*, optional) If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.
- •channels (*int* or *list* of *int* or all or None) If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.
- •interpolation (See Below, optional) The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

- •**cmap_name** (*str*, optional,) If None, single channel and three channel images default to greyscale and rgb colormaps respectively.
- •alpha (*float*, optional) The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•final_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_marker_edge_colour (See Below, optional) – The edge colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_line_colour (See Below, optional) – The line colour of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_edge_colour (See Below, optional) - The edge colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_line_colour (See Below, optional) – The line colour of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_edge_colour (See Below, optional) – The edge colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_line_colour (See Below, optional) – The line colour of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_lines (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•line_style (*str* or *list* of *str*, optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{ '-', '--', '-.', ':' }

•line_width (*float* or *list* of *float*, optional) – The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•marker_style (*str* or *list* of *str*, optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order.

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align ({center, right, left}, optional) - The horizontal alignment of the numbers' texts.

•numbers_vertical_align ({center, top, bottom, baseline}, optional) – The vertical alignment of the numbers' texts.

•numbers_font_name (See Below, optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (See Below, optional) – The font weight of the numbers. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (*bool*, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style ({normal, italic, oblique}, optional) - The font style of the legend.

•legend_font_size (*int*, optional) – The font size of the legend.

•legend_font_weight (See Below, optional) – The font weight of the legend. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (int, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

•legend_border (bool, optional) – If True, a frame will be drawn around the legend.

•legend_border_padding (*float*, optional) – The fractional whitespace inside the legend border.

•legend_shadow (bool, optional) – If True, a shadow will be drawn behind legend.

•legend_rounded_corners (*bool*, optional) – If True, the frame's corners will be rounded (fancybox).

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (See Below, optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (int, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (See Below, optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) - The renderer object.

view_iterations (figure_id=None, new_figure=False, iters=None, render_image=True, subplots enabled=False, channels=None, interpolation='bilinear', cmap_name=None, alpha=1.0,masked=True, render_lines=True, line style='-', line width=2, line colour=None, render markers=True, marker_edge_colour=None, marker_face_colour=None, marker_style='o', marker size=4, marker_edge_width=1.0, render_numbering=False, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers font name='sans-serif', numbers font size=10, numnumbers font weight='normal', bers font style='normal', питbers font colour='k', render legend=True, legend_title='', legend_font_name='sans-serif', legend_font_style='normal', legend_font_size=10, legend_font_weight='normal', legend_marker_scale=None, *legend location=2*, legend bbox to anchor=(1.05,1.0), legend border axes pad=None, legend n columns=1, legend horizontal spacing=None, *legend vertical spacing=None*, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sans-serif', axes_font_style='normal', axes_font_weight='normal', axes_font_size=10, axes x limits=None, axes y limits=None, axes x ticks=None, axes_y_ticks=None, figure_size=(7, 7))

Visualize the iterations of the fitting process.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•iters (*int* or *list* of *int* or None, optional) – The iterations to be visualized. If None, then all the iterations are rendered.

No.	Visualised shape	Description
0	self.initial_shape	Initial shape
1	self.reconstructed_initial_shape	Reconstructed initial
2	self.shapes[2]	Iteration 1
i	self.shapes[i]	Iteration i-1
n_iters+1	self.final_shape	Final shape

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

•channels (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (*str* (See Below), optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (*bool*, optional) – If True, then the image is rendered as masked.

•**render_lines** (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•line_style (*str* or *list* of *str* (See below), optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options:

{-, --, -., :}

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_colour (*colour* or *list* of *colour* (See Below), optional) The colour of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_style (*str or 'list* of *str* (See below), optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_edge_colour (*colour* or *list* of *colour* (See Below), optional) – The edge colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_face_colour (*colour* or *list* of *colour* (See Below), optional) – The face (filling) colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{r, g, b, c, m, k, w}
or
(3,) ndarray

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align (*str* (See below), optional) – The horizontal alignment of the numbers' texts. Example options

{center, right, left}

•numbers_vertical_align (*str* (See below), optional) – The vertical alignment of the numbers' texts. Example options

{center, top, bottom, baseline}

•numbers_font_name (*str* (See below), optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (*str* (See below), optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) - If True, the legend will be rendered.

•legend_title (str, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style (*str* (See below), optional) – The font style of the legend. Example options

{normal, italic, oblique}

•legend_font_size (int, optional) – The font size of the legend.

•legend_font_weight (*str* (See below), optional) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (*int*, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

•legend_border (bool, optional) – If True, a frame will be drawn around the legend.

•legend_border_padding (*float*, optional) – The fractional whitespace inside the legend border.

•legend_shadow (bool, optional) - If True, a shadow will be drawn behind legend.

•legend_rounded_corners (*bool*, optional) – If True, the frame's corners will be rounded (fancybox).

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) - The renderer object.

view_widget (figure_size=(7, 7))

Visualizes the result object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

appearance_parameters

Returns the *list* of appearance parameters obtained at each iteration of the fitting process. The *list* includes the parameters of the *initial_shape* (if it exists) and *final_shape*.

Type*list* of (n_params,) *ndarray*

costs

Returns a *list* with the cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

final_shape

Returns the final shape of the fitting process.

Typemenpo.shape.PointCloud

gt_shape

Returns the ground truth shape associated with the image. In case there is not an attached ground truth shape, then None is returned.

Typemenpo.shape.PointCloud or None

image

Returns the image that the fitting was applied on, if it was provided. Otherwise, it returns None.

Typemenpo.shape.Image or subclass or None

initial_shape

Returns the initial shape that was provided to the fitting method to initialise the fitting process. In case the initial shape does not exist, then None is returned.

Typemenpo.shape.PointCloud or None

is_iterative

Flag whether the object is an iterative fitting result.

Typebool

n_iters

Returns the total number of iterations of the fitting process.

Typeint

reconstructed_initial_shape

Returns the initial shape's reconstruction with the shape model that was used to initialise the iterative optimisation process.

Typemenpo.shape.PointCloud

shape_parameters

Returns the *list* of shape parameters obtained at each iteration of the fitting process. The *list* includes the parameters of the *reconstructed_initial_shape* and *final_shape*.

Typelist of (n_params,) ndarray

shapes

Returns the *list* of shapes obtained at each iteration of the fitting process. The *list* includes the *initial_shape* (if it exists), *reconstructed_initial_shape* and *final_shape*.

Typelist of menpo.shape.PointCloud

Pre-Trained Model

load_balanced_frontal_face_fitter

menpofit.aam.load_balanced_frontal_face_fitter()

Loads a frontal face patch-based AAM fitter that is a good compromise between model size, fitting time and fitting performance. The model returns 68 facial landmark points (the standard IBUG68 markup).

Note that the first time you invoke this function, menpofit will download the fitter from Menpo's server. The fitter will then be stored locally for future use.

The model is a *PatchAAM* trained using the following parameters:

Parameter	Value
diagonal	110
scales	(0.5, 1.0)
patch_shape	[(13, 13), (13, 13)]
holistic_features	menpo.feature.fast_dsift()
n_shape	[5, 20]
n_appearance	[30, 150]
lk_algorithm_cls	WibergInverseCompositional

It is also using the following sampling grid:

import numpy as np

```
patch_shape = (13, 13)
sampling_step = 4
sampling_grid = np.zeros(patch_shape, dtype=np.bool)
sampling_grid[::sampling_step, ::sampling_step] = True
sampling = [sampling_grid, sampling_grid]
```

Additionally, it is trained on LFPW trainset, HELEN trainset, IBUG and AFW datasets (3283 images in total), which are hosted in http://ibug.doc.ic.ac.uk/resources/facial-point-annotations/.

Returnsfitter (*LucasKanadeAAMFitter*) – A pre-trained *LucasKanadeAAMFitter* based on a *PatchAAM* that performs facial landmark localization returning 68 points (iBUG68).

menpofit.aps

Active Pictorial Structures

APS is a model that utilises a Gaussian Markov Random Field (GMRF) for learning an appearance model with pairwise distributions based on a graph. It also has a parametric statitical shape model (either using PCA or GMRF), as well as a spring-like deformation prior term. The optimisation is performed using a weighted Gauss-Newton algorithm with fixed Jacobian and Hessian.

GenerativeAPS

```
group=None,
class menpofit.aps.GenerativeAPS (images,
                                                                            appearance graph=None,
                                                                 deformation_graph=None,
                                         shape_graph=None,
                                                                                               holis-
                                                                              reference shape=None,
                                         tic features=<function
                                                                  no op>,
                                         diagonal=None,
                                                            scales = (0.5, 
                                                                           1.0).
                                                                                   patch shape=(17,
                                         17),
                                                       patch_normalisation=<function
                                                                                            no_{op>},
                                         use_procrustes=True,
                                                                              precision_dtype=<type</pre>
                                                                       max_shape_components=None,
                                         'numpy.float32'>,
                                         n_appearance_components=None, can_be_incremented=False,
                                         verbose=False, batch_size=None)
```

Bases: object

Class for training a multi-scale Generative Active Pictorial Structures model. Please see the references for a basic list of relevant papers.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•group (*str* or None, optional) – The landmark group that will be used to train the AAM. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.

- •appearance_graph (*list* of graphs or a single graph or None, optional) The graph to be used for the appearance *menpo.model.GMRFModel* training. It must be a *menpo.shape.UndirectedGraph*. If None, then a *menpo.model.PCAModel* is used instead.
- •**shape_graph** (*list* of graphs or a single graph or None, optional) The graph to be used for the shape *menpo.model.GMRFModel* training. It must be a *menpo.shape.UndirectedGraph*. If None, then the shape model is built using *menpo.model.PCAModel*.
- •deformation_graph (*list* of graphs or a single graph or None, optional) The graph to be used for the deformation *menpo.model.GMRFModel* training. It must be either a *menpo.shape.DirectedGraph* or a *menpo.shape.Tree*. If None, then the minimum spanning tree of the data is computed.
- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •**reference_shape** (*menpo.shape.PointCloud* or None, optional) The reference shape that will be used for building the APS. The purpose of the reference shape is to normalise

the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.

- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •**patch_shape** ((*int*, *int*) or *list* of (*int*, *int*), optional) The shape of the patches to be extracted. If a *list* is provided, then it defines a patch shape per scale.
- •patch_normalisation (*list* of *callable* or a single *callable*, optional) The normalisation function to be applied on the extracted patches. If *list*, then it must have length equal to the number of scales. If a single patch normalization *callable*, then this is the one applied to all scales.
- •use_procrustes (*bool*, optional) If True, then Generalized Procrustes Alignment is applied before building the deformation model.
- •**precision_dtype** (*numpy.dtype*, optional) The data type of the appearance GMRF's precision matrix. For example, it can be set to *numpy.float32* for single precision or to *numpy.float64* for double precision. Even though the precision matrix is stored as a *scipy.sparse* matrix, this parameter has a big impact on the amount of memory required by the model.
- •max_shape_components (*int*, *float*, *list* of those or None, optional) The number of shape components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •n_appearance_components (*list* of *int* or *int* or None, optional) The number of appearance components used for building the appearance *menpo.shape.GMRFModel*. If *list*, then it must have length equal to the number of scales. If a single *int*, then this is the one applied to all scales. If None, the covariance matrix of each edge is inverted using *np.linalg.inv*. If *int*, it is inverted using truncated SVD using the specified number of components.
- •can_be_incremented (*bool*, optional) In case you intend to incrementally update the model in the future, then this flag must be set to True from the first place. Note that if True, the appearance and deformation *menpo.shape.GMRFModel* models will occupy double memory.
- •verbose (bool, optional) If True, then the progress of building the APS will be printed.
- •**batch_size** (*int* or None, optional) If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

References

increment (images, group=None, batch_size=None, verbose=False)

Method that incrementally updates the APS model with a new batch of training images.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•group (*str* or None, optional) – The landmark group that will be used to train the APS. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

•verbose (*bool*, optional) – If True, then the progress of building the APS will be printed.

instance (*shape_weights=None*, *scale_index=-1*, *as_graph=False*) Generates an instance of the shape model.

Parameters

•**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.

•scale_index (*int*, optional) – The scale to be used.

•**as_graph** (*bool*, optional) – If True, then the instance will be returned as a *menpo.shape.PointTree* or a *menpo.shape.PointDirectedGraph*, depending on the type of the deformation graph.

random_instance(scale_index=-1, as_graph=False)

Generates a random instance of the APS.

Parameters

•scale_index (int, optional) – The scale to be used.

•**as_graph** (*bool*, optional) – If True, then the instance will be returned as a *menpo.shape.PointTree* or a *menpo.shape.PointDirectedGraph*, depending on the type of the deformation graph.

view_appearance_graph_widget (scale_index=-1, figure_size=(7, 7))

Visualize the appearance graph using an interactive widget.

Parameters

•scale_index (*int*, optional) – The scale to be used.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

RaisesValueError - Scale level {scale_index} uses a PCA appearance model, so there is no graph

view_deformation_graph_widget (scale_index=-1, figure_size=(7, 7))

Visualize the deformation graph using an interactive widget.

Parameters

•scale_index (*int*, optional) – The scale to be used.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

view deformation model (scale index=-1, n std=2, render colour bar=False, colour_map='jet', image_view=True, figure id=None, new figure=False, render graph lines=True, graph line colour='b', graph_line_style='-', graph_line_width=1.0, ellipse_line_colour='r', ellipse line style='-', ellipse line width=1.0, render markers=True, marker_style='o', marker size=5, marker face colour='k', marker_edge_colour='k'. marker edge width=1.0. render_axes=False, axes_font_name='sans-serif', axes_font_size=10, axes_font_style='normal', axes_font_weight='normal', $crop_proportion=0.1, figure_size=(7, 7))$

Visualize the deformation model by plotting a Gaussian ellipsis per graph edge.

Parameters

•scale_index (int, optional) – The scale to be used.

- •**n_std** (*float*, optional) This defines the size of the ellipses in terms of number of standard deviations.
- •**render_colour_bar** (*bool*, optional) If True, then the ellipses will be coloured based on their normalized standard deviations and a colour bar will also appear on the side. If False, then all the ellipses will have the same colour.

•colour_map (*str*, optional) – A valid Matplotlib colour map. For more info, please refer to *matplotlib.cm*.

- •**image_view** (*bool*, optional) If True the ellipses will be rendered in the image coordinates system.
- •figure_id (*object*, optional) The id of the figure to be used.
- •new_figure (bool, optional) If True, a new figure is created.

•render_graph_lines (bool, optional) – Defines whether to plot the graph's edges.

•graph_line_colour (See Below, optional) – The colour of the lines of the graph's edges. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•graph_line_style ({-, --, -., :}, optional) – The style of the lines of the graph's edges.

•graph_line_width (float, optional) – The width of the lines of the graph's edges.

•ellipse_line_colour (See Below, optional) – The colour of the lines of the ellipses. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•ellipse_line_style ({-, --, -., :}, optional) – The style of the lines of the ellipses.

•ellipse_line_width (float, optional) – The width of the lines of the ellipses.

•render_markers (*bool*, optional) – If True, the centers of the ellipses will be rendered.

•marker_style (See Below, optional) – The style of the centers of the ellipses. Example options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the centers of the ellipses in points.

•marker_face_colour (See Below, optional) – The face (filling) colour of the centers of the ellipses. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (See Below, optional) – The edge colour of the centers of the ellipses. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float*, optional) – The edge width of the centers of the ellipses.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (See Below, optional) - The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (See Below, optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•crop_proportion (*float*, optional) – The proportion to be left around the centers' pointcloud.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

view_shape_graph_widget (*scale_index=-1*, *figure_size=*(7, 7)) Visualize the shape graph using an interactive widget.

Parameters

•scale_index (int, optional) – The scale to be used.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

RaisesValueError - Scale level {scale_index} uses a PCA shape model, so there is no graph

view_shape_models_widget (n_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure_size=(7, 7))

Visualizes the shape models of the APS object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•**parameters_bounds** ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

n_scales

Returns the number of scales.

Typeint

Fitters

GaussNewtonAPSFitter

class menpofit.aps.GaussNewtonAPSFitter (aps, gn_algorithm_cls=<class 'menpofit.aps.algorithm.gn.Inverse'>, n_shape=None, weight=200.0, sampling=None)

Bases: APSFitter

A class for fitting an APS model with Gauss-Newton optimization.

Note: When using a method with a parametric shape model, the first step is to **reconstruct the initial shape** using the shape model. The generated reconstructed shape is then used as initialisation for the iterative optimisation. This step takes place at each scale and it is not considered as an iteration, thus it is not counted for the provided *max_iters*.

Parameters

•aps (GenerativeAPS or subclass) – The trained model.

•gn_algorithm_cls (*class*, optional) – The Gauss-Newton optimisation algorithm that will get applied. The possible algorithms are *Inverse* and *Forward*. Note that the *Forward* algorithm is too slow. It is not recommended to be used for fitting an APS and is only included for comparison purposes.

•n_shape (*int* or *float* or *list* of those or None, optional) – The number of shape components that will be used. If *int*, then it defines the exact number of active components. If *float*, then it defines the percentage of variance to keep. If *int* or *float*, then the provided value will be applied for all scales. If *list*, then it defines a value per scale. If None, then all the available components will be used. Note that this simply sets the active components without trimming the unused ones. Also, the available components may have already been trimmed to *max_shape_components* during training.

•weight (*float* or *list* of *float*, optional) – The weight between the appearance cost and the deformation cost. The provided value gets multiplied with the deformation cost. If *float*, then the provided value will be used for all scales. If *list*, then it should define a value per scale.

•**sampling** (*list* of *int* or *ndarray* or None) – It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied. Note that depending on the model and the size of the appearance precision matrix, the sub-sampling may be impossible to be applied due to insufficient memory. This is because the sub-sampling of the appearance precision matrix, sub-sampling it and re-convert it back to *scipy.sparse.bsr_matrix*, which is a memory intensive procedure.

fit_from_bb (*image*, *bounding_box*, *max_iters=20*, *gt_shape=None*, *return_costs=False*, ***kwargs*) Fits the multi-scale fitter to an image given an initial bounding box.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •bounding_box (*menpo.shape.PointDirectedGraph*) The initial bounding box from which the fitting procedure will start. Note that the bounding box is used in order to align the model's reference shape.
- •max_iters (*int* or *list* of *int*, optional) The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.
- •gt_shape (*menpo.shape.PointCloud*, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

Fits the multi-scale fitter to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape estimate from which the fitting procedure will start.

•max_iters (*int* or *list* of *int*, optional) – The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes. •**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

warped_images (image, shapes)

Given an input test image and a list of shapes, it warps the image into the shapes. This is useful for generating the warped images of a fitting procedure stored within an *APSResult*.

Parameters

•image (menpo.image.Image or subclass) – The input image to be warped.

•**shapes** (*list* of *menpo.shape.PointCloud*) – The list of shapes in which the image will be warped. The shapes are obtained during the iterations of a fitting procedure.

Returnswarped_images (*list* of *menpo.image.MaskedImage* or *ndarray*) – The warped images.

aps

The trained APS model.

Type*GenerativeAPS* or subclass

holistic_features

The features that are extracted from the input image at each scale in ascending order, i.e. from lowest to highest scale.

Type*list* of *closure*

n_scales

Returns the number of scales.

Type*int*

reference_shape

The reference shape that is used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of this reference shape.

Typemenpo.shape.PointCloud

scales

The scale value of each scale in ascending order, i.e. from lowest to highest scale.

Typelist of int or float

Gauss-Newton Optimisation Algorithms

Inverse

```
class menpofit.aps.Inverse (aps_interface, eps=1e-05)
Bases: GaussNewton
```

Inverse Gauss-Newton algorithm for APS.

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*) Execute the optimization algorithm.

Parameters

•image (menpo.image.Image) – The input test image.

- •**initial_shape** (*menpo.shape.PointCloud*) The initial shape from which the optimization will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.
- •max_iters (*int*, optional) The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

Returnsfitting_result (APSAlgorithmResult) - The parametric iterative fitting result.

appearance_model

Returns the appearance GMRF model.

Typemenpo.model.GMRFModel

deformation_model

Returns the deformation GMRF model.

Typemenpo.model.GMRFModel

template

Returns the template (usually the mean appearance).

Typemenpo.image.Image

transform

Returns the motion model.

TypeOrthoPDM

Forward

class menpofit.aps.Forward(aps_interface, eps=1e-05)

Bases: GaussNewton

Forward Gauss-Newton algorithm for APS.

Note: The Forward optimization is too slow. It is not recommended to be used for fitting an APS and is only included for comparison purposes. Use *Inverse* instead.

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*) Execute the optimization algorithm.

Parameters

•image (menpo.image.Image) – The input test image.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start. •gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

Returnsfitting_result (*APSAlgorithmResult*) – The parametric iterative fitting result.

appearance_model

Returns the appearance GMRF model.

Typemenpo.model.GMRFModel

deformation_model

Returns the deformation GMRF model.

Typemenpo.model.GMRFModel

template

Returns the template (usually the mean appearance).

Typemenpo.image.Image

transform

Returns the motion model.

TypeOrthoPDM

Fitting Result

APSResult

Class for storing the multi-scale iterative fitting result of an APS. It holds the shapes, shape parameters, appearance parameters and costs per iteration.

Note: When using a method with a parametric shape model, the first step is to **reconstruct the initial shape** using the shape model. The generated reconstructed shape is then used as initialisation for the iterative optimisation. This step is not counted in the number of iterations.

Parameters

•results (list of APSAlgorithmResult) – The list of optimization results per scale.

•scales (*list* or *tuple*) – The *list* of scale values per scale (low to high).

•affine_transforms (*list* of *menpo.transform.Affine*) – The list of affine transforms per scale that transform the shapes into the original image space.

- •scale_transforms (*list* of *menpo.shape.Scale*) The list of scaling transforms per scale.
- •**image** (*menpo.image.Image* or *subclass* or None, optional) The image on which the fitting process was applied. Note that a copy of the image will be assigned as an attribute. If None, then no image is assigned.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated with the image. If None, then no ground truth shape is assigned.

displacements()

A list containing the displacement between the shape of each iteration and the shape of the previous one.

Typelist of ndarray

displacements_stats (stat_type='mean')

- A list containing a statistical metric on the displacements between the shape of each iteration and the shape of the previous one.
 - **Parametersstat_type** ({'mean', 'median', 'min', 'max'}, optional) Specifies a statistic metric to be extracted from the displacements.
 - **Returnsdisplacements_stat** (*list* of *float*) The statistical metric on the points displacements for each iteration.

RaisesValueError - type must be 'mean', 'median', 'min' or 'max'

errors (compute_error=None)

Returns a list containing the error at each fitting iteration, if the ground truth shape exists.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

Returnserrors (*list* of *float*) – The error at each iteration of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

final_error(compute_error=None)

Returns the final error of the fitting process, if the ground truth shape exists. This is the error computed based on the *final_shape*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the fitted and ground truth shapes.
- **Returnsfinal_error** (*float*) The final error at the end of the fitting process.
- **Raises**ValueError Ground truth shape has not been set, so the final error cannot be computed

initial_error(compute_error=None)

- Returns the initial error of the fitting process, if the ground truth shape and initial shape exist. This is the error computed based on the *initial_shape*.
 - **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the initial and ground truth shapes.
 - **Returnsinitial_error** (*float*) The initial error at the beginning of the fitting process.

Raises

•ValueError - Initial shape has not been set, so the initial error cannot be computed

•ValueError – Ground truth shape has not been set, so the initial error cannot be computed

plot_costs (figure_id=None, new_figure=False, render_lines=True, line_colour='b', line_style='', line_width=2, render_markers=True, marker_style='o', marker_size=4,
marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0,
render_axes=True, axes_font_name='sans-serif', axes_font_size=10,
axes_font_style='normal', axes_font_weight='normal', axes_font_size=0.0,
axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6),
render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the cost function evolution at each fitting iteration.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None, optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•line_style ({ '-', '--', '-.', ': '}, optional) – The style of the lines.

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) - If True, the markers will be rendered.

•marker_style (marker, optional) – The style of the markers. Example marker options

{'.', ',', 'o', 'v', '^', '<', '>', '+', 'x', 'D', 'd', 's', 'p', '*', 'h', 'H', '1', '2', '3', '4', '8'}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (See below, optional) - The font of the axes. Example options

{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}

•axes_font_size (*int*, optional) – The font size of the axes.

```
•axes_font_style ({'normal', 'italic', 'oblique'}, optional) - The font style of the axes.
```

•axes_font_weight (See below, optional) - The font weight of the axes. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
    'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
    'extra bold', 'black'}
```

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (float, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

Plot of a statistical metric of the displacement between the shape of each iteration and the shape of the previous one.

Parameters

•**stat_type** ({mean, median, min, max}, optional) – Specifies a statistic metric to be extracted from the displacements (see also *displacements_stats()* method).

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

{-, --, -., :}

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) - If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (float, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

plot_errors (compute_error=None, figure_id=None, new_figure=False, render_lines=True, line colour='b'. line style='-', line width=2, render markers=True, marker_style='o', marker_size=4, marker_face_colour='b', marker_edge_colour='k', marker edge width=1.0, render axes=True, axes font name='sans-serif', axes_font_size=10, axes_font_style='normal', axes_font_weight='normal', axes x limits=0.0, axes y limits=None, axes x ticks=None, axes y ticks=None, figure_size=(10, 6), render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the error evolution at each fitting iteration.

Parameters

•compute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

{-, --, -., :}

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

```
{normal, italic, oblique}
```

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (*list* or *tuple* or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (menpo.visualize.GraphPlotter) – The renderer object.

reconstructed_initial_error(compute_error=None)

Returns the error of the reconstructed initial shape of the fitting process, if the ground truth shape exists. This is the error computed based on the *reconstructed_initial_shapes[0]*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the reconstructed initial and ground truth shapes.
- **Returnsreconstructed_initial_error** (*float*) The error that corresponds to the initial shape's reconstruction.
- **Raises**ValueError Ground truth shape has not been set, so the reconstructed initial error cannot be computed

to_result (*pass_image=True*, *pass_initial_shape=True*, *pass_gt_shape=True*)

Returns a *Result* instance of the object, i.e. a fitting result object that does not store the iterations. This can be useful for reducing the size of saved fitting results.

Parameters

•pass_image (bool, optional) – If True, then the image will get passed (if it exists).

•**pass_initial_shape** (*bool*, optional) – If True, then the initial shape will get passed (if it exists).

•**pass_gt_shape** (*bool*, optional) – If True, then the ground truth shape will get passed (if it exists).

Returnsresult (*Result*) – The final "lightweight" fitting result.

view (figure id=None, new figure=False, render image=True, render final shape=True, render_gt_shape=False, render initial shape=False, subplots enabled=True, channels=None, interpolation='bilinear', cmap_name=None, alpha=1.0, masked=True, final_marker_face_colour='r', final_marker_edge_colour='k', final_line_colour='r', initial_marker_face_colour='b', *initial_marker_edge_colour='k'*, initial_line_colour='b', gt_marker_edge_colour='k', gt_marker_face_colour='y', gt_line_colour='y', render_lines=True, line_style='-', line_width=2, render_markers=True, marker_style='o', marker_size=4, *marker_edge_width=1.0*, render_numbering=False, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers_font_name='sansserif', numbers_font_size=10, numbers_font_style='normal', numbers_font_weight='normal', numbers_font_colour='k', render_legend=True, legend_title='', legend_font_name='sanslegend_font_style='normal', legend_font_size=10, legend_font_weight='normal', serif', legend marker scale=None, legend location=2, legend bbox to anchor=(1.05, 1.0), legend_border_axes_pad=None, *legend_n_columns=1*, legend_horizontal_spacing=None, *legend vertical spacing=None*, legend border=True, legend border padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sansserif', axes font size=10, axes font style='normal', axes font weight='normal', axes x limits=None, axes y limits=None, axes x ticks=None, figure size=(7, 7))

Visualize the fitting result. The method renders the final fitted shape and optionally the initial shape, ground truth shape and the image, id they were provided.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•render_final_shape (*bool*, optional) – If True, then the final fitting shape gets rendered.
- •render_initial_shape (*bool*, optional) If True and the initial fitting shape exists, then it gets rendered.
- •render_gt_shape (*bool*, optional) If True and the ground truth shape exists, then it gets rendered.
- •**subplots_enabled** (*bool*, optional) If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.
- •channels (*int* or *list* of *int* or all or None) If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.
- •interpolation (See Below, optional) The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•final_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_marker_edge_colour (See Below, optional) – The edge colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_line_colour (See Below, optional) – The line colour of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_edge_colour (See Below, optional) – The edge colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_line_colour (See Below, optional) – The line colour of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_edge_colour (See Below, optional) – The edge colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_line_colour (See Below, optional) – The line colour of the ground truth shape. Example options

{r, g, b, c, m, k, w}
or
(3,) ndarray

•**render_lines** (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•line_style (*str* or *list* of *str*, optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{ '-', '--', '-.', ':' }

•line_width (*float* or *list* of *float*, optional) – The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•marker_style (*str* or *list* of *str*, optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order.

- •marker_edge_width (*float* or *list* of *float*, optional) The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.
- •render_numbering (bool, optional) If True, the landmarks will be numbered.
- •numbers_horizontal_align ({center, right, left}, optional) The horizontal alignment of the numbers' texts.
- •numbers_vertical_align ({center, top, bottom, baseline}, optional) The vertical alignment of the numbers' texts.
- •numbers_font_name (See Below, optional) The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (See Below, optional) – The font weight of the numbers. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (*bool*, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

- •legend_font_style ({normal, italic, oblique}, optional) The font style of the legend.
- •legend_font_size (*int*, optional) The font size of the legend.

•legend_font_weight (See Below, optional) – The font weight of the legend. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

- •legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) The bbox that the legend will be anchored.
- •legend_border_axes_pad (*float*, optional) The pad between the axes and legend border.
- •legend_n_columns (int, optional) The number of the legend's columns.
- •legend_horizontal_spacing (*float*, optional) The spacing between the columns.
- •legend_vertical_spacing (*float*, optional) The vertical space between the legend entries.
- •legend_border (bool, optional) If True, a frame will be drawn around the legend.
- •legend_border_padding (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.
- •legend_rounded_corners (*bool*, optional) If True, the frame's corners will be rounded (fancybox).
- •render_axes (bool, optional) If True, the axes will be rendered.
- •axes_font_name (See Below, optional) The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

- •axes_font_size (int, optional) The font size of the axes.
- •axes_font_style ({normal, italic, oblique}, optional) The font style of the axes.
- •axes_font_weight (See Below, optional) The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) - The renderer object.

view_iterations (figure_id=None, new_figure=False, iters=None, render_image=True, subplots enabled=False, channels=None, interpolation='bilinear', cmap_name=None, alpha=1.0,masked=True, render_lines=True, line style='-', line width=2, line colour=None, render markers=True, marker_edge_colour=None, marker_face_colour=None, marker_style='o', marker size=4, marker_edge_width=1.0, render_numbering=False, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers font name='sans-serif', numbers font size=10, numnumbers font weight='normal', bers font style='normal', питbers font colour='k', render legend=True, legend_title='', legend_font_name='sans-serif', legend_font_style='normal', legend_font_size=10, legend_font_weight='normal', legend_marker_scale=None, legend location=2, legend bbox to anchor=(1.05,1.0), legend border axes pad=None, legend n columns=1, legend horizontal spacing=None, *legend vertical spacing=None*, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sans-serif', axes_font_style='normal', axes_font_weight='normal', axes_font_size=10, axes x limits=None, axes y limits=None, axes x ticks=None, axes_y_ticks=None, figure_size=(7, 7))

Visualize the iterations of the fitting process.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•iters (*int* or *list* of *int* or None, optional) – The iterations to be visualized. If None, then all the iterations are rendered.

No.	Visualised shape	Description
0	self.initial_shape	Initial shape
1	self.reconstructed_initial_shape	Reconstructed initial
2	self.shapes[2]	Iteration 1
i	self.shapes[i]	Iteration i-1
n_iters+1	self.final_shape	Final shape

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

•channels (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (*str* (See Below), optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•**render_lines** (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•line_style (*str* or *list* of *str* (See below), optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options:

{-, --, -., :}

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_colour (*colour* or *list* of *colour* (See Below), optional) The colour of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_style (*str or 'list* of *str* (See below), optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_edge_colour (*colour* or *list* of *colour* (See Below), optional) – The edge colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_face_colour (*colour* or *list* of *colour* (See Below), optional) – The face (filling) colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{r, g, b, c, m, k, w}
or
(3,) ndarray

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align (*str* (See below), optional) – The horizontal alignment of the numbers' texts. Example options

{center, right, left}

•numbers_vertical_align (*str* (See below), optional) – The vertical alignment of the numbers' texts. Example options

{center, top, bottom, baseline}

•numbers_font_name (*str* (See below), optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (*str* (See below), optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) - If True, the legend will be rendered.

•legend_title (str, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style (*str* (See below), optional) – The font style of the legend. Example options

{normal, italic, oblique}

•legend_font_size (*int*, optional) – The font size of the legend.

•legend_font_weight (*str* (See below), optional) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (*int*, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

•legend_border (bool, optional) – If True, a frame will be drawn around the legend.

•legend_border_padding (*float*, optional) – The fractional whitespace inside the legend border.

•legend_shadow (bool, optional) - If True, a shadow will be drawn behind legend.

•legend_rounded_corners (*bool*, optional) – If True, the frame's corners will be rounded (fancybox).

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) - The renderer object.

view_widget (figure_size=(7, 7))

Visualizes the result object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

appearance_costs

Returns a list with the appearance cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

costs

Returns a *list* with the cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

deformation_costs

Returns a list with the deformation cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

final_shape

Returns the final shape of the fitting process.

Typemenpo.shape.PointCloud

gt_shape

Returns the ground truth shape associated with the image. In case there is not an attached ground truth shape, then None is returned.

Typemenpo.shape.PointCloud or None

image

Returns the image that the fitting was applied on, if it was provided. Otherwise, it returns None.

Typemenpo.shape.Image or subclass or None

initial_shape

Returns the initial shape that was provided to the fitting method to initialise the fitting process. In case the initial shape does not exist, then None is returned.

Typemenpo.shape.PointCloud or None

is_iterative

Flag whether the object is an iterative fitting result.

Typebool

n_iters

Returns the total number of iterations of the fitting process.

Typeint

n_iters_per_scale

Returns the number of iterations per scale of the fitting process.

Typelist of int

n_scales

Returns the number of scales used during the fitting process.

Type*int*

reconstructed_initial_shapes

Returns the result of the reconstruction step that takes place at each scale before applying the iterative optimisation.

Typelist of menpo.shape.PointCloud

shape_parameters

Returns the *list* of shape parameters obtained at each iteration of the fitting process. The *list* includes the parameters of the *initial_shape* (if it exists) and *final_shape*.

Typelist of (n_params,) ndarray

shapes

Returns the *list* of shapes obtained at each iteration of the fitting process. The *list* includes the *initial_shape* (if it exists) and *final_shape*.

Typelist of menpo.shape.PointCloud

APSAlgorithmResult

class menpofit.aps.result.APSAlgorithmResu	lt (<i>shapes</i> ,	shap	e_parameters,	ini-
	tial_shape=	None,	image=	=None,
	gt_shape=N	Vone,	appearance_costs=	=None,
	deformation	deformation_costs=None, costs=None		
Bases: ParametricIterativeResult				

Class for storing the iterative result of an APS optimisation algorithm.

Note: When using a method with a parametric shape model, the first step is to **reconstruct the initial shape** using the shape model. The generated reconstructed shape is then used as initialisation for the iterative optimisation. This step is not counted in the number of iterations.

Parameters

•**shapes** (*list* of *menpo.shape.PointCloud*) – The *list* of shapes per iteration. The first and last members correspond to the initial and final shapes, respectively.

•**shape_parameters** (*list* of (n_shape_parameters,) *ndarray*) – The *list* of shape parameters per iteration. The first and last members correspond to the initial and final shapes, respectively.

- •initial_shape (*menpo.shape.PointCloud* or None, optional) The initial shape from which the fitting process started. If None, then no initial shape is assigned.
- •**image** (*menpo.image.Image* or *subclass* or None, optional) The image on which the fitting process was applied. Note that a copy of the image will be assigned as an attribute. If None, then no image is assigned.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated with the image. If None, then no ground truth shape is assigned.
- •appearance_costs (*list* of *float* or None, optional) The *list* of the appearance cost per iteration. If None, then it is assumed that the cost function cannot be computed for the specific algorithm.
- •deformation_costs (*list* of *float* or None, optional) The *list* of the deformation cost per iteration. If None, then it is assumed that the cost function cannot be computed for the specific algorithm.
- •costs (*list* of *float* or None, optional) The *list* of the total cost per iteration. If None, then it is assumed that the cost function cannot be computed for the specific algorithm.

displacements()

A list containing the displacement between the shape of each iteration and the shape of the previous one.

Typelist of ndarray

displacements_stats (stat_type='mean')

A list containing a statistical metric on the displacements between the shape of each iteration and the shape of the previous one.

- **Parametersstat_type** ({'mean', 'median', 'min', 'max'}, optional) Specifies a statistic metric to be extracted from the displacements.
- **Returnsdisplacements_stat** (*list* of *float*) The statistical metric on the points displacements for each iteration.
- RaisesValueError type must be 'mean', 'median', 'min' or 'max'

errors (compute_error=None)

Returns a list containing the error at each fitting iteration, if the ground truth shape exists.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

Returnserrors (*list* of *float*) – The error at each iteration of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

final_error (compute_error=None)

Returns the final error of the fitting process, if the ground truth shape exists. This is the error computed based on the *final_shape*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the fitted and ground truth shapes.
- **Returnsfinal_error** (*float*) The final error at the end of the fitting process.
- **Raises**ValueError Ground truth shape has not been set, so the final error cannot be computed

initial_error(compute_error=None)

Returns the initial error of the fitting process, if the ground truth shape and initial shape exist. This is the error computed based on the *initial_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the initial and ground truth shapes.

Returnsinitial_error (*float*) – The initial error at the beginning of the fitting process.

Raises

•ValueError - Initial shape has not been set, so the initial error cannot be computed

•ValueError – Ground truth shape has not been set, so the initial error cannot be computed

plot_costs (figure_id=None, new_figure=False, render_lines=True, line_colour='b', line_style='line_width=2, render_markers=True, marker_style='o', marker_size=4, **'**, marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0, render_axes=True, axes_font_name='sans-serif', axes_font_size=10, axes font style='normal', axes font weight='normal'. axes x limits=0.0, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6), render grid=True, grid line style='-', grid line width=0.5)

Plot of the cost function evolution at each fitting iteration.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None, optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3,) ndarray

•line_style ({ '-', '--', '-.', ':'}, optional) – The style of the lines.

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (marker, optional) – The style of the markers. Example marker options

{'.', ',', 'o', 'v', '^', '<', '>', '+', 'x', 'D', 'd', 's', 'p', '*', 'h', 'H', '1', '2', '3', '4', '8'}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (See below, optional) - The font of the axes. Example options

{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({'normal', 'italic', 'oblique'}, optional) - The font style of the axes.

•axes_font_weight (See below, optional) – The font weight of the axes. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
    'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
    'extra bold', 'black'}
```

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

Plot of a statistical metric of the displacement between the shape of each iteration and the shape of the previous one.

Parameters

•**stat_type** ({mean, median, min, max}, optional) – Specifies a statistic metric to be extracted from the displacements (see also *displacements_stats()* method).

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

```
\{-, --, -., :\}
```

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) - If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

```
{normal, italic, oblique}
```

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (menpo.visualize.GraphPlotter) – The renderer object.

plot errors (compute error=None, figure_id=None, new_figure=False, render lines=True, render_markers=True, line width=2, line_colour='b', line_style='-', marker_style='o', marker_size=4, marker_face_colour='b', marker_edge_colour='k', marker edge width=1.0, render axes=True, axes font name='sans-serif', axes_font_style='normal', axes_font_weight='normal', axes_font_size=10, axes x limits=0.0, axes y limits=None, axes x ticks=None, axes y ticks=None, figure size=(10, 6), render grid=True, grid line style='-', grid line width=0.5)

Plot of the error evolution at each fitting iteration.

Parameters

•compute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

{r, g, b, c, m, k, w}
or
(3,) ndarray

•line_style (*str* (See below), optional) – The style of the lines. Example options:

{-, --, -., :}

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (str (See below), optional) – The style of the markers. Example marker
options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (int, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (menpo.visualize.GraphPlotter) - The renderer object.

reconstructed_initial_error(compute_error=None)

Returns the error of the reconstructed initial shape of the fitting process, if the ground truth shape exists. This is the error computed based on the *reconstructed_initial_shape*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the reconstructed initial and ground truth shapes.
- **Returnsreconstructed_initial_error** (*float*) The error that corresponds to the initial shape's reconstruction.
- **Raises**ValueError Ground truth shape has not been set, so the reconstructed initial error cannot be computed
- to_result (pass_image=True, pass_initial_shape=True, pass_gt_shape=True)

Returns a *Result* instance of the object, i.e. a fitting result object that does not store the iterations. This can be useful for reducing the size of saved fitting results.

Parameters

•pass_image (bool, optional) – If True, then the image will get passed (if it exists).

•**pass_initial_shape** (*bool*, optional) – If True, then the initial shape will get passed (if it exists).

•**pass_gt_shape** (*bool*, optional) – If True, then the ground truth shape will get passed (if it exists).

Returnsresult (*Result*) – The final "lightweight" fitting result.

view (*figure_id=None*, *new_figure=False*, *render_image=True*, *render_final_shape=True*, *subplots_enabled=True*, *render_initial_shape=False*, *render_gt_shape=False*, channels=None, interpolation='bilinear', cmap_name=None, alpha=1.0, masked=True, final marker_face_colour='r', final_marker_edge_colour='k', final_line_colour='r', initial_marker_face_colour='b', *initial_marker_edge_colour='k'*, initial line colour='b', gt marker face colour='y', gt_marker_edge_colour='k', gt line colour='y', render_lines=True, line_style='-', line_width=2, render_markers=True, marker_style='o', marker_size=4, marker edge width=1.0, render numbering=False, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers_font_name='sansserif', numbers font size=10, numbers font style='normal', numbers font weight='normal', numbers_font_colour='k', render_legend=True, legend_title='', legend_font_name='sansserif', legend_font_style='normal', legend_font_size=10, legend_font_weight='normal', legend_marker_scale=None, legend_location=2, legend_bbox_to_anchor=(1.05, 1.0), legend_border_axes_pad=None, $legend_n_columns=1$, *legend_horizontal_spacing=None*, legend_border=True, legend_border_padding=None, leg*legend_vertical_spacing=None*, end_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sansaxes_font_size=10, axes_font_style='normal', axes_font_weight='normal', serif', axes_x_limits=None, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure size=(7, 7))

Visualize the fitting result. The method renders the final fitted shape and optionally the initial shape, ground truth shape and the image, id they were provided.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

- •render_image (bool, optional) If True and the image exists, then it gets rendered.
- •render_final_shape (*bool*, optional) If True, then the final fitting shape gets rendered.
- •render_initial_shape (*bool*, optional) If True and the initial fitting shape exists, then it gets rendered.
- •**render_gt_shape** (*bool*, optional) If True and the ground truth shape exists, then it gets rendered.
- •**subplots_enabled** (*bool*, optional) If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.
- •channels (*int* or *list* of *int* or all or None) If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.
- •interpolation (See Below, optional) The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•final_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_marker_edge_colour (See Below, optional) – The edge colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_line_colour (See Below, optional) – The line colour of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_edge_colour (See Below, optional) - The edge colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_line_colour (See Below, optional) – The line colour of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_edge_colour (See Below, optional) – The edge colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_line_colour (See Below, optional) – The line colour of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•**render_lines** (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•line_style (*str* or *list* of *str*, optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{ '-', '--', '-.', ':' }

•line_width (*float* or *list* of *float*, optional) – The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a

different value per shape in (final, initial, groundtruth) order.

•marker_style (*str* or *list* of *str*, optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order.

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align ({center, right, left}, optional) - The horizontal alignment of the numbers' texts.

•numbers_vertical_align ({center, top, bottom, baseline}, optional) – The vertical alignment of the numbers' texts.

•numbers_font_name (See Below, optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (See Below, optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) – If True, the legend will be rendered.

•legend_title (str, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style ({normal, italic, oblique}, optional) - The font style of the legend.

•legend_font_size (int, optional) – The font size of the legend.

•legend_font_weight (See Below, optional) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (*int*, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

•legend_border (bool, optional) – If True, a frame will be drawn around the legend.

•legend_border_padding (*float*, optional) – The fractional whitespace inside the legend border.

•legend_shadow (bool, optional) - If True, a shadow will be drawn behind legend.

•legend_rounded_corners (*bool*, optional) – If True, the frame's corners will be rounded (fancybox).

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (See Below, optional) - The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (See Below, optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (*list* or *tuple* or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) – The renderer object.

view_iterations (figure_id=None, new_figure=False, *iters=None*, render_image=True, interpolation='bilinear', subplots_enabled=False, channels=None, cmap_name=None, alpha=1.0, masked=True, render_lines=True, *line_style='-', line_width=2, line_colour=None*, render_markers=True, marker_edge_colour=None, marker_face_colour=None, marker_style='o', marker_size=4, marker edge width=1.0, render_numbering=False, numbers horizontal align='center', numbers vertical align='bottom', numbers font name='sans-serif', numbers font size=10, num*bers_font_style='normal'*, numbers_font_weight='normal', numbers font colour='k', render legend=True, legend title="', legend_font_name='sans-serif', *legend_font_style='normal'*, legend font size=10, legend font weight='normal', legend marker scale=None, legend bbox to anchor=(1.05,1.0). *legend location=2*, leglegend n columns=1, end border axes pad=None, legend_horizontal_spacing=None, *legend_vertical_spacing=None*, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sans-serif', axes_font_size=10, axes_font_style='normal', axes_font_weight='normal', axes_x_limits=None, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(7, 7))

Visualize the iterations of the fitting process.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•iters (*int* or *list* of *int* or None, optional) – The iterations to be visualized. If None, then all the iterations are rendered.

No.	Visualised shape	Description
0	self.initial_shape	Initial shape
1	self.reconstructed_initial_shape	Reconstructed initial
2	self.shapes[2]	Iteration 1
i	self.shapes[i]	Iteration i-1
n_iters+1	self.final_shape	Final shape

•render_image (bool, optional) - If True and the image exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

- •channels (*int* or *list* of *int* or all or None) If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.
- •interpolation (*str* (See Below), optional) The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•**render_lines** (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•line_style (*str* or *list* of *str* (See below), optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options:

{-, --, -., :}

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_colour (*colour* or *list* of *colour* (See Below), optional) The colour of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_style (*str or 'list* of *str* (See below), optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_edge_colour (*colour* or *list* of *colour* (See Below), optional) – The edge colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{r, g, b, c, m, k, w}
or
(3,) ndarray

•marker_face_colour (*colour* or *list* of *colour* (See Below), optional) – The face (filling) colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align (*str* (See below), optional) – The horizontal alignment of the numbers' texts. Example options

{center, right, left}

•numbers_vertical_align (*str* (See below), optional) – The vertical alignment of the numbers' texts. Example options

{center, top, bottom, baseline}

•numbers_font_name (*str* (See below), optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (int, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (*str* (See below), optional) – The font weight of the numbers. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (*bool*, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style (*str* (See below), optional) – The font style of the legend. Example options

```
{normal, italic, oblique}
```

- •legend_font_size (int, optional) The font size of the legend.
- •legend_font_weight (*str* (See below), optional) The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
ʻright'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- •legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) The bbox that the legend will be anchored.
- •legend_border_axes_pad (*float*, optional) The pad between the axes and legend border.
- •legend_n_columns (*int*, optional) The number of the legend's columns.
- •legend_horizontal_spacing (*float*, optional) The spacing between the columns.
- •legend_vertical_spacing (*float*, optional) The vertical space between the legend entries.
- •legend_border (bool, optional) If True, a frame will be drawn around the legend.
- •legend_border_padding (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.
- •legend_rounded_corners (*bool*, optional) If True, the frame's corners will be rounded (fancybox).
- •render_axes (bool, optional) If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes font size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((*float*, *float*) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (*class*) – The renderer object.

view_widget (figure_size=(7, 7))

Visualizes the result object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

appearance_costs

Returns a list with the appearance cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

costs

Returns a *list* with the cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

deformation_costs

Returns a *list* with the deformation cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

final_shape

Returns the final shape of the fitting process.

Typemenpo.shape.PointCloud

gt_shape

Returns the ground truth shape associated with the image. In case there is not an attached ground truth shape, then None is returned.

Typemenpo.shape.PointCloud or None

image

Returns the image that the fitting was applied on, if it was provided. Otherwise, it returns None.

Typemenpo.shape.Image or subclass or None

initial_shape

Returns the initial shape that was provided to the fitting method to initialise the fitting process. In case the initial shape does not exist, then None is returned.

Typemenpo.shape.PointCloud or None

is_iterative

Flag whether the object is an iterative fitting result.

Typebool

n_iters

Returns the total number of iterations of the fitting process.

Typeint

reconstructed_initial_shape

Returns the initial shape's reconstruction with the shape model that was used to initialise the iterative optimisation process.

Typemenpo.shape.PointCloud

shape_parameters

Returns the *list* of shape parameters obtained at each iteration of the fitting process. The *list* includes the parameters of the *reconstructed_initial_shape* and *final_shape*.

Typelist of (n_params,) ndarray

shapes

Returns the *list* of shapes obtained at each iteration of the fitting process. The *list* includes the *initial_shape* (if it exists), *reconstructed_initial_shape* and *final_shape*.

Typelist of menpo.shape.PointCloud

menpofit.atm

Active Template Model

ATM is a generative model that performs deformable alignment between a template image and a test image with respect to a statistical parametric shape model. MenpoFit has several ATMs which differ in the manner that they compute the warp (thus represent the appearance features).

ATM

Bases: object

Class for training a multi-scale holistic Active Template Model.

Parameters

•template (menpo.image.Image) – The template image.

- •**shapes** (*list* of *menpo.shape.PointCloud*) The *list* of training shapes.
- •group (*str* or None, optional) The landmark group of the *template* that will be used to train the ATM. If None and the *template* only has a single landmark group, then that is the one that will be used.
- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •reference_shape (menpo.shape.PointCloud or None, optional) The reference shape that will be used for building the ATM. The purpose of the reference shape is to normalise the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.
- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •transform (subclass of DL and DX, optional) A differential warp transform object, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •max_shape_components (*int*, *float*, *list* of those or None, optional) The number of shape components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •verbose (bool, optional) If True, then the progress of building the ATM will be printed.
- •**batch_size** (*int* or None, optional) If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

References

build_fitter_interfaces(sampling)

Method that builds the correct Lucas-Kanade fitting interface.

Parameterssampling (*list* of *int* or *ndarray* or None) – It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.

Returnsfitter_interfaces (list) – The list of Lucas-Kanade interface per scale.

- - Method to increment the trained ATM with a new set of training shapes and a new template.

Parameters

- •template (menpo.image.Image) The template image.
- •shapes (list of menpo.shape.PointCloud) The list of training shapes.
- •group (*str* or None, optional) The landmark group of the *template* that will be used to train the ATM. If None and the *template* only has a single landmark group, then that is the one that will be used.
- •**shape_forgetting_factor** ([0.0, 1.0] *float*, optional) Forgetting factor that weights the relative contribution of new samples vs old samples for the shape model. If 1. 0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.

•verbose (*bool*, optional) – If True, then the progress of building the ATM will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

instance (shape_weights=None, scale_index=-1)

Generates a novel ATM instance given a set of shape weights. If no weights are provided, the mean ATM instance is returned.

Parameters

•**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.

•scale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The ATM instance.

random_instance(scale_index=-1)

Generates a random instance of the ATM.

Parametersscale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The ATM instance.

view_atm_widget (n_shape_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure_size=(7, 7))

Visualizes the ATM using an interactive widget.

Parameters

•n_shape_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

Visualizes the shape models of the ATM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

n_scales

Returns the number of scales.

Type*int*

HolisticATM

menpofit.atm.HolisticATM alias of ATM

MaskedATM

Bases: ATM

Class for training a multi-scale patch-based Masked Active Template Model. The appearance of this model is formulated by simply masking an image with a patch-based mask.

Parameters

•template (menpo.image.Image) – The template image.

•shapes (list of menpo.shape.PointCloud) – The list of training shapes.

•group (*str* or None, optional) – The landmark group of the *template* that will be used to train the ATM. If None and the *template* only has a single landmark group, then that is the one that will be used.

- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •reference_shape (*menpo.shape.PointCloud* or None, optional) The reference shape that will be used for building the ATM. The purpose of the reference shape is to normalise the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.
- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •**patch_shape** ((*int*, *int*), optional) The size of the patches of the mask that is used to sample the appearance vectors.
- •max_shape_components (*int*, *float*, *list* of those or None, optional) The number of shape components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •verbose (bool, optional) If True, then the progress of building the ATM will be printed.
- •**batch_size** (*int* or None, optional) If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

build_fitter_interfaces(sampling)

- Method that builds the correct Lucas-Kanade fitting interface.
 - **Parameterssampling** (*list* of *int* or *ndarray* or None) It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.

Returnsfitter_interfaces (list) – The list of Lucas-Kanade interface per scale.

Method to increment the trained ATM with a new set of training shapes and a new template.

Parameters

•template (menpo.image.Image) - The template image.

•shapes (list of menpo.shape.PointCloud) – The list of training shapes.

•group (*str* or None, optional) – The landmark group of the *template* that will be used to train the ATM. If None and the *template* only has a single landmark group, then that is the one that will be used.

•**shape_forgetting_factor** ([0.0, 1.0] *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples for the shape model. If 1.0, all samples are weighted equally and, hence, the result is the exact same as performing

batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.

•verbose (*bool*, optional) – If True, then the progress of building the ATM will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

```
instance (shape_weights=None, scale_index=-1)
```

Generates a novel ATM instance given a set of shape weights. If no weights are provided, the mean ATM instance is returned.

Parameters

•**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.

•scale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The ATM instance.

random_instance(scale_index=-1)

Generates a random instance of the ATM.

Parametersscale_index (*int*, optional) – The scale to be used.

Returnsimage (menpo.image.Image) – The ATM instance.

view_atm_widget (n_shape_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure_size=(7, 7))

Visualizes the ATM using an interactive widget.

Parameters

•n_shape_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

view_shape_models_widget (n_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure_size=(7, 7))

Visualizes the shape models of the ATM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

n_scales

Returns the number of scales.

Typeint

LinearATM

Bases: ATM

Class for training a multi-scale Linear Active Template Model.

Parameters

- •template (menpo.image.Image) The template image.
- •shapes (list of menpo.shape.PointCloud) The list of training shapes.
- •group (*str* or None, optional) The landmark group of the *template* that will be used to train the ATM. If None and the *template* only has a single landmark group, then that is the one that will be used.
- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •reference_shape (menpo.shape.PointCloud or None, optional) The reference shape that will be used for building the ATM. The purpose of the reference shape is to normalise the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.
- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •transform (subclass of DL and DX, optional) A differential warp transform object, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

•max_shape_components (*int*, *float*, *list* of those or None, optional) – The number of shape components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.

•verbose (bool, optional) – If True, then the progress of building the ATM will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

build_fitter_interfaces (sampling)

Method that builds the correct Lucas-Kanade fitting interface.

Parameterssampling (*list* of *int* or *ndarray* or None) – It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.

Returnsfitter_interfaces (list) – The list of Lucas-Kanade interface per scale.

Method to increment the trained ATM with a new set of training shapes and a new template.

Parameters

•template (menpo.image.Image) – The template image.

•shapes (list of menpo.shape.PointCloud) – The list of training shapes.

•group (*str* or None, optional) – The landmark group of the *template* that will be used to train the ATM. If None and the *template* only has a single landmark group, then that is the one that will be used.

•**shape_forgetting_factor** ([0.0, 1.0] *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples for the shape model. If 1. 0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.

•verbose (*bool*, optional) – If True, then the progress of building the ATM will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

```
instance (shape_weights=None, scale_index=-1)
```

Generates a novel ATM instance given a set of shape weights. If no weights are provided, the mean ATM instance is returned.

Parameters

•**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.

•scale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The ATM instance.

```
random_instance(scale_index=-1)
```

Generates a random instance of the ATM.

Parametersscale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The ATM instance.

Visualizes the shape models of the ATM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

n_scales

Returns the number of scales.

Type*int*

LinearMaskedATM

class menpofit.atm.LinearMaskedATM	(template, sl	hapes, group=	None, holistic_fe	atures= <f< th=""><th>unction</th></f<>	unction
	no_op>,	reference_s	hape=None,	diagonal	=None,
	scales = (0.5, 0.5)	, 1.0),	patch_shape	e=(17,	17),
	max_shape_	_components=1	None,	verbose	=False,
	<pre>batch_size=</pre>	None)			

Bases: ATM

Class for training a multi-scale Linear Masked Active Template Model.

Parameters

•template (menpo.image.Image) – The template image.

- •shapes (list of menpo.shape.PointCloud) The list of training shapes.
- •group (*str* or None, optional) The landmark group of the *template* that will be used to train the ATM. If None and the *template* only has a single landmark group, then that is the one that will be used.
- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •reference_shape (*menpo.shape.PointCloud* or None, optional) The reference shape that will be used for building the ATM. The purpose of the reference shape is to normalise the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape.

Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.

- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •**patch_shape** ((*int*, *int*) or *list* of (*int*, *int*), optional) The shape of the patches of the mask that is used to extract the appearance vectors. If a *list* is provided, then it defines a patch shape per scale.
- •max_shape_components (*int*, *float*, *list* of those or None, optional) The number of shape components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •verbose (bool, optional) If True, then the progress of building the ATM will be printed.
- •**batch_size** (*int* or None, optional) If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

build_fitter_interfaces (sampling)

Method that builds the correct Lucas-Kanade fitting interface.

- **Parameterssampling** (*list* of *int* or *ndarray* or None) It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.
- Returnsfitter_interfaces (list) The list of Lucas-Kanade interface per scale.

Method to increment the trained ATM with a new set of training shapes and a new template.

Parameters

•template (*menpo.image.Image*) – The template image.

•shapes (list of menpo.shape.PointCloud) – The list of training shapes.

•group (*str* or None, optional) – The landmark group of the *template* that will be used to train the ATM. If None and the *template* only has a single landmark group, then that is the one that will be used.

- •**shape_forgetting_factor** ([0.0, 1.0] *float*, optional) Forgetting factor that weights the relative contribution of new samples vs old samples for the shape model. If 1. 0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.
- •verbose (*bool*, optional) If True, then the progress of building the ATM will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.
instance (shape_weights=None, scale_index=-1)

Generates a novel ATM instance given a set of shape weights. If no weights are provided, the mean ATM instance is returned.

Parameters

•**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.

•scale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The ATM instance.

random_instance(scale_index=-1)

Generates a random instance of the ATM.

Parametersscale_index (*int*, optional) – The scale to be used.

Returnsimage (menpo.image.Image) – The ATM instance.

view_shape_models_widget (n_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure_size=(7, 7))

Visualizes the shape models of the ATM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) – If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

n_scales

Returns the number of scales.

Type*int*

PatchATM

Bases: ATM

Class for training a multi-scale Patch-Based Active Template Model.

Parameters

•template (menpo.image.Image) – The template image.

•shapes (list of menpo.shape.PointCloud) – The list of training shapes.

- •group (*str* or None, optional) The landmark group of the *template* that will be used to train the ATM. If None and the *template* only has a single landmark group, then that is the one that will be used.
- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •reference_shape (menpo.shape.PointCloud or None, optional) The reference shape that will be used for building the ATM. The purpose of the reference shape is to normalise the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.
- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •**patch_shape** ((*int*, *int*) or *list* of (*int*, *int*), optional) The shape of the patches to be extracted. If a *list* is provided, then it defines a patch shape per scale.
- •max_shape_components (*int*, *float*, *list* of those or None, optional) The number of shape components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •verbose (bool, optional) If True, then the progress of building the ATM will be printed.
- •**batch_size** (*int* or None, optional) If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

build_fitter_interfaces(sampling)

Method that builds the correct Lucas-Kanade fitting interface.

- **Parameterssampling** (*list* of *int* or *ndarray* or None) It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.
- **Returnsfitter_interfaces** (*list*) The *list* of Lucas-Kanade interface per scale.

Method to increment the trained ATM with a new set of training shapes and a new template.

Parameters

•template (*menpo.image.Image*) – The template image.

•shapes (list of menpo.shape.PointCloud) – The list of training shapes.

•group (*str* or None, optional) – The landmark group of the *template* that will be used to train the ATM. If None and the *template* only has a single landmark group, then that is the one that will be used.

•**shape_forgetting_factor** ([0.0, 1.0] *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples for the shape model. If 1. 0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.

•verbose (*bool*, optional) – If True, then the progress of building the ATM will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

```
instance (shape_weights=None, scale_index=-1)
```

Generates a novel ATM instance given a set of shape weights. If no weights are provided, the mean ATM instance is returned.

Parameters

•**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.

•scale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The ATM instance.

random_instance(scale_index=-1)

Generates a random instance of the ATM.

Parametersscale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The ATM instance.

view_atm_widget (n_shape_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure_size=(7, 7))

Visualizes the ATM using an interactive widget.

Parameters

•n_shape_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•**parameters_bounds** ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) – If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

Visualizes the shape models of the ATM object using an interactive widget.

Parameters

•**n_parameters** (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per

scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

n_scales

Returns the number of scales.

Type*int*

Fitter

LucasKanadeATMFitter

$class \verb+menpofit.atm+.LucasKanadeATMFitter+$	(atm,	lk_algorithm_cls= <class< th=""><th>'men-</th></class<>	'men-
	pofit.atm.algo	rithm.InverseCompositional'>,	
	n_shape=Non	e, sampling=None)	

Bases: MultiScaleParametricFitter

Class for defining an ATM fitter using the Lucas-Kanade optimization.

Parameters

•atm (ATM or subclass) – The trained ATM model.

•**lk_algorithm_cls** (*class*, optional) – The Lukas-Kanade optimisation algorithm that will get applied. The possible algorithms are:

Class	Warp Direction	Warp Update
ForwardCompositional	Forward	Compositional
InverseCompositional	Inverse	

•**n_shape** (*int* or *float* or *list* of those or None, optional) – The number of shape components that will be used. If *int*, then it defines the exact number of active components. If *float*, then it defines the percentage of variance to keep. If *int* or *float*, then the provided value will be applied for all scales. If *list*, then it defines a value per scale. If None, then all the available components will be used. Note that this simply sets the active components without trimming the unused ones. Also, the available components may have already been trimmed to *max_shape_components* during training.

•**sampling** (*list* of *int* or *ndarray* or None) – It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.

fit_from_bb (*image*, *bounding_box*, *max_iters=20*, *gt_shape=None*, *return_costs=False*, ***kwargs*) Fits the multi-scale fitter to an image given an initial bounding box.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•**bounding_box** (*menpo.shape.PointDirectedGraph*) – The initial bounding box from which the fitting procedure will start. Note that the bounding box is used in order to align the model's reference shape.

•max_iters (*int* or *list* of *int*, optional) – The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

Fits the multi-scale fitter to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape estimate from which the fitting procedure will start.

•max_iters (*int* or *list* of *int*, optional) – The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

warped_images (image, shapes)

Given an input test image and a list of shapes, it warps the image into the shapes. This is useful for generating the warped images of a fitting procedure stored within a *MultiScaleParametricIterativeResult*.

Parameters

•image (menpo.image.Image or subclass) – The input image to be warped.

•**shapes** (*list* of *menpo.shape.PointCloud*) – The list of shapes in which the image will be warped. The shapes are obtained during the iterations of a fitting procedure.

Returnswarped_images (*list* of *menpo.image.MaskedImage* or *ndarray*) – The warped images.

atm

The trained ATM model.

TypeATM or subclass

holistic_features

The features that are extracted from the input image at each scale in ascending order, i.e. from lowest to highest scale.

Typelist of closure

n_scales

Returns the number of scales.

Typeint

reference_shape

The reference shape that is used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of this reference shape.

Typemenpo.shape.PointCloud

scales

The scale value of each scale in ascending order, i.e. from lowest to highest scale.

Typelist of int or float

Lucas-Kanade Optimisation Algorithms

ForwardCompositional

class menpofit.atm.ForwardCompositional(atm_interface, eps=1e-05)

Bases: Compositional

Forward Compositional (FC) Gauss-Newton algorithm.

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

•image (menpo.image.Image) – The input test image.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•map_inference (*bool*, optional) – If True, then the solution will be given after performing MAP inference. **Returnsfitting_result** (*ParametricIterativeResult*) – The parametric iterative fitting result.

template

Returns the template of the ATM.

Typemenpo.image.Image or subclass

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of DL and DX

InverseCompositional

class menpofit.atm.InverseCompositional (atm_interface, eps=1e-05)

Bases: Compositional

Inverse Compositional (IC) Gauss-Newton algorithm.

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

•image (menpo.image.Image) – The input test image.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•map_inference (*bool*, optional) – If True, then the solution will be given after performing MAP inference.

Returnsfitting_result (*ParametricIterativeResult*) – The parametric iterative fitting result.

template

Returns the template of the ATM.

Typemenpo.image.Image or subclass

transform

Returns the model driven differential transform object of the AAM, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.

Typesubclass of *DL* and *DX*

menpofit.clm

Constrained Local Model

Deformable model that consists of a generative parametric shape model and discriminatively trained experts per part.

CLM

```
class menpofit.clm.CLM (images, group=None, holistic_features=<function no_op>, refer-
ence_shape=None, diagonal=None, scales=(0.5, 1), patch_shape=(17,
17), patch_normalisation=<function no_op>, context_shape=(34, 34),
cosine_mask=True, sample_offsets=None, shape_model_cls=<class
'menpofit.modelinstance.OrthoPDM'>, expert_ensemble_cls=<class
'menpofit.clm.expert.ensemble.CorrelationFilterExpertEnsemble'>,
max_shape_components=None, verbose=False, batch_size=None)
```

Bases: object

Class for training a multi-scale holistic Constrained Local Model. Please see the references for a basic list of relevant papers.

- •images (list of menpo.image.Image) The list of training images.
- •group (*str* or None, optional) The landmark group that will be used to train the CLM. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.
- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •reference_shape (*menpo.shape.PointCloud* or None, optional) The reference shape that will be used for building the CLM. The purpose of the reference shape is to normalise the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.
- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •**patch_shape** ((*int*, *int*) or *list* of (*int*, *int*), optional) The shape of the patches to be extracted. If a *list* is provided, then it defines a patch shape per scale.
- •**patch_normalisation** (*callable*, optional) The normalisation function to be applied on the extracted patches.
- •context_shape ((*int*, *int*) or *list* of (*int*, *int*), optional) The context shape for the convolution. If a *list* is provided, then it defines a context shape per scale.
- •**cosine_mask** (*bool*, optional) If True, then a cosine mask (Hanning function) will be applied on the extracted patches.

- •sample_offsets ((n_offsets, n_dims) *ndarray* or None, optional) The offsets to sample from within a patch. So (0, 0) is the centre of the patch (no offset) and (1, 0) would be sampling the patch from 1 pixel up the first axis away from the centre. If None, then no offsets are applied.
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •expert_ensemble_cls (*subclass* of ExpertEnsemble, optional) The class to be used for training the ensemble of experts. The most common choice is *CorrelationFilterExpertEnsemble*.
- •max_shape_components (*int*, *float*, *list* of those or None, optional) The number of shape components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •verbose (bool, optional) If True, then the progress of building the CLM will be printed.
- •**batch_size** (*int* or None, optional) If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

References

increment (*images*, group=None, shape_forgetting_factor=1.0, verbose=False, batch_size=None) Method to increment the trained CLM with a new set of training images.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •group (*str* or None, optional) The landmark group that will be used to train the CLM. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.
- •**shape_forgetting_factor** ([0.0, 1.0] *float*, optional) Forgetting factor that weights the relative contribution of new samples vs old samples for the shape model. If 1. 0, all samples are weighted equally and, hence, the result is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples.

•verbose (*bool*, optional) – If True, then the progress of building the CLM will be printed.

•batch_size (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

shape_instance (shape_weights=None, scale_index=-1)

Generates a novel shape instance given a set of shape weights. If no weights are provided, the mean shape is returned.

Parameters

•**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.

•scale_index (*int*, optional) – The scale to be used.

Returnsinstance (*menpo.shape.PointCloud*) – The shape instance.

view_clm_widget (n_shape_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure_size=(7, 7))

Visualizes the CLM object using an interactive widget.

Parameters

•n_shape_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) – If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

RaisesValueError – Only convolution-based expert ensembles can be visualized.

view_expert_ensemble_widget (figure_size=(7, 7))

Visualizes the ensemble of experts of the CLM object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The size of the plotted figures.

RaisesValueError – Only convolution-based expert ensembles can be visualized.

view_shape_models_widget (n_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure_size=(7, 7))

Visualizes the shape models of the CLM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) – If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

n_scales

Returns the number of scales.

Type*int*

Fitter

GradientDescentCLMFitter

class menpofit.clm.**GradientDescentCLMFitter**(*clm*, *gd_*

(clm, gd_algorithm_cls=<class 'menpofit.clm.algorithm.gd.RegularisedLandmarkMeanShift'>, n_shape=None)

Bases: CLMFitter

Class for defining an CLM fitter using gradient descent optimization.

Note: When using a method with a parametric shape model, the first step is to **reconstruct the initial shape** using the shape model. The generated reconstructed shape is then used as initialisation for the iterative optimisation. This step takes place at each scale and it is not considered as an iteration, thus it is not counted for the provided *max_iters*.

Parameters

•clm (*CLM* or *subclass*) – The trained CLM model.

•gd_algorithm_cls (*class*, optional) – The gradient descent optimisation algorithm that will get applied. The possible options are *RegularisedLandmarkMeanShift* and *ActiveShapeModel*.

•**n_shape** (*int* or *float* or *list* of those or None, optional) – The number of shape components that will be used. If *int*, then it defines the exact number of active components. If *float*, then it defines the percentage of variance to keep. If *int* or *float*, then the provided value will be applied for all scales. If *list*, then it defines a value per scale. If None, then all the available components will be used. Note that this simply sets the active components without trimming the unused ones. Also, the available components may have already been trimmed to *max_shape_components* during training.

fit_from_bb (*image*, *bounding_box*, *max_iters=20*, *gt_shape=None*, *return_costs=False*, ***kwargs*) Fits the multi-scale fitter to an image given an initial bounding box.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •**bounding_box** (*menpo.shape.PointDirectedGraph*) The initial bounding box from which the fitting procedure will start. Note that the bounding box is used in order to align the model's reference shape.

•max_iters (*int* or *list* of *int*, optional) – The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

- **Returnsfitting_result** (*MultiScaleNonParametricIterativeResult* or subclass) The multi-scale fitting result containing the result of the fitting procedure.

Fits the multi-scale fitter to an image given an initial shape.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape estimate from which the fitting procedure will start.
- •max_iters (*int* or *list* of *int*, optional) The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

clm

The trained CLM model.

Type*CLM* or *subclass*

holistic_features

The features that are extracted from the input image at each scale in ascending order, i.e. from lowest to highest scale.

Typelist of closure

n_scales

Returns the number of scales.

Type*int*

reference_shape

The reference shape that is used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of this reference shape.

Typemenpo.shape.PointCloud

scales

The scale value of each scale in ascending order, i.e. from lowest to highest scale.

Typelist of int or float

Gradient Descent Optimisation Algorithms

ActiveShapeModel

Bases: GradientDescentCLMAlgorithm

Active Shape Model (ASM) algorithm.

Parameters

•expert_ensemble (*subclass* of ExpertEnsemble) - The ensemble of experts object, e.g. CorrelationFilterExpertEnsemble.

•shape_model (subclass of PDM, optional) – The shape model object, e.g. OrthoPDM.

•gaussian_covariance (int or float, optional) – The covariance of the Gaussian kernel.

•eps (float, optional) – Value for checking the convergence of the optimization.

References

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

•image (menpo.image.Image) – The input test image.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to 'True''. This is because it is not possible to evaluate the cost function of this algorithm.

•map_inference (*bool*, optional) – If True, then the solution will be given after performing MAP inference.

Returnsfitting_result (*ParametricIterativeResult*) – The parametric iterative fitting result.

RegularisedLandmarkMeanShift

```
class menpofit.clm.RegularisedLandmarkMeanShift(expert_ensemble, shape_model, ker-
nel_covariance=10, eps=1e-05)
```

Bases: GradientDescentCLMAlgorithm

Regularized Landmark Mean-Shift (RLMS) algorithm.

•expert_ensemble (*subclass* of ExpertEnsemble) – The ensemble of experts object, e.g. *CorrelationFilterExpertEnsemble*.

•shape_model (subclass of PDM, optional) – The shape model object, e.g. OrthoPDM.

•kernel_covariance (int or float, optional) – The covariance of the kernel.

•eps (*float*, optional) – Value for checking the convergence of the optimization.

References

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *map_inference=False*) Execute the optimization algorithm.

Parameters

- •image (*menpo.image.Image*) The input test image.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the optimization will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.
- •max_iters (*int*, optional) The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.
- •map_inference (*bool*, optional) If True, then the solution will be given after performing MAP inference.
- **Returnsfitting_result** (*ParametricIterativeResult*) The parametric iterative fitting result.

Experts Ensemble

Algorithms for learning an ensemble of discriminative experts.

CorrelationFilterExpertEnsemble

class menpofit.clm.CorrelationFilterExpertEnsembl	e (images, shapes, icf_e	cls= <clas< th=""><th>s 'men-</th></clas<>	s 'men-
	pofit.clm.expert.base	.Incremen	tal Correlation Filter Thin Wrapp
	patch_shape=(17,	17),	con-
	tout al an a-(21	21)	

text_shape=(34, 34), response_covariance=3, patch_normalisation=<functools.partial object>, cosine_mask=True, sample_offsets=None, prefix='', verbose=False)

Bases: ConvolutionBasedExpertEnsemble

Class for defining an ensemble of correlation filter experts.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •**shapes** (*list* of *menpo.shape.PointCloud*) The *list* of training shapes that correspond to the images.
- •icf_cls (*class*, optional) The incremental correlation filter class. For example IncrementalCorrelationFilterThinWrapper.
- •patch_shape ((*int*, *int*), optional) The shape of the patches that will be extracted around the landmarks. Those patches are used to train the experts.
- •context_shape ((*int*, *int*), optional) The context shape for the convolution.
- •**response_covariance** (*int*, optional) The covariance of the generated Gaussian response.
- •**patch_normalisation** (*callable*, optional) A normalisation function that will be applied on the extracted patches.
- •cosine_mask (*bool*, optional) If True, then a cosine mask (Hanning function) will be applied on the extracted patches.
- •sample_offsets ((n_offsets, n_dims) *ndarray* or None, optional) The offsets to sample from within a patch. So (0, 0) is the centre of the patch (no offset) and (1, 0) would be sampling the patch from 1 pixel up the first axis away from the centre. If None, then no offsets are applied.
- •**prefix** (*str*, optional) The prefix of the printed progress information.
- •verbose (*bool*, optional) If True, then information will be printed regarding the training progress.
- increment (images, shapes, prefix='', verbose=False)

Increments the learned ensemble of convolution-based experts given a new set of training data.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •**shapes** (*list* of *menpo.shape.PointCloud*) The list of training shapes that correspond to the images.
- •**prefix** (*str*, optional) The prefix of the printed training progress.
- •verbose (*bool*, optional) If True, then information about the training progress will be printed.

predict_probability(image, shape)

Method for predicting the probability map of the response experts on a given image. Note that the provided shape must have the same number of points as the number of experts.

- •image (menpo.image.Image or subclass) The test image.
- •**shape** (*menpo.shape.PointCloud*) The shape that corresponds to the image from which the patches will be extracted.
- **Returnsprobability_map**((n_experts, 1, height, width) *ndarray*)-The probability map of the response of each expert.

predict response(image, shape)

Method for predicting the response of the experts on a given image. Note that the provided shape must have the same number of points as the number of experts.

Parameters

•image (menpo.image.Image or subclass) – The test image.

•shape (menpo.shape.PointCloud) – The shape that corresponds to the image from which the patches will be extracted.

Returnsresponse ((n_experts, 1, height, width) ndarray) - The response of each expert.

view_frequency_filter_images_widget (figure_size=(7, 7), style='coloured'.

browser style='buttons')

Visualizes the filters on the frequency domain using an interactive widget.

Parameters

•figure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

•style ({ 'coloured', 'minimal'}, optional) - If 'coloured', then the style of the widget will be coloured. If minimal, then the style is simple using black and white colours.

•browser_style ({ 'buttons', 'slider'}, optional) - It defines whether the selector of the objects will have the form of plus/minus buttons or a slider.

view_spatial_filter_images_widget (figure_size=(7, 7), style='coloured',

browser style='buttons')

Visualizes the filters on the spatial domain using an interactive widget.

Parameters

•figure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

•style ({ 'coloured', 'minimal'}, optional) – If 'coloured', then the style of the widget will be coloured. If minimal, then the style is simple using black and white colours.

•browser_style ({ 'buttons', 'slider'}, optional) - It defines whether the selector of the objects will have the form of plus/minus buttons or a slider.

frequency_filter_images

Returns a *list* of *n_experts* filter images on the frequency domain.

Type*list* of *menpo.image.Image*

n experts

Returns the number of experts.

Type*int*

n sample offsets

Returns the number of offsets that are sampled within a patch.

Type*int*

padded_size

Returns the convolution pad size, i.e. floor (1.5 * patch_shape - 1).

Type(*int*, *int*)

search_shape

Returns the search shape (*patch_shape*).

Type(int, int)

spatial_filter_images

Returns a *list* of *n_experts* filter images on the spatial domain.

Type*list* of *menpo.image.Image*

Experts

Discriminative experts

IncrementalCorrelationFilterThinWrapper

```
class menpofit.clm.IncrementalCorrelationFilterThinWrapper(cf_callable=<function
                                                                   mccf>,
                                                                   icf_callable=<function
                                                                   imccf>)
```

Bases: object

Wrapper class for defining an Incremental Correlation Filter.

Parameters

•cf_callable (*callable*, optional) – The correlation filter function. Possible options are:

Class	Method
mccf	Multi-Channel Correlation Filter
mosse	Minimum Output Sum of Squared Errors Filter

•icf_callable (callable, optional) – The incremental correlation filter function. Possible options are:

Class	Method
imccf	Incremental Multi-Channel Correlation Filter
imosse	Incremental Minimum Output Sum of Squared Errors Filter

$increment(A, B, n_x, Z, t)$

Method that trains the correlation filter.

Parameters

```
•A ((N_{1}) ndarray) – The current auto-correlation array,
                                                       where N =
(patch_h+response_h-1) * (patch_w+response_w-1) *
n channels
```

- •B ((N, N) *ndarray*) – The current cross-correlation array, where N = (patch_h+response_h-1) * (patch_w+response_w-1) * n_channels
- •**n_x** (*int*) The current number of images.

•Z (list or (n_images, n_channels, patch_h, patch_w) ndarray) - The training images (patches). If *list*, then it consists of *n images* (n channels, patch_h, patch_w) ndarray members.

•t ((1, response_h, response_w) *ndarray*) – The desired response.

Returns

•correlation_filter((n_channels, response_h, response_w) ndarray) - The learned correlation filter.

•auto_correlation ((N,) ndarray) - The auto-correlation array, where N
= (patch_h+response_h-1) * (patch_w+response_w-1) *
n_channels
•cross_correlation ((N, N) ndarray) - The cross-correlation array, where

```
N = (patch_h+response_h-1) * (patch_w+response_w-1) *
n_channels
```

train(X, t)

Method that trains the correlation filter.

Parameters

•X (*list* or (n_images, n_channels, patch_h, patch_w) *ndarray*) - The training images (patches). If *list*, then it consists of *n_images* (n_channels, patch_h, patch_w) *ndarray* members.

•t((1, response_h, response_w) *ndarray*) – The desired response.

Returns

•correlation_filter ((n_channels, response_h, response_w) *ndarray*) – The learned correlation filter.

•auto_correlation ((N,) ndarray) - The auto-correlation array, where N
= (patch_h+response_h-1) * (patch_w+response_w-1) *
n_channels

```
•cross_correlation ((N, N) ndarray) - The cross-correlation array, where
N = (patch_h+response_h-1) * (patch_w+response_w-1) *
n_channels
```

menpofit.unified_aam_clm

Unified Active Appearance Model and Constrained Local Model

This method combines a holistic AAM with a part-based CLM under a unified optimisation problem.

UnifiedAAMCLM

class menpofit.unified_aam_clm.base.Unified	AAMCLM (images, group=None, holis-	
	tic_features= <function no_op="">,</function>	
	reference_shape=None, diago-	
	nal=None, scales=(0.5, 1.0), ex-	
	pert_ensemble_cls= <class 'men-<="" td=""><td></td></class>	
	pofit.clm.expert.ensemble.CorrelationFilterExpertEnse	mble'>
	patch_shape=(17, 17),	
	$context_shape=(34, 34),$	
	sample_offsets=None,	
	transform= <class 'men-<="" td=""><td></td></class>	
	pofit.transform.piecewiseaffine.DifferentiablePiecewise	Affine'>
	shape model cls= <class 'men-<="" td=""><td></td></class>	
	pofit.modelinstance.OrthoPDM'>,	
	max_shape_components=None,	
	max appearance components=None,	
	sigma=None, boundary=3,	
	response covariance=2,	
	patch normalisation= <function< td=""><td></td></function<>	
	no op>, cosine mask=True, ver-	
	bose=False	
	,	

Bases: object

Class for training a multi-scale unified holistic AAM and CLM as presented in [1]. Please see the references for AAMs and CLMs in their respective base classes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•group (*str* or None, optional) – The landmark group that will be used to train the model. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.

- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •reference_shape (*menpo.shape.PointCloud* or None, optional) The reference shape that will be used for building the AAM. The purpose of the reference shape is to normalise the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.
- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •expert_ensemble_cls (*subclass* of ExpertEnsemble, optional) The class to be used for training the ensemble of experts. The most common choice is

CorrelationFilterExpertEnsemble.

- •**patch_shape** ((*int*, *int*) or *list* of (*int*, *int*), optional) The shape of the patches to be extracted. If a *list* is provided, then it defines a patch shape per scale.
- •context_shape ((*int*, *int*) or *list* of (*int*, *int*), optional) The context shape for the convolution. If a *list* is provided, then it defines a context shape per scale.
- •sample_offsets ((n_offsets, n_dims) *ndarray* or None, optional) The sample_offsets to sample from within a patch. So (0, 0) is the centre of the patch (no offset) and (1, 0) would be sampling the patch from 1 pixel up the first axis away from the centre. If None, then no sample_offsets are applied.
- •transform (subclass of DL and DX, optional) A differential warp transform object, e.g. DifferentiablePiecewiseAffine or DifferentiableThinPlateSplines.
- •**shape_model_cls** (*subclass* of *OrthoPDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •max_shape_components (*int*, *float*, *list* of those or None, optional) The number of shape components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •max_appearance_components (*int*, *float*, *list* of those or None, optional) The number of appearance components to keep. If *int*, then it sets the exact number of components. If *float*, then it defines the variance percentage that will be kept. If *list*, then it should define a value per scale. If a single number, then this will be applied to all scales. If None, then all the components are kept. Note that the unused components will be permanently trimmed.
- •**sigma** (*float* or None, optional) If not None, the input images are smoothed with an isotropic Gaussian filter with the specified standard deviation.
- •**boundary** (*int*, optional) The number of pixels to be left as a safe margin on the boundaries of the reference frame (has potential effects on the gradient computation).
- •**response_covariance** (*int*, optional) The covariance of the generated Gaussian response.
- •**patch_normalisation** (*callable*, optional) The normalisation function to be applied on the extracted patches.
- •cosine_mask (*bool*, optional) If True, then a cosine mask (Hanning function) will be applied on the extracted patches.
- •verbose (*bool*, optional) If True, then the progress of building the model will be printed.

References

appearance_reconstructions (*appearance_parameters*, *n_iters_per_scale*)

Method that generates the appearance reconstructions given a set of appearance parameters. This is to be combined with a *UnifiedAAMCLMResult* object, in order to generate the appearance reconstructions of a fitting procedure.

- •appearance_parameters (*list* of (n_params,) *ndarray*) A set of appearance parameters per fitting iteration. It can be retrieved as a property of an *UnifiedAAMCLMResult* object.
- •n_iters_per_scale (*list* of *int*) The number of iterations per scale. This is necessary in order to figure out which appearance parameters correspond to the model of each scale. It can be retrieved as a property of a *UnifiedAAMCLMResult* object.
- **Returnsappearance_reconstructions** (*list* of *menpo.image.Image*) *List* of the appearance reconstructions that correspond to the provided parameters.

build_fitter_interfaces (sampling)

Method that builds the correct fitting interface for a UnifiedAAMCLMFitter.

Parameterssampling (*list* of *int* or *ndarray* or None) – It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.

Returnsfitter_interfaces (*list*) – The *list* of fitting interfaces per scale.

instance (*shape_weights=None*, *appearance_weights=None*, *scale_index=-1*)

Generates a novel instance of the AAM part of the model given a set of shape and appearance weights. If no weights are provided, then the mean AAM instance is returned.

Parameters

•**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.

•appearance_weights ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the appearance model that will be used to create a novel appearance instance. If None, the weights are assumed to be zero, thus the mean appearance is used.

•scale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The AAM instance.

random_instance(scale_index=-1)

Generates a random instance of the AAM part of the model.

Parametersscale_index (*int*, optional) – The scale to be used.

Returnsimage (*menpo.image.Image*) – The AAM instance.

shape_instance (shape_weights=None, scale_index=-1)

Generates a novel shape instance given a set of shape weights. If no weights are provided, the mean shape is returned.

Parameters

•**shape_weights** ((n_weights,) *ndarray* or *list* or None, optional) – The weights of the shape model that will be used to create a novel shape instance. If None, the weights are assumed to be zero, thus the mean shape is used.

•scale_index (*int*, optional) – The scale to be used.

Returnsinstance (*menpo.shape.PointCloud*) – The shape instance.

Visualizes the AAM part of the model using an interactive widget.

•n_shape_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•n_appearance_parameters (*int* or *list* of *int* or None, optional) – The number of appearance principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•**parameters_bounds** ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) – If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

Visualizes the appearance models of the Unified AAM CLM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of appearance principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

view_clm_widget (n_shape_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure_size=(10, 8))

Visualizes the CLM part of the model using an interactive widget.

Parameters

•n_shape_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•**parameters_bounds** ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

Raises ValueError – Only convolution-based expert ensembles can be visualized.

view_expert_ensemble_widget (figure_size=(10, 8))

Visualizes the ensemble of experts of the Unified AAM CLM object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The size of the plotted figures.

RaisesValueError – Only convolution-based expert ensembles can be visualized.

view_shape_models_widget (n_parameters=5, parameters_bounds=(-3.0, 3.0), mode='multiple', figure size=(10, 8))

Visualizes the shape models of the Unified AAM CLM object using an interactive widget.

Parameters

•n_parameters (*int* or *list* of *int* or None, optional) – The number of shape principal components to be used for the parameters sliders. If *int*, then the number of sliders per scale is the minimum between *n_parameters* and the number of active components per scale. If *list* of *int*, then a number of sliders is defined per scale. If None, all the active components per scale will have a slider.

•parameters_bounds ((float, float), optional) – The minimum and maximum bounds, in std units, for the sliders.

•mode ({single, multiple}, optional) - If 'single', only a single slider is constructed along with a drop down menu. If 'multiple', a slider is constructed for each parameter.

•figure_size ((*int*, *int*), optional) – The size of the rendered figure.

n_scales

Returns the number of scales.

Type*int*

Fitter

The model optimised with a combination of Lucas-Kanade and Regularised Landmark Mean Shift algorithms.

UnifiedAAMCLMFitter

<pre>class menpofit.unified_aam_clm.UnifiedAAMCLMFitter</pre>	(unified_aam_clm,	algo-
	rithm_cls= <class< th=""><th>'men-</th></class<>	'men-
	pofit.unified_aam_clm.alg	gorithm.AlternatingRegularisedLana
	n_shape=None,	
	n_appearance=None,	sam-
	pling=None)	

Bases: MultiScaleParametricFitter

Class defining a Unified AAM - CLM fitter.

Note: When using a method with a parametric shape model, the first step is to **reconstruct the initial shape** using the shape model. The generated reconstructed shape is then used as initialisation for the iterative optimisation. This step takes place at each scale and it is not considered as an iteration, thus it is not counted for the provided *max_iters*.

•unified_aam_clm (*UnifiedAAMCLM* or subclass) – The trained unified AAM-CLM model.

•algorithm_cls (*class*, optional) – The unified optimisation algorithm that will get applied. The possible algorithms are:

Class	Method
${\it ProjectOutRegularisedLandmarkMeanShift}$	Project-Out IC + RLMS
AlternatingRegularisedLandmarkMeanShift	Alternating IC + RLMS

•**n_shape** (*int* or *float* or *list* of those or None, optional) – The number of shape components that will be used. If *int*, then it defines the exact number of active components. If *float*, then it defines the percentage of variance to keep. If *int* or *float*, then the provided value will be applied for all scales. If *list*, then it defines a value per scale. If None, then all the available components will be used. Note that this simply sets the active components without trimming the unused ones. Also, the available components may have already been trimmed to *max_shape_components* during training.

•n_appearance (*int* or *float* or *list* of those or None, optional) – The number of appearance components that will be used. If *int*, then it defines the exact number of active components. If *float*, then it defines the percentage of variance to keep. If *int* or *float*, then the provided value will be applied for all scales. If *list*, then it defines a value per scale. If None, then all the available components will be used. Note that this simply sets the active components without trimming the unused ones. Also, the available components may have already been trimmed to *max_appearance_components* during training.

•**sampling** (*list* of *int* or *ndarray* or None) – It defines a sampling mask per scale. If *int*, then it defines the sub-sampling step of the sampling mask. If *ndarray*, then it explicitly defines the sampling mask. If None, then no sub-sampling is applied.

appearance_reconstructions (*appearance_parameters*, *n_iters_per_scale*)

Method that generates the appearance reconstructions given a set of appearance parameters. This is to be combined with a *UnifiedAAMCLMResult* object, in order to generate the appearance reconstructions of a fitting procedure.

Parameters

•appearance_parameters (*list* of (n_params,) *ndarray*) – A set of appearance parameters per fitting iteration. It can be retrieved as a property of an *UnifiedAAMCLMResult* object.

•n_iters_per_scale (*list* of *int*) – The number of iterations per scale. This is necessary in order to figure out which appearance parameters correspond to the model of each scale. It can be retrieved as a property of a *UnifiedAAMCLMResult* object.

Returnsappearance_reconstructions (*list* of *menpo.image.Image*) – *List* of the appearance reconstructions that correspond to the provided parameters.

fit_from_bb (*image*, *bounding_box*, *max_iters=20*, *gt_shape=None*, *return_costs=False*, ***kwargs*) Fits the multi-scale fitter to an image given an initial bounding box.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•bounding_box (*menpo.shape.PointDirectedGraph*) – The initial bounding box from which the fitting procedure will start. Note that the bounding box is used in order to align the model's reference shape.

•max_iters (*int* or *list* of *int*, optional) – The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

Fits the multi-scale fitter to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape estimate from which the fitting procedure will start.

•max_iters (*int* or *list* of *int*, optional) – The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

warped_images (image, shapes)

Given an input test image and a list of shapes, it warps the image into the shapes. This is useful for generating the warped images of a fitting procedure stored within an *UnifiedAAMCLMResult*.

Parameters

•image (menpo.image.Image or subclass) – The input image to be warped.

•**shapes** (*list* of *menpo.shape.PointCloud*) – The list of shapes in which the image will be warped. The shapes are obtained during the iterations of a fitting procedure.

Returnswarped_images (list of menpo.image.MaskedImage or ndarray) - The warped images.

holistic_features

The features that are extracted from the input image at each scale in ascending order, i.e. from lowest to highest scale.

Typelist of closure

n_scales

Returns the number of scales.

Type*int*

reference_shape

The reference shape that is used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of this reference shape.

Typemenpo.shape.PointCloud

response_covariance

Returns the covariance value of the desired Gaussian response used to train the ensemble of experts.

Type*int*

scales

The scale value of each scale in ascending order, i.e. from lowest to highest scale.

Typelist of int or float

unified_aam_clm

The trained unified AAM-CLM model.

TypeUnifiedAAMCLM or subclass

Optimisation Algorithms

AlternatingRegularisedLandmarkMeanShift

class menpofit.unified_aam_clm.AlternatingRegularisedLandmarkMeanShift (aam_interface,

expert_ensemble, patch_shape, response_covariance, eps=1e-05, **kwargs)

Bases: UnifiedAlgorithm

Alternating Inverse Compositional + Regularized Landmark Mean Shift

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *prior=False*, *a=0.5*) Execute the optimization algorithm.

Parameters

•**image** (*menpo.image.Image*) – The input test image.

•**initial_shape** (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

- •max_iters (*int*, optional) The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.
- •return_costs (*bool*, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned *fitting_result*. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.
- •prior (*bool*, optional) If True, use a Gaussian priors over the latent shape and appearance spaces. see the reference [1] section 3.1.1 for details.
- •a (*float*, optional) Ratio of the image noise variance and the shape noise variance. See [1] section 5 equations (25) & (26) and footnote 6.
- **Returnsfitting_result** (*UnifiedAAMCLMAlgorithmResult*) The parametric iterative fitting result.

References

ProjectOutRegularisedLandmarkMeanShift

class menpofit.unified_aam_clm.ProjectOutRegularisedLandmarkMeanShift (aam_interface,

expert_ensemble, patch_shape, response_covariance, eps=1e-05, **kwargs)

Bases: UnifiedAlgorithm

Project-Out Inverse Compositional + Regularized Landmark Mean Shift

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*, *prior=False*, *a=0.5*) Execute the optimization algorithm.

Parameters

•image (menpo.image.Image) – The input test image.

- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the optimization will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.
- •max_iters (*int*, optional) The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.
- •return_costs (*bool*, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned *fitting_result*. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**prior** (*bool*, optional) – If True, use a Gaussian priors over the latent shape and appearance spaces. see the reference [1] section 3.1.1 for details.

•a (*float*, optional) – Ratio of the image noise variance and the shape noise variance. See [1] section 5 equations (25) & (26) and footnote 6.

Returnsfitting_result (*UnifiedAAMCLMAlgorithmResult*) – The parametric iterative fitting result.

References

Fitting Result

UnifiedAAMCLMResult

<pre>class menpofit.unified_aam_clm.result.UnifiedAAMCLMRes</pre>	sult (<i>results</i> ,	scales,
	affine_transforms,	
	scale_transforms,	
	image=None,	
	gt_shape=None)	
Bases: MultiScaleParametricIterativeResult		

Class for storing the multi-scale iterative fitting result of a Unified AAM-CLM. It holds the shapes, shape parameters, appearance parameters and costs per iteration.

Note: When using a method with a parametric shape model, the first step is to **reconstruct the initial shape** using the shape model. The generated reconstructed shape is then used as initialisation for the iterative optimisation. This step is not counted in the number of iterations.

Parameters

- •results (*list* of *UnifiedAAMCLMAlgorithmResult*) The *list* of optimization results per scale.
- •scales (*list* or *tuple*) The *list* of scale values per scale (low to high).
- •affine_transforms (*list* of *menpo.transform.Affine*) The list of affine transforms per scale that transform the shapes into the original image space.
- •scale_transforms (*list* of *menpo.shape.Scale*) The list of scaling transforms per scale.
- •**image** (*menpo.image.Image* or *subclass* or None, optional) The image on which the fitting process was applied. Note that a copy of the image will be assigned as an attribute. If None, then no image is assigned.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated with the image. If None, then no ground truth shape is assigned.

displacements()

A list containing the displacement between the shape of each iteration and the shape of the previous one.

Typelist of ndarray

displacements_stats (stat_type='mean')

A list containing a statistical metric on the displacements between the shape of each iteration and the shape of the previous one.

- **Parametersstat_type** ({'mean', 'median', 'min', 'max'}, optional) Specifies a statistic metric to be extracted from the displacements.
- **Returnsdisplacements_stat** (*list* of *float*) The statistical metric on the points displacements for each iteration.

RaisesValueError - type must be 'mean', 'median', 'min' or 'max'

errors (compute_error=None)

Returns a list containing the error at each fitting iteration, if the ground truth shape exists.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

Returnserrors (*list* of *float*) – The error at each iteration of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

final_error (compute_error=None)

Returns the final error of the fitting process, if the ground truth shape exists. This is the error computed based on the *final_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the fitted and ground truth shapes.

Returnsfinal_error (*float*) – The final error at the end of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

initial_error(compute_error=None)

Returns the initial error of the fitting process, if the ground truth shape and initial shape exist. This is the error computed based on the *initial_shape*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the initial and ground truth shapes.
- **Returnsinitial_error** (*float*) The initial error at the beginning of the fitting process.

Raises

•ValueError - Initial shape has not been set, so the initial error cannot be computed

•ValueError – Ground truth shape has not been set, so the initial error cannot be computed

plot costs (figure id=None, new figure=False, render lines=True, line colour='b', line style='line_width=2, marker_style='o', *render_markers=True*, marker_size=4, marker_edge_colour='k', marker_edge_width=1.0, marker_face_colour='b', axes_font_name='sans-serif' render_axes=True, axes_font_size=10, axes_font_weight='normal', axes_font_style='normal', $axes_x_limits=0.0$, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6), render grid=True, grid line style='-', grid line width=0.5)

Plot of the cost function evolution at each fitting iteration.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None, optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•line_style ({ '-', '--', '-.', ':'}, optional) – The style of the lines.

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (marker, optional) – The style of the markers. Example marker options

```
{'.', ',', 'o', 'v', '^', '<', '>', '+', 'x', 'D', 'd', 's',
'p', '*', 'h', 'H', '1', '2', '3', '4', '8'}
```

•marker_size (*int*, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (See below, optional) - The font of the axes. Example options

{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({'normal', 'italic', 'oblique'}, optional) - The font style of the axes.

•axes_font_weight (See below, optional) - The font weight of the axes. Example options

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves'

width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

- •axes_y_limits (*float* or (*float*, *float*) or None, optional) The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.
- •axes_x_ticks (list or tuple or None, optional) The ticks of the x axis.
- •axes_y_ticks (list or tuple or None, optional) The ticks of the y axis.
- •figure_size ((float, float) or None, optional) The size of the figure in inches.
- •render_grid (*bool*, optional) If True, the grid will be rendered.
- •grid_line_style ({ '-', '--', '-.', ':'}, optional) The style of the grid lines.

•grid_line_width (float, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

Plot of a statistical metric of the displacement between the shape of each iteration and the shape of the previous one.

Parameters

•**stat_type** ({mean, median, min, max}, optional) – Specifies a statistic metric to be extracted from the displacements (see also *displacements_stats()* method).

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

{-, --, -., :}

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int*, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (*bool*, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

```
{normal, italic, oblique}
```

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

plot_errors (compute_error=None, figure_id=None, new_figure=False, render_lines=True, line colour='b', line style='-', line width=2, render markers=True, marker style='o', marker size=4, marker face colour='b', marker edge colour='k', marker edge width=1.0, render axes=True. axes font name='sans-serif', axes font style='normal', axes font size=10, axes font weight='normal', axes_x_limits=0.0, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6), render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the error evolution at each fitting iteration.

Parameters

•compute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

```
{-, --, -., :}
```

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float*, optional) – The width of the markers' edge.

•render_axes (*bool*, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (float, optional) – The width of the grid lines.

Returnsrenderer (menpo.visualize.GraphPlotter) – The renderer object.

reconstructed_initial_error(compute_error=None)

Returns the error of the reconstructed initial shape of the fitting process, if the ground truth shape exists. This is the error computed based on the *reconstructed_initial_shapes[0]*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the reconstructed initial and ground truth shapes.
- **Returnsreconstructed_initial_error** (*float*) The error that corresponds to the initial shape's reconstruction.
- **Raises**ValueError Ground truth shape has not been set, so the reconstructed initial error cannot be computed

to_result (pass_image=True, pass_initial_shape=True, pass_gt_shape=True)

Returns a *Result* instance of the object, i.e. a fitting result object that does not store the iterations. This can be useful for reducing the size of saved fitting results.

•pass_image (bool, optional) – If True, then the image will get passed (if it exists).

•**pass_initial_shape** (*bool*, optional) – If True, then the initial shape will get passed (if it exists).

•**pass_gt_shape** (*bool*, optional) – If True, then the ground truth shape will get passed (if it exists).

Returnsresult (*Result*) – The final "lightweight" fitting result.

view (figure id=None, new figure=False, render image=True, render final shape=True, render_initial_shape=False, render_gt_shape=False, *subplots_enabled=True*, channels=None, interpolation='bilinear', cmap_name=None, alpha=1.0, masked=True, final_marker_face_colour='r', final_marker_edge_colour='k', final line colour='r'. initial_marker_face_colour='b', *initial_marker_edge_colour='k'*, initial line colour='b'. gt_line_colour='y', gt_marker_face_colour='y', gt_marker_edge_colour='k', render_lines=True, line_style='-', line_width=2, render_markers=True, marker_style='o', marker_size=4, marker_edge_width=1.0, render_numbering=False, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers_font_name='sansserif', numbers font size=10, numbers font style='normal', numbers font weight='normal', numbers_font_colour='k', render_legend=True, legend_title='', legend_font_name='sansserif', legend font style='normal', legend font size=10, legend font weight='normal', legend_marker_scale=None, legend_location=2, legend_bbox_to_anchor=(1.05, 1.0), legend border axes pad=None, legend n columns=1, legend horizontal spacing=None, *legend_vertical_spacing=None*, legend_border=True, legend_border_padding=None, legend shadow=False, legend rounded corners=False, render axes=False, axes font name='sansaxes_font_style='normal', serif', axes font size=10, axes font weight='normal', axes_x_limits=None, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, fig $ure_size=(7, 7)$)

Visualize the fitting result. The method renders the final fitted shape and optionally the initial shape, ground truth shape and the image, id they were provided.

- •figure_id (*object*, optional) The id of the figure to be used.
- •new_figure (bool, optional) If True, a new figure is created.
- •render_image (bool, optional) If True and the image exists, then it gets rendered.
- •render_final_shape (*bool*, optional) If True, then the final fitting shape gets rendered.
- •render_initial_shape (*bool*, optional) If True and the initial fitting shape exists, then it gets rendered.
- •render_gt_shape (*bool*, optional) If True and the ground truth shape exists, then it gets rendered.
- •**subplots_enabled** (*bool*, optional) If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.
- •channels (*int* or *list* of *int* or all or None) If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.
- •interpolation (See Below, optional) The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•final_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_marker_edge_colour (See Below, optional) – The edge colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_line_colour (See Below, optional) – The line colour of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_edge_colour (See Below, optional) – The edge colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_line_colour (See Below, optional) – The line colour of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the ground truth shape. Example options
```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_edge_colour (See Below, optional) – The edge colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_line_colour (See Below, optional) – The line colour of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_lines (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•line_style (*str* or *list* of *str*, optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{'-', '--', '-.', ':'}

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.
- •**render_markers** (*bool* or *list* of *bool*, optional) If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.
- •marker_style (*str* or *list* of *str*, optional) The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order.

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•render_numbering (bool, optional) - If True, the landmarks will be numbered.

•numbers_horizontal_align ({center, right, left}, optional) - The horizontal alignment of the numbers' texts.

•numbers_vertical_align ({center, top, bottom, baseline}, optional) - The vertical alignment of the numbers' texts.

•numbers_font_name (See Below, optional) - The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (See Below, optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) - If True, the legend will be rendered.

•legend_title (str, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style ({normal, italic, oblique}, optional) - The font style of the legend.

•legend_font_size (int, optional) – The font size of the legend.

•legend_font_weight (See Below, optional) – The font weight of the legend. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
ʻright'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- •legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) The bbox that the legend will be anchored.
- •legend_border_axes_pad (*float*, optional) The pad between the axes and legend border.
- •legend_n_columns (*int*, optional) The number of the legend's columns.
- •legend_horizontal_spacing (*float*, optional) The spacing between the columns.
- •legend_vertical_spacing (*float*, optional) The vertical space between the legend entries.
- •legend_border (bool, optional) If True, a frame will be drawn around the legend.
- •legend_border_padding (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.
- •legend_rounded_corners (*bool*, optional) If True, the frame's corners will be rounded (fancybox).
- •render_axes (bool, optional) If True, the axes will be rendered.
- •axes_font_name (See Below, optional) The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

- •axes_font_size (*int*, optional) The font size of the axes.
- •axes_font_style ({normal, italic, oblique}, optional) The font style of the axes.
- •axes_font_weight (See Below, optional) The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (*class*) – The renderer object.

view iterations (figure id=None, new figure=False, iters=None, render image=True, subplots_enabled=False, channels=None. interpolation='bilinear', render lines=True, cmap name=None, alpha=1.0, masked=True, line_style='-', line width=2, *line_colour=None*, render_markers=True, marker edge colour=None, marker face colour=None, marker_style='o', marker_size=4. marker_edge_width=1.0, render numbering=False, numbers_horizontal_align='center'. numbers vertical align='bottom', numbers font name='sans-serif', numbers font size=10, numbers font style='normal', numbers font weight='normal', numrender_legend=True, *bers_font_colour='k'*, legend_title='', legend_font_name='sans-serif', legend_font_style='normal', legend_font_size=10, legend_font_weight='normal', legend_marker_scale=None, *legend location=2*, legend_bbox_to_anchor=(1.05, 1.0). legend_border_axes_pad=None, *legend_n_columns=1*, legend_horizontal_spacing=None, *legend_vertical_spacing=None*, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sans-serif', axes font size=10, axes font style='normal', axes font weight='normal', axes x limits=None, axes y limits=None, axes x ticks=None, axes y ticks=None, figure size=(7, 7))

Visualize the iterations of the fitting process.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•iters (*int* or *list* of *int* or None, optional) – The iterations to be visualized. If None, then all the iterations are rendered.

No.	Visualised shape	Description
0	self.initial_shape	Initial shape
1	self.reconstructed_initial_shape	Reconstructed initial
2	self.shapes[2]	Iteration 1
i	self.shapes[i]	Iteration i-1
n_iters+1	self.final_shape	Final shape

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

•channels (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (*str* (See Below), optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

{none, nearest, bilinear, bicubic, spline16, spline36, hanning, hamming, hermite, kaiser, quadric, catrom, gaussian, bessel, mitchell, sinc, lanczos}

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

- •**render_lines** (*bool* or *list* of *bool*, optional) If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_style (*str* or *list* of *str* (See below), optional) The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options:

```
\{-, --, -., :\}
```

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_colour (*colour* or *list* of *colour* (See Below), optional) The colour of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_style (*str or 'list* of *str* (See below), optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_edge_colour (*colour* or *list* of *colour* (See Below), optional) – The edge colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_face_colour (*colour* or *list* of *colour* (See Below), optional) – The face (filling) colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align (*str* (See below), optional) – The horizontal alignment of the numbers' texts. Example options

```
{center, right, left}
```

•numbers_vertical_align (*str* (See below), optional) – The vertical alignment of the numbers' texts. Example options

```
{center, top, bottom, baseline}
```

•numbers_font_name (*str* (See below), optional) – The font of the numbers. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (*str* (See below), optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style (*str* (See below), optional) – The font style of the legend. Example options

{normal, italic, oblique}

•legend_font_size (*int*, optional) – The font size of the legend.

•legend_font_weight (*str* (See below), optional) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (int, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

•legend_border (bool, optional) – If True, a frame will be drawn around the legend.

•legend_border_padding (*float*, optional) – The fractional whitespace inside the legend border.

•legend_shadow (bool, optional) - If True, a shadow will be drawn behind legend.

•legend_rounded_corners (*bool*, optional) – If True, the frame's corners will be rounded (fancybox).

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) – The renderer object.

view_widget (figure_size=(7, 7))

Visualizes the result object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

appearance_parameters

Returns the *list* of appearance parameters obtained at each iteration of the fitting process. The *list* includes the parameters of the *initial_shape* (if it exists) and *final_shape*.

Type*list* of (n_params,) *ndarray*

costs

Returns a *list* with the cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

final_shape

Returns the final shape of the fitting process.

Typemenpo.shape.PointCloud

gt_shape

Returns the ground truth shape associated with the image. In case there is not an attached ground truth shape, then None is returned.

Typemenpo.shape.PointCloud or None

image

Returns the image that the fitting was applied on, if it was provided. Otherwise, it returns None.

Typemenpo.shape.Image or subclass or None

initial_shape

Returns the initial shape that was provided to the fitting method to initialise the fitting process. In case the initial shape does not exist, then None is returned.

Typemenpo.shape.PointCloud or None

is_iterative

Flag whether the object is an iterative fitting result.

Typebool

n_iters

Returns the total number of iterations of the fitting process.

Type*int*

n_iters_per_scale

Returns the number of iterations per scale of the fitting process.

Typelist of int

n_scales

Returns the number of scales used during the fitting process.

Type*int*

reconstructed_initial_shapes

Returns the result of the reconstruction step that takes place at each scale before applying the iterative optimisation.

Typelist of menpo.shape.PointCloud

shape_parameters

Returns the *list* of shape parameters obtained at each iteration of the fitting process. The *list* includes the parameters of the *initial_shape* (if it exists) and *final_shape*.

Typelist of (n_params,) ndarray

shapes

Returns the *list* of shapes obtained at each iteration of the fitting process. The *list* includes the *initial_shape* (if it exists) and *final_shape*.

Typelist of menpo.shape.PointCloud

UnifiedAAMCLMAlgorithmResult

class menpofit.unified_aam_clm.result.UnifiedAAMCLMAlgorithmResult (shapes,

shape_parameters, appearance_parameters, initial_shape=None, image=None, gt_shape=None, costs=None)

Bases: ParametricIterativeResult

Class for storing the iterative result of a Unified AAM-CLM optimisation algorithm.

Note: When using a method with a parametric shape model, the first step is to **reconstruct the initial shape** using the shape model. The generated reconstructed shape is then used as initialisation for the iterative optimisation. This step is not counted in the number of iterations.

Parameters

•**shapes** (*list* of *menpo.shape.PointCloud*) – The *list* of shapes per iteration. The first and last members correspond to the initial and final shapes, respectively.

•**shape_parameters** (*list* of (n_shape_parameters,) *ndarray*) – The *list* of shape parameters per iteration. The first and last members correspond to the initial and final shapes, respectively.

•appearance_parameters (*list* of (n_appearance_parameters,) *ndarray*) – The *list* of appearance parameters per iteration. The first and last members correspond to the initial and final shapes, respectively.

•initial_shape (*menpo.shape.PointCloud* or None, optional) – The initial shape from which the fitting process started. If None, then no initial shape is assigned.

•**image** (*menpo.image.Image* or *subclass* or None, optional) – The image on which the fitting process was applied. Note that a copy of the image will be assigned as an attribute. If None, then no image is assigned.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated with the image. If None, then no ground truth shape is assigned.

•costs (*list* of *float* or None, optional) – The *list* of cost per iteration. If None, then it is assumed that the cost function cannot be computed for the specific algorithm.

displacements()

A list containing the displacement between the shape of each iteration and the shape of the previous one.

Typelist of ndarray

displacements_stats (stat_type='mean')

A list containing a statistical metric on the displacements between the shape of each iteration and the shape of the previous one.

- **Parametersstat_type** ({'mean', 'median', 'min', 'max'}, optional) Specifies a statistic metric to be extracted from the displacements.
- **Returnsdisplacements_stat** (*list* of *float*) The statistical metric on the points displacements for each iteration.

RaisesValueError - type must be 'mean', 'median', 'min' or 'max'

errors (compute_error=None)

Returns a list containing the error at each fitting iteration, if the ground truth shape exists.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

Returnserrors (*list* of *float*) – The error at each iteration of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

final_error(compute_error=None)

Returns the final error of the fitting process, if the ground truth shape exists. This is the error computed based on the *final_shape*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the fitted and ground truth shapes.
- **Returnsfinal_error** (*float*) The final error at the end of the fitting process.
- **Raises**ValueError Ground truth shape has not been set, so the final error cannot be computed

initial_error(compute_error=None)

Returns the initial error of the fitting process, if the ground truth shape and initial shape exist. This is the error computed based on the *initial_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the initial and ground truth shapes.

Returnsinitial_error (*float*) – The initial error at the beginning of the fitting process.

Raises

•ValueError - Initial shape has not been set, so the initial error cannot be computed

•ValueError – Ground truth shape has not been set, so the initial error cannot be computed

plot_costs (figure_id=None, new_figure=False, render_lines=True, line_colour='b', line_style='', line_width=2, render_markers=True, marker_style='o', marker_size=4,
marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0,
render_axes=True, axes_font_name='sans-serif', axes_font_size=10,
axes_font_style='normal', axes_font_weight='normal', axes_font_size=0.0,
axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6),
render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the cost function evolution at each fitting iteration.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None, optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•line_style ({ '-', '--', '-.', ': '}, optional) – The style of the lines.

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) - If True, the markers will be rendered.

•marker_style (marker, optional) – The style of the markers. Example marker options

{'.', ', ', 'o', 'v', '^', '<', '>', '+', 'x', 'D', 'd', 's', 'p', '*', 'h', 'H', '1', '2', '3', '4', '8'}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (See below, optional) - The font of the axes. Example options

{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}

•axes_font_size (*int*, optional) – The font size of the axes.

```
•axes_font_style ({'normal', 'italic', 'oblique'}, optional) - The font style of the axes.
```

•axes_font_weight (See below, optional) - The font weight of the axes. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
    'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
    'extra bold', 'black'}
```

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (float, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

Plot of a statistical metric of the displacement between the shape of each iteration and the shape of the previous one.

Parameters

•**stat_type** ({mean, median, min, max}, optional) – Specifies a statistic metric to be extracted from the displacements (see also *displacements_stats()* method).

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

{-, --, -., :}

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) - If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (float, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

plot_errors (compute_error=None, figure_id=None, new_figure=False, render_lines=True, line colour='b'. line style='-', line width=2, render markers=True, marker_style='o', marker_size=4, marker_face_colour='b', marker_edge_colour='k', marker edge width=1.0, render axes=True, axes font name='sans-serif', axes_font_size=10, axes_font_style='normal', axes_font_weight='normal', axes x limits=0.0, axes y limits=None, axes x ticks=None, axes y ticks=None, figure_size=(10, 6), render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the error evolution at each fitting iteration.

Parameters

•compute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

{-, --, -., :}

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

```
{normal, italic, oblique}
```

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (*list* or *tuple* or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (menpo.visualize.GraphPlotter) – The renderer object.

reconstructed_initial_error(compute_error=None)

Returns the error of the reconstructed initial shape of the fitting process, if the ground truth shape exists. This is the error computed based on the *reconstructed_initial_shape*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the reconstructed initial and ground truth shapes.
- **Returnsreconstructed_initial_error** (*float*) The error that corresponds to the initial shape's reconstruction.
- **Raises**ValueError Ground truth shape has not been set, so the reconstructed initial error cannot be computed

to_result (*pass_image=True*, *pass_initial_shape=True*, *pass_gt_shape=True*)

Returns a *Result* instance of the object, i.e. a fitting result object that does not store the iterations. This can be useful for reducing the size of saved fitting results.

Parameters

•pass_image (bool, optional) – If True, then the image will get passed (if it exists).

•**pass_initial_shape** (*bool*, optional) – If True, then the initial shape will get passed (if it exists).

•**pass_gt_shape** (*bool*, optional) – If True, then the ground truth shape will get passed (if it exists).

Returnsresult (*Result*) – The final "lightweight" fitting result.

view (figure id=None, new figure=False, render image=True, render final shape=True, render_gt_shape=False, render initial shape=False, subplots enabled=True, channels=None, interpolation='bilinear', cmap_name=None, alpha=1.0, masked=True, final_marker_face_colour='r', final_marker_edge_colour='k', final_line_colour='r', initial_marker_face_colour='b', *initial_marker_edge_colour='k'*, initial_line_colour='b', gt_marker_edge_colour='k', gt_marker_face_colour='y', gt_line_colour='y', render_lines=True, line_style='-', line_width=2, render_markers=True, marker_style='o', marker_size=4, *marker_edge_width=1.0*, render_numbering=False, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers_font_name='sansserif', numbers_font_size=10, numbers_font_style='normal', numbers_font_weight='normal', numbers_font_colour='k', render_legend=True, legend_title='', legend_font_name='sanslegend_font_style='normal', legend_font_size=10, legend_font_weight='normal', serif', legend marker scale=None, legend location=2, legend bbox to anchor=(1.05, 1.0), legend_border_axes_pad=None, *legend_n_columns=1*, *legend_horizontal_spacing=None*, *legend vertical spacing=None*, legend border=True, legend border padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sansserif', axes font size=10, axes font style='normal', axes font weight='normal', axes x limits=None, axes y limits=None, axes x ticks=None, figure size=(7, 7))

Visualize the fitting result. The method renders the final fitted shape and optionally the initial shape, ground truth shape and the image, id they were provided.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•render_final_shape (*bool*, optional) – If True, then the final fitting shape gets rendered.

- •render_initial_shape (*bool*, optional) If True and the initial fitting shape exists, then it gets rendered.
- •render_gt_shape (*bool*, optional) If True and the ground truth shape exists, then it gets rendered.
- •**subplots_enabled** (*bool*, optional) If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.
- •channels (*int* or *list* of *int* or all or None) If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.
- •interpolation (See Below, optional) The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•final_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_marker_edge_colour (See Below, optional) – The edge colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_line_colour (See Below, optional) – The line colour of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_edge_colour (See Below, optional) – The edge colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_line_colour (See Below, optional) – The line colour of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_edge_colour (See Below, optional) – The edge colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_line_colour (See Below, optional) – The line colour of the ground truth shape. Example options

{r, g, b, c, m, k, w}
or
(3,) ndarray

•**render_lines** (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•line_style (*str* or *list* of *str*, optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{ '-', '--', '-.', ':' }

•line_width (*float* or *list* of *float*, optional) – The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•marker_style (*str* or *list* of *str*, optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order.

- •marker_edge_width (*float* or *list* of *float*, optional) The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.
- •render_numbering (bool, optional) If True, the landmarks will be numbered.
- •numbers_horizontal_align ({center, right, left}, optional) The horizontal alignment of the numbers' texts.
- •numbers_vertical_align ({center, top, bottom, baseline}, optional) The vertical alignment of the numbers' texts.
- •numbers_font_name (See Below, optional) The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (See Below, optional) – The font weight of the numbers. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (*bool*, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

- •legend_font_style ({normal, italic, oblique}, optional) The font style of the legend.
- •legend_font_size (*int*, optional) The font size of the legend.

•legend_font_weight (See Below, optional) – The font weight of the legend. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

- •legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) The bbox that the legend will be anchored.
- •legend_border_axes_pad (*float*, optional) The pad between the axes and legend border.
- •legend_n_columns (int, optional) The number of the legend's columns.
- •legend_horizontal_spacing (*float*, optional) The spacing between the columns.
- •legend_vertical_spacing (*float*, optional) The vertical space between the legend entries.
- •legend_border (bool, optional) If True, a frame will be drawn around the legend.
- •legend_border_padding (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.
- •legend_rounded_corners (*bool*, optional) If True, the frame's corners will be rounded (fancybox).
- •render_axes (bool, optional) If True, the axes will be rendered.
- •axes_font_name (See Below, optional) The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

- •axes_font_size (int, optional) The font size of the axes.
- •axes_font_style ({normal, italic, oblique}, optional) The font style of the axes.
- •axes_font_weight (See Below, optional) The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) - The renderer object.

view_iterations (figure_id=None, new_figure=False, iters=None, render_image=True, subplots enabled=False, channels=None, interpolation='bilinear', cmap_name=None, alpha=1.0,masked=True, render_lines=True, line style='-', line width=2, line colour=None, render markers=True, marker_edge_colour=None, marker_face_colour=None, marker_style='o', marker size=4, marker_edge_width=1.0, render_numbering=False, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers font name='sans-serif', numbers font size=10, numnumbers font weight='normal', bers font style='normal', питbers font colour='k', render legend=True, legend_title='', legend_font_name='sans-serif', legend_font_style='normal', legend_font_size=10, legend_font_weight='normal', legend_marker_scale=None, legend location=2, legend bbox to anchor=(1.05,1.0), legend border axes pad=None, legend n columns=1, legend horizontal spacing=None, *legend vertical spacing=None*, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sans-serif', axes_font_style='normal', axes_font_weight='normal', axes_font_size=10, axes x limits=None, axes y limits=None, axes x ticks=None, axes_y_ticks=None, figure_size=(7, 7))

Visualize the iterations of the fitting process.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•iters (*int* or *list* of *int* or None, optional) – The iterations to be visualized. If None, then all the iterations are rendered.

No.	Visualised shape	Description
0	self.initial_shape	Initial shape
1	self.reconstructed_initial_shape	Reconstructed initial
2	self.shapes[2]	Iteration 1
i	self.shapes[i]	Iteration i-1
n_iters+1	self.final_shape	Final shape

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

•channels (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (*str* (See Below), optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (*bool*, optional) – If True, then the image is rendered as masked.

•**render_lines** (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•line_style (*str* or *list* of *str* (See below), optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options:

{-, --, -., :}

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_colour (*colour* or *list* of *colour* (See Below), optional) The colour of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_style (*str or 'list* of *str* (See below), optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_edge_colour (*colour* or *list* of *colour* (See Below), optional) – The edge colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_face_colour (*colour* or *list* of *colour* (See Below), optional) – The face (filling) colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{r, g, b, c, m, k, w}
or
(3,) ndarray

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align (*str* (See below), optional) – The horizontal alignment of the numbers' texts. Example options

{center, right, left}

•numbers_vertical_align (*str* (See below), optional) – The vertical alignment of the numbers' texts. Example options

{center, top, bottom, baseline}

•numbers_font_name (*str* (See below), optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (*str* (See below), optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) - If True, the legend will be rendered.

•legend_title (str, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style (*str* (See below), optional) – The font style of the legend. Example options

{normal, italic, oblique}

•legend_font_size (*int*, optional) – The font size of the legend.

•legend_font_weight (*str* (See below), optional) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (*int*, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

•legend_border (bool, optional) – If True, a frame will be drawn around the legend.

•legend_border_padding (*float*, optional) – The fractional whitespace inside the legend border.

•legend_shadow (bool, optional) - If True, a shadow will be drawn behind legend.

•legend_rounded_corners (*bool*, optional) – If True, the frame's corners will be rounded (fancybox).

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) - The renderer object.

view_widget (figure_size=(7, 7))

Visualizes the result object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

appearance_parameters

Returns the *list* of appearance parameters obtained at each iteration of the fitting process. The *list* includes the parameters of the *initial_shape* (if it exists) and *final_shape*.

Type*list* of (n_params,) *ndarray*

costs

Returns a *list* with the cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

final_shape

Returns the final shape of the fitting process.

Typemenpo.shape.PointCloud

gt_shape

Returns the ground truth shape associated with the image. In case there is not an attached ground truth shape, then None is returned.

Typemenpo.shape.PointCloud or None

image

Returns the image that the fitting was applied on, if it was provided. Otherwise, it returns None.

Typemenpo.shape.Image or subclass or None

initial_shape

Returns the initial shape that was provided to the fitting method to initialise the fitting process. In case the initial shape does not exist, then None is returned.

Typemenpo.shape.PointCloud or None

is_iterative

Flag whether the object is an iterative fitting result.

Typebool

n_iters

Returns the total number of iterations of the fitting process.

Typeint

reconstructed_initial_shape

Returns the initial shape's reconstruction with the shape model that was used to initialise the iterative optimisation process.

Typemenpo.shape.PointCloud

shape_parameters

Returns the *list* of shape parameters obtained at each iteration of the fitting process. The *list* includes the parameters of the *reconstructed_initial_shape* and *final_shape*.

Typelist of (n_params,) ndarray

shapes

Returns the *list* of shapes obtained at each iteration of the fitting process. The *list* includes the *initial_shape* (if it exists), *reconstructed_initial_shape* and *final_shape*.

Typelist of menpo.shape.PointCloud

menpofit.dlib

Ensemble of Regression Trees (provided by DLib)

Method that employs gradient boosting for learning an ensemble of regression trees to estimate the landmark positions directly from a sparse subset of pixel intensities.

DlibERT

```
group=None.
class menpofit.dlib.DlibERT (images,
                                                                     bounding_box_group_glob=None,
                                   reference_shape=None,
                                                                 diagonal=None,
                                                                                         scales = (0.5,
                                                 n perturbations=30,
                                   1.0).
                                                                              n dlib perturbations=1,
                                   perturb_from_gt_bounding_box=<function
                                   noisy shape from bounding box>,
                                                                           n iterations=10,
                                                                                                 fea-
                                   ture_padding=0, n_pixel_pairs=400, distance_prior_weighting=0.1,
                                                                  n_{split_tests=20},
                                   regularisation_weight=0.1,
                                                                                         n trees=500,
                                   n_tree_levels=5, verbose=False)
```

Bases: MultiScaleNonParametricFitter

Class for training a multi-scale Ensemble of Regression Trees model. This class uses the implementation provided by the official DLib package (http://dlib.net/) and makes it multi-scale.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•group (*str* or None, optional) – The landmark group that corresponds to the ground truth shape of each image. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.

•bounding_box_group_glob (*glob* or None, optional) – Glob that defines the bounding boxes to be used for training. If None, then the bounding boxes of the ground truth shapes are used.

- •**reference_shape** (*menpo.shape.PointCloud* or None, optional) The reference shape that will be used for normalising the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.
- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •**n_perturbations** (*int* or None, optional) The number of perturbations to be generated from each of the bounding boxes using *perturb_from_gt_bounding_box*. Note that the total number of perturbations is *n_perturbations* * *n_dlib_perturbations*.
- •**perturb_from_gt_bounding_box** (*function*, optional) The function that will be used to generate the perturbations.
- •n_dlib_perturbations (*int* or None or *list* of those, optional) The number of perturbations to be generated from the part of DLib. DLib calls this "oversampling amount". If *list*, it must specify a value per scale. Note that the total number of perturbations is *n_perturbations* * *n_dlib_perturbations*.
- •**n_iterations** (*int* or *list* of *int*, optional) The number of iterations (cascades) of each level. If *list*, it must specify a value per scale. If *int*, then it defines the total number of iterations (cascades) over all scales.
- •feature_padding (*float* or *list* of *float*, optional) When we randomly sample the pixels for the feature pool we do so in a box fit around the provided training landmarks. By default, this box is the tightest box that contains the landmarks. However, you can expand or shrink the size of the pixel sampling region by setting a different value of padding. To explain this precisely, for a padding of 0 we say that the pixels are sampled from a box of size 1x1. The padding value is added to each side of the box. So a padding of 0.5 would cause the algorithm to sample pixels from a box that was 2x2, effectively multiplying the area pixels are sampled from by 4. Similarly, setting the padding to -0.2 would cause it to sample from a box 0.6x0.6 in size. If *list*, it must specify a value per scale.
- •**n_pixel_pairs** (*int* or *list* of *int*, optional) P parameter from [1]. At each level of the cascade we randomly sample pixels from the image. These pixels are used to generate features for the random trees. So in general larger settings of this parameter give better accuracy but make the algorithm run slower. If *list*, it must specify a value per scale.
- •distance_prior_weighting (*float* or *list* of *float*, optional) To decide how to split nodes in the regression trees the algorithm looks at pairs of pixels in the image. These pixel pairs are sampled randomly but with a preference for selecting pixels that are near each other. This parameter controls this "nearness" preference. In particular, smaller values will make the algorithm prefer to select pixels close together and larger values will make it care less about picking nearby pixel pairs. Note that this is the inverse of how it is defined in [1]. For this object, you should think of *distance_prior_weighting* as "the fraction of the bounding box will we traverse to find a neighboring pixel". Nominally, this is normalized between 0 and 1. So reasonable settings are values in the range (0, 1). If *list*, it must specify a value per scale.

•regularisation_weight (*float* or *list* of *float*, optional) – Boosting regularization parameter - *nu* from [1]. Larger values may cause overfitting but improve performance on training data. If *list*, it must specify a value per scale.

•**n_split_tests** (*int* or *list* of *int*, optional) – When generating the random trees we randomly sample n_split_tests possible split features at each node and pick the one that gives the best split. Larger values of this parameter will usually give more accurate outputs but take longer to train. It is equivalent of S from [1]. If *list*, it must specify a value per scale.

•**n_trees** (*int* or *list* of *int*, optional) – Number of trees created for each cascade. The total number of trees in the learned model is equal n_trees * n_tree_levels. Equivalent to *K* from [1]. If *list*, it must specify a value per scale.

•**n_tree_levels** (*int* or *list* of *int*, optional) – The number of levels in the tree (depth of tree). In particular, there are pow(2, n_tree_levels) leaves in each tree. Equivalent to F from [1]. If *list*, it must specify a value per scale.

•verbose (bool, optional) - If True, then the progress of building ERT will be printed.

References

fit_from_bb (image, bounding_box, gt_shape=None)

Fits the model to an image given an initial bounding box.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•**bounding_box** (*menpo.shape.PointDirectedGraph*) – The initial bounding box from which the fitting procedure will start.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult*) – The result of the fitting procedure.

fit_from_shape (image, initial_shape, gt_shape=None)

Fits the model to an image. Note that it is not possible to initialise the fitting process from a shape. Thus, this method raises a warning and calls *fit_from_bb* with the bounding box of the provided *initial_shape*.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape estimate from which the fitting procedure will start. Note that the shape won't actually be used, only its bounding box.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult*) – The result of the fitting procedure.

holistic_features

The features that are extracted from the input image at each scale in ascending order, i.e. from lowest to highest scale.

Typelist of closure

n_scales

Returns the number of scales.

Type*int*

reference_shape

The reference shape that is used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of this reference shape.

Typemenpo.shape.PointCloud

scales

The scale value of each scale in ascending order, i.e. from lowest to highest scale.

Type*list* of *int* or *float*

DlibWrapper

class menpofit.dlib.DlibWrapper(model)

Bases: object

Wrapper class for fitting a pre-trained ERT model. Pre-trained models are provided by the official DLib package (http://dlib.net/).

Parametersmodel (*Path* or *str*) – Path to the pre-trained model.

fit_from_bb(image, bounding_box, gt_shape=None)

Fits the model to an image given an initial bounding box.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•bounding_box (*menpo.shape.PointDirectedGraph*) – The initial bounding box.

•gt_shape (menpo.shape.PointCloud) – The ground truth shape associated to the image.

Returnsfitting_result (*Result*) – The result of the fitting procedure.

fit_from_shape (image, initial_shape, gt_shape=None)

Fits the model to an image. Note that it is not possible to initialise the fitting process from a shape. Thus, this method raises a warning and calls *fit_from_bb* with the bounding box of the provided *initial_shape*.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape estimate from which the fitting procedure will start. Note that the shape won't actually be used, only its bounding box.

•gt_shape (menpo.shape.PointCloud) - The ground truth shape associated to the image.

Returnsfitting_result (*Result*) – The result of the fitting procedure.

menpofit.lk

Lucas-Kanade Alignment

LK performs alignment (or optical flow estimation) between a template image and a test image with respect to an affine transformation.

LucasKanadeFitter

class menpofit.lk.LucasKanadeFitter (template, group=None, *holistic_features=<function* no op>. diagonal=None, *transform*=<*class* 'menpofit.transform.homogeneous.DifferentiableAlignmentAffine'>, *algorithm_cls=<class* scales = (0.5,1.0), 'menpofit.lk.algorithm.InverseCompositional'>, resid*ual cls=<class 'menpofit.lk.residual.SSD'>*) Bases: MultiScaleNonParametricFitter

Class for defining a multi-scale Lucas-Kanade fitter that performs alignment with respect to a homogeneous transform. Please see the references for a basic list of relevant papers.

Parameters

•template (menpo.image.Image) – The template image.

•group (*str* or None, optional) – The landmark group of the *template* that will be used as reference shape. If None and the *template* only has a single landmark group, then that is the one that will be used.

- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape (specified by *group*) so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •**scales** (*tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale.
- •transform (*subclass* of *DP* and *DX*, optional) A differential homogeneous transform object, e.g. *DifferentiableAlignmentAffine*.
- •algorithm_cls (*class*, optional) The Lukas-Kanade optimisation algorithm that will get applied. The possible algorithms in *menpofit.lk.algorithm* are:

Class	Warp Direction	Warp Update
ForwardAdditive	Forward	Additive
ForwardCompositional	Forward	Compositional
InverseCompositional	Inverse	

•**residual_cls** (*class* subclass, optional) – The residual that will get applied. All possible residuals are:

Class	Description
SSD	Sum of Squared Differences
FourierSSD	Sum of Squared Differences on Fourier domain
ECC	Enhanced Correlation Coefficient
GradientImages	Image Gradient
GradientCorrelation	Gradient Correlation

References

fit_from_bb (image, bounding_box, max_iters=20, gt_shape=None, return_costs=False, **kwargs)
Fits the multi-scale fitter to an image given an initial bounding box.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •**bounding_box** (*menpo.shape.PointDirectedGraph*) The initial bounding box from which the fitting procedure will start. Note that the bounding box is used in order to align the model's reference shape.
- •max_iters (*int* or *list* of *int*, optional) The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.
- •gt_shape (*menpo.shape.PointCloud*, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

- **Returnsfitting_result** (*MultiScaleNonParametricIterativeResult* or subclass) The multi-scale fitting result containing the result of the fitting procedure.

Fits the multi-scale fitter to an image given an initial shape.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape estimate from which the fitting procedure will start.
- •max_iters (*int* or *list* of *int*, optional) The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.
- •gt_shape (*menpo.shape.PointCloud*, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.
- •**kwargs** (*dict*, optional) Additional keyword arguments that can be passed to specific implementations.
- **Returnsfitting_result** (*MultiScaleNonParametricIterativeResult* or subclass) The multi-scale fitting result containing the result of the fitting procedure.

warped_images (image, shapes)

Given an input test image and a list of shapes, it warps the image into the shapes. This is useful for generating the warped images of a fitting procedure stored within a *LucasKanadeResult*.

Parameters

•image (menpo.image.Image or subclass) – The input image to be warped.

•**shapes** (*list* of *menpo.shape.PointCloud*) – The list of shapes in which the image will be warped. The shapes are obtained during the iterations of a fitting procedure.

Returnswarped_images (*list* of *menpo.image.MaskedImage* or *ndarray*) – The warped images.

holistic_features

The features that are extracted from the input image at each scale in ascending order, i.e. from lowest to highest scale.

Typelist of closure

n_scales

Returns the number of scales.

Typeint

reference_shape

The reference shape that is used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of this reference shape.

Typemenpo.shape.PointCloud

scales

The scale value of each scale in ascending order, i.e. from lowest to highest scale.

Typelist of int or float

Optimisation Algorithms

ForwardAdditive

class menpofit.lk.ForwardAdditive (template, transform, residual, eps=1e-10)
Bases: LucasKanade

Forward Additive (FA) Lucas-Kanade algorithm.

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*) Execute the optimization algorithm.

Parameters

•image (menpo.image.Image) – The input test image.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

Returnsfitting_result (LucasKanadeAlgorithmResult) – The parametric iterative fitting result.

warped_images (image, shapes)

Given an input test image and a list of shapes, it warps the image into the shapes. This is useful for generating the warped images of a fitting procedure stored within a *LucasKanadeResult*.

Parameters

•image (menpo.image.Image or subclass) – The input image to be warped.

•**shapes** (*list* of *menpo.shape.PointCloud*) – The list of shapes in which the image will be warped. The shapes are obtained during the iterations of a fitting procedure.

Returnswarped_images (*list* of *menpo.image.MaskedImage* or *ndarray*) – The warped images.

ForwardCompositional

class menpofit.lk.ForwardCompositional (template, transform, residual, eps=1e-10)
Bases: LucasKanade

Forward Compositional (FC) Lucas-Kanade algorithm

Parameters

•template (menpo.image.Image or subclass) – The image template.

•transform (*subclass* of *DP* and *DX*, optional) – A differential affine transform object, e.g. *DifferentiableAlignmentAffine*.

•**residual** (*class* subclass, optional) – The residual that will get applied. All possible residuals are:

Class	Description
SSD	Sum of Squared Differences
FourierSSD	Sum of Squared Differences on Fourier domain
ECC	Enhanced Correlation Coefficient
GradientImages	Image Gradient
GradientCorrelation	Gradient Correlation

•eps (float, optional) - Value for checking the convergence of the optimization.

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*) Execute the optimization algorithm.

Parameters

•image (menpo.image.Image) – The input test image.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes. **Returnsfitting_result** (*LucasKanadeAlgorithmResult*) – The parametric iterative fitting result.

warped_images (image, shapes)

Given an input test image and a list of shapes, it warps the image into the shapes. This is useful for generating the warped images of a fitting procedure stored within a *LucasKanadeResult*.

Parameters

•image (menpo.image.Image or subclass) – The input image to be warped.

•**shapes** (*list* of *menpo.shape.PointCloud*) – The list of shapes in which the image will be warped. The shapes are obtained during the iterations of a fitting procedure.

Returnswarped_images (*list* of *menpo.image.MaskedImage* or *ndarray*) – The warped images.

InverseCompositional

class menpofit.lk.InverseCompositional (template, transform, residual, eps=1e-10)
Bases: LucasKanade

Inverse Compositional (IC) Lucas-Kanade algorithm

Parameters

•template (menpo.image.Image or subclass) – The image template.

•transform (*subclass* of *DP* and *DX*, optional) – A differential affine transform object, e.g. *DifferentiableAlignmentAffine*.

•**residual** (*class* subclass, optional) – The residual that will get applied. All possible residuals are:

Class	Description
SSD	Sum of Squared Differences
FourierSSD	Sum of Squared Differences on Fourier domain
ECC	Enhanced Correlation Coefficient
GradientImages	Image Gradient
GradientCorrelation	Gradient Correlation

•eps (float, optional) – Value for checking the convergence of the optimization.

run (*image*, *initial_shape*, *gt_shape=None*, *max_iters=20*, *return_costs=False*) Execute the optimization algorithm.

Parameters

•image (menpo.image.Image) – The input test image.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the optimization will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape of the image. It is only needed in order to get passed in the optimization result object, which has the ability to compute the fitting error.

•max_iters (*int*, optional) – The maximum number of iterations. Note that the algorithm may converge, and thus stop, earlier.

•return_costs (*bool*, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

Returnsfitting_result (*LucasKanadeAlgorithmResult*) – The parametric iterative fitting result.

warped_images (image, shapes)

Given an input test image and a list of shapes, it warps the image into the shapes. This is useful for generating the warped images of a fitting procedure stored within a *LucasKanadeResult*.

Parameters

•image (menpo.image.Image or subclass) – The input image to be warped.

•**shapes** (*list* of *menpo.shape.PointCloud*) – The list of shapes in which the image will be warped. The shapes are obtained during the iterations of a fitting procedure.

Returnswarped_images (*list* of *menpo.image.MaskedImage* or *ndarray*) – The warped images.

Residuals

SSD

class menpofit.lk.SSD (kernel=None)

Bases: Residual

Class for Sum of Squared Differences residual.

References

```
cost_closure()
```

Method to compute the optimization cost.

Returnscost (*float*) – The cost value.

gradient (image, forward=None)

Calculates the gradients of the given method.

If forward is provided, then the gradients are warped (as required in the forward additive algorithm)

Parameters

- •image (menpo.image.Image) The image to calculate the gradients for
- •forward (*tuple* or None, optional) A *tuple* containing the extra weights required for the function *warp* (which should be passed as a function handle), i.e. (`menpo.image. Image`, `menpo.transform.AlignableTransform>`). If None, then the optimization algorithm is assumed to be inverse.

hessian (*sdi*, *sdi*2=None)

Calculates the Gauss-Newton approximation to the Hessian.

This is abstracted because some residuals expect the Hessian to be pre-processed. The Gauss-Newton approximation to the Hessian is defined as:

 $\mathbf{J}\mathbf{J}^{\mathbf{T}}$

Parameters

•sdi ((N, n_params) *ndarray*) – The steepest descent images.

•sdi2 ((N, n_params) *ndarray* or None, optional) – The steepest descent images.

ReturnsH ((n_params, n_params) *ndarray*) – The approximation to the Hessian

steepest_descent_images (image, dW_dp, forward=None)

Calculates the standard steepest descent images.

Within the forward additive framework this is defined as

 $\nabla I \frac{\partial W}{\partial p}$

The input image is vectorised (N-pixels) so that masked images can be handled.

Parameters

•**image** (*menpo.image.Image*) – The image to calculate the steepest descent images from, could be either the template or input image depending on which framework is used.

•dW_dp (*ndarray*) – The Jacobian of the warp.

•forward (*tuple* or None, optional) – A *tuple* containing the extra weights required for the function *warp* (which should be passed as a function handle), i.e. (`menpo.image. Image`, `menpo.transform.AlignableTransform>`). If None, then the optimization algorithm is assumed to be inverse.

ReturnsVT_dW_dp((N, n_params) *ndarray*) – The steepest descent images

steepest_descent_update (sdi, image, template)

Calculates the steepest descent parameter updates.

These are defined, for the forward additive algorithm, as:

$$\sum_{x} [\nabla I \frac{\partial W}{\partial p}]^{T} [T(x) - I(W(x; p))]$$

Parameters

•sdi ((N, n_params) ndarray) – The steepest descent images.

•**image** (*menpo.image.Image*) – Either the warped image or the template (depending on the framework)

•template (*menpo.image.Image*) – Either the warped image or the template (depending on the framework)

Returnssd_delta_p ((n_params,) *ndarray*) – The steepest descent parameter updates.

FourierSSD

class menpofit.lk.FourierSSD (kernel=None)

Bases: Residual

Class for Sum of Squared Differences on the Fourier domain residual.

References

cost_closure()

Method to compute the optimization cost.
Returnscost (*float*) – The cost value.

gradient (image, forward=None)

Calculates the gradients of the given method.

If forward is provided, then the gradients are warped (as required in the forward additive algorithm)

Parameters

•image (menpo.image.Image) - The image to calculate the gradients for

•forward (*tuple* or None, optional) – A *tuple* containing the extra weights required for the function *warp* (which should be passed as a function handle), i.e. (`menpo.image. Image`, `menpo.transform.AlignableTransform>`). If None, then the optimization algorithm is assumed to be inverse.

hessian (*sdi*, *sdi*2=*None*)

Calculates the Gauss-Newton approximation to the Hessian.

This is abstracted because some residuals expect the Hessian to be pre-processed. The Gauss-Newton approximation to the Hessian is defined as:

 JJ^{T}

Parameters

•sdi ((N, n_params) ndarray) - The steepest descent images.

•sdi2((N, n_params) ndarray or None, optional) – The steepest descent images.

ReturnsH ((n_params, n_params) *ndarray*) – The approximation to the Hessian

steepest_descent_images (image, dW_dp, forward=None) Calculates the standard steepest descent images.

Within the forward additive framework this is defined as

$$\nabla I \frac{\partial W}{\partial p}$$

The input image is vectorised (*N*-pixels) so that masked images can be handled.

Parameters

•**image** (*menpo.image.Image*) – The image to calculate the steepest descent images from, could be either the template or input image depending on which framework is used.

•dW_dp (*ndarray*) – The Jacobian of the warp.

•forward (*tuple* or None, optional) – A *tuple* containing the extra weights required for the function *warp* (which should be passed as a function handle), i.e. (`menpo.image. Image`, `menpo.transform.AlignableTransform>`). If None, then the optimization algorithm is assumed to be inverse.

ReturnsVT_dW_dp((N, n_params) *ndarray*) – The steepest descent images

steepest_descent_update(sdi, image, template)

Calculates the steepest descent parameter updates.

These are defined, for the forward additive algorithm, as:

$$\sum_{x} [\nabla I \frac{\partial W}{\partial p}]^{T} [T(x) - I(W(x;p))]$$

Parameters

•sdi ((N, n_params) ndarray) – The steepest descent images.

•**image** (*menpo.image.Image*) – Either the warped image or the template (depending on the framework)

•template (*menpo.image.Image*) – Either the warped image or the template (depending on the framework)

Returnssd_delta_p ((n_params,) *ndarray*) – The steepest descent parameter updates.

ECC

class menpofit.lk.ECC

Bases: Residual

Class for Enhanced Correlation Coefficient residual.

cost_closure()

Method to compute the optimization cost.

Returnscost (*float*) – The cost value.

gradient (image, forward=None)

Calculates the gradients of the given method.

If forward is provided, then the gradients are warped (as required in the forward additive algorithm)

Parameters

•image (menpo.image.Image) – The image to calculate the gradients for

•forward (*tuple* or None, optional) – A *tuple* containing the extra weights required for the function *warp* (which should be passed as a function handle), i.e. (`menpo.image. Image`, `menpo.transform.AlignableTransform>`). If None, then the optimization algorithm is assumed to be inverse.

hessian (*sdi*, *sdi*2=*None*)

Calculates the Gauss-Newton approximation to the Hessian.

This is abstracted because some residuals expect the Hessian to be pre-processed. The Gauss-Newton approximation to the Hessian is defined as:

$\mathbf{J}\mathbf{J}^{\mathrm{T}}$

Parameters

•sdi ((N, n_params) *ndarray*) – The steepest descent images.

•sdi2 ((N, n_params) *ndarray* or None, optional) – The steepest descent images.

ReturnsH ((n_params, n_params) *ndarray*) – The approximation to the Hessian

steepest_descent_images (image, dW_dp, forward=None)
Calculates the standard steepest descent images.

Within the forward additive framework this is defined as

$$\nabla I \frac{\partial W}{\partial p}$$

The input image is vectorised (N-pixels) so that masked images can be handled.

Parameters

•**image** (*menpo.image.Image*) – The image to calculate the steepest descent images from, could be either the template or input image depending on which framework is used.

•dW_dp (*ndarray*) – The Jacobian of the warp.

•forward (*tuple* or None, optional) – A *tuple* containing the extra weights required for the function *warp* (which should be passed as a function handle), i.e. (`menpo.image. Image`, `menpo.transform.AlignableTransform>`). If None, then the optimization algorithm is assumed to be inverse.

ReturnsVT_dW_dp ((N, n_params) *ndarray*) – The steepest descent images

steepest_descent_update(sdi, image, template)

Calculates the steepest descent parameter updates.

These are defined, for the forward additive algorithm, as:

$$\sum_{x} [\nabla I \frac{\partial W}{\partial p}]^{T} [T(x) - I(W(x;p))]$$

Parameters

•sdi ((N, n_params) ndarray) – The steepest descent images.

- •**image** (*menpo.image.Image*) Either the warped image or the template (depending on the framework)
- •template (*menpo.image.Image*) Either the warped image or the template (depending on the framework)

Returnssd_delta_p ((n_params,) *ndarray*) – The steepest descent parameter updates.

GradientImages

class menpofit.lk.GradientImages
 Bases: Residual

Class for Gradient Images residual.

References

```
cost_closure()
```

Method to compute the optimization cost.

Returnscost (*float*) – The cost value.

```
gradient (image, forward=None)
```

Calculates the gradients of the given method.

If forward is provided, then the gradients are warped (as required in the forward additive algorithm)

Parameters

•image (menpo.image.Image) - The image to calculate the gradients for

•forward (*tuple* or None, optional) – A *tuple* containing the extra weights required for the function *warp* (which should be passed as a function handle), i.e. (`menpo.image. Image`, `menpo.transform.AlignableTransform>`). If None, then the optimization algorithm is assumed to be inverse.

hessian (*sdi*, *sdi*2=None)

Calculates the Gauss-Newton approximation to the Hessian.

This is abstracted because some residuals expect the Hessian to be pre-processed. The Gauss-Newton approximation to the Hessian is defined as:

 $\mathbf{J}\mathbf{J}^{\mathrm{T}}$

Parameters

•sdi ((N, n_params) *ndarray*) – The steepest descent images.

•sdi2((N, n_params) ndarray or None, optional) – The steepest descent images.

ReturnsH ((n_params, n_params) ndarray) - The approximation to the Hessian

steepest_descent_images (image, dW_dp, forward=None)

Calculates the standard steepest descent images.

Within the forward additive framework this is defined as

$$\nabla I \frac{\partial W}{\partial p}$$

The input image is vectorised (N-pixels) so that masked images can be handled.

Parameters

•**image** (*menpo.image.Image*) – The image to calculate the steepest descent images from, could be either the template or input image depending on which framework is used.

•dW_dp (*ndarray*) – The Jacobian of the warp.

•forward (*tuple* or None, optional) – A *tuple* containing the extra weights required for the function *warp* (which should be passed as a function handle), i.e. (`menpo.image. Image`, `menpo.transform.AlignableTransform>`). If None, then the optimization algorithm is assumed to be inverse.

ReturnsVT_dW_dp((N, n_params) *ndarray*) – The steepest descent images

steepest_descent_update(sdi, image, template)

Calculates the steepest descent parameter updates.

These are defined, for the forward additive algorithm, as:

$$\sum_{x} [\nabla I \frac{\partial W}{\partial p}]^{T} [T(x) - I(W(x; p))]$$

Parameters

•sdi ((N, n_params) ndarray) - The steepest descent images.

- •**image** (*menpo.image.Image*) Either the warped image or the template (depending on the framework)
- •template (*menpo.image.Image*) Either the warped image or the template (depending on the framework)

Returnssd_delta_p ((n_params,) *ndarray*) – The steepest descent parameter updates.

GradientCorrelation

class menpofit.lk.GradientCorrelation

Bases: Residual

Class for Gradient Correlation residual.

References

cost_closure()

Method to compute the optimization cost.

Returnscost (*float*) – The cost value.

gradient (image, forward=None)

Calculates the gradients of the given method.

If forward is provided, then the gradients are warped (as required in the forward additive algorithm)

Parameters

•image (menpo.image.Image) - The image to calculate the gradients for

•forward (*tuple* or None, optional) – A *tuple* containing the extra weights required for the function *warp* (which should be passed as a function handle), i.e. (`menpo.image. Image`, `menpo.transform.AlignableTransform>`). If None, then the optimization algorithm is assumed to be inverse.

hessian (*sdi*, *sdi*2=*None*)

Calculates the Gauss-Newton approximation to the Hessian.

This is abstracted because some residuals expect the Hessian to be pre-processed. The Gauss-Newton approximation to the Hessian is defined as:

$\mathbf{J}\mathbf{J}^{\mathrm{T}}$

Parameters

•sdi ((N, n_params) ndarray) – The steepest descent images.

•sdi2((N, n_params) ndarray or None, optional) - The steepest descent images.

ReturnsH ((n_params, n_params) *ndarray*) – The approximation to the Hessian

steepest_descent_images (image, dW_dp, forward=None)
Calculates the standard steepest descent images.

Within the forward additive framework this is defined as

$$\nabla I \frac{\partial W}{\partial p}$$

The input image is vectorised (N-pixels) so that masked images can be handled.

Parameters

•**image** (*menpo.image.Image*) – The image to calculate the steepest descent images from, could be either the template or input image depending on which framework is used.

•dW_dp (*ndarray*) – The Jacobian of the warp.

•forward (*tuple* or None, optional) – A *tuple* containing the extra weights required for the function *warp* (which should be passed as a function handle), i.e. (`menpo.image. Image`, `menpo.transform.AlignableTransform>`). If None, then the optimization algorithm is assumed to be inverse.

ReturnsVT_dW_dp((N, n_params) *ndarray*) – The steepest descent images

steepest_descent_update(sdi, image, template)

Calculates the steepest descent parameter updates.

These are defined, for the forward additive algorithm, as:

$$\sum_{x} [\nabla I \frac{\partial W}{\partial p}]^{T} [T(x) - I(W(x; p))]$$

Parameters

•sdi ((N, n_params) ndarray) – The steepest descent images.

- •**image** (*menpo.image.Image*) Either the warped image or the template (depending on the framework)
- •template (*menpo.image.Image*) Either the warped image or the template (depending on the framework)

Returnssd_delta_p ((n_params,) *ndarray*) – The steepest descent parameter updates.

Fitting Result

LucasKanadeResult

Class for storing the multi-scale iterative fitting result of an ATM. It holds the shapes, shape parameters and costs per iteration.

Parameters

- •results (list of ATMAlgorithmResult) The list of optimization results per scale.
- •scales (*list* or *tuple*) The *list* of scale values per scale (low to high).
- •affine_transforms (*list* of *menpo.transform.Affine*) The list of affine transforms per scale that transform the shapes into the original image space.
- •scale_transforms (*list* of *menpo.shape.Scale*) The list of scaling transforms per scale.
- •**image** (*menpo.image.Image* or *subclass* or None, optional) The image on which the fitting process was applied. Note that a copy of the image will be assigned as an attribute. If None, then no image is assigned.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated with the image. If None, then no ground truth shape is assigned.

displacements()

A list containing the displacement between the shape of each iteration and the shape of the previous one.

Typelist of ndarray

displacements_stats (stat_type='mean')

A list containing a statistical metric on the displacements between the shape of each iteration and the shape of the previous one.

- **Parametersstat_type** ({'mean', 'median', 'min', 'max'}, optional) Specifies a statistic metric to be extracted from the displacements.
- **Returnsdisplacements_stat** (*list* of *float*) The statistical metric on the points displacements for each iteration.

RaisesValueError - type must be 'mean', 'median', 'min' or 'max'

errors (compute_error=None)

Returns a list containing the error at each fitting iteration, if the ground truth shape exists.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

Returnserrors (*list* of *float*) – The error at each iteration of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

final_error (compute_error=None)

Returns the final error of the fitting process, if the ground truth shape exists. This is the error computed based on the *final_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the fitted and ground truth shapes.

Returnsfinal_error (*float*) – The final error at the end of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

initial_error(compute_error=None)

Returns the initial error of the fitting process, if the ground truth shape and initial shape exist. This is the error computed based on the *initial_shape*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the initial and ground truth shapes.
- **Returnsinitial_error** (*float*) The initial error at the beginning of the fitting process.

Raises

•ValueError - Initial shape has not been set, so the initial error cannot be computed

•ValueError – Ground truth shape has not been set, so the initial error cannot be computed

plot costs (figure id=None, new figure=False, render lines=True, line colour='b', line style='line_width=2, marker_style='o', *render_markers=True*, marker_size=4, marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0, axes_font_name='sans-serif' axes_font_size=10, render_axes=True, axes_font_weight='normal', axes_font_style='normal', $axes_x_limits=0.0$, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6), render grid=True, grid line style='-', grid line width=0.5)

Plot of the cost function evolution at each fitting iteration.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None, optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•line_style ({ '-', '--', '-.', ':'}, optional) – The style of the lines.

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (marker, optional) – The style of the markers. Example marker options

```
{'.', ',', 'o', 'v', '^', '<', '>', '+', 'x', 'D', 'd', 's',
'p', '*', 'h', 'H', '1', '2', '3', '4', '8'}
```

•marker_size (*int*, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (See below, optional) - The font of the axes. Example options

{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({'normal', 'italic', 'oblique'}, optional) - The font style of the axes.

•axes_font_weight (See below, optional) - The font weight of the axes. Example options

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves'

width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

- •axes_y_limits (*float* or (*float*, *float*) or None, optional) The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.
- •axes_x_ticks (list or tuple or None, optional) The ticks of the x axis.
- •axes_y_ticks (list or tuple or None, optional) The ticks of the y axis.
- •figure_size ((float, float) or None, optional) The size of the figure in inches.
- •render_grid (*bool*, optional) If True, the grid will be rendered.
- •grid_line_style ({ '-', '--', '-.', ':'}, optional) The style of the grid lines.

•grid_line_width (float, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

Plot of a statistical metric of the displacement between the shape of each iteration and the shape of the previous one.

Parameters

•**stat_type** ({mean, median, min, max}, optional) – Specifies a statistic metric to be extracted from the displacements (see also *displacements_stats()* method).

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

{-, --, -., :}

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int*, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (*bool*, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

```
{normal, italic, oblique}
```

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

plot_errors (compute_error=None, figure_id=None, new_figure=False, render_lines=True, line colour='b', line style='-', line width=2, render markers=True, marker style='o', marker size=4, marker face colour='b', marker edge colour='k', marker edge width=1.0, render axes=True. axes font name='sans-serif', axes font style='normal', axes font size=10, axes font weight='normal', axes_x_limits=0.0, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6), render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the error evolution at each fitting iteration.

Parameters

•compute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

```
{-, --, -., :}
```

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float*, optional) – The width of the markers' edge.

•render_axes (*bool*, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (float, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

reconstructed_initial_error(compute_error=None)

Returns the error of the reconstructed initial shape of the fitting process, if the ground truth shape exists. This is the error computed based on the *reconstructed_initial_shapes[0]*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the reconstructed initial and ground truth shapes.
- **Returnsreconstructed_initial_error** (*float*) The error that corresponds to the initial shape's reconstruction.
- **Raises**ValueError Ground truth shape has not been set, so the reconstructed initial error cannot be computed

to_result (pass_image=True, pass_initial_shape=True, pass_gt_shape=True)

Returns a *Result* instance of the object, i.e. a fitting result object that does not store the iterations. This can be useful for reducing the size of saved fitting results.

Parameters

•pass_image (bool, optional) – If True, then the image will get passed (if it exists).

•**pass_initial_shape** (*bool*, optional) – If True, then the initial shape will get passed (if it exists).

•**pass_gt_shape** (*bool*, optional) – If True, then the ground truth shape will get passed (if it exists).

Returnsresult (*Result*) – The final "lightweight" fitting result.

view (figure id=None, new_figure=False, render image=True, render final shape=True, render_initial_shape=False, render_gt_shape=False, *subplots_enabled=True*, channels=None, interpolation='bilinear', cmap_name=None, alpha=1.0, masked=True, final_marker_face_colour='r', final_marker_edge_colour='k', final line colour='r'. initial_marker_face_colour='b', *initial_marker_edge_colour='k'*, initial line colour='b'. gt_line_colour='y', gt_marker_face_colour='y', gt_marker_edge_colour='k', render_lines=True, line_style='-', line_width=2, render_markers=True, marker_style='o', marker_size=4, marker_edge_width=1.0, render_numbering=False, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers_font_name='sansserif', numbers font size=10, numbers font style='normal', numbers font weight='normal', numbers_font_colour='k', render_legend=True, legend_title='', legend_font_name='sansserif', legend_font_style='normal', legend_font_size=10, legend_font_weight='normal', legend_marker_scale=None, legend_location=2, legend_bbox_to_anchor=(1.05, 1.0), legend border axes pad=None, legend n columns=1, legend horizontal spacing=None, *legend_vertical_spacing=None*, legend_border=True, legend_border_padding=None, legend shadow=False, legend rounded corners=False, render axes=False, axes font name='sansaxes_font_style='normal', serif', axes font size=10, axes font weight='normal', axes_x_limits=None, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, fig $ure_size=(7, 7)$)

Visualize the fitting result. The method renders the final fitted shape and optionally the initial shape, ground truth shape and the image, id they were provided.

Parameters

- •figure_id (*object*, optional) The id of the figure to be used.
- •new_figure (bool, optional) If True, a new figure is created.
- •render_image (bool, optional) If True and the image exists, then it gets rendered.
- •render_final_shape (*bool*, optional) If True, then the final fitting shape gets rendered.
- •render_initial_shape (*bool*, optional) If True and the initial fitting shape exists, then it gets rendered.
- •render_gt_shape (*bool*, optional) If True and the ground truth shape exists, then it gets rendered.
- •**subplots_enabled** (*bool*, optional) If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.
- •channels (*int* or *list* of *int* or all or None) If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.
- •interpolation (See Below, optional) The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•final_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_marker_edge_colour (See Below, optional) – The edge colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_line_colour (See Below, optional) – The line colour of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_edge_colour (See Below, optional) – The edge colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_line_colour (See Below, optional) – The line colour of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_edge_colour (See Below, optional) – The edge colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_line_colour (See Below, optional) – The line colour of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_lines (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•line_style (*str* or *list* of *str*, optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{'-', '--', '-.', ':'}

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.
- •**render_markers** (*bool* or *list* of *bool*, optional) If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.
- •marker_style (*str* or *list* of *str*, optional) The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order. Example options:

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order.

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•render_numbering (bool, optional) - If True, the landmarks will be numbered.

•numbers_horizontal_align ({center, right, left}, optional) - The horizontal alignment of the numbers' texts.

•numbers_vertical_align ({center, top, bottom, baseline}, optional) - The vertical alignment of the numbers' texts.

•numbers_font_name (See Below, optional) - The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (See Below, optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) - If True, the legend will be rendered.

•legend_title (str, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style ({normal, italic, oblique}, optional) - The font style of the legend.

•legend_font_size (int, optional) – The font size of the legend.

•legend_font_weight (See Below, optional) – The font weight of the legend. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
ʻright'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- •legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) The bbox that the legend will be anchored.
- •legend_border_axes_pad (*float*, optional) The pad between the axes and legend border.
- •legend_n_columns (*int*, optional) The number of the legend's columns.
- •legend_horizontal_spacing (float, optional) The spacing between the columns.
- •legend_vertical_spacing (*float*, optional) The vertical space between the legend entries.
- •legend_border (bool, optional) If True, a frame will be drawn around the legend.
- •legend_border_padding (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.
- •legend_rounded_corners (*bool*, optional) If True, the frame's corners will be rounded (fancybox).
- •render_axes (bool, optional) If True, the axes will be rendered.
- •axes_font_name (See Below, optional) The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

- •axes_font_size (*int*, optional) The font size of the axes.
- •axes_font_style ({normal, italic, oblique}, optional) The font style of the axes.
- •axes_font_weight (See Below, optional) The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (*class*) – The renderer object.

view iterations (figure id=None, new figure=False, iters=None, render image=True, subplots_enabled=False, channels=None. interpolation='bilinear', render lines=True, cmap name=None, alpha=1.0, masked=True. *line_style='-'*, line width=2, *line_colour=None*, render_markers=True, marker edge colour=None, marker face colour=None, marker_style='o', marker_size=4. marker_edge_width=1.0, render numbering=False, numbers horizontal align='center'. numbers vertical align='bottom', numbers font name='sans-serif', numbers font size=10, numbers font style='normal', numbers font weight='normal', numrender_legend=True, *bers_font_colour='k'*, legend_title='', legend_font_name='sans-serif', legend_font_style='normal', legend_font_size=10, legend_font_weight='normal', legend_marker_scale=None, *legend location=2*, legend_bbox_to_anchor=(1.05, 1.0). legend_border_axes_pad=None, *legend_n_columns=1*, legend_horizontal_spacing=None, legend_vertical_spacing=None, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sans-serif', axes font size=10, axes font style='normal', axes font weight='normal', axes x limits=None, axes y limits=None, axes x ticks=None, axes y ticks=None, figure size=(7, 7))

Visualize the iterations of the fitting process.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•iters (*int* or *list* of *int* or None, optional) – The iterations to be visualized. If None, then all the iterations are rendered.

No.	Visualised shape	Description
0	self.initial_shape	Initial shape
1	self.reconstructed_initial_shape	Reconstructed initial
2	self.shapes[2]	Iteration 1
i	self.shapes[i]	Iteration i-1
n_iters+1	self.final_shape	Final shape

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

•channels (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (*str* (See Below), optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

{none, nearest, bilinear, bicubic, spline16, spline36, hanning, hamming, hermite, kaiser, quadric, catrom, gaussian, bessel, mitchell, sinc, lanczos}

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

- •**render_lines** (*bool* or *list* of *bool*, optional) If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_style (*str* or *list* of *str* (See below), optional) The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options:

```
\{-, --, -., :\}
```

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_colour (*colour* or *list* of *colour* (See Below), optional) The colour of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_style (*str or 'list* of *str* (See below), optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_edge_colour (*colour* or *list* of *colour* (See Below), optional) – The edge colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_face_colour (*colour* or *list* of *colour* (See Below), optional) – The face (filling) colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align (*str* (See below), optional) – The horizontal alignment of the numbers' texts. Example options

```
{center, right, left}
```

•numbers_vertical_align (*str* (See below), optional) – The vertical alignment of the numbers' texts. Example options

```
{center, top, bottom, baseline}
```

•numbers_font_name (*str* (See below), optional) – The font of the numbers. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (*str* (See below), optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style (*str* (See below), optional) – The font style of the legend. Example options

{normal, italic, oblique}

•legend_font_size (*int*, optional) – The font size of the legend.

•legend_font_weight (*str* (See below), optional) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (int, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

•legend_border (bool, optional) – If True, a frame will be drawn around the legend.

• **legend_border_padding** (*float*, optional) – The fractional whitespace inside the legend border.

•legend_shadow (bool, optional) – If True, a shadow will be drawn behind legend.

•legend_rounded_corners (*bool*, optional) – If True, the frame's corners will be rounded (fancybox).

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) – The renderer object.

view_widget (figure_size=(7, 7))

Visualizes the result object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

costs

Returns a *list* with the cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

final_shape

Returns the final shape of the fitting process.

Typemenpo.shape.PointCloud

gt_shape

Returns the ground truth shape associated with the image. In case there is not an attached ground truth shape, then None is returned.

Typemenpo.shape.PointCloud or None

homogeneous_parameters

Returns the *list* of parameters of the homogeneous transform obtained at each iteration of the fitting process. The *list* includes the parameters of the *initial_shape* (if it exists) and *final_shape*.

Typelist of (n_params,) ndarray

image

Returns the image that the fitting was applied on, if it was provided. Otherwise, it returns None.

Typemenpo.shape.Image or subclass or None

initial_shape

Returns the initial shape that was provided to the fitting method to initialise the fitting process. In case the initial shape does not exist, then None is returned.

Typemenpo.shape.PointCloud or None

is_iterative

Flag whether the object is an iterative fitting result.

Typebool

n_iters

Returns the total number of iterations of the fitting process.

Typeint

n_iters_per_scale

Returns the number of iterations per scale of the fitting process.

Typelist of int

n_scales

Returns the number of scales used during the fitting process.

Type*int*

reconstructed_initial_shapes

Returns the result of the reconstruction step that takes place at each scale before applying the iterative optimisation.

Typelist of menpo.shape.PointCloud

shapes

Returns the *list* of shapes obtained at each iteration of the fitting process. The *list* includes the *initial_shape* (if it exists) and *final_shape*.

Typelist of menpo.shape.PointCloud

LucasKanadeAlgorithmResult

Bases: ParametricIterativeResult

Class for storing the iterative result of a Lucas-Kanade Image Alignment optimization algorithm.

Parameters

•**shapes** (*list* of *menpo.shape.PointCloud*) – The *list* of shapes per iteration. The first and last members correspond to the initial and final shapes, respectively.

- •homogeneous_parameters (*list* of (n_parameters,) *ndarray*) The *list* of parameters of the homogeneous transform per iteration. The first and last members correspond to the initial and final shapes, respectively.
- •initial_shape (*menpo.shape.PointCloud* or None, optional) The initial shape from which the fitting process started. If None, then no initial shape is assigned.
- •**image** (*menpo.image.Image* or *subclass* or None, optional) The image on which the fitting process was applied. Note that a copy of the image will be assigned as an attribute. If None, then no image is assigned.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated with the image. If None, then no ground truth shape is assigned.

•costs (*list* of *float* or None, optional) – The *list* of cost per iteration. If None, then it is assumed that the cost function cannot be computed for the specific algorithm.

displacements()

A list containing the displacement between the shape of each iteration and the shape of the previous one.

Typelist of ndarray

displacements_stats (stat_type='mean')

A list containing a statistical metric on the displacements between the shape of each iteration and the shape of the previous one.

Parametersstat_type ({'mean', 'median', 'min', 'max'}, optional) – Specifies a statistic metric to be extracted from the displacements.

Returnsdisplacements_stat (*list* of *float*) – The statistical metric on the points displacements for each iteration.

RaisesValueError - type must be 'mean', 'median', 'min' or 'max'

errors (compute_error=None)

Returns a list containing the error at each fitting iteration, if the ground truth shape exists.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

Returnserrors (*list* of *float*) – The error at each iteration of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

final_error(compute_error=None)

Returns the final error of the fitting process, if the ground truth shape exists. This is the error computed based on the *final_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the fitted and ground truth shapes.

Returnsfinal_error (*float*) – The final error at the end of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

initial_error(compute_error=None)

Returns the initial error of the fitting process, if the ground truth shape and initial shape exist. This is the error computed based on the *initial_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the initial and ground truth shapes.

Returnsinitial_error (*float*) – The initial error at the beginning of the fitting process.

Raises

- •ValueError Initial shape has not been set, so the initial error cannot be computed
- •ValueError Ground truth shape has not been set, so the initial error cannot be computed
- plot_costs (figure_id=None, new_figure=False, render_lines=True, line_colour='b', line_style='render markers=True, marker style='o'. line width=2, marker size=4. marker face colour='b', marker edge width=1.0, marker_edge_colour='k', render axes=True, axes font name='sans-serif', axes font size=10, axes_font_style='normal', axes_font_weight='normal', $axes_x_limits=0.0$, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6), render grid=True, grid line style='-', grid line width=0.5)

Plot of the cost function evolution at each fitting iteration.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (*bool*, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None, optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3,) ndarray

•line_style ({ '-', '--', '-.', ':'}, optional) – The style of the lines.

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) - If True, the markers will be rendered.

•marker_style (marker, optional) – The style of the markers. Example marker options

```
{'.', ', ', 'o', 'v', '^', '<', '>', '+', 'x', 'D', 'd', 's',
'p', '*', 'h', 'H', '1', '2', '3', '4', '8'}
```

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (See below, optional) - The font of the axes. Example options

```
{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}
```

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({'normal', 'italic', 'oblique'}, optional) - The font style of the axes.

•axes_font_weight (See below, optional) - The font weight of the axes. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
'extra bold', 'black'}
```

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

Plot of a statistical metric of the displacement between the shape of each iteration and the shape of the previous one.

Parameters

•**stat_type** ({mean, median, min, max}, optional) – Specifies a statistic metric to be extracted from the displacements (see also *displacements_stats()* method).

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (*bool*, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

{-, --, -., :}

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((*float*, *float*) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•**grid_line_style** ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

plot errors (*compute* error=None, figure id=None. new figure=False, render lines=True, *line_style='-'*, line width=2, render markers=True, line colour='b', marker style='o', marker size=4, marker face colour='b', marker edge colour='k', marker_edge_width=1.0, render_axes=True, axes_font_name='sans-serif', axes_font_weight='normal', axes font size=10, axes font style='normal', axes x limits=0.0, axes y limits=None, axes x ticks=None, axes y ticks=None, figure size=(10, 6), render grid=True, grid line style='-', grid line width=0.5)

Plot of the error evolution at each fitting iteration.

Parameters

•compute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

```
\{-, --, -., :\}
```

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float*, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes font size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

reconstructed_initial_error(compute_error=None)

Returns the error of the reconstructed initial shape of the fitting process, if the ground truth shape exists. This is the error computed based on the *reconstructed_initial_shape*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the reconstructed initial and ground truth shapes.
- **Returnsreconstructed_initial_error** (*float*) The error that corresponds to the initial shape's reconstruction.
- **Raises**ValueError Ground truth shape has not been set, so the reconstructed initial error cannot be computed

to_result (pass_image=True, pass_initial_shape=True, pass_gt_shape=True)

Returns a *Result* instance of the object, i.e. a fitting result object that does not store the iterations. This can be useful for reducing the size of saved fitting results.

Parameters

•pass_image (bool, optional) – If True, then the image will get passed (if it exists).

•**pass_initial_shape** (*bool*, optional) – If True, then the initial shape will get passed (if it exists).

•**pass_gt_shape** (*bool*, optional) – If True, then the ground truth shape will get passed (if it exists).

Returnsresult (*Result*) – The final "lightweight" fitting result.

view (figure id=None, new figure=False, render image=True, render final shape=True, render initial shape=False, render gt shape=False, subplots enabled=True, channels=None, interpolation='bilinear', cmap_name=None, alpha=1.0, masked=True, final_marker_face_colour='r', final_marker_edge_colour='k', final_line_colour='r', ini*initial_marker_edge_colour='k'*, initial_line_colour='b', tial_marker_face_colour='b', gt_marker_edge_colour='k', gt marker face colour='y'. gt line colour='y', render_lines=True, line_style='-', line_width=2, render_markers=True, marker_style='o', marker size=4. marker_edge_width=1.0, render_numbering=False, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers_font_name='sansserif', numbers_font_size=10, numbers_font_style='normal', numbers_font_weight='normal', numbers_font_colour='k', render_legend=True, legend_title='', legend_font_name='sansserif'. legend font style='normal', legend font size=10, legend font weight='normal', legend_marker_scale=None, legend_location=2, legend_bbox_to_anchor=(1.05, 1.0), legend border axes pad=None, legend n columns=1, legend horizontal spacing=None, *legend_vertical_spacing=None*, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sansserif', axes font size=10, axes font style='normal', axes font weight='normal', axes x limits=None, axes y limits=None, axes x ticks=None, figure size=(7, 7))

Visualize the fitting result. The method renders the final fitted shape and optionally the initial shape, ground truth shape and the image, id they were provided.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

- •render_image (bool, optional) If True and the image exists, then it gets rendered.
- •render_final_shape (*bool*, optional) If True, then the final fitting shape gets rendered.
- •render_initial_shape (*bool*, optional) If True and the initial fitting shape exists, then it gets rendered.

•**render_gt_shape** (*bool*, optional) – If True and the ground truth shape exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

•channels (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (See Below, optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•final_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_marker_edge_colour (See Below, optional) – The edge colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_line_colour (See Below, optional) – The line colour of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_edge_colour (See Below, optional) – The edge colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_line_colour (See Below, optional) – The line colour of the initial shape. Example options

{r, g, b, c, m, k, w}
or
(3,) ndarray

•gt_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_edge_colour (See Below, optional) – The edge colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_line_colour (See Below, optional) – The line colour of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_lines (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•line_style (*str* or *list* of *str*, optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{'-', '--', '-.', ':'}

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.
- •**render_markers** (*bool* or *list* of *bool*, optional) If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.
- •marker_style (*str* or *list* of *str*, optional) The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order.

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•render_numbering (bool, optional) - If True, the landmarks will be numbered.

•numbers_horizontal_align ({center, right, left}, optional) - The horizontal alignment of the numbers' texts.

•numbers_vertical_align ({center, top, bottom, baseline}, optional) – The vertical alignment of the numbers' texts.

•numbers_font_name (See Below, optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (See Below, optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) - If True, the legend will be rendered.

•legend_title (str, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style ({normal, italic, oblique}, optional) - The font style of the legend.

•legend_font_size (int, optional) – The font size of the legend.

•legend_font_weight (See Below, optional) – The font weight of the legend. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- •legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) The bbox that the legend will be anchored.
- •legend_border_axes_pad (*float*, optional) The pad between the axes and legend border.
- •legend_n_columns (*int*, optional) The number of the legend's columns.
- •legend_horizontal_spacing (*float*, optional) The spacing between the columns.
- •legend_vertical_spacing (*float*, optional) The vertical space between the legend entries.
- •legend_border (bool, optional) If True, a frame will be drawn around the legend.
- •legend_border_padding (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.
- •legend_rounded_corners (*bool*, optional) If True, the frame's corners will be rounded (fancybox).
- •render_axes (bool, optional) If True, the axes will be rendered.
- •axes_font_name (See Below, optional) The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

- •axes_font_size (*int*, optional) The font size of the axes.
- •axes_font_style ({normal, italic, oblique}, optional) The font style of the axes.
- •axes_font_weight (See Below, optional) The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (*class*) – The renderer object.

view iterations (figure id=None, new figure=False, iters=None, render image=True, subplots_enabled=False, channels=None. interpolation='bilinear', render lines=True, cmap name=None, alpha=1.0, masked=True. *line_style='-'*, line width=2, *line_colour=None*, render_markers=True, marker edge colour=None, marker face colour=None, marker_style='o', marker_size=4. marker_edge_width=1.0, render numbering=False, numbers horizontal align='center'. numbers vertical align='bottom', numbers font name='sans-serif', numbers font size=10, numbers font style='normal', numbers font weight='normal', numrender_legend=True, *bers_font_colour='k'*, legend_title='', legend_font_name='sans-serif', legend_font_style='normal', legend_font_size=10, legend_font_weight='normal', legend_marker_scale=None, *legend location=2*, legend_bbox_to_anchor=(1.05, 1.0). legend_border_axes_pad=None, *legend_n_columns=1*, legend_horizontal_spacing=None, legend_vertical_spacing=None, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sans-serif', axes font size=10, axes font style='normal', axes font weight='normal', axes x limits=None, axes y limits=None, axes x ticks=None, axes y ticks=None, figure size=(7, 7))

Visualize the iterations of the fitting process.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•iters (*int* or *list* of *int* or None, optional) – The iterations to be visualized. If None, then all the iterations are rendered.

No.	Visualised shape	Description
0	self.initial_shape	Initial shape
1	self.reconstructed_initial_shape	Reconstructed initial
2	self.shapes[2]	Iteration 1
i	self.shapes[i]	Iteration i-1
n_iters+1	self.final_shape	Final shape

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

•channels (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (*str* (See Below), optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

{none, nearest, bilinear, bicubic, spline16, spline36, hanning, hamming, hermite, kaiser, quadric, catrom, gaussian, bessel, mitchell, sinc, lanczos}

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•**render_lines** (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•line_style (*str* or *list* of *str* (See below), optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options:

{-, --, -., :}

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_colour (*colour* or *list* of *colour* (See Below), optional) The colour of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_style (*str or 'list* of *str* (See below), optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_edge_colour (*colour* or *list* of *colour* (See Below), optional) – The edge colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_face_colour (*colour* or *list* of *colour* (See Below), optional) – The face (filling) colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different
value per iteration shape.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align (*str* (See below), optional) – The horizontal alignment of the numbers' texts. Example options

```
{center, right, left}
```

•numbers_vertical_align (*str* (See below), optional) – The vertical alignment of the numbers' texts. Example options

{center, top, bottom, baseline}

•numbers_font_name (*str* (See below), optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (*str* (See below), optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) - If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style (*str* (See below), optional) – The font style of the legend. Example options

{normal, italic, oblique}

•legend_font_size (*int*, optional) – The font size of the legend.

•legend_font_weight (*str* (See below), optional) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (*int*, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

•legend_border (bool, optional) – If True, a frame will be drawn around the legend.

• **legend_border_padding** (*float*, optional) – The fractional whitespace inside the legend border.

•legend_shadow (bool, optional) – If True, a shadow will be drawn behind legend.

•legend_rounded_corners (*bool*, optional) – If True, the frame's corners will be rounded (fancybox).

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) - The renderer object.

view_widget (figure_size=(7, 7))

Visualizes the result object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

costs

Returns a *list* with the cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

final_shape

Returns the final shape of the fitting process.

Typemenpo.shape.PointCloud

gt_shape

Returns the ground truth shape associated with the image. In case there is not an attached ground truth shape, then None is returned.

Typemenpo.shape.PointCloud or None

homogeneous_parameters

Returns the *list* of parameters of the homogeneous transform obtained at each iteration of the fitting process. The *list* includes the parameters of the *initial_shape* (if it exists) and *final_shape*.

Typelist of (n_params,) ndarray

image

Returns the image that the fitting was applied on, if it was provided. Otherwise, it returns None.

Typemenpo.shape.Image or subclass or None

initial_shape

Returns the initial shape that was provided to the fitting method to initialise the fitting process. In case the initial shape does not exist, then None is returned.

Typemenpo.shape.PointCloud or None

is_iterative

Flag whether the object is an iterative fitting result.

Typebool

n_iters

Returns the total number of iterations of the fitting process.

Typeint

reconstructed_initial_shape

Returns the initial shape's reconstruction with the shape model that was used to initialise the iterative optimisation process.

Typemenpo.shape.PointCloud

shape_parameters

Returns the *list* of shape parameters obtained at each iteration of the fitting process. The *list* includes the parameters of the *reconstructed_initial_shape* and *final_shape*.

Typelist of (n_params,) ndarray

shapes

Returns the *list* of shapes obtained at each iteration of the fitting process. The *list* includes the *initial_shape* (if it exists), *reconstructed_initial_shape* and *final_shape*.

Typelist of menpo.shape.PointCloud

menpofit.sdm

Supervised Descent Method

SDM is a cascaded-regression deformable model that learns average descent directions that minimise a given cost function.

SupervisedDescentFitter

class menpofit.sdm.SupervisedDescentFitter	(images,	group=None,	bound-
	ing_box_group_g	lob=None,	
	sd_algorithm_cls	=None, reference_shape	=None,
	diagonal=None,	holistic_features= <f< td=""><td>unction</td></f<>	unction
	no_op>, patch	_features= <function n<="" td=""><td>o_op>,</td></function>	o_op>,
	patch_shape=(17	, 17), scales=(0.5,	1.0),
	n_iterations=3,	n_perturbations=30,	per-
	turb_from_gt_boi	unding_box= <function< td=""><td></td></function<>	
	noisy_shape_from_bounding_box>,		
	batch_size=None	, verbose=False)	
Bases: MultiScaleNonParametricFitter			

Class for training a multi-scale Supervised Descent model.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •group (*str* or None, optional) The landmark group that corresponds to the ground truth shape of each image. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.
- •bounding_box_group_glob (*glob* or None, optional) Glob that defines the bounding boxes to be used for training. If None, then the bounding boxes of the ground truth shapes are used.
- •sd_algorithm_cls (*class*, optional) The Supervised Descent algorithm to be used. The possible algorithms are are separated in the following four categories:

Non-parametric:

Class	Regression
NonParametricNewton	IRLRegression
NonParametricGaussNewton	IIRLRegression
NonParametricPCRRegression	PCRRegression
NonParametricOptimalRegression	OptimalLinearRegression
NonParametricOPPRegression	OPPRegression

Parametric shape:

Class	Regression
ParametricShapeNewton	IRLRegression
ParametricShapeGaussNewton	IIRLRegression
ParametricShapePCRRegression	PCRRegression
ParametricShapeOptimalRegressio.	n OptimalLinearRegression
ParametricShapeOPPRegression	ParametricShapeOPPRegression

Parametric appearance:

Class	Regression
ParametricAppearanceProjectOutNewton	IRLRegression
ParametricAppearanceProjectOutGuassNewton	IIRLRegression
ParametricAppearanceMeanTemplateNewton	IRLRegression
ParametricAppearanceMeanTemplateGuassNewton	IIRLRegression
ParametricAppearanceWeightsNewton	IRLRegression
ParametricAppearanceWeightsGuassNewton	IIRLRegression

Parametric shape and appearance:

Class	Regression
FullyParametricProjectOutNewton	IRLRegression
FullyParametricProjectOutGaussNewton	IIRLRegression
FullyParametricMeanTemplateNewton	IRLRegression
FullyParametricWeightsNewton	IRLRegression
FullyParametricProjectOutOPP	OPPRegression

•**reference_shape** (*menpo.shape.PointCloud* or None, optional) – The reference shape that will be used for normalising the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.

- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •patch_features (closure or list of closure, optional) The features that will be extracted from the patches of the training images. Note that, as opposed to *holistic_features*, these features are extracted after extracting the patches. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* and *menpofit.feature* for a list of potential features.

- •**patch_shape** ((*int*, *int*) or *list* of (*int*, *int*), optional) The shape of the patches to be extracted. If a *list* is provided, then it defines a patch shape per scale.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •n_iterations (*int* or *list* of *int*, optional) The number of iterations (cascades) of each level. If *list*, it must specify a value per scale. If *int*, then it defines the total number of iterations (cascades) over all scales.
- •**n_perturbations** (*int*, optional) The number of perturbations to be generated from each of the bounding boxes using *perturb_from_gt_bounding_box*.
- •**perturb_from_gt_bounding_box** (*callable*, optional) The function that will be used to generate the perturbations from each of the bounding boxes.
- •**batch_size** (*int* or None, optional) If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.
- •verbose (bool, optional) If True, then the progress of the training will be printed.

References

fit_from_bb (image, bounding_box, max_iters=20, gt_shape=None, return_costs=False, **kwargs)
Fits the multi-scale fitter to an image given an initial bounding box.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •bounding_box (*menpo.shape.PointDirectedGraph*) The initial bounding box from which the fitting procedure will start. Note that the bounding box is used in order to align the model's reference shape.
- •max_iters (*int* or *list* of *int*, optional) The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.
- •gt_shape (*menpo.shape.PointCloud*, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.
- •**kwargs** (*dict*, optional) Additional keyword arguments that can be passed to specific implementations.
- **Returnsfitting_result** (*MultiScaleNonParametricIterativeResult* or subclass) The multi-scale fitting result containing the result of the fitting procedure.

Fits the multi-scale fitter to an image given an initial shape.

Parameters

•image (*menpo.image.Image* or subclass) – The image to be fitted.

- •**initial_shape** (*menpo.shape.PointCloud*) The initial shape estimate from which the fitting procedure will start.
- •max_iters (*int* or *list* of *int*, optional) The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

Method to increment the trained SDM with a new set of training images.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•group (*str* or None, optional) – The landmark group that corresponds to the ground truth shape of each image. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.

•bounding_box_group_glob (*glob* or None, optional) – Glob that defines the bounding boxes to be used for training. If None, then the bounding boxes of the ground truth shapes are used.

•verbose (bool, optional) – If True, then the progress of training will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

holistic_features

The features that are extracted from the input image at each scale in ascending order, i.e. from lowest to highest scale.

Typelist of closure

n_scales

Returns the number of scales.

Typeint

reference_shape

The reference shape that is used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of this reference shape.

Typemenpo.shape.PointCloud

scales

The scale value of each scale in ascending order, i.e. from lowest to highest scale.

Typelist of int or float

Pre-defined Models

Models with pre-defined algorithms that are commonly-used in literature.

SDM

menpofit.sdm.SDM (images, group=None, bounding_box_group_glob=None, reference_shape=None, diagonal=None, holistic_features=<function no_op>, patch_features=<function no_op>, patch_shape=(17, 17), scales=(0.5, 1.0), n_iterations=3, n_perturbations=30, perturb_from_gt_bounding_box=<function noisy_shape_from_bounding_box>, batch_size=None, verbose=False)

Class for training a non-parametric multi-scale Supervised Descent model using NonParametricNewton.

- •images (list of menpo.image.Image) The list of training images.
- •group (*str* or None, optional) The landmark group that corresponds to the ground truth shape of each image. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.
- •bounding_box_group_glob (*glob* or None, optional) Glob that defines the bounding boxes to be used for training. If None, then the bounding boxes of the ground truth shapes are used.
- •**reference_shape** (*menpo.shape.PointCloud* or None, optional) The reference shape that will be used for normalising the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.
- •diagonal (*int* or None, optional) This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.
- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •patch_features (closure or list of closure, optional) The features that will be extracted from the patches of the training images. Note that, as opposed to *holistic_features*, these features are extracted after extracting the patches. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* and *menpofit.feature* for a list of potential features.
- •**patch_shape** ((*int*, *int*) or *list* of (*int*, *int*), optional) The shape of the patches to be extracted. If a *list* is provided, then it defines a patch shape per scale.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.

•**n_iterations** (*int* or *list* of *int*, optional) – The number of iterations (cascades) of each level. If *list*, it must specify a value per scale. If *int*, then it defines the total number of iterations (cascades) over all scales.

•**n_perturbations** (*int*, optional) – The number of perturbations to be generated from each of the bounding boxes using *perturb_from_gt_bounding_box*.

•**perturb_from_gt_bounding_box** (*callable*, optional) – The function that will be used to generate the perturbations from each of the bounding boxes.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

•verbose (bool, optional) – If True, then the progress of the training will be printed.

References

RegularizedSDM

Bases: SupervisedDescentFitter

Class for training a non-parametric multi-scale Supervised Descent model using *NonParametricNewton* with regularization.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •group (*str* or None, optional) The landmark group that corresponds to the ground truth shape of each image. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.
- •bounding_box_group_glob (*glob* or None, optional) Glob that defines the bounding boxes to be used for training. If None, then the bounding boxes of the ground truth shapes are used.
- •alpha (float, optional) The regression regularization parameter.
- •reference_shape (menpo.shape.PointCloud or None, optional) The reference shape that will be used for normalising the size of the training images. The normalization is performed by rescaling all the training images so that the scale of their ground truth shapes matches the scale of the reference shape. Note that the reference shape is rescaled with respect to the *diagonal* before performing the normalisation. If None, then the mean shape will be used.

•diagonal (*int* or None, optional) – This parameter is used to rescale the reference shape so that the diagonal of its bounding box matches the provided value. In other words, this

parameter controls the size of the model at the highest scale. If None, then the reference shape does not get rescaled.

- •holistic_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the training images. Note that the features are extracted before warping the images to the reference shape. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* for a list of potential features.
- •patch_features (*closure* or *list* of *closure*, optional) The features that will be extracted from the patches of the training images. Note that, as opposed to *holistic_features*, these features are extracted after extracting the patches. If *list*, then it must define a feature function per scale. Please refer to *menpo.feature* and *menpofit.feature* for a list of potential features.
- •**patch_shape** ((*int*, *int*) or *list* of (*int*, *int*), optional) The shape of the patches to be extracted. If a *list* is provided, then it defines a patch shape per scale.
- •scales (*float* or *tuple* of *float*, optional) The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale. If *float*, then a single scale is assumed.
- •**n_iterations** (*int* or *list* of *int*, optional) The number of iterations (cascades) of each level. If *list*, it must specify a value per scale. If *int*, then it defines the total number of iterations (cascades) over all scales.
- •**n_perturbations** (*int*, optional) The number of perturbations to be generated from each of the bounding boxes using *perturb_from_gt_bounding_box*.
- •**perturb_from_gt_bounding_box** (*callable*, optional) The function that will be used to generate the perturbations from each of the bounding boxes.
- •**batch_size** (*int* or None, optional) If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.
- •verbose (bool, optional) If True, then the progress of the training will be printed.

References

fit_from_bb (image, bounding_box, max_iters=20, gt_shape=None, return_costs=False, **kwargs)
Fits the multi-scale fitter to an image given an initial bounding box.

- •image (menpo.image.Image or subclass) The image to be fitted.
- •**bounding_box** (*menpo.shape.PointDirectedGraph*) The initial bounding box from which the fitting procedure will start. Note that the bounding box is used in order to align the model's reference shape.
- •max_iters (*int* or *list* of *int*, optional) The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.
- •gt_shape (*menpo.shape.PointCloud*, optional) The ground truth shape associated to the image.
- •return_costs (*bool*, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned

fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

- **Returnsfitting_result** (*MultiScaleNonParametricIterativeResult* or subclass) The multi-scale fitting result containing the result of the fitting procedure.

Fits the multi-scale fitter to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•**initial_shape** (*menpo.shape.PointCloud*) – The initial shape estimate from which the fitting procedure will start.

•max_iters (*int* or *list* of *int*, optional) – The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

Method to increment the trained SDM with a new set of training images.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•group (*str* or None, optional) – The landmark group that corresponds to the ground truth shape of each image. If None and the images only have a single landmark group, then that is the one that will be used. Note that all the training images need to have the specified landmark group.

•bounding_box_group_glob (*glob* or None, optional) – Glob that defines the bounding boxes to be used for training. If None, then the bounding boxes of the ground truth shapes are used.

•verbose (bool, optional) – If True, then the progress of training will be printed.

•**batch_size** (*int* or None, optional) – If an *int* is provided, then the training is performed in an incremental fashion on image batches of size equal to the provided value. If None, then the training is performed directly on the all the images.

holistic_features

The features that are extracted from the input image at each scale in ascending order, i.e. from lowest to highest scale.

Typelist of closure

n_scales

Returns the number of scales.

Type*int*

reference_shape

The reference shape that is used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of this reference shape.

Typemenpo.shape.PointCloud

scales

The scale value of each scale in ascending order, i.e. from lowest to highest scale.

Typelist of int or float

Non-Parametric Algorithms

The cascaded regression of these algorithms is performed between landmark coordinates and image-based features.

NonParametricNewton

```
class menpofit.sdm.NonParametricNewton (patch_features=<function no_op>, patch_shape=(17,
17), n_iterations=3, compute_error=<function eu-
clidean_bb_normalised_error>, alpha=0, bias=True)
```

Bases: NonParametricSDAlgorithm

Class for training a non-parametric cascaded-regression algorithm using Incremental Regularized Linear Regression (*IRLRegression*).

Parameters

•patch_features (*callable*, optional) – The features to be extracted from the patches of an image.

•patch_shape ((*int*, *int*), optional) – The shape of the extracted patches.

•n_iterations (*int*, optional) – The number of iterations (cascades).

•compute_error (*callable*, optional) – The function to be used for computing the fitting error when training each cascade.

•alpha (*float*, optional) – The regularization parameter.

•bias (bool, optional) - Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

•**prefix** (*str*, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (class : *menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.

Returnsfitting_result (*NonParametricIterativeResult*) – The result of the fitting procedure.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•**prefix** (*str*, optional) – The prefix to use when printing information.

- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

NonParametricGaussNewton

class menpofit.sdm.NonParametricGaussNewton	no_op>,	
	<i>patch_shape=(17, 17),</i>	$n_{iterations=3}$,
	compute_error= <function< td=""><td>eu-</td></function<>	eu-
	clidean_bb_normalised_error>,	, alpha=0,
	<i>bias=True</i> , <i>alpha2=0</i>)	

Bases: NonParametricSDAlgorithm

Class for training a non-parametric cascaded-regression algorithm using Indirect Incremental Regularized Linear Regression (*IIRLRegression*).

Parameters

- •patch_features (*callable*, optional) The features to be extracted from the patches of an image.
- •patch_shape ((int, int), optional) The shape of the extracted patches.
- •n_iterations (int, optional) The number of iterations (cascades).
- •compute_error (*callable*, optional) The function to be used for computing the fitting error when training each cascade.
- •alpha (float, optional) The regularization parameter.
- •bias (bool, optional) Flag that controls whether to use a bias term.
- •alpha2 (*float*, optional) The regularization parameter of the Hessian matrix.
- increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
 Method to increment the model with the set of current shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •prefix (*str*, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (class : *menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.
- **Returnsfitting_result** (*NonParametricIterativeResult*) The result of the fitting procedure.
- **train** (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

NonParametricPCRRegression

<pre>class menpofit.sdm.NonParametricPCRRegression (patch_features=<function< pre=""></function<></pre>	no_op>,
patch_shape=(17, 17), n_	iterations=3,
compute_error= <function< td=""><td>eu-</td></function<>	eu-
clidean_bb_normalised_error>,	vari-
ance=None, bias=True)	

Bases: NonParametricSDAlgorithm

Class for training a non-parametric cascaded-regression algorithm using Principal Component Regression (*PCRRegression*).

Parameters

•patch_features (*callable*, optional) – The features to be extracted from the patches of an image.

•patch_shape ((*int*, *int*), optional) – The shape of the extracted patches.

•n_iterations (int, optional) – The number of iterations (cascades).

•compute_error (*callable*, optional) – The function to be used for computing the fitting error when training each cascade.

- •variance (float or None, optional) The SVD variance.
- •bias (bool, optional) Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

•images (*list* of *menpo.image.Image*) – The *list* of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (class : *menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.
- **Returnsfitting_result** (*NonParametricIterativeResult*) The result of the fitting procedure.
- **train** (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images, which will be used as initial shapes.
- •prefix (str, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

NonParametricOptimalRegression

<pre>class menpofit.sdm.NonParametricOptimalRegression</pre>	(patch_features= <function< th=""><th>no_op>,</th></function<>	no_op>,
	patch_shape=(17, 17), n_iterat	tions=3,
	compute_error= <function< th=""><th>eu-</th></function<>	eu-
	clidean_bb_normalised_error>	',
	variance=None. bias=True)	

Bases: NonParametricSDAlgorithm

Class for training a non-parametric cascaded-regression algorithm using Multivariate Linear Regression with optimal reconstructions (*OptimalLinearRegression*).

Parameters

•patch_features (*callable*, optional) – The features to be extracted from the patches of an image.

•patch_shape ((int, int), optional) – The shape of the extracted patches.

•n_iterations (*int*, optional) – The number of iterations (cascades).

•compute_error (*callable*, optional) – The function to be used for computing the fitting error when training each cascade.

•variance (float or None, optional) – The SVD variance.

•bias (bool, optional) – Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

•images (*list* of *menpo.image.Image*) – The *list* of training images.

- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •prefix (*str*, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

run (*image*, *initial_shape*, *gt_shape=None*, *return_costs=False*, ***kwargs*) Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (class : *menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.
- **Returnsfitting_result** (*NonParametricIterativeResult*) The result of the fitting procedure.
- **train** (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•**prefix** (*str*, optional) – The prefix to use when printing information.

•verbose (*bool*, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

NonParametricOPPRegression

class menpofit.sdm.NonParametricOPPRegression	ı (patch_features= <fu< th=""><th>nction</th><th>no_op>,</th></fu<>	nction	no_op>,
	patch_shape=(17,	17),	n_iterations=3,
	compute_error= <fu< td=""><td>nction</td><td>eu-</td></fu<>	nction	eu-
	clidean_bb_normali	ised_erra	or>, bias=True)

Bases: NonParametricSDAlgorithm

Class for training a non-parametric cascaded-regression algorithm using Multivariate Linear Regression with Orthogonal Procrustes Problem reconstructions (*OPPRegression*).

Parameters

- •patch_features (*callable*, optional) The features to be extracted from the patches of an image.
- •patch_shape ((*int*, *int*), optional) The shape of the extracted patches.
- •n_iterations (int, optional) The number of iterations (cascades).
- •compute_error (*callable*, optional) The function to be used for computing the fitting error when training each cascade.
- •bias (bool, optional) Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •prefix (*str*, optional) The prefix to use when printing information.
- •verbose (*bool*, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)

Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) - The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the fitting procedure will start.

•gt_shape (class : *menpo.shape.PointCloud* or None, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm. **Returnsfitting_result** (*NonParametricIterativeResult*) – The result of the fitting procedure.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) - If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

Parametric Shape Algorithms

The cascaded regression of these algorithms is performed between the parameters of a statistical shape model and image-based features.

ParametricShapeNewton

class menpofit.sdm.ParametricShapeNewton	n (<i>patch_features</i> =< <i>function</i>	no_op>,
	$patch_shape=(17, 17),$	n_iterations=3,
	<pre>shape_model_cls=<class< pre=""></class<></pre>	'men-
	pofit.modelinstance.OrthoPDM'>,	
	compute_error= <function< td=""><td>eu-</td></function<>	eu-
	clidean_bb_normalised_error>,	alpha=0,
	bias=True)	-
Decase Demonstry's Chame CDAl mentithm		

Bases: ParametricShapeSDAlgorithm

Class for training a cascaded-regression algorithm that employs a parametric shape model using Incremental Regularized Linear Regression (*IRLRegression*).

Parameters

- •**patch_features** (*callable*, optional) The features to be extracted from the patches of an image.
- •patch_shape ((*int, int*), optional) The shape of the extracted patches.
- •n_iterations (*int*, optional) The number of iterations (cascades).
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.

•compute_error (*callable*, optional) – The function to be used for computing the fitting error when training each cascade.

•alpha (*float*, optional) – The regularization parameter.

•bias (bool, optional) – Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the fitting procedure will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to ''True''. This is because it is not possible to evaluate the cost function of this algorithm.

Returnsfitting_result (*ParametricIterativeResult*) – The result of the fitting procedure.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

ParametricShapeGaussNewton

<pre>class menpofit.sdm.ParametricShapeGaussNewton (</pre>	(patch_features= <fu< th=""><th>nction</th><th>no_op>,</th></fu<>	nction	no_op>,
	patch_shape=(17,	17), n_it	erations=3,
	shape_model_cls= <class< td=""><td>'men-</td></class<>		'men-
	pofit.modelinstance.OrthoPDM'>,		
	compute_error= <fu< td=""><td>eu-</td></fu<>	eu-	
	clidean_bb_normalised_error>,		alpha=0,
	bias=True, alpha2=	0)	

Bases: ParametricShapeSDAlgorithm

Class for training a cascaded-regression algorithm that employs a parametric shape model using Indirect Incremental Regularized Linear Regression (*IIRLRegression*).

Parameters

- •patch_features (*callable*, optional) The features to be extracted from the patches of an image.
- •patch_shape ((*int*, *int*), optional) The shape of the extracted patches.
- •n_iterations (int, optional) The number of iterations (cascades).
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •compute_error (*callable*, optional) The function to be used for computing the fitting error when training each cascade.
- •alpha (float, optional) The regularization parameter.
- •bias (bool, optional) Flag that controls whether to use a bias term.
- •alpha2 (*float*, optional) The regularization parameter of the Hessian matrix.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •prefix (*str*, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

run (*image*, *initial_shape*, *gt_shape=None*, *return_costs=False*, ***kwargs*) Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the fitting procedure will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to 'True''. This is because it is not possible to evaluate the cost function of this algorithm.

Returnsfitting_result (*ParametricIterativeResult*) – The result of the fitting procedure.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=``*, *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images, which will be used as initial shapes.
- •**prefix** (*str*, optional) The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

ParametricShapePCRRegression

class menpofit.sdm.ParametricShapePCRRegress	sion (<i>patch_features</i> =< <i>function no_op</i> >,	
	patch_shape=(17, 17), n_iterations=3,	
	shape_model_cls= <class 'men-<="" td=""><td></td></class>	
	pofit.modelinstance.OrthoPDM'>,	
	compute_error= <function eu-<="" td=""><td></td></function>	
	clidean_bb_normalised_error>, vari-	vari-
	ance=None, bias=True)	
Decase Demonstrate Change (DD) are within		

Bases: ParametricShapeSDAlgorithm

Class for training a cascaded-regression algorithm that employs a parametric shape model using Principal Component Regression (*PCRRegression*).

- •patch_features (*callable*, optional) The features to be extracted from the patches of an image.
- •patch_shape ((*int*, *int*), optional) The shape of the extracted patches.
- •n_iterations (*int*, optional) The number of iterations (cascades).
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •compute_error (*callable*, optional) The function to be used for computing the fitting error when training each cascade.
- •variance (*float* or None, optional) The SVD variance.

•bias (*bool*, optional) – Flag that controls whether to use a bias term.

RaisesValueError – variance must be set to a number between 0 and 1

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

•images (*list* of *menpo.image.Image*) – The *list* of training images.

- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •prefix (*str*, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

run (*image*, *initial_shape*, *gt_shape=None*, *return_costs=False*, ***kwargs*) Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.
- **Returnsfitting_result** (*ParametricIterativeResult*) The result of the fitting procedure.
- **train** (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images, which will be used as initial shapes.
- •**prefix** (*str*, optional) The prefix to use when printing information.
- •verbose (*bool*, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

ParametricShapeOptimalRegression

class menpofit.sdm.ParametricShapeOptimalRegression (patch_features=<function

no_op>, patch_shape=(17, 17), n_iterations=3, shape_model_cls=<class 'menpofit.modelinstance.OrthoPDM'>, compute_error=<function euclidean_bb_normalised_error>, variance=None, bias=True)

Bases: ParametricShapeSDAlgorithm

Class for training a cascaded-regression algorithm that employs a parametric shape model using Multivariate Linear Regression with optimal reconstructions (*OptimalLinearRegression*).

Parameters

•patch_features (*callable*, optional) – The features to be extracted from the patches of an image.

•patch_shape ((*int*, *int*), optional) – The shape of the extracted patches.

•n_iterations (*int*, optional) – The number of iterations (cascades).

•**shape_model_cls** (*subclass* of *PDM*, optional) – The class to be used for building the shape model. The most common choice is *OrthoPDM*.

•compute_error (*callable*, optional) – The function to be used for computing the fitting error when training each cascade.

•variance (float or None, optional) – The SVD variance.

•bias (bool, optional) – Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)

Method to increment the model with the set of current shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

•prefix (str, optional) – The prefix to use when printing information.

- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the fitting procedure will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated to the image.

- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.
- **Returnsfitting_result** (*ParametricIterativeResult*) The result of the fitting procedure.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=``*, *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images, which will be used as initial shapes.
- •prefix (*str*, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

ParametricShapeOPPRegression

patch shape=(17, 17), n iterations=3
paren_snape (1), 1), n_nense
shape_model_cls= <class 'men<="" td=""></class>
pofit.modelinstance.OrthoPDM'>,
compute_error= <function eu<="" td=""></function>
clidean_bb_normalised_error>,
whiten=False, bias=True)

Bases: ParametricShapeSDAlgorithm

Class for training a cascaded-regression algorithm that employs a parametric shape model using Multivariate Linear Regression with Orthogonal Procrustes Problem reconstructions (*OPPRegression*).

- •patch_features (*callable*, optional) The features to be extracted from the patches of an image.
- •patch_shape ((*int*, *int*), optional) The shape of the extracted patches.
- •n_iterations (int, optional) The number of iterations (cascades).
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •compute_error (*callable*, optional) The function to be used for computing the fitting error when training each cascade.
- •whiten (*bool*, optional) Whether to use a whitened PCA model.

•bias (bool, optional) – Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)

Method to increment the model with the set of current shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

•prefix (str, optional) – The prefix to use when printing information.

- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.
- **Returnsfitting_result** (*ParametricIterativeResult*) The result of the fitting procedure.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=``*, *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•prefix (*str*, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

Parametric Appearance Algorithms

The cascaded regression of these algorithms is performed between landmark coordinates and features that are based on a statistical parametric appearance model.

ParametricAppearanceProjectOutNewton

pearance_model_cls=<class
'menpo.model.pca.PCAVectorModel'>,
compute_error=<function euclidean_bb_normalised_error>,
alpha=0, bias=True)

Bases: ParametricAppearanceNewton

Class for training a cascaded-regression Newton algorithm that employs a parametric appearance model using Incremental Regularized Linear Regression (*IRLRegression*). The algorithm uses the projected-out appearance vectors as features in the regression.

increment (*images*, *gt_shapes*, *current_shapes*, *prefix=``*, *verbose=False*) Mathed to increment the model with the set of current shapes

Method to increment the model with the set of current shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) - The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the fitting procedure will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm. **Returnsfitting_result** (*NonParametricIterativeResult*) – The result of the fitting procedure.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

ParametricAppearanceProjectOutGuassNewton

class menpofit.sdm.ParametricAppearanceProjectOutGuassNewton (patch_features=<function

no_op>,
patch_shape=(17,
17), n_iterations=3,
appearance_model_cls=<class
'menpo.model.pca.PCAVectorModel'>,
compute_error=<function
euclidean_bb_normalised_error>,
alpha=0, bias=True,
alpha2=0)

Bases: ParametricAppearanceGaussNewton

Class for training a cascaded-regression Gauss-Newton algorithm that employs a parametric appearance model using Indirect Incremental Regularized Linear Regression (*IIRLRegression*). The algorithm uses the projected-out appearance vectors as features in the regression.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.
- **Returnsfitting_result** (*NonParametricIterativeResult*) The result of the fitting procedure.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=``*, *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

ParametricAppearanceMeanTemplateNewton

class menpofit.sdm.ParametricAppearanceMeanTemplateNewton (patch_features=<function

no_op>, patch_shape=(17, 17), n_iterations=3, appearance_model_cls=<class 'menpo.model.pca.PCAVectorModel'>, compute_error=<function euclidean_bb_normalised_error>, alpha=0, bias=True)

Bases: ParametricAppearanceNewton

Class for training a cascaded-regression Newton algorithm that employs a parametric appearance model using Incremental Regularized Linear Regression (*IRLRegression*). The algorithm uses the centered appearance vectors as features in the regression.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •prefix (str, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the fitting procedure will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.

Returnsfitting_result (*NonParametricIterativeResult*) – The result of the fitting procedure.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images, which will be used as initial shapes.
- •prefix (str, optional) The prefix to use when printing information.
- •verbose (*bool*, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

ParametricAppearanceMeanTemplateGuassNewton

class menpofit.sdm.ParametricAppearanceMeanTemplateGuassNewton (patch_features=<function

no_op>, patch_shape=(17, 17), n_iterations=3, appearance_model_cls=<class 'menpo.model.pca.PCAVectorModel'>, compute_error=<function euclidean_bb_normalised_error>, alpha=0, bias=True, alpha2=0)

Bases: ParametricAppearanceGaussNewton

Class for training a cascaded-regression Gauss-Newton algorithm that employs a parametric appearance model using Indirect Incremental Regularized Linear Regression (*IIRLRegression*). The algorithm uses the centered appearance vectors as features in the regression.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

•prefix (str, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) - The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape from which the fitting procedure will start.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to 'True''. This is because it is not possible to evaluate the cost function of this algorithm. **Returnsfitting_result** (*NonParametricIterativeResult*) – The result of the fitting procedure.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•prefix (*str*, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

ParametricAppearanceWeightsNewton

class menpofit.sdm.**ParametricAppearanceWeightsNewton** (*patch_features=<function*

no_op>, patch_shape=(17, 17), n_iterations=3, appearance_model_cls=<class 'menpo.model.pca.PCAVectorModel'>, compute_error=<function euclidean_bb_normalised_error>, alpha=0, bias=True)

Bases: ParametricAppearanceNewton

Class for training a cascaded-regression Newton algorithm that employs a parametric appearance model using Incremental Regularized Linear Regression (*IRLRegression*). The algorithm uses the projection weights of the appearance vectors as features in the regression.

increment (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to increment the model with the set of current shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

•**prefix** (*str*, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to ''True''. This is because it is not possible to evaluate the cost function of this algorithm.
- **Returnsfitting_result** (*NonParametricIterativeResult*) The result of the fitting procedure.
- **train** (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images, which will be used as initial shapes.
- •prefix (*str*, optional) The prefix to use when printing information.
- •verbose (*bool*, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

ParametricAppearanceWeightsGuassNewton

```
class menpofit.sdm.ParametricAppearanceWeightsGuassNewton (patch_features=<function)</pre>
```

no_op>, patch_shape=(17, 17), n_iterations=3, appearance_model_cls=<class 'menpo.model.pca.PCAVectorModel'>, compute_error=<function euclidean_bb_normalised_error>, alpha=0, bias=True, alpha2=0)

 $Bases: {\tt ParametricAppearanceGaussNewton}$

Class for training a cascaded-regression Gauss-Newton algorithm that employs a parametric appearance model using Indirect Incremental Regularized Linear Regression (*IIRLRegression*). The algorithm uses the projection weights of the appearance vectors as features in the regression.

increment (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to increment the model with the set of current shapes.

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

•prefix (*str*, optional) – The prefix to use when printing information.

•verbose (*bool*, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

run (*image*, *initial_shape*, *gt_shape=None*, *return_costs=False*, ***kwargs*) Run the algorithm to an image given an initial shape.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to 'True''. This is because it is not possible to evaluate the cost function of this algorithm.

Returnsfitting_result (*NonParametricIterativeResult*) – The result of the fitting procedure.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=''*, *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images, which will be used as initial shapes.
- •prefix (*str*, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

Fully Parametric Algorithms

The cascaded regression is performed between the parameters of a statistical shape model and features that are based on a statistical parametric appearance model.

FullyParametricProjectOutNewton

<pre>class menpofit.sdm.FullyParametricProjectOut</pre>	Newton (patch_feature	s= <function< th=""><th></th></function<>		
	no_op>,	patch_shape=(17, n_iterations=3,		
	17),			
	shape_model_	_cls= <class< td=""><td>'men-</td></class<>	'men-	
	pofit.modelins	pofit.modelinstance.OrthoPDM'>,		
	appearance_model_cls= <class< td=""></class<>			
	'menpo.mode	<pre>`menpo.model.pca.PCAVectorModel'>,</pre>		
	compute_erro	r= <function< td=""><td>eu-</td></function<>	eu-	
	clidean_bb_n	clidean_bb_normalised_error>,		
	alpha=0, bias=True)			

Bases: ParametricAppearanceProjectOut

Class for training a cascaded-regression algorithm that employs parametric shape and appearance models using Incremental Regularized Linear Regression (*IRLRegression*). The algorithm uses the projected-out appearance vectors as features in the regression.

Parameters

- •patch_features (*callable*, optional) The features to be extracted from the patches of an image.
- •patch_shape ((*int, int*), optional) The shape of the extracted patches.
- •n_iterations (*int*, optional) The number of iterations (cascades).
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •appearance_model_cls (*menpo.model.PCAVectorModel* or *subclass*) The class to be used for building the appearance model.
- •compute_error (*callable*, optional) The function to be used for computing the fitting error when training each cascade.
- •alpha (*float*, optional) The regularization parameter.
- •bias (bool, optional) Flag that controls whether to use a bias term.
- increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
 Method to increment the model with the set of current shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •**prefix** (*str*, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
 Run the algorithm to an image given an initial shape.

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.
- **Returnsfitting_result** (*ParametricIterativeResult*) The result of the fitting procedure.
- **train** (*images*, *gt_shapes*, *current_shapes*, *prefix=``*, *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images, which will be used as initial shapes.
- •prefix (*str*, optional) The prefix to use when printing information.
- •verbose (*bool*, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

FullyParametricProjectOutGaussNewton

class menpofit.sdm.**FullyParametricProjectOutGaussNewton** (*patch_features=<function*

no_op>, patch_shape=(17, 17), n_iterations=3, shape_model_cls=<class 'menpofit.modelinstance.OrthoPDM'>, appearance_model_cls=<class 'menpo.model.pca.PCAVectorModel'>, compute_error=<function euclidean_bb_normalised_error>, alpha=0, bias=True, alpha2=0)

Bases: ParametricAppearanceProjectOut

Class for training a cascaded-regression algorithm that employs parametric shape and appearance models using Indirect Incremental Regularized Linear Regression (*IIRLRegression*). The algorithm uses the projected-out appearance vectors as features in the regression.
- •patch_features (*callable*, optional) The features to be extracted from the patches of an image.
- •patch_shape ((*int*, *int*), optional) The shape of the extracted patches.
- •n_iterations (*int*, optional) The number of iterations (cascades).
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •appearance_model_cls (*menpo.model.PCAVectorModel* or *subclass*) The class to be used for building the appearance model.
- •compute_error (*callable*, optional) The function to be used for computing the fitting error when training each cascade.
- •alpha (float, optional) The regularization parameter.
- •bias (bool, optional) Flag that controls whether to use a bias term.
- •alpha2 (float, optional) The regularization parameter of the Hessian matrix.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •prefix (str, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- **run** (*image*, *initial_shape*, *gt_shape=None*, *return_costs=False*, ***kwargs*) Run the algorithm to an image given an initial shape.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.
- **Returnsfitting_result** (*ParametricIterativeResult*) The result of the fitting procedure.
- **train** (*images*, *gt_shapes*, *current_shapes*, *prefix=``*, *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

•images (list of menpo.image.Image) – The list of training images.

•gt_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of ground truth shapes that correspond to the images.

•current_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•prefix (*str*, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

FullyParametricMeanTemplateNewton

class menpofit.sdm.FullyParametricMeanTemplateNewton (patch_features=<function</pre>

no_op>, patch_shape=(17, 17), n_iterations=3, shape_model_cls=<class 'menpofit.modelinstance.OrthoPDM'>, appearance_model_cls=<class 'menpo.model.pca.PCAVectorModel'>, compute_error=<function euclidean_bb_normalised_error>, alpha=0, bias=True)

Bases: ParametricAppearanceMeanTemplate

Class for training a cascaded-regression algorithm that employs parametric shape and appearance models using Incremental Regularized Linear Regression (*IRLRegression*). The algorithm uses the centered appearance vectors as features in the regression.

Parameters

- •patch_features (*callable*, optional) The features to be extracted from the patches of an image.
- •patch_shape ((*int*, *int*), optional) The shape of the extracted patches.
- •n_iterations (int, optional) The number of iterations (cascades).

•**shape_model_cls** (*subclass* of *PDM*, optional) – The class to be used for building the shape model. The most common choice is *OrthoPDM*.

- •appearance_model_cls (*menpo.model.PCAVectorModel* or *subclass*) The class to be used for building the appearance model.
- •compute_error (*callable*, optional) The function to be used for computing the fitting error when training each cascade.
- •alpha (*float*, optional) The regularization parameter.

•bias (bool, optional) – Flag that controls whether to use a bias term.

increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
Method to increment the model with the set of current shapes.

Parameters

•images (*list* of *menpo.image.Image*) – The *list* of training images.

- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •prefix (str, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
 Run the algorithm to an image given an initial shape.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.
- **Returnsfitting_result** (*ParametricIterativeResult*) The result of the fitting procedure.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=*'', *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•prefix (str, optional) – The prefix to use when printing information.

- •verbose (*bool*, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

FullyParametricWeightsNewton

 class menpofit.sdm.FullyParametricWeightsNewton (patch_features=<function no_op>, patch_shape=(17, 17), n_iterations=3, shape_model_cls=<class 'menpofit.modelinstance.OrthoPDM'>, appearance_model_cls=<class 'menpo.model.pca.PCAVectorModel'>, compute_error=<function euclidean_bb_normalised_error>, alpha=0, bias=True)

Bases: ParametricAppearanceWeights

Class for training a cascaded-regression algorithm that employs parametric shape and appearance models using Incremental Regularized Linear Regression (*IRLRegression*). The algorithm uses the projection weights of the appearance vectors as features in the regression.

Parameters

- •patch_features (*callable*, optional) The features to be extracted from the patches of an image.
- •patch_shape ((*int*, *int*), optional) The shape of the extracted patches.
- •n_iterations (*int*, optional) The number of iterations (cascades).
- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •appearance_model_cls (*menpo.model.PCAVectorModel* or *subclass*) The class to be used for building the appearance model.
- •compute_error (*callable*, optional) The function to be used for computing the fitting error when training each cascade.
- •alpha (*float*, optional) The regularization parameter.
- •bias (bool, optional) Flag that controls whether to use a bias term.
- increment (images, gt_shapes, current_shapes, prefix='', verbose=False)
 Method to increment the model with the set of current shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •prefix (str, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)
Run the algorithm to an image given an initial shape.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (menpo.shape.PointCloud) The initial shape from which the fitting procedure will start.
- •gt_shape (menpo.shape.PointCloud or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.
- Returnsfitting_result (ParametricIterativeResult) The result of the fitting procedure.
- train (images, gt_shapes, current_shapes, prefix='', verbose=False) Method to train the model given a set of initial shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (list of menpo.shape.PointCloud) The list of ground truth shapes that correspond to the images.
- •current shapes (list of menpo.shape.PointCloud) The list of current shapes that correspond to the images, which will be used as initial shapes.
- •prefix (str, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

FullyParametricProjectOutOPP

class menpofit.sdm.FullyParametricProjectOutO	PP (patch_features= <function n<="" th=""><th>o_op>,</th></function>	o_op>,
	patch_shape=(17, 17), n_iterati	ons=3,
	<pre>shape_model_cls=<class< pre=""></class<></pre>	'men-
	pofit.modelinstance.OrthoPDM'>,	
	appearance_model_cls= <class< td=""><td></td></class<>	
	`menpo.model.pca.PCAVectorMode	l'>,
	compute_error= <function< td=""><td>eu-</td></function<>	eu-
	clidean_bb_normalised_error>,	
	bias=True)	
Bases: ParametricAppearanceProjectOut		

Bases: ParametricAppearanceProjectOut

Class for training a cascaded-regression algorithm that employs parametric shape and appearance models using Multivariate Linear Regression with Orthogonal Procrustes Problem reconstructions (OPPRegression).

Parameters

•patch_features (callable, optional) – The features to be extracted from the patches of an image.

•patch_shape ((*int*, *int*), optional) – The shape of the extracted patches.

•n_iterations (int, optional) – The number of iterations (cascades).

- •**shape_model_cls** (*subclass* of *PDM*, optional) The class to be used for building the shape model. The most common choice is *OrthoPDM*.
- •appearance_model_cls (*menpo.model.PCAVectorModel* or *subclass*) The class to be used for building the appearance model.
- •compute_error (*callable*, optional) The function to be used for computing the fitting error when training each cascade.
- •bias (*bool*, optional) Flag that controls whether to use a bias term.

increment (*images*, *gt_shapes*, *current_shapes*, *prefix=``*, *verbose=False*) Method to increment the model with the set of current shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.
- •prefix (str, optional) The prefix to use when printing information.
- •verbose (bool, optional) If True, then information is printed during training.
- **Returnscurrent_shapes** (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images.

run (image, initial_shape, gt_shape=None, return_costs=False, **kwargs)

Run the algorithm to an image given an initial shape.

Parameters

- •image (menpo.image.Image or subclass) The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape from which the fitting procedure will start.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated to the image.
- •return_costs (bool, optional) If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that this argument currently has no effect and will raise a warning if set to "True". This is because it is not possible to evaluate the cost function of this algorithm.
- **Returnsfitting_result** (*ParametricIterativeResult*) The result of the fitting procedure.

train (*images*, *gt_shapes*, *current_shapes*, *prefix=``*, *verbose=False*) Method to train the model given a set of initial shapes.

Parameters

- •images (list of menpo.image.Image) The list of training images.
- •gt_shapes (*list* of *menpo.shape.PointCloud*) The *list* of ground truth shapes that correspond to the images.
- •current_shapes (*list* of *menpo.shape.PointCloud*) The *list* of current shapes that correspond to the images, which will be used as initial shapes.

•**prefix** (*str*, optional) – The prefix to use when printing information.

•verbose (bool, optional) – If True, then information is printed during training.

Returnscurrent_shapes (*list* of *menpo.shape.PointCloud*) – The *list* of current shapes that correspond to the images.

Internal API

menpofit.builder

Building Functions

Collection of functions that are commonly-used by most deformable model builders.

align_shapes

```
menpofit.builder.align_shapes (shapes)
Function that aligns a set of shapes by applying Generalized Procrustes Analysis.
```

Parametersshapes (*list* of *menpo.shape.PointCloud*) – The input shapes.

Returnsaligned_shapes (*list* of *menpo.shape.PointCloud*) – The list of aligned shapes.

build_patch_reference_frame

Builds a patch-based reference frame from a particular set of landmarks.

Parameters

- •landmarks (*menpo.shape.PointCloud*) The landmarks that will be used to build the reference frame.
- •**boundary** (*int*, optional) The number of pixels to be left as a safe margin on the boundaries of the reference frame (has potential effects on the gradient computation).
- •group (*str*, optional) Group that will be assigned to the provided set of landmarks on the reference frame.
- •patch_shape ((*int*, *int*), optional) The shape of the patches.
- **Returnspatch_based_reference_frame** (*menpo.image.MaskedImage*) The patch-based reference frame.

build_reference_frame

menpofit.builder.build_reference_frame (landmarks, boundary=3, group='source')
Builds a reference frame from a particular set of landmarks.

Parameters

•landmarks (*menpo.shape.PointCloud*) – The landmarks that will be used to build the reference frame.

•**boundary** (*int*, optional) – The number of pixels to be left as a safe margin on the boundaries of the reference frame (has potential effects on the gradient computation).

•group (*str*, optional) – Group that will be assigned to the provided set of landmarks on the reference frame.

Returnsreference_frame (*manpo.image.MaskedImage*) – The reference frame.

compute_features

menpofit.builder.compute_features (images, features, prefix='', verbose=False)
Function that extracts features from a list of images.

Parameters

•images (*list* of *menpo.image.Image*) – The set of images.

•features (*callable*) – The features extraction function. Please refer to *menpo.feature* and *menpofit.feature*.

•**prefix** (*str*) – The prefix of the printed information.

•verbose (bool, Optional) – Flag that controls information and progress printing.

Returnsfeature_images (list of menpo.image.Image) – The list of feature images.

compute_reference_shape

menpofit.builder.compute_reference_shape (shapes, diagonal, verbose=False)
Function that computes the reference shape as the mean shape of the provided shapes.

Parameters

•**shapes** (*list* of *menpo.shape.PointCloud*) – The set of shapes from which to build the reference shape.

•diagonal (*int* or None) – If *int*, it ensures that the mean shape is scaled so that the diagonal of the bounding box containing it matches the provided value. If None, then the mean shape is not rescaled.

•verbose (*bool*, optional) – If True, then progress information is printed.

Returnsreference_shape (*menpo.shape.PointCloud*) – The reference shape.

densify_shapes

menpofit.builder.densify_shapes (shapes, reference_frame, transform)
Function that densifies a set of sparse shapes given a reference frame.

Parameters

•shapes (list of menpo.shape.PointCloud) – The input shapes.

•**reference_frame** (*menpo.image.BooleanImage*) – The reference frame, the mask of which will be used.

•**transform** (*menpo.transform.Transform*) – The transform to use for mapping the dense points.

Returnsdense_shapes (*list* of *menpo.shape.PointCloud*) – The list of dense shapes.

extract_patches

Function that extracts patches around the landmarks of the provided images.

Parameters

- •images (list of menpo.image.Image) The set of images to warp.
- •**shapes** (*list* of *menpo.shape.PointCloud*) The set of shapes that correspond to the images.
- •patch_shape ((*int*, *int*)) The shape of the patches.
- •normalise_function (*callable*) A normalisation function to apply on the values of the patches.
- •**prefix** (*str*) The prefix of the printed information.
- •verbose (bool, Optional) Flag that controls information and progress printing.
- Returnspatch_images (list of menpo.image.Image) The list of images with the patches per image. Each output image has shape (n_center, n_offset, n_channels, patch_shape).

normalization_wrt_reference_shape

```
menpofit.builder.normalization_wrt_reference_shape(images, group, diagonal, ver-
```

bose=False)

Function that normalizes the images' sizes with respect to the size of the mean shape. This step is essential before building a deformable model.

The normalization includes: 1) Computation of the reference shape as the mean shape of the images' landmarks. 2) Scaling of the reference shape using the diagonal. 3) Rescaling of all the images so that their shape's scale is in correspondence with the reference shape's scale.

Parameters

- •images (list of menpo.image.Image) The set of images to normalize.
- •group (*str*) If *str*, then it specifies the group of the images's shapes. If None, then the images must have only one landmark group.
- •diagonal (*int* or None) If *int*, it ensures that the mean shape is scaled so that the diagonal of the bounding box containing it matches the provided value. If None, then the mean shape is not rescaled.
- •verbose (bool, Optional) Flag that controls information and progress printing.

Returns

- •reference_shape (*menpo.shape.PointCloud*) The reference shape that was used to resize all training images to a consistent object size.
- •normalized_images (list of menpo.image.Image) The images with normalized size.

rescale_images_to_reference_shape

Function that normalizes the images' sizes with respect to the size of the provided reference shape. In other words, the function rescales the provided images so that the size of the bounding box of their attached shape is the same as the size of the bounding box of the provided reference shape.

Parameters

•images (list of menpo.image.Image) - The set of images that will be rescaled.

•group (*str* or None) – If *str*, then it specifies the group of the images's shapes. If None, then the images must have only one landmark group.

•reference_shape (*menpo.shape.PointCloud*) – The reference shape.

•verbose (bool, optional) – If True, then progress information is printed.

Returnsnormalized_images (list of menpo.image.Image) – The rescaled images.

scale_images

menpofit.builder.scale_images (images, scale, prefix='', return_transforms=False, verbose=False)

Function that rescales a list of images and optionally returns the scale transforms.

Parameters

•images (*list* of *menpo.image.Image*) – The set of images to scale.

•**scale** (*float* or *tuple* of *floats*) – The scale factor. If a tuple, the scale to apply to each dimension. If a single *float*, the scale will be applied uniformly across each dimension.

•**prefix** (*str*, optional) – The prefix of the printed information.

•return_transforms (bool, optional) – If True, then a *list* with the *menpo.transform.Scale* objects that were used to perform the rescale for each image is also returned.

•verbose (*bool*, optional) – Flag that controls information and progress printing.

Returns

•scaled_images (list of menpo.image.Image) - The list of rescaled images.

•scale_transforms (*list* of *menpo.transform.Scale*) – The list of scale transforms that were used. It is returned only if *return_transforms* is True.

warp_images

menpofit.builder.warp_images(images, shapes, reference_frame, transform, prefix='', verbose=None)

Function that warps a list of images into the provided reference frame.

Parameters

•images (*list* of *menpo.image.Image*) – The set of images to warp.

•**shapes** (*list* of *menpo.shape.PointCloud*) – The set of shapes that correspond to the images.

•reference_frame (menpo.image.BooleanImage) – The reference frame to warp to.

•transform (*menpo.transform.Transform*) – Transform from the reference frame back to the image. Defines, for each pixel location on the reference frame, which pixel location should be sampled from on the image.

•**prefix** (*str*) – The prefix of the printed information.

•verbose (bool, Optional) – Flag that controls information and progress printing.

Returnswarped_images (list of menpo.image.MaskedImage) – The list of warped images.

Warnings

MenpoFitBuilderWarning

class menpofit.builder.MenpoFitBuilderWarning
 Bases: Warning

abes. Warning

A warning that some part of building the model may cause issues.

MenpoFitModelBuilderWarning

class menpofit.builder.MenpoFitModelBuilderWarning
 Bases: Warning

A warning that the parameters chosen to build a given model may cause unexpected behaviour.

menpofit.checks

Functions for checking the parameters' values that are passed in MenpoFit's classes.

Parameters Check Functions

check_diagonal

menpofit.checks.check_diagonal (diagonal)
 Checks that the diagonal length used to normalize the images' size is >= 20.

Parametersdiagonal (*int*) – The value to check.

Returnsdiagonal (*int*) – The value if it's correct.

RaisesValueError – diagonal must be >= 20 or None

check_landmark_trilist

menpofit.checks.check_landmark_trilist (image, transform, group=None)
Checks that the provided image has a triangulated shape (thus an isntance of menpo.shape.TriMesh) and the
transform is menpo.transform.PiecewiseAffine

Parameters

•image (*menpo.image.Image* or subclass) – The input image.

•transform (menpo.transform.PiecewiseAffine) – The transform object.

•group (str or None, optional) – The group of the shape to check.

RaisesWarning – The given images do not have an explicit triangulation applied. A Delaunay Triangulation will be computed and used for warping. This may be suboptimal and cause warping artifacts.

check_trilist

menpofit.checks.check_trilist(shape, transform)

Checks that the provided shape is triangulated (thus an isntance of *menpo.shape.TriMesh*) and the transform is *menpo.transform.PiecewiseAffine*

Parameters

•**shape** (*menpo.shape.TriMesh*) – The input shape (usually the reference/mean shape of a model).

•transform (menpo.transform.PiecewiseAffine) – The transform object.

RaisesWarning – The given images do not have an explicit triangulation applied. A Delaunay Triangulation will be computed and used for warping. This may be suboptimal and cause warping artifacts.

check_model

menpofit.checks.check_model(model, cls)

Function that checks whether the provided *class* object is a subclass of the provided base *class*.

Parameters

•model (*class*) – The object.

•cls (class) – The required base class.

RaisesValueError – Model must be a {cls} instance.

Multi-Scale Parameters Check Functions

check_scales

```
menpofit.checks.check_scales(scales)
```

Checks that the provided *scales* argument is either *int* or *float* or an iterable of those. It makes sure that it returns a *list* of *scales*.

Parametersscales (*int* or *float* or *list/tuple* of those) – The value to check.

Returnsscales (list of int or float) – The scales in a list.

Raises ValueError - scales must be an int/float or a list/tuple of int/float

check_multi_scale_param

menpofit.checks.check_multi_scale_param (n_scales, types, param_name, param)
General function for checking a parameter defined for multiple scales. It raises an error if the parameter is not
an iterable with the correct size and correct types.

Parameters

•n_scales (*int*) – The number of scales.

•types (tuple) – The tuple of variable types that the parameter is allowed to have.

•param_name (*str*) – The name of the parameter.

•param (*types*) – The parameter value.

Returnsparam (list of types) - The list of values per scale.

RaisesValueError – {param_name} must be in {types} or a list/tuple of {types} with the same length as the number of scales

check_callable

Parameters

•callables (callable or list of callables) – The callable to be used per scale.

•**n_scales** (*int*) – The number of scales.

Returnscallable_list (*list*) – A *list* of callables.

RaisesValueError – callables must be a callable or a list/tuple of callables with the same length as the number of scales

check_patch_shape

menpofit.checks.check_patch_shape (patch_shape, n_scales)
Function for checking a multi-scale patch_shape parameter value.

Parameters

•patch_shape (list/tuple of int/float or list of those) - The patch shape per scale

•n_scales (*int*) – The number of scales.

Returnspatch_shape (*list* of *list/tuple* of *int/float*) – The list of patch shape per scale.

RaisesValueError – patch_shape must be a list/tuple of int or a list/tuple of lit/tuple of int/float with the same length as the number of scales

check_max_iters

menpofit.checks.check_max_iters (max_iters, n_scales)
Function that checks the value of a max_iters parameter defined for multiple scales. It must be int or list of int.

Parameters

•max_iters (*int* or *list* of *int*) – The value to check.

•**n_scales** (*int*) – The number of scales.

Returnsmax_iters (*list* of *int*) – The list of values per scale.

RaisesValueError - max_iters can be integer, integer list containing 1 or {n_scales} elements or None

check_max_components

menpofit.checks.check_max_components(max_components, n_scales, var_name)

Checks the maximum number of components per scale. It must be None or *int* or *float* or a *list* of those containing 1 or $\{n_scales\}$ elements.

Parameters

•max_components (None or *int* or *float* or a *list* of those) – The value to check.

•**n_scales** (*int*) – The number of scales.

•**var_name** (*str*) – The name of the variable.

Returnsmax_components (*list* of None or *int* or *float*) – The list of max components per scale.

RaisesValueError - {var_name} must be None or an int > 0 or a 0 <= float <= 1 or a list of those containing 1 or {n_scales} elements

set_models_components

menpofit.checks.set_models_components (models, n_components)
Function that sets the number of active components to a list of models.

Parameters

•models (list or class) – The list of models per scale.

•n_components (*int* or *float* or None or *list* of those) – The number of components per model.

Raises ValueError – n_components can be an integer or a float or None or a list containing 1 or $\{n_scales\}$ of those

check_algorithm_cls

menpofit.checks.check_algorithm_cls (algorithm_cls, n_scales, base_algorithm_cls)
Function that checks whether the list of class objects defined per scale are subclasses of the provided base class.

Parameters

•algorithm_cls (*class* or *list* of *class*) – The list of objects per scale.

•n_scales (*int*) – The number of scales.

•base_algorithm_cls (class) – The required base class.

RaisesValueError – algorithm_cls must be a subclass of {base_algorithm_cls} or a list/tuple of {base_algorithm_cls} subclasses with the same length as the number of scales {n_scales}

check_sampling

menpofit.checks.check_sampling(sampling, n_scales)

Function that checks the value of a *sampling* parameter defined for multiple scales. It must be *int* or *ndarray* or *list* of those.

Parameters

•sampling (*int* or *ndarray* or *list* of those) – The value to check.

•n_scales (*int*) – The number of scales.

Returnssampling (*list* of *int* or *ndarray*) – The list of values per scale.

Raises

•ValueError - A sampling list can only contain 1 element or {n_scales} elements

•ValueError – sampling can be an integer or ndarray, a integer or ndarray list containing 1 or {n_scales} elements or None

check_graph

menpofit.checks.check_graph(graph,graph_types,param_name,n_scales)

Checks the provided graph per pyramidal level. The graph must be a subclass of graph_types or a list of those.

Parameters

•graph (graph or list of graph types) – The graph argument to check.

•graph_types (graph or tuple of graphs) – The tuple of allowed graph types.

•param_name (*str*) – The name of the graph parameter.

•**n_scales** (*int*) – The number of pyramidal levels.

Returnsgraph (list of graph types) – The graph per scale in a list.

Raises

•ValueError – {param_name} must be a list of length equal to the number of scales.

•ValueError - {param_name} must be a list of {graph_types_str}. {} given instead.

menpofit.differentiable

Differentiable Abstract Classes

Objects that are able to compute their own derivatives.

DL

class menpofit.differentiable.DL Bases: object

Object that is able to take its own derivative with respect to landmark changes.

d_dl (points)

The derivative of this spatial object with respect to spatial changes in anchor landmark points or centres, evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dl ((n_points, n_centres, n_dims) *ndarray*) - The Jacobian wrt landmark changes.

 $d_dl[i, k, m]$ is the scalar differential change that the any dimension of the i'th point experiences due to a first order change in the m'th dimension of the k'th landmark point.

Note that at present this assumes that the change in every dimension is equal.

DP

class menpofit.differentiable.DP

Bases: object

Object that is able to take its own derivative with respect to the parametrisation.

The parametrisation of objects is typically defined by the *menpo.base.Vectorizable* interface. As a result, *DP* is a mix-in that should be inherited along with *menpo.base.Vectorizable*.

d_dp (points)

The derivative of this spatial object with respect to the parametrisation changes evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dp((n_points, n_parameters, n_dims) *ndarray*) – The Jacobian with respect to the parametrisation.

 $d_dp[i, j, k]$ is the scalar differential change that the k'th dimension of the i'th point experiences due to a first order change in the j'th scalar in the parametrisation vector.

DX

class menpofit.differentiable.DX

Bases: object

Object that is able to take its own derivative with respect to spatial changes.

d_dx (points)

The first order derivative of this spatial object with respect to spatial changes evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dx ((n_points, n_dims, n_dims) *ndarray*) – The Jacobian wrt spatial changes.

 $d_dx[i, j, k]$ is the scalar differential change that the j'th dimension of the i'th point experiences due to a first order change in the k'th dimension.

It may be the case that the Jacobian is constant across space - in this case axis zero may have length 1 to allow for broadcasting.

menpofit.error

Normalisers

Functions that compute a metric which can be used to normalise the error between two shapes.

Bounding Box Normalisers

bb_area

menpofit.error.bb_area (shape)
Computes the area of the bounding box of the provided shape, i.e.

hw

where h and w are the height and width of the bounding box.

Parametersshape (*menpo.shape.PointCloud* or *subclass*) – The input shape.

Returnsbb_area (*float*) – The area of the bounding box.

bb_perimeter

menpofit.error.**bb_perimeter** (*shape*) Computes the perimeter of the bounding box of the provided shape, i.e.

2(h+w)

where h and w are the height and width of the bounding box.

Parametersshape (*menpo.shape.PointCloud* or *subclass*) – The input shape.

Returnsbb_perimeter (*float*) – The perimeter of the bounding box.

bb_avg_edge_length

```
menpofit.error.bb_avg_edge_length(shape)
```

Computes the average edge length of the bounding box of the provided shape, i.e.

$$\frac{h+w}{2} = \frac{2h+2w}{4}$$

where h and w are the height and width of the bounding box.

Parametersshape (menpo.shape.PointCloud or subclass) - The input shape.

Returnsbb_avg_edge_length (*float*) – The average edge length of the bounding box.

bb_diagonal

```
menpofit.error.bb_diagonal(shape)
```

Computes the diagonal of the bounding box of the provided shape, i.e.

 $\sqrt{h^2 + w^2}$

where h and w are the height and width of the bounding box.

Parametersshape (*menpo.shape.PointCloud* or *subclass*) – The input shape.

Returnsbb_diagonal (*float*) – The diagonal of the bounding box.

Distance Normalisers

distance_two_indices

menpofit.error.distance_two_indices (index1, index2, shape)
Computes the Euclidean distance between two points of a shape, i.e.

$$\sqrt{(s_{i,x} - s_{j,x})^2 + (s_{i,y} - s_{j,y})^2}$$

where $s_{i,x}$, $s_{i,y}$ are the x and y coordinates of the *i*'th point (*index1*) and $s_{j,x}$, $s_{j,y}$ are the x and y coordinates of the *j*'th point (*index2*).

Parameters

•index1 (*int*) – The index of the first point.

•index2 (*int*) – The index of the second point.

•**shape** (*menpo.shape.PointCloud*) – The input shape.

Returnsdistance_two_indices (float) – The Euclidean distance between the points.

Errors

Functions that compute the error between two shapes.

Root Mean Square Error

root_mean_square_error

```
menpofit.error.root_mean_square_error(*args, **kwargs)
Computes the root mean square error between two shapes, i.e.
```

$$\sqrt{\frac{1}{N}\sum_{i=1}^{N}(s_i - s_i^*)^2}$$

where s_i and s_i^* are the coordinates of the *i*'th point of the final and ground truth shapes, and N is the total number of points.

Parameters

•**shape** (*menpo.shape.PointCloud*) – The input shape (e.g. the final shape of a fitting procedure).

•gt_shape (*menpo.shape.PointCloud*) – The ground truth shape.

Returnsroot_mean_square_error (*float*) – The root mean square error.

root_mean_square_bb_normalised_error

menpofit.error.root_mean_square_bb_normalised_error(shape, gt_shape,

norm_shape=None,

norm_type='avg_edge_length')

Computes the root mean square error between two shapes normalised by a measure based on the ground truth

shape's bounding box, i.e.

$$\frac{\mathcal{F}(s,s^*)}{\mathcal{N}(s^*)}$$

where

$$\mathcal{F}(s, s^*) = \sqrt{\frac{1}{N} \sum_{i=1}^{N} (s_i - s_i^*)^2}$$

where s and s^* are the final and ground truth shapes, respectively. s_i and s_i^* are the coordinates of the *i*'th point of the final and ground truth shapes, and N is the total number of points. Finally, $\mathcal{N}(s^*)$ is a normalising function that returns a measure based on the ground truth shape's bounding box.

Parameters

- •**shape** (*menpo.shape.PointCloud*) The input shape (e.g. the final shape of a fitting procedure).
- •gt_shape (*menpo.shape.PointCloud*) The ground truth shape.
- •norm_shape (*menpo.shape.PointCloud* or None, optional) The shape to be used to compute the normaliser. If None, then the ground truth shape is used.

•norm_type ({'area', 'perimeter', 'avg_edge_length', 'diagonal'}, optional) - The type of the normaliser. Possible options are:

Method	Description
bb_area	Area of <i>norm_shape</i> 's bounding box
bb_perimeter	Perimeter of <i>norm_shape</i> 's bounding box
bb_avg_edge_length	Average edge length of <i>norm_shape</i> 's bbox
bb_diagonal	Diagonal of <i>norm_shape</i> 's bounding box

Returnserror (*float*) – The computed root mean square normalised error.

root_mean_square_distance_normalised_error

menpofit.error.root_mean_square_distance_normalised_error(shape, gt_shape, dis-

tance_norm_f)

Computes the root mean square error between two shapes normalised by a distance measure between two shapes, i.e.

$$\frac{\mathcal{F}(s,s^*)}{\mathcal{N}(s,s^*)}$$

where

$$\mathcal{F}(s, s^*) = \sqrt{\frac{1}{N} \sum_{i=1}^{N} (s_i - s_i^*)^2}$$

where s and s^{*} are the final and ground truth shapes, respectively. s_i and s_i^* are the coordinates of the *i*'th point of the final and ground truth shapes, and N is the total number of points. Finally, $\mathcal{N}(s, s^*)$ is a normalising function based on a distance metric between the two shapes.

Parameters

•**shape** (*menpo.shape.PointCloud*) – The input shape (e.g. the final shape of a fitting procedure).

•gt_shape (*menpo.shape.PointCloud*) – The ground truth shape.

•distance_norm_f (*callable*) – The function to be used for computing the normalisation distance metric.

Returnserror (*float*) – The computed root mean square normalised error.

root_mean_square_distance_indexed_normalised_error

menpofit.error.root_mean_square_distance_indexed_normalised_error(shape,

gt_shape, index1,

index2)

Computes the root mean square error between two shapes normalised by the distance measure between two points of the ground truth shape, i.e.

$$\frac{\mathcal{F}(s,s^*)}{\mathcal{N}(s^*)}$$

where

$$\mathcal{F}(s,s^*) = \sqrt{\frac{1}{N}\sum_{i=1}^{N}(s_i - s_i^*)^2}$$

where s and s^* are the final and ground truth shapes, respectively. s_i and s_i^* are the coordinates of the *i*'th point of the final and ground truth shapes, and N is the total number of points. Finally, $\mathcal{N}(s^*)$ is a normalising function that returns the distance between two points of the ground truth shape.

Parameters

•**shape** (*menpo.shape.PointCloud*) – The input shape (e.g. the final shape of a fitting procedure).

•gt_shape (menpo.shape.PointCloud) – The ground truth shape.

•index1 (*int*) – The index of the first point.

•index2 (*int*) – The index of the second point.

Returnserror (float) – The computed root mean square normalised error.

Euclidean Distance Error

euclidean_error

menpofit.error.euclidean_error(*args, **kwargs)

Computes the Euclidean error between two shapes, i.e.

$$\frac{1}{N}\sum_{i=1}^{N}\sqrt{(s_{i,x}-s_{i,x}^{*})^{2}+(s_{i,y}-s_{i,y}^{*})^{2}}$$

where $(s_{i,x}, s_{i,y})$ are the x and y coordinates of the *i*'th point of the final shape, $(s_{i,x}^*, s_{i,y}^*)$ are the x and y coordinates of the *i*'th point of the ground truth shape and N is the total number of points.

Parameters

•**shape** (*menpo.shape.PointCloud*) – The input shape (e.g. the final shape of a fitting procedure).

•gt_shape (*menpo.shape.PointCloud*) – The ground truth shape.

Returnsroot_mean_square_error (*float*) – The Euclidean error.

euclidean_bb_normalised_error

Computes the Euclidean error between two shapes normalised by a measure based on the ground truth shape's bounding box, i.e.

$$\frac{\mathcal{F}(s,s^*)}{\mathcal{N}(s^*)}$$

where

$$\mathcal{F}(s,s^*) = \frac{1}{N} \sum_{i=1}^{N} \sqrt{(s_{i,x} - s^*_{i,x})^2 + (s_{i,y} - s^*_{i,y})^2}$$

where s and s^{*} are the final and ground truth shapes, respectively. $(s_{i,x}, s_{i,y})$ are the x and y coordinates of the *i*'th point of the final shape, $(s_{i,x}^*, s_{i,y}^*)$ are the x and y coordinates of the *i*'th point of the ground truth shape and N is the total number of points. Finally, $\mathcal{N}(s^*)$ is a normalising function that returns a measure based on the ground truth shape's bounding box.

Parameters

- •**shape** (*menpo.shape.PointCloud*) The input shape (e.g. the final shape of a fitting procedure).
- •gt_shape (menpo.shape.PointCloud) The ground truth shape.

•norm_shape (*menpo.shape.PointCloud* or None, optional) – The shape to be used to compute the normaliser. If None, then the ground truth shape is used.

norm_type	({'a:	rea',	'perimet	cer',	avg_edge_l	length',
'diagonal'}, optional) -	The typ	pe of th	ne normaliser.	. Possible	e options are:	

Method	Description
bb_area	Area of <i>norm_shape</i> 's bounding box
bb_perimeter	Perimeter of <i>norm_shape</i> 's bounding box
bb_avg_edge_length	Average edge length of <i>norm_shape</i> 's bbox
bb_diagonal	Diagonal of <i>norm_shape</i> 's bounding box

Returnserror (*float*) – The computed Euclidean normalised error.

euclidean_distance_normalised_error

menpofit.error.euclidean_distance_normalised_error(shape, gt_shape, distance_norm_f)

Computes the Euclidean error between two shapes normalised by a distance measure between two shapes, i.e.

$$\frac{\mathcal{F}(s,s^*)}{\mathcal{N}(s,s^*)}$$

where

$$\mathcal{F}(s,s^*) = \frac{1}{N} \sum_{i=1}^{N} \sqrt{(s_{i,x} - s^*_{i,x})^2 + (s_{i,y} - s^*_{i,y})^2}$$

where s and s^* are the final and ground truth shapes, respectively. $(s_{i,x}, s_{i,y})$ are the x and y coordinates of the *i*'th point of the final shape, $(s_{i,x}^*, s_{i,y}^*)$ are the x and y coordinates of the *i*'th point of the ground truth shape and N is the total number of points. Finally, $\mathcal{N}(s, s^*)$ is a normalising function based on a distance metric between the two shapes.

Parameters

•**shape** (*menpo.shape.PointCloud*) – The input shape (e.g. the final shape of a fitting procedure).

•gt_shape (menpo.shape.PointCloud) – The ground truth shape.

•distance_norm_f (*callable*) – The function to be used for computing the normalisation distance metric.

Returnserror (*float*) – The computed Euclidean normalised error.

euclidean_distance_indexed_normalised_error

menpofit.error.euclidean_distance_indexed_normalised_error(shape, gt_shape, in-

dex1, index2)

Computes the Euclidean error between two shapes normalised by the distance measure between two points of the ground truth shape, i.e.

$$\frac{\mathcal{F}(s,s^*)}{\mathcal{N}(s^*)}$$

where

$$\mathcal{F}(s,s^*) = \frac{1}{N} \sum_{i=1}^{N} \sqrt{(s_{i,x} - s_{i,x}^*)^2 + (s_{i,y} - s_{i,y}^*)^2}$$

where s and s^{*} are the final and ground truth shapes, respectively. $(s_{i,x}, s_{i,y})$ are the x and y coordinates of the *i*'th point of the final shape, $(s_{i,x}^*, s_{i,y}^*)$ are the x and y coordinates of the *i*'th point of the ground truth shape and N is the total number of points. Finally, $\mathcal{N}(s^*)$ is a normalising function that returns the distance between two points of the ground truth shape.

Parameters

•**shape** (*menpo.shape.PointCloud*) – The input shape (e.g. the final shape of a fitting procedure).

•gt_shape (*menpo.shape.PointCloud*) – The ground truth shape.

•index1 (*int*) – The index of the first point.

•index2 (int) – The index of the second point.

Returnserror (float) - The computed Euclidean normalised error.

Statistical Measures

Functions that compute statistical measures given a set of errors for multiple images.

compute_cumulative_error

```
menpofit.error.compute_cumulative_error (errors, bins)
Computes the values of the Cumulative Error Distribution (CED).
```

Parameters

•errors (*list* of *float*) – The *list* of errors per image.

•bins (*list* of *float*) – The values of the error bins centers at which the CED is evaluated.

Returnsced (*list* of *float*) – The computed CED.

area_under_curve_and_failure_rate

```
menpofit.error.area_under_curve_and_failure_rate(errors, step_error, max_error,
min_error=0.0)
```

Computes the Area Under the Curve (AUC) and Failure Rate (FR) of a given Cumulative Distribution Error (CED).

Parameters

•errors (*list* of *float*) – The *list* of errors per image.

•step_error (float) – The sampling step of the error bins of the CED.

•max_error (*float*) – The maximum error value of the CED.

•min_error (*float*) – The minimum error value of the CED.

Returns

•auc (*float*) – The Area Under the Curve value.

•fr (*float*) – The Failure Rate value.

mad

menpofit.error.mad (*errors*) Computes the Median Absolute Deviation of a set of errors.

Parameterserrors (*list* of *float*) – The *list* of errors per image.

Returnsmad (*float*) – The median absolute deviation value.

compute_statistical_measures

Computes various statistics given a set of errors that correspond to multiple images. It can also deal with multiple sets of errors that correspond to different methods.

Parameters

•errors (*list* of *float* or *list* of *list* of *float*) – The *list* of errors per image. You can provide a *list* of *lists* for the errors of multiple methods.

- •**step_error** (*float*) The sampling step of the error bins of the CED for computing the Area Under the Curve and the Failure Rate.
- •max_error (*float*) The maximum error value of the CED for computing the Area Under the Curve and the Failure Rate.
- •min_error (*float*) The minimum error value of the CED for computing the Area Under the Curve and the Failure Rate.

Returns

•mean (*float* or *list* of *float*) – The mean value.
•mean (*float* or *list* of *float*) – The standard deviation.
•median (*float* or *list* of *float*) – The median value.
•mad (*float* or *list* of *float*) – The mean absolute deviation value.
•max (*float* or *list* of *float*) – The maximum value.
•auc (*float* or *list* of *float*) – The area under the curve value.
•fr (*float* or *list* of *float*) – The failure rate value.

Object-Specific Errors

Error functions for specific objects.

Face

bb_avg_edge_length_68_euclidean_error

menpofit.error.bb_avg_edge_length_68_euclidean_error(shape, gt_shape)

Computes the Euclidean error based on 68 points normalised by the average edge length of the 68-point ground truth shape's bounding box, i.e.

$$\frac{\mathcal{F}(s,s^*)}{\mathcal{N}(s^*)}$$

where

$$\mathcal{F}(s,s^*) = \frac{1}{68} \sum_{i=1}^{68} \sqrt{(s_{i,x} - s_{i,x}^*)^2 + (s_{i,y} - s_{i,y}^*)^2}$$

where s and s^{*} are the final and ground truth shapes, respectively. $(s_{i,x}, s_{i,y})$ are the x and y coordinates of the *i*th point of the final shape, $(s_{i,x}^*, s_{i,y}^*)$ are the x and y coordinates of the *i*th point of the ground truth shape. Finally, $\mathcal{N}(s^*)$ is a normalising function that returns the average edge length of the bounding box of the 68-point ground truth shape (*bb_avg_edge_length*).

Parameters

•**shape** (*menpo.shape.PointCloud*) – The input shape (e.g. the final shape of a fitting procedure). It must have 68 points.

•gt_shape (menpo.shape.PointCloud) - The ground truth shape. It must have 68 points.

Returnsnormalised_error (float) – The computed Euclidean normalised error.

Raises

•ValueError - Final shape must have 68 points

•ValueError - Ground truth shape must have 68 points

bb_avg_edge_length_49_euclidean_error

menpofit.error.bb_avg_edge_length_49_euclidean_error(shape, gt_shape)

Computes the Euclidean error based on 49 points normalised by the average edge length of the 68-point ground truth shape's bounding box, i.e.

$$\frac{\mathcal{F}(s,s^*)}{\mathcal{N}(s^*)}$$

where

$$\mathcal{F}(s,s^*) = \frac{1}{49} \sum_{i=1}^{49} \sqrt{(s_{i,x} - s^*_{i,x})^2 + (s_{i,y} - s^*_{i,y})^2}$$

where s and s^{*} are the final and ground truth shapes, respectively. $(s_{i,x}, s_{i,y})$ are the x and y coordinates of the *i*'th point of the final shape, $(s_{i,x}^*, s_{i,y}^*)$ are the x and y coordinates of the *i*'th point of the ground truth shape. Finally, $\mathcal{N}(s^*)$ is a normalising function that returns the average edge length of the bounding box of the 68-point ground truth shape (*bb_avg_edge_length*).

Parameters

•**shape** (*menpo.shape.PointCloud*) – The input shape (e.g. the final shape of a fitting procedure). It must have 68 or 66 or 51 or 49 points.

•gt_shape (menpo.shape.PointCloud) – The ground truth shape. It must have 68 points.

Returnsnormalised_error (*float*) – The computed Euclidean normalised error.

Raises

•ValueError - Final shape must have 68 or 51 or 49 points

•ValueError - Ground truth shape must have 68 points

mean_pupil_68_error

menpofit.error.mean_pupil_68_error(shape, gt_shape)

Computes the Euclidean error based on 68 points normalised with the distance between the mean eye points (pupils), i.e.

$$\frac{\mathcal{F}(s,s^*)}{\mathcal{N}(s)}$$

where

$$\mathcal{F}(s,s^*) = \frac{1}{68} \sum_{i=1}^{68} \sqrt{(s_{i,x} - s^*_{i,x})^2 + (s_{i,y} - s^*_{i,y})^2}$$

where s and s^{*} are the final and ground truth shapes, respectively. $(s_{i,x}, s_{i,y})$ are the x and y coordinates of the *i*'th point of the final shape, $(s_{i,x}^*, s_{i,y}^*)$ are the x and y coordinates of the *i*'th point of the ground truth shape. Finally, $\mathcal{N}(s)$ is the distance between the mean eye points (pupils).

Parameters

•**shape** (*menpo.shape.PointCloud*) – The input shape (e.g. the final shape of a fitting procedure). It must have 68 points.

•gt_shape (menpo.shape.PointCloud) - The ground truth shape. It must have 68 points.

Returnsnormalised_error (*float*) – The computed normalised Euclidean error.

Raises

•ValueError – Final shape must have 68 points

•ValueError - Ground truth shape must have 68 points

mean_pupil_49_error

menpofit.error.mean_pupil_49_error(shape, gt_shape)

Computes the euclidean error based on 49 points normalised with the distance between the mean eye points (pupils), i.e.

$$\frac{\mathcal{F}(s,s^*)}{\mathcal{N}(s)}$$

where

$$\mathcal{F}(s,s^*) = \frac{1}{49} \sum_{i=1}^{49} \sqrt{(s_{i,x} - s^*_{i,x})^2 + (s_{i,y} - s^*_{i,y})^2}$$

where s and s^{*} are the final and ground truth shapes, respectively. $(s_{i,x}, s_{i,y})$ are the x and y coordinates of the *i*'th point of the final shape, $(s_{i,x}^*, s_{i,y}^*)$ are the x and y coordinates of the *i*'th point of the ground truth shape. Finally, $\mathcal{N}(s)$ is the distance between the mean eye points (pupils).

Parameters

•**shape** (*menpo.shape.PointCloud*) – The input shape (e.g. the final shape of a fitting procedure). It must have either 68 or 66 or 51 or 49 points.

•gt_shape (*menpo.shape.PointCloud*) – The ground truth shape. It must have either 68 or 66 or 51 or 49 points.

Returnsnormalised_error (*float*) – The computed normalised Euclidean error.

Raises

•ValueError - Final shape must have 68 or 66 or 51 or 49 points

•ValueError - Ground truth shape must have 68 or 66 or 51 or 49 points

outer_eye_corner_68_euclidean_error

menpofit.error.outer_eye_corner_68_euclidean_error(shape, gt_shape)

Computes the Euclidean error based on 68 points normalised with the distance between the mean eye points (pupils), i.e.

$$\frac{\mathcal{F}(s,s^*)}{\mathcal{N}(s^*)}$$

where

$$\mathcal{F}(s,s^*) = \frac{1}{68} \sum_{i=1}^{68} \sqrt{(s_{i,x} - s^*_{i,x})^2 + (s_{i,y} - s^*_{i,y})^2}$$

where s and s^{*} are the final and ground truth shapes, respectively. $(s_{i,x}, s_{i,y})$ are the x and y coordinates of the *i*'th point of the final shape, $(s_{i,x}^*, s_{i,y}^*)$ are the x and y coordinates of the *i*'th point of the ground truth shape. Finally, $\mathcal{N}(s^*)$ is the distance between the 36-th and 45-th points.

Parameters

•**shape** (*menpo.shape.PointCloud*) – The input shape (e.g. the final shape of a fitting procedure). It must have 68 points.

•gt_shape (menpo.shape.PointCloud) - The ground truth shape. It must have 68 points.

Returnsnormalised_error (*float*) – The computed normalised Euclidean error.

Raises

•ValueError - Final shape must have 68 points

•ValueError - Ground truth shape must have 68 points

outer_eye_corner_51_euclidean_error

menpofit.error.outer_eye_corner_51_euclidean_error(shape, gt_shape)

Computes the Euclidean error based on 51 points normalised with the distance between the mean eye points (pupils), i.e.

$$\frac{\mathcal{F}(s,s^*)}{\mathcal{N}(s^*)}$$

where

$$\mathcal{F}(s,s^*) = \frac{1}{51} \sum_{i=1}^{51} \sqrt{(s_{i,x} - s_{i,x}^*)^2 + (s_{i,y} - s_{i,y}^*)^2}$$

where s and s^{*} are the final and ground truth shapes, respectively. $(s_{i,x}, s_{i,y})$ are the x and y coordinates of the *i*'th point of the final shape, $(s_{i,x}^*, s_{i,y}^*)$ are the x and y coordinates of the *i*'th point of the ground truth shape. Finally, $\mathcal{N}(s^*)$ is the distance between the 19-th and 28-th points.

Parameters

•**shape** (*menpo.shape.PointCloud*) – The input shape (e.g. the final shape of a fitting procedure). It must 68 or 51 points.

•gt_shape (*menpo.shape.PointCloud*) – The ground truth shape. It must have 68 or 51 points.

Returnsnormalised_error (*float*) – The computed normalised Euclidean error.

Raises

•ValueError - Final shape must have 68 or 51 points

•ValueError - Ground truth shape must have 68 or 51 points

outer_eye_corner_49_euclidean_error

menpofit.error.outer_eye_corner_49_euclidean_error(shape, gt_shape)

Computes the Euclidean error based on 49 points normalised with the distance between the mean eye points (pupils), i.e.

$$\frac{\mathcal{F}(s,s^*)}{\mathcal{N}(s^*)}$$

where

$$\mathcal{F}(s,s^*) = \frac{1}{49} \sum_{i=1}^{49} \sqrt{(s_{i,x} - s_{i,x}^*)^2 + (s_{i,y} - s_{i,y}^*)^2}$$

where s and s^{*} are the final and ground truth shapes, respectively. $(s_{i,x}, s_{i,y})$ are the x and y coordinates of the *i*'th point of the final shape, $(s_{i,x}^*, s_{i,y}^*)$ are the x and y coordinates of the *i*'th point of the ground truth shape. Finally, $\mathcal{N}(s^*)$ is the distance between the 19-th and 28-th points.

Parameters

- •**shape** (*menpo.shape.PointCloud*) The input shape (e.g. the final shape of a fitting procedure). It must 68 or 66 or 51 or 49 points.
- •gt_shape (*menpo.shape.PointCloud*) The ground truth shape. It must have 68 or 66 or 51 or 49 points.

Returnsnormalised_error (float) – The computed normalised Euclidean error.

Raises

•ValueError - Final shape must have 68 or 66 or 51 or 49 points

•ValueError - Ground truth shape must have 68 or 66 or 51 or 49 points

menpofit.fitter

Fitter Classes

MultiScaleNonParametricFitter

class menpofit.fitter.MultiScaleNonParametricFitter(scales, reference_shape, holistic_features, algorithms)

Bases: object

Class for defining a multi-scale fitter for a non-parametric fitting method, i.e. a method that does not optimise over a parametric shape model.

Parameters

•scales (*list* of *int* or *float*) – The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale.

•**reference_shape** (*menpo.shape.PointCloud*) – The reference shape that will be used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of the reference shape.

•holistic_features (*list* of *closure*) – The features that will be extracted from the input image at each scale. They must provided in ascending order, i.e. from lowest to highest scale.

•algorithms (*list* of *class*) – The list of algorithm objects that will perform the fitting per scale.

fit_from_bb (*image*, *bounding_box*, *max_iters=20*, *gt_shape=None*, *return_costs=False*, ***kwargs*) Fits the multi-scale fitter to an image given an initial bounding box.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

- •bounding_box (*menpo.shape.PointDirectedGraph*) The initial bounding box from which the fitting procedure will start. Note that the bounding box is used in order to align the model's reference shape.
- •max_iters (*int* or *list* of *int*, optional) The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

- **Returnsfitting_result** (*MultiScaleNonParametricIterativeResult* or subclass) The multi-scale fitting result containing the result of the fitting procedure.

Fits the multi-scale fitter to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape estimate from which the fitting procedure will start.

•max_iters (*int* or *list* of *int*, optional) – The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

holistic_features

The features that are extracted from the input image at each scale in ascending order, i.e. from lowest to highest scale.

Type*list* of *closure*

n_scales

Returns the number of scales.

Typeint

reference_shape

The reference shape that is used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of this reference shape.

Typemenpo.shape.PointCloud

scales

The scale value of each scale in ascending order, i.e. from lowest to highest scale.

Typelist of int or float

MultiScaleParametricFitter

```
class menpofit.fitter.MultiScaleParametricFitter(scales, reference_shape, holis-
tic_features, algorithms)
Bases: MultiScaleNonParametricFitter
```

Class for defining a multi-scale fitter for a parametric fitting method, i.e. a method that optimises over the parameters of a statistical shape model.

Note: When using a method with a parametric shape model, the first step is to **reconstruct the initial shape** using the shape model. The generated reconstructed shape is then used as initialisation for the iterative optimisation. This step takes place at each scale and it is not considered as an iteration, thus it is not counted for the provided *max_iters*.

Parameters

•scales (*list* of *int* or *float*) – The scale value of each scale. They must provided in ascending order, i.e. from lowest to highest scale.

- •**reference_shape** (*menpo.shape.PointCloud*) The reference shape that will be used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of the reference shape.
- •holistic_features (*list* of *closure*) The features that will be extracted from the input image at each scale. They must provided in ascending order, i.e. from lowest to highest scale.
- •algorithms (*list* of *class*) The list of algorithm objects that will perform the fitting per scale.
- fit_from_bb (image, bounding_box, max_iters=20, gt_shape=None, return_costs=False, **kwargs)
 Fits the multi-scale fitter to an image given an initial bounding box.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•bounding_box (*menpo.shape.PointDirectedGraph*) – The initial bounding box from which the fitting procedure will start. Note that the bounding box is used in order to align the model's reference shape.

•max_iters (*int* or *list* of *int*, optional) – The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

Fits the multi-scale fitter to an image given an initial shape.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•initial_shape (*menpo.shape.PointCloud*) – The initial shape estimate from which the fitting procedure will start.

•max_iters (*int* or *list* of *int*, optional) – The maximum number of iterations. If *int*, then it specifies the maximum number of iterations over all scales. If *list* of *int*, then specifies the maximum number of iterations per scale.

•gt_shape (*menpo.shape.PointCloud*, optional) – The ground truth shape associated to the image.

•return_costs (bool, optional) – If True, then the cost function values will be computed during the fitting procedure. Then these cost values will be assigned to the returned fitting_result. Note that the costs computation increases the computational cost of the fitting. The additional computation cost depends on the fitting method. Only use this option for research purposes.

•**kwargs** (*dict*, optional) – Additional keyword arguments that can be passed to specific implementations.

Returnsfitting_result (*MultiScaleNonParametricIterativeResult* or subclass) – The multi-scale fitting result containing the result of the fitting procedure.

holistic_features

The features that are extracted from the input image at each scale in ascending order, i.e. from lowest to highest scale.

Typelist of closure

n_scales

Returns the number of scales.

Type*int*

reference_shape

The reference shape that is used to normalise the size of an input image so that the scale of its initial fitting shape matches the scale of this reference shape.

Typemenpo.shape.PointCloud

scales

The scale value of each scale in ascending order, i.e. from lowest to highest scale.

Typelist of int or float

Perturb Functions

Collection of functions that perform a kind of perturbation on a shape or bounding box.

align_shape_with_bounding_box

menpofit.fitter.align_shape_with_bounding_box(shape, bounding_box, alignment_transform_cls=<class 'menpo.transform.homogeneous.similarity.AlignmentSimilarity'>,

**kwargs)

Aligns the provided shape with the bounding box using a particular alignment transform.

Parameters

•**shape** (*menpo.shape.PointCloud*) – The shape instance used in the alignment.

•**bounding_box** (*menpo.shape.PointDirectedGraph*) – The bounding box instance used in the alignment.

•alignment_transform_cls (*menpo.transform.Alignment*, optional) – The class of the alignment transform used to perform the alignment.

Returnsnoisy_shape (menpo.shape.PointCloud) – The noisy shape

generate_perturbations_from_gt

verbose=False) Function that returns a callable that generates perturbations of the bounding boxes of the provided images.

Parameters

•images (list of menpo.image.Image) – The list of images.

•n_perturbations (*int*) – The number of perturbed shapes to be generated per image.

•**perturb_func** (*callable*) – The function that will be used for generating the perturbations.

•gt_group (str) – The group of the ground truth shapes attached to the images.

•bb_group_glob (*str*) – The group of the bounding boxes attached to the images.

•verbose (bool, optional) – If True, then progress information is printed.

Returnsgenerated_bb_func (*callable*) – The function that generates the perturbations.

noisy_alignment_similarity_transform

Constructs and perturbs the optimal similarity transform between the source and target shapes by adding noise to its parameters.

Parameters

•source (menpo.shape.PointCloud) - The source pointcloud instance used in the alignment

•target (menpo.shape.PointCloud) - The target pointcloud instance used in the alignment

•noise_type ({'uniform', 'gaussian'}, optional) - The type of noise to be
added.

•noise_percentage (*float* in (0, 1) or *list* of *len 3*, optional) – The standard percentage of noise to be added. If *float*, then the same amount of noise is applied to the scale, rotation and translation parameters of the optimal similarity transform. If *list* of *float* it must have length 3, where the first, second and third elements denote the amount of noise to be applied to the scale, rotation and translation parameters, respectively.

•allow_alignment_rotation (*bool*, optional) – If False, then the rotation is not considered when computing the optimal similarity transform between source and target.

Returnsnoisy_alignment_similarity_transform (*menpo.transform.Similarity*) – The noisy Similarity Transform between source and target.

noisy_shape_from_bounding_box

<pre>menpofit.fitter.noisy_shape_from_bounding_box(shape,</pre>	bounding_box,
noise_type='uniform',	
noise_percentage=0.05,	al-
low_alignment_rotation=	=False)

Constructs and perturbs the optimal similarity transform between the bounding box of the source shape and the target bounding box, by adding noise to its parameters. It returns the noisy version of the provided shape.

Parameters

- •**shape** (*menpo.shape.PointCloud*) The source pointcloud instance used in the alignment. Note that the bounding box of the shape will be used.
- •**bounding_box** (*menpo.shape.PointDirectedGraph*) The target bounding box instance used in the alignment

•noise_type ({'uniform', 'gaussian'}, optional) - The type of noise to be added.

•noise_percentage (*float* in (0, 1) or *list* of *len 3*, optional) – The standard percentage of noise to be added. If *float*, then the same amount of noise is applied to the scale, rotation and translation parameters of the optimal similarity transform. If *list* of *float* it must have length 3, where the first, second and third elements denote the amount of noise to be applied to the scale, rotation and translation parameters, respectively.

•allow_alignment_rotation (*bool*, optional) – If False, then the rotation is not considered when computing the optimal similarity transform between source and target.

Returnsnoisy_shape (*menpo.shape.PointCloud*) – The noisy shape.

noisy_shape_from_shape

low_alignment_rotation=False)

Constructs and perturbs the optimal similarity transform between the provided reference shape and the target shape, by adding noise to its parameters. It returns the noisy version of the reference shape.

Parameters

- •**reference_shape** (*menpo.shape.PointCloud*) The source reference shape instance used in the alignment.
- •**shape** (*menpo.shape.PointDirectedGraph*) The target shape instance used in the alignment

•noise_type ({'uniform', 'gaussian'}, optional) - The type of noise to be added.

- •noise_percentage (*float* in (0, 1) or *list* of *len 3*, optional) The standard percentage of noise to be added. If *float*, then the same amount of noise is applied to the scale, rotation and translation parameters of the optimal similarity transform. If *list* of *float* it must have length 3, where the first, second and third elements denote the amount of noise to be applied to the scale, rotation and translation parameters, respectively.
- •allow_alignment_rotation (*bool*, optional) If False, then the rotation is not considered when computing the optimal similarity transform between source and target.

Returnsnoisy_reference_shape (*menpo.shape.PointCloud*) – The noisy reference shape.

noisy_target_alignment_transform

Constructs the optimal alignment transform between the source and a noisy version of the target obtained by adding white noise to each of its points.

Parameters

•source (menpo.shape.PointCloud) - The source pointcloud instance used in the alignment

•target (menpo.shape.PointCloud) - The target pointcloud instance used in the alignment

- •alignment_transform_cls (*menpo.transform.Alignment*, optional) The alignment transform class used to perform the alignment.
- •noise_std (*float* or *list* of *float*, optional) The standard deviation of the white noise to be added to each one of the target points. If *float*, then the same standard deviation is used for all points. If *list*, then it must define a value per point.

Returnsnoisy_transform (*menpo.transform.Alignment*) – The noisy Similarity Transform

menpofit.io

Menpofit includes the ability to save and load pre-trained models for specific tasks. This module contains code for pickling down, downloading, and restoring fitters efficiently.

If you make use of one of menpofit's pre-trained models, you will find that the type that is provided to you is the PickleWrappedFitter. See it's documentation to understand it's purpose and how you can effectively use it.

PickleWrappedFitter

Bases: object

Wrapper around a menpofit fitter so that we can a) efficiently pickle it and b) parametrize over both the fitter construction and the fit methods (e.g. .fit_from_bb() and .fit_from_shape())

Pickling menpofit fitters is a little tricky for a two reasons. Firstly, on construction of a fitter from a deformable model some amount of pre-processing takes place which allocates potentially large arrays. To ship a compact model we would therefore rather delay the construction of the fitter until load time on the client.

If this was the only issue, we could achieve this by simply saving a partial over the fitter constructor with all the args and kwargs the fitter constructor takes - after loading the pickle, invoking the partial with no args (it's parameters being fully specified) would return the fitter and all would be well.

However, we also may want to choose **fit-time** parameters for the fitter for optimal usage, (for instance, a choice over the max_iters kwarg that we know to be efficient). This leaves us with a problem, as now we need to have some entity that can store state which we can pass to both the fitter and to the resulting fitters methods on the client at unpickle time.

This class is the solution to this problem. To use, you should **pickle down a partial over this class** specifying all arguments and kwargs needed for the fitter constructor and for the fit methods.

At load time, menpofit will invoke the partial, returning this object instantiated. This offers the same API as a menpofit fitter, and so can be used transparently to fit. If you wish to access the original fitter (without fit parameter customization) this can be accessed as the *wrapped_fitter* property.

Parameters

- •fitter_cls (*Fitter*) A menpofit fitter class that will be constructed at unpickle time, e.g. LucasKanadeAAMFitter
- •fitter_args (*tuple*) A tuple of all args that need to be passed to fitter_cls at construction time e.g. (aam,)
- •fitter_kwargs (dict) A dictionary of kwargs that will to be passed to fitter_cls at construction time e.g. { 'lk_algorithm_cls': WibergInverseCompositional }
- •fit_from_bb_kwargs (dict, e.g. { max_iters: [25, 5] }) A dictionary of kwargs that will to be passed to the wrapped fitter's fit_from_bb method at fit time. These in effect change the defaults that the original fitter offered, but can still be overridden at call time (e.g. self.fit_from_bb(image, bbox, max_iters=[50, 50]) would take precedence over the max_iters in the above example)
- •fit_from_shape_kwargs (*dict*, e.g. { max_iters: [25, 5] }) A dictionary of kwargs that will to be passed to the wrapped fitter's fit_from_shape method at fit time. These in effect change the defaults that the original fitter offered, but can still be overridden at call time (e.g. self.fit_from_shape(image, shape, max_iters=[50, 50]) would take precedence over the max_iters in the above example)
- •**image_preprocess** (*callable* or None, optional) A pre-processing function to apply on the test image before fitting. The default option converts the image to greyscale. The function needs to have the following signature:

new_image, transform = image_preprocess(image, pointcloud)

where *new_image* is the pre-processed image and *transform* is the *menpo.transform.Homogeneous* object that was applied on the image. If None, then no pre-processing is performed.

Examples

```
from menpofit.io import PickleWrappedFitter, image_greyscale_crop_preprocess
from functools import partial
# LucasKanadeAAMFitter only takes one argument, a trained aam.
fitter_args = (aam, )
# kwargs for fitter construction. Note that here sampling is a
# list of numpy arrays we have already constructed (one per level)
fitter_kwargs = dict(lk_algorithm_cls=WibergInverseCompositional,
                    sampling=sampling)
# kwarqs for fitter.fit_from_{bb, shape}
# (note here we reuse the same kwargs twice)
fit_kwargs = dict(max_iters=[25, 5])
# Partial over the PickleWrappedFitter to prepare an object that can be
# invoked at load time
fitter_wrapper = partial(PickleWrappedFitter, LucasKanadeAAMFitter,
                        fitter_args, fitter_kwargs,
                        fit_kwargs, fit_kwargs,
                        image_preprocess=image_greyscale_crop_preprocess)
# save the pickle down.
mio.export_pickle(fitter_wrapper, 'pretrained_aam.pkl')
     ----- L O A D T I M E ------#
# at load time, invoke the partial to instantiate this class (and build
# the internally-held wrapped fitter)
fitter = mio.import_pickle('pretrained_aam.pkl')()
```

fit_from_bb (image, bounding_box, **kwargs)

Fits the fitter to an image given an initial bounding box, using the optimal parameters that we chosen for this pickled fitter.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.

•**bounding_box** (*menpo.shape.PointDirectedGraph*) – The initial bounding box from which the fitting procedure will start. Note that the bounding box is used in order to align the model's reference shape.

•**kwargs** (*dict*, optional) – Other kwargs to override the optimal defaults. See the documentation for .fit_from_bb() on the type of *self.wrapped_fitter* to see what can be provided here.

Returnsfitting_result (FittingResult or subclass) – The fitting result containing the result of the fitting procedure.

fit_from_shape (image, initial_shape, **kwargs)

Fits the fitter to an image given an initial shape, using the optimal parameters that we chosen for this pickled fitter.

Parameters

•image (menpo.image.Image or subclass) – The image to be fitted.
- •initial_shape (*menpo.shape.PointCloud*) The initial shape estimate from which the fitting procedure will start.
- •**kwargs** (*dict*) Other kwargs to override the optimal defaults. See the documentation for .fit_from_shape() on the type of *self.wrapped_fitter* to see what can be provided here.
- **Returnsfitting_result** (FittingResult or subclass) The fitting result containing the result of the fitting procedure.

menpofit.math

Regression

IRLRegression

class menpofit.math.IRLRegression(alpha=0, bias=True, incrementable=False)
Bases: object

Class for training and applying Incremental Regularized Linear Regression.

Parameters

•alpha (float, optional) – The regularization parameter of the features.

•bias (bool, optional) – If True, a bias term is used.

•incrementable (*bool*, optional) – If True, then the regression model will have the ability to get incremented.

increment(X, Y)

Incrementally update the regression model.

Parameters

•X ((n_features, n_samples) *ndarray*) – The array of feature vectors.

•Y ((n_dims, n_samples) *ndarray*) – The array of target vectors.

 $Raises \verb"ValueError-Model" is not incrementable$

predict (x)

Makes a prediction using the trained regression model.

Parametersx ((n_features,) *ndarray*) – The input feature vector.

Returnsprediction ((n_dims,) *ndarray*) – The prediction vector.

train(X, Y)

Train the regression model.

Parameters

•X ((n_features, n_samples) *ndarray*) – The array of feature vectors.

•Y ((n_dims, n_samples) *ndarray*) – The array of target vectors.

IIRLRegression

```
class menpofit.math.IIRLRegression (alpha=0, bias=False, alpha2=0)
Bases: IRLRegression
```

Class for training and applying Indirect Incremental Regularized Linear Regression.

Parameters

•alpha (*float*, optional) – The regularization parameter.

•bias (bool, optional) – If True, a bias term is used.

•alpha2 (float, optional) – The regularization parameter of the Hessian.

increment (X, Y)

Incrementally update the regression model.

Parameters

•X ((n_features, n_samples) *ndarray*) – The array of feature vectors.

•Y ((n_dims, n_samples) *ndarray*) – The array of target vectors.

Raises
ValueError - Model is not incrementable

predict(x)

Makes a prediction using the trained regression model.

Parametersx ((n_features,) ndarray) - The input feature vector.

Returnsprediction ((n_dims,) *ndarray*) – The prediction vector.

train(X, Y)

Train the regression model.

Parameters

•X((n_features, n_samples) *ndarray*) – The array of feature vectors.

•Y ((n_dims, n_samples) *ndarray*) – The array of target vectors.

PCRRegression

class menpofit.math.PCRRegression (variance=None, bias=True)
Bases: object

Class for training and applying Multivariate Linear Regression using Principal Component Regression.

Parameters

•variance (float or None, optional) – The SVD variance.

•bias (bool, optional) – If True, a bias term is used.

increment (X, Y)

Incrementally update the regression model.

Parameters

•X ((n_features, n_samples) *ndarray*) – The array of feature vectors.

•Y ((n_dims, n_samples) *ndarray*) – The array of target vectors.

RaisesValueError – Model is not incrementable

predict(x)

Makes a prediction using the trained regression model.

Parametersx ((n_features,) ndarray) - The input feature vector.

Returnsprediction ((n_dims,) *ndarray*) – The prediction vector.

train(X, Y)

Train the regression model.

Parameters

•X ((n_features, n_samples) ndarray) – The array of feature vectors.

•Y ((n_dims, n_samples) *ndarray*) – The array of target vectors.

OptimalLinearRegression

class menpofit.math.OptimalLinearRegression (variance=None, bias=True)
Bases: object

Class for training and applying Multivariate Linear Regression using optimal reconstructions.

Parameters

•variance (float or None, optional) – The SVD variance.

•bias (bool, optional) – If True, a bias term is used.

increment(X, Y)

Incrementally update the regression model.

Parameters

•X ((n_features, n_samples) *ndarray*) – The array of feature vectors.

•Y ((n_dims, n_samples) *ndarray*) – The array of target vectors.

RaisesValueError – Model is not incrementable

predict(x)

Makes a prediction using the trained regression model.

Parametersx ((n_features,) *ndarray*) – The input feature vector.

Returnsprediction ((n_dims,) *ndarray*) – The prediction vector.

train(X, Y)

Train the regression model.

Parameters

•X ((n_features, n_samples) *ndarray*) – The array of feature vectors.

•Y ((n_dims, n_samples) *ndarray*) – The array of target vectors.

OPPRegression

class menpofit.math.OPPRegression(bias=True, whiten=False)

Bases: object

Class for training and applying Multivariate Linear Regression using Orthogonal Procrustes Problem reconstructions.

Parameters

•bias (*bool*, optional) – If True, a bias term is used.

•whiten (bool, optional) – Whether to use a whitened PCA model.

increment(X, Y)

Incrementally update the regression model.

Parameters

•X ((n_features, n_samples) *ndarray*) – The array of feature vectors.

•Y ((n_dims, n_samples) *ndarray*) – The array of target vectors.

Raises
ValueError - Model is not incrementable

predict (x)

Makes a prediction using the trained regression model.

Parametersx ((n_features,) *ndarray*) – The input feature vector.

Returnsprediction ((n_dims,) *ndarray*) – The prediction vector.

train(X, Y)

Train the regression model.

Parameters

•X ((n_features, n_samples) *ndarray*) – The array of feature vectors.

•Y ((n_dims, n_samples) *ndarray*) – The array of target vectors.

Correlation Filters

mccf

menpofit.math.mccf(X, y, l=0.01, boundary='constant', crop_filter=True)
Multi-Channel Correlation Filter (MCCF).

Parameters

•X((n_images, n_channels, image_h, image_w) *ndarray*) – The training images.

•y((1, response_h, response_w) *ndarray*) – The desired response.

•1 (float, optional) – Regularization parameter.

•boundary ({ 'constant', 'symmetric'}, optional) - Determines how the image is padded.

•crop_filter (*bool*, optional) – If True, the shape of the MOSSE filter is the same as the shape of the desired response. If False, the filter's shape is equal to: X[0].shape + y.shape - 1

Returns

•f ((1, response_h, response_w) *ndarray*) – Multi-Channel Correlation Filter (MCCF) filter associated to the training images.

•sXY ((N,) ndarray) The auto-correlation arrav. where N = _ (image_h+response_h-1) * (image_w+response_w-1) * n_channels. •**sXX** ((N, N) *ndarray*) – The cross-correlation array, where N = (image_h+response_h-1) * (image_w+response_w-1) * n_channels.

References

imccf

```
menpofit.math.imccf(A, B, n_ab, X, y, l=0.01, boundary='constant', crop_filter=True, f=1.0)
Incremental Multi-Channel Correlation Filter (MCCF)
```

Parameters

•A ((N,) ndarray) - The current auto-correlation array, where N = (patch_h+response_h-1) * (patch_w+response_w-1) * n_channels.
•B ((N, N) ndarray) - The current cross-correlation array, where N = (patch_h+response_h-1) * (patch_w+response_w-1) * n_channels.

•n_ab (*int*) – The current number of images.

•X((n_images, n_channels, image_h, image_w) *ndarray*) – The training images (patches).

•y((1, response_h, response_w) *ndarray*) – The desired response.

•1 (float, optional) – Regularization parameter.

•boundary ({ 'constant', 'symmetric'}, optional) - Determines how the image is padded.

•crop_filter (*bool*, optional) – If True, the shape of the MOSSE filter is the same as the shape of the desired response. If False, the filter's shape is equal to: X[0].shape + y.shape - 1

•**f** ([0, 1] *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples. If 1.0, all samples are weighted equally. If <1.0, more emphasis is put on the new samples.

Returns

•**f** ((1, response_h, response_w) *ndarray*) – Multi-Channel Correlation Filter (MCCF) filter associated to the training images.

```
•sXY
              ndarray)
                            The
                                  auto-correlation
      ((N,)
                                                 array,
                                                         where
                                                                 N =
(image_h+response_h-1) * (image_w+response_w-1) * n_channels.
                             The cross-correlation
•sXX
     ((N, N)
                ndarray) –
                                                  array,
                                                         where
                                                               N =
(image_h+response_h-1) * (image_w+response_w-1) * n_channels.
```

References

mosse

```
menpofit.math.mosse(X, y, l=0.01, boundary='constant', crop_filter=True)
Minimum Output Sum of Squared Errors (MOSSE) filter.
```

Parameters

•X ((n_images, n_channels, image_h, image_w) ndarray) - The training images.
•Y ((1, response_h, response_w) ndarray) - The desired response.
•1 (float, optional) - Regularization parameter.

•boundary ({ 'constant', 'symmetric'}, optional) - Determines how the image is padded.

•crop_filter (*bool*, optional) – If True, the shape of the MOSSE filter is the same as the shape of the desired response. If False, the filter's shape is equal to: X[0].shape + y.shape - 1

Returns

•f ((1, response_h, response_w) *ndarray*) – Minimum Output Sum od Squared Errors (MOSSE) filter associated to the training images.

```
•sXY
      ((N,)
              ndarray)
                       _
                            The
                                  auto-correlation
                                                array,
                                                        where
                                                                N =
(image_h+response_h-1) * (image_w+response_w-1) * n_channels.
•sXX
                ndarray)
                        – The cross-correlation array,
     ((N, N)
                                                        where
                                                                N =
(image_h+response_h-1) * (image_w+response_w-1) * n_channels.
```

References

imosse

```
menpofit.math.imosse (A, B, n_ab, X, y, l=0.01, boundary='constant', crop_filter=True, f=1.0)
Incremental Minimum Output Sum of Squared Errors (iMOSSE) filter.
```

Parameters

- •A ((N,) *ndarray*) The current auto-correlation array, where N = (patch_h+response_h-1) * (patch_w+response_w-1) * n_channels.
- •B ((N, N) *ndarray*) The current cross-correlation array, where N = (patch_h+response_h-1) * (patch_w+response_w-1) * n_channels.

•n_ab (*int*) – The current number of images.

- •X((n_images, n_channels, image_h, image_w) *ndarray*) The training images (patches).
- •y((1, response_h, response_w) *ndarray*) The desired response.
- •1 (float, optional) Regularization parameter.
- •boundary ({ 'constant', 'symmetric'}, optional) Determines how the image is padded.
- •crop_filter (*bool*, optional) If True, the shape of the MOSSE filter is the same as the shape of the desired response. If False, the filter's shape is equal to: X[0].shape + y.shape 1
- •**f** ([0, 1] *float*, optional) Forgetting factor that weights the relative contribution of new samples vs old samples. If 1.0, all samples are weighted equally. If <1.0, more emphasis is put on the new samples.

Returns

- •**f** ((1, response_h, response_w) *ndarray*) Minimum Output Sum od Squared Errors (MOSSE) filter associated to the training images.
- •**sXY** ((N,) *ndarray*) The auto-correlation array, where N = (image_h+response_h-1) * (image_w+response_w-1) * n_channels.

•**sXX** ((N, N) *ndarray*) - The cross-correlation array, where N = (image_h+response_h-1) * (image_w+response_w-1) * n_channels.

References

menpofit.modelinstance

Abstract Classes

ModelInstance

```
class menpofit.modelinstance.ModelInstance(model)
```

Bases: Targetable, Vectorizable, DP

Base class for creating a model that can produce a target *menpo.shape.PointCloud* and knows how to compute its own derivative with respect to its parametrisation.

Parametersmodel (*class*) – The trained model (e.g. *menpo.model.PCAModel*).

as_vector(**kwargs)

Returns a flattened representation of the object as a single vector.

Returnsvector ((N, ndarray) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other **Copyable** objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returnstype(self) – A copy of this object

d_dp (points)

The derivative of this spatial object with respect to the parametrisation changes evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dp((n_points, n_parameters, n_dims) *ndarray*) – The Jacobian with respect to the parametrisation.

 $d_dp[i, j, k]$ is the scalar differential change that the k'th dimension of the i'th point experiences due to a first order change in the j'th scalar in the parametrisation vector.

from_vector (vector)

Build a new instance of the object from it's vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returnsobject (type (self)) – An new instance of this class.

from_vector_inplace(vector)

Deprecated. Use the non-mutating API, from_vector.

For internal usage in performance-sensitive spots, see _from_vector_inplace()

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of this object

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returnshas_nan_values (bool) – If the vectorized object contains nan values.

set_target (new_target)

Update this object so that it attempts to recreate the new_target.

Parametersnew_target (**PointCloud**) – The new target that this object should try and regenerate.

n_dims

The number of dimensions of the *target*.

Type*int*

n_parameters

The length of the vector that this object produces.

Type*int*

n_points

The number of points on the *target*.

Type*int*

n_weights

The number of parameters in the linear model.

Type*int*

target

The current menpo.shape.PointCloud that this object produces.

Typemenpo.shape.PointCloud

weights

The weights of the model.

Type(n_weights,) ndarray

Similarity Model

similarity_2d_instance_model

menpofit.modelinstance.similarity_2d_instance_model(shape)

Creates a *menpo.model.MeanLinearModel* that encodes the 2D similarity transforms that can be applied on a 2D shape that consists of *n_points*.

Parametersshape (*menpo.shape.PointCloud*) – The input 2D shape.

Returnsmodel (*subclass* of *menpo.model.MeanLinearModel*) – Linear model with four components, the linear combinations of which represent the original shape under a similarity transform. The model is exhaustive (that is, all possible similarity transforms can be expressed with the model).

GlobalSimilarityModel

```
class menpofit.modelinstance.GlobalSimilarityModel(data, **kwargs)
Bases: Targetable, Vectorizable
```

Class for creating a model that represents a global similarity transform (in-plane rotation, scaling, translation).

Parametersdata (list of menpo.shape.PointCloud) - The list of shapes to use as training data.

as_vector(**kwargs)

Returns a flattened representation of the object as a single vector.

Returnsvector $((N_i) ndarray)$ – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other **Copyable** objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returnstype(self) - A copy of this object

$d_dp\left(_\right)$

Returns the Jacobian of the similarity model reshaped in order to have the standard Jacobian shape, i.e. (n_points, n_weights, n_dims) which maps to (n_features, n_components, n_dims) on the linear model.

Returnsjacobian ((n_features, n_components, n_dims) *ndarray*) – The Jacobian of the model in the standard Jacobian shape.

from_vector(vector)

Build a new instance of the object from it's vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returnsobject (type(self)) – An new instance of this class.

from_vector_inplace(vector)

Deprecated. Use the non-mutating API, from_vector.

For internal usage in performance-sensitive spots, see _from_vector_inplace()

Parametersvector ((n_parameters,) ndarray) - Flattened representation of this object

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returnshas_nan_values (*bool*) – If the vectorized object contains nan values.

set_target (new_target)

Update this object so that it attempts to recreate the new_target.

Parametersnew_target (*menpo.shape.PointCloud*) – The new target that this object should try and regenerate.

n_dims

The number of dimensions of the spatial instance of the model.

Typeint

n_parameters

The length of the vector that this object produces.

Type*int*

n_points

The number of points on the *target*.

Type*int*

n_weights

The number of parameters in the linear model.

Type*int*

target

The current menpo.shape.PointCloud that this object produces.

Typemenpo.shape.PointCloud

weights

The weights of the model.

Type(n_weights,) ndarray

Point Distribution Model

PDM

class menpofit.modelinstance.PDM(data, max_n_components=None)
Bases: ModelInstance

Class for building a Point Distribution Model. It is a specialised version of *ModelInstance* for use with spatial data.

Parameters

•data (*list* of *menpo.shape.PointCloud* or *menpo.model.PCAModel* instance) – If a *list* of *menpo.shape.PointCloud*, then a *menpo.model.PCAModel* will be trained from those training shapes. Otherwise, a trained *menpo.model.PCAModel* instance can be provided.

•max_n_components (*int* or None, optional) – The maximum number of components that the model will keep. If None, then all the components will be kept.

as_vector(**kwargs)

Returns a flattened representation of the object as a single vector.

Returnsvector $((N_i) ndarray)$ – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other **Copyable** objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returnstype (self) - A copy of this object

d_dp (points)

Returns the Jacobian of the similarity model reshaped in order to have the standard Jacobian shape, i.e. (n_points, n_weights, n_dims) which maps to (n_features, n_components, n_dims) on the linear model.

Returnsjacobian ((n_features, n_components, n_dims) *ndarray*) – The Jacobian of the model in the standard Jacobian shape.

from_vector (vector)

Build a new instance of the object from it's vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returnsobject (type(self)) – An new instance of this class.

from_vector_inplace(vector)

Deprecated. Use the non-mutating API, from_vector.

For internal usage in performance-sensitive spots, see _from_vector_inplace()

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of this object

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returnshas_nan_values (bool) – If the vectorized object contains nan values.

increment (shapes, n_shapes=None, forgetting_factor=1.0, max_n_components=None, ver-

bose=False)

Update the eigenvectors, eigenvalues and mean vector of this model by performing incremental PCA on the given samples.

Parameters

•shapes (list of menpo.shape.PointCloud) - List of new shapes to update the model from.

•**n_shapes** (*int* or None, optional) – If *int*, then *shapes* must be an iterator that yields n_shapes . If None, then *shapes* has to be a list (so we know how large the data matrix needs to be).

•forgetting_factor ([0.0, 1.0] *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples. If 1.0, all samples are weighted equally and, hence, the results is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples. See [1] for details.

•max_n_components (*int* or None, optional) – The maximum number of components that the model will keep. If None, then all the components will be kept.

•verbose (bool, optional) – If True, then information about the progress will be printed.

References

set_target (new_target)

Update this object so that it attempts to recreate the new_target.

Parametersnew_target (**PointCloud**) – The new target that this object should try and regenerate.

n_active_components

The number of components currently in use on this model.

Type*int*

n_dims

The number of dimensions of the spatial instance of the model

Type*int*

n_parameters

The length of the vector that this object produces.

Type*int*

n_points

The number of points on the *target*.

Type*int*

n_weights

The number of parameters in the linear model.

Type*int*

target

The current menpo.shape.PointCloud that this object produces.

Typemenpo.shape.PointCloud

weights

The weights of the model.

Type(n_weights,) ndarray

GlobalPDM

class menpofit.modelinstance.GlobalPDM (data,

global_transform_cls,

Bases: PDM

Class for building a Point Distribution Model that also stores a Global Alignment transform. The final transform couples the Global Alignment transform to a statistical linear model, so that its weights are fully specified by both the weights of statistical model and the weights of the similarity transform.

Parameters

•data (*list* of *menpo.shape.PointCloud* or *menpo.model.PCAModel* instance) – If a *list* of *menpo.shape.PointCloud*, then a *menpo.model.PCAModel* will be trained from those training shapes. Otherwise, a trained *menpo.model.PCAModel* instance can be provided.

max n components=None)

•global_transform_cls (*class*) - The Global Similarity transform class (e.g. DifferentiableAlignmentSimilarity).

•max_n_components (*int* or None, optional) – The maximum number of components that the model will keep. If None, then all the components will be kept.

as_vector(**kwargs)

Returns a flattened representation of the object as a single vector.

Returnsvector ((N,) ndarray) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other **Copyable** objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returnstype (self) - A copy of this object

d_dp (points)

The derivative with respect to the parametrisation changes evaluated at points.

- **Parameterspoints** ((n_points, n_dims) *ndarray*) The spatial points at which the derivative should be evaluated.
- **Returnsd_dp**((n_points, n_parameters, n_dims) *ndarray*) The Jacobian with respect to the parametrisation.

from_vector (vector)

Build a new instance of the object from it's vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returnsobject (type (self)) – An new instance of this class.

from_vector_inplace(vector)

Deprecated. Use the non-mutating API, from_vector.

For internal usage in performance-sensitive spots, see _from_vector_inplace()

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of this object

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returnshas_nan_values (*bool*) – If the vectorized object contains nan values.

increment (shapes, n_shapes=None, forgetting_factor=1.0, max_n_components=None, ver-

bose=False)

Update the eigenvectors, eigenvalues and mean vector of this model by performing incremental PCA on the given samples.

Parameters

•shapes (list of menpo.shape.PointCloud) – List of new shapes to update the model from.

•**n_shapes** (*int* or None, optional) – If *int*, then *shapes* must be an iterator that yields *n_shapes*. If None, then *shapes* has to be a list (so we know how large the data matrix needs to be).

•forgetting_factor ([0.0, 1.0] *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples. If 1.0, all samples are weighted equally and, hence, the results is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples. See [1] for details.

•max_n_components (*int* or None, optional) – The maximum number of components that the model will keep. If None, then all the components will be kept.

•verbose (bool, optional) – If True, then information about the progress will be printed.

References

set_target (new_target)

Update this object so that it attempts to recreate the new_target.

Parametersnew_target (**PointCloud**) – The new target that this object should try and regenerate.

global_parameters

The parameters for the global transform.

Type"(n_global_parameters,) *ndarray*

n_active_components

The number of components currently in use on this model.

Type*int*

n_dims

The number of dimensions of the spatial instance of the model

Type*int*

n_global_parameters

The number of parameters in the global_transform

Type*int*

n_parameters

The length of the vector that this object produces.

Type*int*

n_points

The number of points on the *target*.

Type*int*

n_weights

The number of parameters in the linear model.

Type*int*

target

The current *menpo.shape.PointCloud* that this object produces.

Typemenpo.shape.PointCloud

weights

The weights of the model.

Type(n_weights,) ndarray

OrthoPDM

```
class menpofit.modelinstance.OrthoPDM(data, max_n_components=None)
    Bases: GlobalPDM
```

Class for building a Point Distribution Model that also stores a Global Alignment transform. The final transform couples the Global Alignment transform to a statistical linear model, so that its weights are fully specified by both the weights of statistical model and the weights of the similarity transform.

This transform (in contrast to the :map'GlobalPDM') additionally orthonormalises both the global and the model basis against each other, ensuring that orthogonality and normalization is enforced across the unified bases.

Parameters

•data (list of menpo.shape.PointCloud or menpo.model.PCAModel instance) – If a list of menpo.shape.PointCloud, then a menpo.model.PCAModel will be trained from those training shapes. Otherwise, a trained menpo.model.PCAModel instance can be provided.

•max_n_components (*int* or None, optional) – The maximum number of components that the model will keep. If None, then all the components will be kept.

as_vector(**kwargs)

Returns a flattened representation of the object as a single vector.

Returnsvector $((N_i) ndarray)$ – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other **Copyable** objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returnstype(self) – A copy of this object

d_dp (points)

The derivative with respect to the parametrisation changes evaluated at points.

- **Parameterspoints** ((n_points, n_dims) *ndarray*) The spatial points at which the derivative should be evaluated.
- **Returnsd_dp**((n_points, n_parameters, n_dims) *ndarray*) The Jacobian with respect to the parametrisation.

from_vector(vector)

Build a new instance of the object from it's vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returnsobject (type(self)) – An new instance of this class.

from_vector_inplace(vector)

Deprecated. Use the non-mutating API, from_vector.

For internal usage in performance-sensitive spots, see _from_vector_inplace()

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of this object

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returnshas_nan_values (*bool*) – If the vectorized object contains nan values.

increment (shapes, n_shapes=None, forgetting_factor=1.0, max_n_components=None, verbose=False)

Update the eigenvectors, eigenvalues and mean vector of this model by performing incremental PCA on the given samples.

Parameters

•shapes (*list* of *menpo.shape.PointCloud*) – List of new shapes to update the model from.

•**n_shapes** (*int* or None, optional) – If *int*, then *shapes* must be an iterator that yields n_{shapes} . If None, then *shapes* has to be a list (so we know how large the data matrix needs to be).

•forgetting_factor ([0.0, 1.0] *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples. If 1.0, all samples are weighted equally and, hence, the results is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples. See [1] for details.

•max_n_components (*int* or None, optional) – The maximum number of components that the model will keep. If None, then all the components will be kept.

•verbose (bool, optional) – If True, then information about the progress will be printed.

```
References
```

set_target (new_target)

Update this object so that it attempts to recreate the new_target.

Parametersnew_target (**PointCloud**) – The new target that this object should try and regenerate.

global_parameters

The parameters for the global transform.

Type(n_global_parameters,) ndarray

n_active_components

The number of components currently in use on this model.

Type*int*

n_dims

The number of dimensions of the spatial instance of the model

Type*int*

n_global_parameters

The number of parameters in the global_transform

Typeint

n_parameters

The length of the vector that this object produces.

Type*int*

n_points

The number of points on the *target*.

Type*int*

n_weights

The number of parameters in the linear model.

Type*int*

target

The current menpo.shape.PointCloud that this object produces.

Typemenpo.shape.PointCloud

weights

The weights of the model.

Type(n_weights,) ndarray

menpofit.result

Basic Result

Class for defining a basic fitting result.

Result

```
class menpofit.result.Result (final_shape, image=None, initial_shape=None, gt_shape=None)
Bases: object
```

Class for defining a basic fitting result. It holds the final shape of a fitting process and, optionally, the initial shape, ground truth shape and the image object.

Parameters

•final_shape (menpo.shape.PointCloud) – The final shape of the fitting process.

•**image** (*menpo.image.Image* or *subclass* or None, optional) – The image on which the fitting process was applied. Note that a copy of the image will be assigned as an attribute. If None, then no image is assigned.

•initial_shape (*menpo.shape.PointCloud* or None, optional) – The initial shape that was provided to the fitting method to initialise the fitting process. If None, then no initial shape is assigned.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated with the image. If None, then no ground truth shape is assigned.

final_error(compute_error=None)

Returns the final error of the fitting process, if the ground truth shape exists. This is the error computed based on the *final_shape*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the fitted and ground truth shapes.
- **Returnsfinal_error** (*float*) The final error at the end of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

initial_error(compute_error=None)

Returns the initial error of the fitting process, if the ground truth shape and initial shape exist. This is the error computed based on the *initial_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the initial and ground truth shapes.

Returnsinitial_error (*float*) – The initial error at the beginning of the fitting process.

Raises

•ValueError – Initial shape has not been set, so the initial error cannot be computed

•ValueError – Ground truth shape has not been set, so the initial error cannot be computed

view (*figure_id=None*, *new_figure=False*, render_image=True, render_final_shape=True, render_initial_shape=False, render_gt_shape=False, *subplots_enabled=True*, chan*nels=None, interpolation='bilinear', cmap_name=None,* alpha=1.0, masked=True, final_marker_face_colour='r', final_marker_edge_colour='k', final_line_colour='r', initial_marker_face_colour='b', *initial_marker_edge_colour='k'*, initial line colour='b'. gt_marker_face_colour='y', gt_marker_edge_colour='k', gt_line_colour='y', renline_width=2, render_markers=True, marker_style='o', der_lines=True, line_style='-', marker_size=4, marker_edge_width=1.0, render_numbering=False, numbers horizontal align='center', numbers vertical align='bottom', numbers font name='sansserif', numbers_font_size=10, numbers_font_style='normal', numbers_font_weight='normal', numbers_font_colour='k', render_legend=True, legend_title='', legend_font_name='sanslegend_font_style='normal', legend_font_size=10, legend_font_weight='normal', serif', legend_marker_scale=None, legend_location=2, legend_bbox_to_anchor=(1.05, 1.0), legend border axes pad=None, legend n columns=1, legend horizontal spacing=None, *legend vertical spacing=None*, legend_border=True, legend_border_padding=None, legend shadow=False, legend rounded corners=False, render axes=False, axes font name='sansserif', axes font size=10, axes_font_style='normal', axes_font_weight='normal', axes_x_limits=None, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, fig $ure_size=(7, 7)$)

Visualize the fitting result. The method renders the final fitted shape and optionally the initial shape, ground truth shape and the image, id they were provided.

Parameters

- •figure_id (*object*, optional) The id of the figure to be used.
- •new_figure (*bool*, optional) If True, a new figure is created.
- •render_image (bool, optional) If True and the image exists, then it gets rendered.
- •render_final_shape (*bool*, optional) If True, then the final fitting shape gets rendered.

•render_initial_shape (*bool*, optional) – If True and the initial fitting shape exists, then it gets rendered.

•**render_gt_shape** (*bool*, optional) – If True and the ground truth shape exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

•channels (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (See Below, optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•final_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_marker_edge_colour (See Below, optional) – The edge colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_line_colour (See Below, optional) – The line colour of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_edge_colour (See Below, optional) – The edge colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_line_colour (See Below, optional) – The line colour of the initial shape. Example options

{r, g, b, c, m, k, w}
or
(3,) ndarray

•gt_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_edge_colour (See Below, optional) – The edge colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_line_colour (See Below, optional) – The line colour of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_lines (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•line_style (*str* or *list* of *str*, optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{'-', '--', '-.', ':'}

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.
- •**render_markers** (*bool* or *list* of *bool*, optional) If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.
- •marker_style (*str* or *list* of *str*, optional) The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order.

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•render_numbering (bool, optional) - If True, the landmarks will be numbered.

•numbers_horizontal_align ({center, right, left}, optional) - The horizontal alignment of the numbers' texts.

•numbers_vertical_align ({center, top, bottom, baseline}, optional) – The vertical alignment of the numbers' texts.

•numbers_font_name (See Below, optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (See Below, optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) - If True, the legend will be rendered.

•legend_title (str, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style ({normal, italic, oblique}, optional) - The font style of the legend.

•legend_font_size (int, optional) – The font size of the legend.

•legend_font_weight (See Below, optional) – The font weight of the legend. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
ʻright'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- •legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) The bbox that the legend will be anchored.
- •legend_border_axes_pad (*float*, optional) The pad between the axes and legend border.
- •legend_n_columns (*int*, optional) The number of the legend's columns.
- •legend_horizontal_spacing (*float*, optional) The spacing between the columns.
- •legend_vertical_spacing (*float*, optional) The vertical space between the legend entries.
- •legend_border (bool, optional) If True, a frame will be drawn around the legend.
- •legend_border_padding (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.
- •legend_rounded_corners (*bool*, optional) If True, the frame's corners will be rounded (fancybox).
- •render_axes (bool, optional) If True, the axes will be rendered.
- •axes_font_name (See Below, optional) The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

- •axes_font_size (*int*, optional) The font size of the axes.
- •axes_font_style ({normal, italic, oblique}, optional) The font style of the axes.
- •axes_font_weight (See Below, optional) The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (*class*) – The renderer object.

view_widget (figure_size=(7, 7))

Visualizes the result object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

final_shape

Returns the final shape of the fitting process.

Typemenpo.shape.PointCloud

gt_shape

Returns the ground truth shape associated with the image. In case there is not an attached ground truth shape, then None is returned.

Typemenpo.shape.PointCloud or None

image

Returns the image that the fitting was applied on, if it was provided. Otherwise, it returns None.

Typemenpo.shape.Image or subclass or None

initial_shape

Returns the initial shape that was provided to the fitting method to initialise the fitting process. In case the initial shape does not exist, then None is returned.

Typemenpo.shape.PointCloud or None

is_iterative

Flag whether the object is an iterative fitting result.

Typebool

Iterative Result

Classes for defining an iterative fitting result.

NonParametricIterativeResult

class menpofit.result.NonParametricIterativeResult	(shapes,	initial_shape=None,
	image=None,	gt_shape=None,
	costs=None)	

Bases: Result

Class for defining a non-parametric iterative fitting result, i.e. the result of a method that does not optimize over a parametric shape model. It holds the shapes of all the iterations of the fitting procedure. It can optionally store the image on which the fitting was applied, as well as its ground truth shape.

Parameters

- •**shapes** (*list* of *menpo.shape.PointCloud*) The *list* of shapes per iteration. Note that the list does not include the initial shape. The last member of the list is the final shape.
- •initial_shape (*menpo.shape.PointCloud* or None, optional) The initial shape from which the fitting process started. If None, then no initial shape is assigned.
- •**image** (*menpo.image.Image* or *subclass* or None, optional) The image on which the fitting process was applied. Note that a copy of the image will be assigned as an attribute. If None, then no image is assigned.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated with the image. If None, then no ground truth shape is assigned.
- •costs (*list* of *float* or None, optional) The *list* of cost per iteration. If None, then it is assumed that the cost function cannot be computed for the specific algorithm. It must have the same length as *shapes*.

displacements()

A list containing the displacement between the shape of each iteration and the shape of the previous one.

Typelist of ndarray

displacements_stats (stat_type='mean')

A list containing a statistical metric on the displacements between the shape of each iteration and the shape of the previous one.

- **Parametersstat_type** ({'mean', 'median', 'min', 'max'}, optional) Specifies a statistic metric to be extracted from the displacements.
- **Returnsdisplacements_stat** (*list* of *float*) The statistical metric on the points displacements for each iteration.

RaisesValueError - type must be 'mean', 'median', 'min' or 'max'

errors (*compute_error=None*)

Returns a list containing the error at each fitting iteration, if the ground truth shape exists.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

Returnserrors (*list* of *float*) – The error at each iteration of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

final_error(compute_error=None)

Returns the final error of the fitting process, if the ground truth shape exists. This is the error computed based on the *final_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the fitted and ground truth shapes.

Returnsfinal_error (float) – The final error at the end of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

initial_error(compute_error=None)

Returns the initial error of the fitting process, if the ground truth shape and initial shape exist. This is the error computed based on the *initial_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the initial and ground truth shapes.

Returnsinitial_error (*float*) – The initial error at the beginning of the fitting process.

Raises

- •ValueError Initial shape has not been set, so the initial error cannot be computed
- •ValueError Ground truth shape has not been set, so the initial error cannot be computed

plot_costs (figure_id=None, new_figure=False, render_lines=True, line_colour='b', line_style='', line_width=2, render_markers=True, marker_style='o', marker_size=4,
marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0,
render_axes=True, axes_font_name='sans-serif', axes_font_size=10,
axes_font_style='normal', axes_font_weight='normal', axes_x_limits=0.0,
axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6),
render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the cost function evolution at each fitting iteration.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None, optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•line_style ({ '-', '--', '-.', ':'}, optional) – The style of the lines.

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (marker, optional) – The style of the markers. Example marker options

{'.', ',', 'o', 'v', '^', '<', '>', '+', 'x', 'D', 'd', 's', 'p', '*', 'h', 'H', '1', '2', '3', '4', '8'}

•marker_size (*int*, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker edge width (*float*, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (See below, optional) - The font of the axes. Example options

{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({'normal', 'italic', 'oblique'}, optional) - The font style of the axes.

•axes_font_weight (See below, optional) - The font weight of the axes. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
    'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
    'extra bold', 'black'}
```

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

Plot of a statistical metric of the displacement between the shape of each iteration and the shape of the previous one.

Parameters

•**stat_type** ({mean, median, min, max}, optional) – Specifies a statistic metric to be extracted from the displacements (see also *displacements_stats()* method).

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (*bool*, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

{r, g, b, c, m, k, w}
or
(3,) ndarray

•line_style (*str* (See below), optional) – The style of the lines. Example options:

```
{-, --, -., :}
```

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) - The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

•axes_font_size (int, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

plot_errors (compute_error=None, figure_id=None, new_figure=False, render lines=True, *line_colour='b'*, *line_style='-'*, *line_width=2*, render_markers=True, marker_style='o', marker_size=4, marker_face_colour='b', marker_edge_colour='k', marker edge width=1.0, render axes=True, axes font name='sans-serif'. axes_font_size=10, axes_font_style='normal', axes_font_weight='normal', axes x limits=0.0, axes y limits=None, axes x ticks=None, axes y ticks=None, figure_size=(10, 6), render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the error evolution at each fitting iteration.

Parameters

•compute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

{-, --, -., :}

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int*, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float*, optional) – The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (int, optional) – The font size of the axes.

•axes_font_style (*str* (See below), optional) – The font style of the axes. Example options

```
{normal, italic, oblique}
```

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

to_result (pass_image=True, pass_initial_shape=True, pass_gt_shape=True)

Returns a *Result* instance of the object, i.e. a fitting result object that does not store the iterations. This can be useful for reducing the size of saved fitting results.

Parameters

•pass_image (bool, optional) – If True, then the image will get passed (if it exists).

•**pass_initial_shape** (*bool*, optional) – If True, then the initial shape will get passed (if it exists).

•**pass_gt_shape** (*bool*, optional) – If True, then the ground truth shape will get passed (if it exists).

Returnsresult (*Result*) – The final "lightweight" fitting result.

view (figure id=None, new figure=False, render image=True, render final shape=True, render initial shape=False, render_gt_shape=False, subplots enabled=True, channels=None, interpolation='bilinear', cmap name=None, alpha=1.0, masked=True, final marker face colour='r', final marker edge colour='k', final line colour='r', initial marker face colour='b', initial marker edge colour='k', initial line colour='b', gt_marker_edge_colour='k', gt_marker_face_colour='y', gt_line_colour='y', render_lines=True, line_style='-', line_width=2, render_markers=True, marker_style='o', marker_size=4, marker_edge_width=1.0, render_numbering=False, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers_font_name='sansserif', numbers_font_size=10, numbers_font_style='normal', numbers_font_weight='normal', numbers_font_colour='k', render_legend=True, legend_title='', legend_font_name='sansserif', *legend_font_style='normal', legend_font_size=10,* legend_font_weight='normal', legend_marker_scale=None, legend_location=2, legend_bbox_to_anchor=(1.05, 1.0), legend border axes pad=None, legend n columns=1, legend horizontal spacing=None, *legend vertical spacing=None*, legend border=True, legend border padding=None, legend shadow=False, legend rounded corners=False, render axes=False, axes font name='sansserif', axes_font_size=10, axes_font_style='normal', axes_font_weight='normal', axes x limits=None, axes y limits=None, axes x ticks=None, fig $ure_size = (7, 7)$

Visualize the fitting result. The method renders the final fitted shape and optionally the initial shape, ground truth shape and the image, id they were provided.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

- •render_final_shape (*bool*, optional) If True, then the final fitting shape gets rendered.
- •render_initial_shape (*bool*, optional) If True and the initial fitting shape exists, then it gets rendered.
- •render_gt_shape (*bool*, optional) If True and the ground truth shape exists, then it gets rendered.
- •**subplots_enabled** (*bool*, optional) If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.
- •channels (*int* or *list* of *int* or all or None) If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (See Below, optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•final_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_marker_edge_colour (See Below, optional) – The edge colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_line_colour (See Below, optional) – The line colour of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_edge_colour (See Below, optional) – The edge colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_line_colour (See Below, optional) – The line colour of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_edge_colour (See Below, optional) – The edge colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_line_colour (See Below, optional) – The line colour of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•**render_lines** (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•line_style (*str* or *list* of *str*, optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{'-', '--', '-.', ':'}

•line_width (*float* or *list* of *float*, optional) – The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•marker_style (str or list of str, optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order.

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align ({center, right, left}, optional) - The horizontal alignment of the numbers' texts.

•numbers_vertical_align ({center, top, bottom, baseline}, optional) – The vertical alignment of the numbers' texts.

•numbers_font_name (See Below, optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (See Below, optional) – The font weight of the numbers. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) – If True, the legend will be rendered.

•legend_title (str, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style ({normal, italic, oblique}, optional) - The font style of the legend.

- •legend_font_size (int, optional) The font size of the legend.
- •legend_font_weight (See Below, optional) The font weight of the legend. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
ʻright'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (*int*, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

•legend_border (bool, optional) – If True, a frame will be drawn around the legend.

•legend_border_padding (*float*, optional) – The fractional whitespace inside the legend border.

•legend_shadow (bool, optional) - If True, a shadow will be drawn behind legend.

•legend_rounded_corners (*bool*, optional) – If True, the frame's corners will be rounded (fancybox).

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (See Below, optional) - The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (See Below, optional) - The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) – The renderer object.

view iterations (figure id=None, new figure=False, iters=None, render image=True, subplots_enabled=False, channels=None. interpolation='bilinear', cmap name=None, alpha=1.0, masked=True. render lines=True, *line_style='-'*, *line_width=2*, line_colour=None, render_markers=True, marker edge colour=None, marker face colour=None, marker_style='o', marker_size=4. marker_edge_width=1.0, render numbering=False, numbers_horizontal_align='center'. numbers vertical align='bottom', numbers font name='sans-serif', numbers font size=10, numbers font style='normal', numbers font weight='normal', numrender_legend=True, *bers_font_colour='k'*, legend_title='', legend_font_name='sans-serif', legend_font_style='normal', legend_font_size=10, legend_font_weight='normal', legend_marker_scale=None, *legend location=2*, legend_bbox_to_anchor=(1.05, 1.0). leg*legend_n_columns=1*, end_border_axes_pad=None, legend_horizontal_spacing=None, *legend_vertical_spacing=None*, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sans-serif', axes font size=10, axes font style='normal', axes font weight='normal'. axes_x_limits=None, axes_y_limits=None, axes x ticks=None, axes y ticks=None, figure size=(7, 7))

Visualize the iterations of the fitting process.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•iters (*int* or *list* of *int* or None, optional) – The iterations to be visualized. If None, then all the iterations are rendered.

No.	Visualised shape	Description
0	self.initial_shape	Initial shape
1	self.shapes[1]	Iteration 1
i	self.shapes[i]	Iteration i
n_iters	self.final_shape	Final shape

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

•channels (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (*str* (See Below), optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

{none, nearest, bilinear, bicubic, spline16, spline36, hanning, hamming, hermite, kaiser, quadric, catrom, gaussian, bessel, mitchell, sinc, lanczos}

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

- •render_lines (*bool* or *list* of *bool*, optional) If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_style (*str* or *list* of *str* (See below), optional) The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options:

```
\{-, --, -., :\}
```

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_colour (*colour* or *list* of *colour* (See Below), optional) The colour of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_style (*str or 'list* of *str* (See below), optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_edge_colour (colour or list of colour (See Below), optional) – The edge colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_face_colour (*colour* or *list* of *colour* (See Below), optional) – The face (filling) colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.
•numbers_horizontal_align (*str* (See below), optional) – The horizontal alignment of the numbers' texts. Example options

{center, right, left}

•numbers_vertical_align (*str* (See below), optional) – The vertical alignment of the numbers' texts. Example options

{center, top, bottom, baseline}

•numbers_font_name (*str* (See below), optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (*str* (See below), optional) – The font weight of the numbers. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style (*str* (See below), optional) – The font style of the legend. Example options

{normal, italic, oblique}

•legend_font_size (int, optional) – The font size of the legend.

•legend_font_weight (*str* (See below), optional) – The font weight of the legend. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- •legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) The bbox that the legend will be anchored.
- •legend_border_axes_pad (*float*, optional) The pad between the axes and legend border.
- •legend_n_columns (*int*, optional) The number of the legend's columns.
- •legend_horizontal_spacing (*float*, optional) The spacing between the columns.
- •legend_vertical_spacing (*float*, optional) The vertical space between the legend entries.
- •legend_border (bool, optional) If True, a frame will be drawn around the legend.
- **legend_border_padding** (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.
- •legend_rounded_corners (*bool*, optional) If True, the frame's corners will be rounded (fancybox).
- •render_axes (bool, optional) If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (*list* or *tuple* or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) – The renderer object.

view_widget (figure_size=(7, 7))

Visualizes the result object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

costs

Returns a *list* with the cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

final_shape

Returns the final shape of the fitting process.

Typemenpo.shape.PointCloud

gt_shape

Returns the ground truth shape associated with the image. In case there is not an attached ground truth shape, then None is returned.

Typemenpo.shape.PointCloud or None

image

Returns the image that the fitting was applied on, if it was provided. Otherwise, it returns None.

Typemenpo.shape.Image or subclass or None

initial_shape

Returns the initial shape that was provided to the fitting method to initialise the fitting process. In case the initial shape does not exist, then None is returned.

Typemenpo.shape.PointCloud or None

is_iterative

Flag whether the object is an iterative fitting result.

Typebool

n_iters

Returns the total number of iterations of the fitting process.

Type*int*

shapes

Returns the *list* of shapes obtained at each iteration of the fitting process. The *list* includes the *initial_shape* (if it exists) and *final_shape*.

Typelist of menpo.shape.PointCloud

ParametricIterativeResult

class menpofit.result.ParametricIterativeResult	(shapes,	shape_parame	ters, ini
	tial_shape=1	None,	image=None
	gt_shape=Ne	one, costs=Non	e)

Bases: NonParametricIterativeResult

Class for defining a parametric iterative fitting result, i.e. the result of a method that optimizes the parameters of a shape model. It holds the shapes and shape parameters of all the iterations of the fitting procedure. It can optionally store the image on which the fitting was applied, as well as its ground truth shape.

Note: When using a method with a parametric shape model, the first step is to **reconstruct the initial shape** using the shape model. The generated reconstructed shape is then used as initialisation for the iterative optimisation. This step is not counted in the number of iterations.

Parameters

- •**shapes** (*list* of *menpo.shape.PointCloud*) The *list* of shapes per iteration. Note that the list does not include the initial shape. However, it includes the reconstruction of the initial shape. The last member of the list is the final shape.
- •**shape_parameters** (*list* of *ndarray*) The *list* of shape parameters per iteration. Note that the list includes the parameters of the projection of the initial shape. The last member of the list corresponds to the final shape's parameters. It must have the same length as *shapes*.
- •initial_shape (*menpo.shape.PointCloud* or None, optional) The initial shape from which the fitting process started. If None, then no initial shape is assigned.
- •**image** (*menpo.image.Image* or *subclass* or None, optional) The image on which the fitting process was applied. Note that a copy of the image will be assigned as an attribute. If None, then no image is assigned.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated with the image. If None, then no ground truth shape is assigned.
- •costs (*list* of *float* or None, optional) The *list* of cost per iteration. If None, then it is assumed that the cost function cannot be computed for the specific algorithm. It must have the same length as *shapes*.

displacements()

A list containing the displacement between the shape of each iteration and the shape of the previous one.

Typelist of ndarray

displacements_stats (stat_type='mean')

A list containing a statistical metric on the displacements between the shape of each iteration and the shape of the previous one.

- **Parametersstat_type** ({'mean', 'median', 'min', 'max'}, optional) Specifies a statistic metric to be extracted from the displacements.
- **Returnsdisplacements_stat** (*list* of *float*) The statistical metric on the points displacements for each iteration.
- RaisesValueError type must be 'mean', 'median', 'min' or 'max'

errors (compute_error=None)

Returns a list containing the error at each fitting iteration, if the ground truth shape exists.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the shape at each iteration and the ground truth shape.
- **Returnserrors** (*list* of *float*) The error at each iteration of the fitting process.
- **Raises**ValueError Ground truth shape has not been set, so the final error cannot be computed

final_error(compute_error=None)

Returns the final error of the fitting process, if the ground truth shape exists. This is the error computed based on the *final_shape*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the fitted and ground truth shapes.
- **Returnsfinal_error** (*float*) The final error at the end of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

initial_error(compute_error=None)

Returns the initial error of the fitting process, if the ground truth shape and initial shape exist. This is the error computed based on the *initial_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the initial and ground truth shapes.

Returnsinitial_error (*float*) – The initial error at the beginning of the fitting process.

Raises

•ValueError – Initial shape has not been set, so the initial error cannot be computed

•ValueError – Ground truth shape has not been set, so the initial error cannot be computed

plot_costs (figure_id=None, new_figure=False, render_lines=True, line_colour='b', line_style='', line_width=2, render_markers=True, marker_style='o', marker_size=4,
marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0,
render_axes=True, axes_font_name='sans-serif', axes_font_size=10,
axes_font_style='normal', axes_font_weight='normal', axes_r_limits=0.0,
axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6),
render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the cost function evolution at each fitting iteration.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None, optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•line_style ({ '-', '--', '-.', ':'}, optional) – The style of the lines.

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (marker, optional) – The style of the markers. Example marker options

{'.', ',', 'o', 'v', '^', '<', '>', '+', 'x', 'D', 'd', 's', 'p', '*', 'h', 'H', '1', '2', '3', '4', '8'}

•marker_size (*int*, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) - The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (See below, optional) - The font of the axes. Example options

{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({'normal', 'italic', 'oblique'}, optional) - The font style of the axes.

•axes_font_weight (See below, optional) - The font weight of the axes. Example options

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

Plot of a statistical metric of the displacement between the shape of each iteration and the shape of the previous one.

Parameters

•**stat_type** ({mean, median, min, max}, optional) – Specifies a statistic metric to be extracted from the displacements (see also *displacements_stats(*) method).

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

```
\{-, --, -, :\}
```

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (*bool*, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

plot_errors (compute_error=None, figure_id=None, new_figure=False, render lines=True, line_colour='b', line_style='-', line width=2, render markers=True, marker_style='o', marker_size=4, marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0, render_axes=True, axes_font_name='sans-serif', axes_font_size=10, axes_font_style='normal', axes_font_weight='normal', axes_x_limits=0.0, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6), render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the error evolution at each fitting iteration.

Parameters

•compute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

```
{-, --, -., :}
```

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

{normal, italic, oblique}

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves'

width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

- •axes_y_limits (*float* or (*float*, *float*) or None, optional) The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.
- •axes_x_ticks (*list* or *tuple* or None, optional) The ticks of the x axis.
- •axes_y_ticks (*list* or *tuple* or None, optional) The ticks of the y axis.
- •figure_size ((float, float) or None, optional) The size of the figure in inches.
- •render_grid (*bool*, optional) If True, the grid will be rendered.
- •grid_line_style ({ '-', '--', '-.', ':'}, optional) The style of the grid lines.

•grid_line_width (float, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

reconstructed_initial_error(compute_error=None)

Returns the error of the reconstructed initial shape of the fitting process, if the ground truth shape exists. This is the error computed based on the *reconstructed_initial_shape*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the reconstructed initial and ground truth shapes.
- **Returnsreconstructed_initial_error** (*float*) The error that corresponds to the initial shape's reconstruction.

RaisesValueError – Ground truth shape has not been set, so the reconstructed initial error cannot be computed

to_result (pass_image=True, pass_initial_shape=True, pass_gt_shape=True)

Returns a *Result* instance of the object, i.e. a fitting result object that does not store the iterations. This can be useful for reducing the size of saved fitting results.

Parameters

•pass_image (bool, optional) – If True, then the image will get passed (if it exists).

•**pass_initial_shape** (*bool*, optional) – If True, then the initial shape will get passed (if it exists).

•**pass_gt_shape** (*bool*, optional) – If True, then the ground truth shape will get passed (if it exists).

Returnsresult (*Result*) – The final "lightweight" fitting result.

view (figure id=None, new figure=False, render image=True, render final shape=True, render_initial_shape=False, render_gt_shape=False, subplots enabled=True, channels=None, interpolation='bilinear', cmap name=None, alpha=1.0, masked=True, final_marker_face_colour='r', final_marker_edge_colour='k', final_line_colour='r', initial marker face colour='b', initial marker edge colour='k', initial line colour='b', gt marker face colour='y', gt marker edge colour='k', gt line colour='y', render lines=True, line style='-', line_width=2, render_markers=True, marker_style='o', marker edge width=1.0, render numbering=False, marker size=4, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers_font_name='sansserif', numbers_font_size=10, numbers_font_style='normal', numbers_font_weight='normal', numbers_font_colour='k', render_legend=True, legend_title='', legend_font_name='sanslegend font style='normal', legend font size=10, legend_font_weight='normal', serif'. legend_marker_scale=None, legend_location=2, legend_bbox_to_anchor=(1.05, 1.0), legend_border_axes_pad=None, *legend_horizontal_spacing=None*, *legend_n_columns=1*, *legend_vertical_spacing=None*, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sansaxes_font_size=10, axes_font_style='normal', axes_font_weight='normal', serif', axes x limits=None, axes y limits=None, axes x ticks=None, axes v ticks=None, figure size=(7, 7))

Visualize the fitting result. The method renders the final fitted shape and optionally the initial shape, ground truth shape and the image, id they were provided.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

- •render_final_shape (*bool*, optional) If True, then the final fitting shape gets rendered.
- •render_initial_shape (*bool*, optional) If True and the initial fitting shape exists, then it gets rendered.
- •**render_gt_shape** (*bool*, optional) If True and the ground truth shape exists, then it gets rendered.
- •**subplots_enabled** (*bool*, optional) If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.
- •channels (*int* or *list* of *int* or all or None) If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.
- •interpolation (See Below, optional) The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

{none, nearest, bilinear, bicubic, spline16, spline36, hanning, hamming, hermite, kaiser, quadric, catrom, gaussian, bessel, mitchell, sinc, lanczos}

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•final_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_marker_edge_colour (See Below, optional) – The edge colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_line_colour (See Below, optional) – The line colour of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_edge_colour (See Below, optional) - The edge colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_line_colour (See Below, optional) – The line colour of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_edge_colour (See Below, optional) – The edge colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_line_colour (See Below, optional) – The line colour of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_lines (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•line_style (*str* or *list* of *str*, optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{'-', '--', '-.', ':'}

•line_width (*float* or *list* of *float*, optional) – The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•marker_style (*str* or *list* of *str*, optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order.

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align ({center, right, left}, optional) - The horizontal alignment of the numbers' texts.

•numbers_vertical_align ({center, top, bottom, baseline}, optional) – The vertical alignment of the numbers' texts.

•numbers_font_name (See Below, optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (See Below, optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style ({normal, italic, oblique}, optional) - The font style of the legend.

•legend_font_size (int, optional) – The font size of the legend.

•legend_font_weight (See Below, optional) – The font weight of the legend. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (*int*, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

- •legend_border (bool, optional) If True, a frame will be drawn around the legend.
- •legend_border_padding (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.
- •legend_rounded_corners (*bool*, optional) If True, the frame's corners will be rounded (fancybox).
- •render_axes (bool, optional) If True, the axes will be rendered.
- •axes_font_name (See Below, optional) The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- •axes_font_size (*int*, optional) The font size of the axes.
- •axes_font_style ({normal, italic, oblique}, optional) The font style of the axes.
- •axes_font_weight (See Below, optional) The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

- •axes_x_limits (float or (float, float) or None, optional) The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.
- •axes_y_limits ((*float*, *float*) tuple or None, optional) The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.
- •axes_x_ticks (list or tuple or None, optional) The ticks of the x axis.
- •axes_y_ticks (list or tuple or None, optional) The ticks of the y axis.
- •figure_size ((float, float) tuple or None optional) The size of the figure in inches.

Returnsrenderer (*class*) – The renderer object.

view iterations (figure id=None, new figure=False, iters=None, render image=True, subplots enabled=False, channels=None. interpolation='bilinear', cmap name=None, alpha=1.0, masked=True. render lines=True, *line_style='-'*, line width=2, *line_colour=None*, render_markers=True, marker edge colour=None, marker face colour=None, marker_style='o', marker_size=4. marker_edge_width=1.0, render numbering=False, numbers horizontal align='center'. numbers vertical align='bottom', numbers font name='sans-serif', numbers font size=10, numbers font style='normal', numbers font weight='normal', numrender_legend=True, *bers_font_colour='k'*, legend_title='', legend_font_name='sans-serif', legend_font_style='normal', legend_font_size=10, legend_font_weight='normal', legend_marker_scale=None, *legend location=2*, legend_bbox_to_anchor=(1.05, 1.0). legend_border_axes_pad=None, *legend_n_columns=1*, legend_horizontal_spacing=None, legend_vertical_spacing=None, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sans-serif', axes font size=10, axes font style='normal', axes font weight='normal', axes x limits=None, axes y limits=None, axes x ticks=None, axes y ticks=None, figure size=(7, 7))

Visualize the iterations of the fitting process.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•iters (*int* or *list* of *int* or None, optional) – The iterations to be visualized. If None, then all the iterations are rendered.

No.	Visualised shape	Description
0	self.initial_shape	Initial shape
1	self.reconstructed_initial_shape	Reconstructed initial
2	self.shapes[2]	Iteration 1
i	self.shapes[i]	Iteration i-1
n_iters+1	self.final_shape	Final shape

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

•channels (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (*str* (See Below), optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

{none, nearest, bilinear, bicubic, spline16, spline36, hanning, hamming, hermite, kaiser, quadric, catrom, gaussian, bessel, mitchell, sinc, lanczos}

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

- •**render_lines** (*bool* or *list* of *bool*, optional) If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_style (*str* or *list* of *str* (See below), optional) The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options:

```
{-, --, -., :}
```

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_colour (*colour* or *list* of *colour* (See Below), optional) The colour of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_style (*str or 'list* of *str* (See below), optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_edge_colour (*colour* or *list* of *colour* (See Below), optional) – The edge colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_face_colour (*colour* or *list* of *colour* (See Below), optional) – The face (filling) colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align (*str* (See below), optional) – The horizontal alignment of the numbers' texts. Example options

```
{center, right, left}
```

•numbers_vertical_align (*str* (See below), optional) – The vertical alignment of the numbers' texts. Example options

```
{center, top, bottom, baseline}
```

•numbers_font_name (*str* (See below), optional) – The font of the numbers. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (*str* (See below), optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) - If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style (*str* (See below), optional) – The font style of the legend. Example options

{normal, italic, oblique}

•legend_font_size (*int*, optional) – The font size of the legend.

•legend_font_weight (*str* (See below), optional) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (int, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

•legend_border (bool, optional) – If True, a frame will be drawn around the legend.

•legend_border_padding (*float*, optional) – The fractional whitespace inside the legend border.

•legend_shadow (bool, optional) – If True, a shadow will be drawn behind legend.

•legend_rounded_corners (*bool*, optional) – If True, the frame's corners will be rounded (fancybox).

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) - The renderer object.

view_widget (figure_size=(7, 7))

Visualizes the result object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

costs

Returns a *list* with the cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

final_shape

Returns the final shape of the fitting process.

Typemenpo.shape.PointCloud

gt_shape

Returns the ground truth shape associated with the image. In case there is not an attached ground truth shape, then None is returned.

Typemenpo.shape.PointCloud or None

image

Returns the image that the fitting was applied on, if it was provided. Otherwise, it returns None.

Typemenpo.shape.Image or subclass or None

initial_shape

Returns the initial shape that was provided to the fitting method to initialise the fitting process. In case the initial shape does not exist, then None is returned.

Typemenpo.shape.PointCloud or None

is_iterative

Flag whether the object is an iterative fitting result.

Typebool

n_iters

Returns the total number of iterations of the fitting process.

Type*int*

reconstructed_initial_shape

Returns the initial shape's reconstruction with the shape model that was used to initialise the iterative optimisation process.

Typemenpo.shape.PointCloud

shape_parameters

Returns the *list* of shape parameters obtained at each iteration of the fitting process. The *list* includes the parameters of the *reconstructed_initial_shape* and *final_shape*.

Typelist of (n_params,) ndarray

shapes

Returns the *list* of shapes obtained at each iteration of the fitting process. The *list* includes the *initial_shape* (if it exists), *reconstructed_initial_shape* and *final_shape*.

Typelist of menpo.shape.PointCloud

Multi-Scale Iterative Result

Classes for defining a multi-scale iterative fitting result.

MultiScaleNonParametricIterativeResult

<pre>class menpofit.result.MultiScaleNonParametricIterativeResult (</pre>	results,	scales,
	affine_transform	ıs,
	scale_transform	<i>s</i> ,
	image=None,	
	gt_shape=None)

Bases: NonParametricIterativeResult

Class for defining a multi-scale non-parametric iterative fitting result, i.e. the result of a multi-scale method that does not optimise over a parametric shape model. It holds the shapes of all the iterations of the fitting procedure, as well as the scales. It can optionally store the image on which the fitting was applied, as well as its ground truth shape.

Parameters

•results (*list* of *NonParametricIterativeResult*) – The *list* of non parametric iterative results per scale.

- •scales (*list* of *float*) The scale values (normally small to high).
- •affine_transforms (*list* of *menpo.transform.Affine*) The list of affine transforms per scale that transform the shapes into the original image space.
- •scale_transforms (*list* of *menpo.shape.Scale*) The list of scaling transforms per scale.

•**image** (*menpo.image.Image* or *subclass* or None, optional) – The image on which the fitting process was applied. Note that a copy of the image will be assigned as an attribute. If None, then no image is assigned.

•gt_shape (*menpo.shape.PointCloud* or None, optional) – The ground truth shape associated with the image. If None, then no ground truth shape is assigned.

displacements()

A list containing the displacement between the shape of each iteration and the shape of the previous one.

Typelist of ndarray

displacements_stats (stat_type='mean')

A list containing a statistical metric on the displacements between the shape of each iteration and the shape of the previous one.

- Parametersstat_type ({'mean', 'median', 'min', 'max'}, optional) Specifies a statistic metric to be extracted from the displacements.
- **Returnsdisplacements_stat** (*list* of *float*) The statistical metric on the points displacements for each iteration.

RaisesValueError - type must be 'mean', 'median', 'min' or 'max'

errors (compute_error=None)

Returns a list containing the error at each fitting iteration, if the ground truth shape exists.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the shape at each iteration and the ground truth shape.
- **Returnserrors** (*list* of *float*) The error at each iteration of the fitting process.
- **Raises**ValueError Ground truth shape has not been set, so the final error cannot be computed

final_error(compute_error=None)

Returns the final error of the fitting process, if the ground truth shape exists. This is the error computed based on the *final_shape*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the fitted and ground truth shapes.
- **Returnsfinal_error** (*float*) The final error at the end of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

initial_error(compute_error=None)

Returns the initial error of the fitting process, if the ground truth shape and initial shape exist. This is the error computed based on the *initial_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the initial and ground truth shapes.

Returnsinitial_error (*float*) – The initial error at the beginning of the fitting process.

Raises

- •ValueError Initial shape has not been set, so the initial error cannot be computed
- •ValueError Ground truth shape has not been set, so the initial error cannot be computed

plot_costs (figure_id=None, new_figure=False, render_lines=True, line_colour='b', line_style='', line_width=2, render_markers=True, marker_style='o', marker_size=4,
marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0,
render_axes=True, axes_font_name='sans-serif', axes_font_size=10,
axes_font_style='normal', axes_font_weight='normal', axes_r_limits=0.0,
axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6),
render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the cost function evolution at each fitting iteration.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (*bool*, optional) – If True, the line will be rendered.

•line_colour (*colour* or None, optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•line_style ({ '-', '--', '-.', ':'}, optional) – The style of the lines.

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (marker, optional) – The style of the markers. Example marker options

{'.', ',', 'o', 'v', '^', '<', '>', '+', 'x', 'D', 'd', 's', 'p', '*', 'h', 'H', '1', '2', '3', '4', '8'}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (See below, optional) - The font of the axes. Example options

{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({'normal', 'italic', 'oblique'}, optional) - The font style of the axes.

•axes_font_weight (See below, optional) - The font weight of the axes. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
'extra bold', 'black'}
```

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

Plot of a statistical metric of the displacement between the shape of each iteration and the shape of the previous one.

Parameters

•**stat_type** ({mean, median, min, max}, optional) – Specifies a statistic metric to be extracted from the displacements (see also *displacements_stats(*) method).

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (str (See below), optional) – The style of the lines. Example options:

{-, --, -., :}

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) - If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float*, optional) – The width of the markers' edge.

•render_axes (*bool*, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (int, optional) – The font size of the axes.

•axes_font_style (*str* (See below), optional) – The font style of the axes. Example options

```
{normal, italic, oblique}
```

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ': '}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

plot_errors (compute_error=None, figure_id=None, *new_figure=False*, render_lines=True, *line_colour='b'*, line_style='-', *line_width=2*, render_markers=True, marker_style='o', marker_size=4, marker_face_colour='b', marker_edge_colour='k', render_axes=True, axes_font_name='sans-serif', marker_edge_width=1.0, axes font size=10, axes font style='normal', axes font weight='normal', axes_x_limits=0.0, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure size=(10, 6), render grid=True, grid line style='-', grid line width=0.5)

Plot of the error evolution at each fitting iteration.

Parameters

•compute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (*str* (See below), optional) – The style of the lines. Example options:

```
{-, --, -., :}
```

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (str (See below), optional) – The style of the markers. Example marker
options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float*, optional) – The width of the markers' edge.

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

```
{normal, italic, oblique}
```

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) - If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

to_result (pass_image=True, pass_initial_shape=True, pass_gt_shape=True)

Returns a *Result* instance of the object, i.e. a fitting result object that does not store the iterations. This can be useful for reducing the size of saved fitting results.

Parameters

•pass_image (bool, optional) – If True, then the image will get passed (if it exists).

•**pass_initial_shape** (*bool*, optional) – If True, then the initial shape will get passed (if it exists).

•**pass_gt_shape** (*bool*, optional) – If True, then the ground truth shape will get passed (if it exists).

Returnsresult (*Result*) – The final "lightweight" fitting result.

view (figure id=None, new figure=False, render image=True, render final shape=True, render_initial_shape=False, subplots enabled=True, *render_gt_shape=False*, channels=None, interpolation='bilinear', cmap name=None, alpha=1.0, masked=True, final_marker_face_colour='r', final_marker_edge_colour='k', final_line_colour='r', initial marker face colour='b', initial marker edge colour='k', initial line colour='b', gt marker face colour='y', gt marker edge colour='k', gt line colour='y', render lines=True, line style='-', line width=2, render markers=True, marker style='o', marker edge width=1.0, marker size=4, render numbering=False, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers_font_name='sansserif', numbers_font_size=10, numbers_font_style='normal', numbers_font_weight='normal', numbers_font_colour='k', render_legend=True, legend_title='', legend_font_name='sanslegend font style='normal', legend font size=10, legend_font_weight='normal', serif', legend_marker_scale=None, legend_location=2, legend_bbox_to_anchor=(1.05, 1.0), legend_border_axes_pad=None, *legend_horizontal_spacing=None*, *legend_n_columns=1*, *legend_vertical_spacing=None*, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sansaxes_font_style='normal', axes_font_weight='normal', serif', axes_font_size=10, axes x limits=None, axes y limits=None, axes x ticks=None, axes v ticks=None, figure size=(7, 7))

Visualize the fitting result. The method renders the final fitted shape and optionally the initial shape, ground truth shape and the image, id they were provided.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

- •render_final_shape (*bool*, optional) If True, then the final fitting shape gets rendered.
- •render_initial_shape (*bool*, optional) If True and the initial fitting shape exists, then it gets rendered.
- •**render_gt_shape** (*bool*, optional) If True and the ground truth shape exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

- •channels (*int* or *list* of *int* or all or None) If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.
- •interpolation (See Below, optional) The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

{none, nearest, bilinear, bicubic, spline16, spline36, hanning, hamming, hermite, kaiser, quadric, catrom, gaussian, bessel, mitchell, sinc, lanczos}

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•final_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_marker_edge_colour (See Below, optional) – The edge colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_line_colour (See Below, optional) – The line colour of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_edge_colour (See Below, optional) - The edge colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_line_colour (See Below, optional) – The line colour of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_edge_colour (See Below, optional) – The edge colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_line_colour (See Below, optional) – The line colour of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_lines (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•line_style (*str* or *list* of *str*, optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{ '-', '--', '-.', ':' }

•line_width (*float* or *list* of *float*, optional) – The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•marker_style (*str* or *list* of *str*, optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align ({center, right, left}, optional) - The horizontal alignment of the numbers' texts.

•numbers_vertical_align ({center, top, bottom, baseline}, optional) – The vertical alignment of the numbers' texts.

•numbers_font_name (See Below, optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (See Below, optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style ({normal, italic, oblique}, optional) - The font style of the legend.

•legend_font_size (*int*, optional) – The font size of the legend.

•legend_font_weight (See Below, optional) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- •legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) The bbox that the legend will be anchored.
- •legend_border_axes_pad (*float*, optional) The pad between the axes and legend border.
- •legend_n_columns (*int*, optional) The number of the legend's columns.
- •legend_horizontal_spacing (*float*, optional) The spacing between the columns.
- •legend_vertical_spacing (*float*, optional) The vertical space between the legend entries.

•legend_border (bool, optional) – If True, a frame will be drawn around the legend.

- •legend_border_padding (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.

•legend_rounded_corners (*bool*, optional) – If True, the frame's corners will be rounded (fancybox).

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (See Below, optional) - The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (See Below, optional) - The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (*class*) – The renderer object.

view iterations (figure id=None, new figure=False, iters=None, render image=True, subplots_enabled=False, channels=None. interpolation='bilinear', render lines=True, cmap name=None, alpha=1.0, masked=True, *line_style='-'*, *line_width=2*, line_colour=None, render_markers=True, marker edge colour=None, marker face colour=None, marker_style='o', marker size=4, marker edge width=1.0, render numbering=False, numbers_horizontal_align='center'. numbers vertical align='bottom', numbers font name='sans-serif', numbers font size=10, numbers font style='normal', numbers font weight='normal', numrender_legend=True, *bers_font_colour='k'*, legend_title='', legend_font_name='sans-serif', legend_font_style='normal', legend_font_size=10, legend_font_weight='normal', legend_marker_scale=None, *legend location=2*, legend_bbox_to_anchor=(1.05, 1.0). leg*legend_n_columns=1*, end_border_axes_pad=None, legend_horizontal_spacing=None, legend_vertical_spacing=None, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sans-serif', axes font size=10, axes font style='normal', axes font weight='normal', axes_y_limits=None, axes x limits=None, axes x ticks=None, axes y ticks=None, figure size=(7, 7))

Visualize the iterations of the fitting process.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•iters (*int* or *list* of *int* or None, optional) – The iterations to be visualized. If None, then all the iterations are rendered.

No.	Visualised shape	Description
0	self.initial_shape	Initial shape
1	self.shapes[1]	Iteration 1
i	self.shapes[i]	Iteration i
n_iters	self.final_shape	Final shape

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

•channels (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (*str* (See Below), optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

{none, nearest, bilinear, bicubic, spline16, spline36, hanning, hamming, hermite, kaiser, quadric, catrom, gaussian, bessel, mitchell, sinc, lanczos}

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

- •render_lines (*bool* or *list* of *bool*, optional) If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_style (*str* or *list* of *str* (See below), optional) The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options:

```
{-, --, -., :}
```

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_colour (*colour* or *list* of *colour* (See Below), optional) The colour of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- •**render_markers** (*bool* or *list* of *bool*, optional) If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •marker_style (*str or 'list* of *str* (See below), optional) The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_edge_colour (colour or list of colour (See Below), optional) – The edge colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_face_colour (*colour* or *list* of *colour* (See Below), optional) – The face (filling) colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align (*str* (See below), optional) – The horizontal alignment of the numbers' texts. Example options

{center, right, left}

•numbers_vertical_align (*str* (See below), optional) – The vertical alignment of the numbers' texts. Example options

{center, top, bottom, baseline}

•numbers_font_name (*str* (See below), optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (*str* (See below), optional) – The font weight of the numbers. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style (*str* (See below), optional) – The font style of the legend. Example options

{normal, italic, oblique}

•legend_font_size (*int*, optional) – The font size of the legend.

•legend_font_weight (*str* (See below), optional) – The font weight of the legend. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- •legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) The bbox that the legend will be anchored.
- •legend_border_axes_pad (*float*, optional) The pad between the axes and legend border.
- •legend_n_columns (*int*, optional) The number of the legend's columns.
- •legend_horizontal_spacing (*float*, optional) The spacing between the columns.
- •legend_vertical_spacing (*float*, optional) The vertical space between the legend entries.
- •legend_border (bool, optional) If True, a frame will be drawn around the legend.
- **legend_border_padding** (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.
- •legend_rounded_corners (*bool*, optional) If True, the frame's corners will be rounded (fancybox).
- •render_axes (bool, optional) If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.
•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (*class*) – The renderer object.

view_widget (figure_size=(7, 7))

Visualizes the result object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

costs

Returns a *list* with the cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

final_shape

Returns the final shape of the fitting process.

Typemenpo.shape.PointCloud

gt_shape

Returns the ground truth shape associated with the image. In case there is not an attached ground truth shape, then None is returned.

Typemenpo.shape.PointCloud or None

image

Returns the image that the fitting was applied on, if it was provided. Otherwise, it returns None.

Typemenpo.shape.Image or subclass or None

initial_shape

Returns the initial shape that was provided to the fitting method to initialise the fitting process. In case the initial shape does not exist, then None is returned.

Typemenpo.shape.PointCloud or None

is_iterative

Flag whether the object is an iterative fitting result.

Typebool

n_iters

Returns the total number of iterations of the fitting process.

Type*int*

n_iters_per_scale

Returns the number of iterations per scale of the fitting process.

Typelist of int

n_scales

Returns the number of scales used during the fitting process.

Type*int*

shapes

Returns the *list* of shapes obtained at each iteration of the fitting process. The *list* includes the *initial_shape* (if it exists) and *final_shape*.

Typelist of menpo.shape.PointCloud

MultiScaleParametricIterativeResult

lass menpofit.result.MultiScaleParametricIterativeResu	lt (<i>results</i> ,	scales,
	affine_transforms,	
	scale_transforms,	
	image=None,	
	$gt_shape=None$)	
Bases: MultiScaleNonParametricIterativeResult		

Class for defining a multi-scale parametric iterative fitting result, i.e. the result of a multi-scale method that optimizes over a parametric shape model. It holds the shapes of all the iterations of the fitting procedure, as well as the scales. It can optionally store the image on which the fitting was applied, as well as its ground truth shape.

Note: When using a method with a parametric shape model, the first step is to **reconstruct the initial shape** using the shape model. The generated reconstructed shape is then used as initialisation for the iterative optimisation. This step is not counted in the number of iterations.

Parameters

•results (*list* of *ParametricIterativeResult*) – The *list* of parametric iterative results per scale.

•scales (*list* of *float*) – The scale values (normally small to high).

- •affine_transforms (*list* of *menpo.transform.Affine*) The list of affine transforms per scale that transform the shapes into the original image space.
- •scale_transforms (*list* of *menpo.shape.Scale*) The list of scaling transforms per scale.
- •**image** (*menpo.image.Image* or *subclass* or None, optional) The image on which the fitting process was applied. Note that a copy of the image will be assigned as an attribute. If None, then no image is assigned.
- •gt_shape (*menpo.shape.PointCloud* or None, optional) The ground truth shape associated with the image. If None, then no ground truth shape is assigned.

displacements()

A list containing the displacement between the shape of each iteration and the shape of the previous one.

Typelist of ndarray

displacements_stats (stat_type='mean')

A list containing a statistical metric on the displacements between the shape of each iteration and the shape of the previous one.

Parametersstat_type ({'mean', 'median', 'min', 'max'}, optional) – Specifies a statistic metric to be extracted from the displacements.

Returnsdisplacements_stat (*list* of *float*) – The statistical metric on the points displacements for each iteration.

RaisesValueError - type must be 'mean', 'median', 'min' or 'max'

errors (compute_error=None)

Returns a list containing the error at each fitting iteration, if the ground truth shape exists.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

Returnserrors (*list* of *float*) – The error at each iteration of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

final_error(compute_error=None)

Returns the final error of the fitting process, if the ground truth shape exists. This is the error computed based on the *final_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the fitted and ground truth shapes.

Returnsfinal_error (*float*) – The final error at the end of the fitting process.

RaisesValueError – Ground truth shape has not been set, so the final error cannot be computed

initial_error(compute_error=None)

Returns the initial error of the fitting process, if the ground truth shape and initial shape exist. This is the error computed based on the *initial_shape*.

Parameterscompute_error (*callable*, optional) – Callable that computes the error between the initial and ground truth shapes.

Returnsinitial_error (*float*) – The initial error at the beginning of the fitting process.

Raises

•ValueError - Initial shape has not been set, so the initial error cannot be computed

•ValueError – Ground truth shape has not been set, so the initial error cannot be computed

plot_costs (figure_id=None, new_figure=False, render_lines=True, line_colour='b', line_style='', line_width=2, render_markers=True, marker_style='o', marker_size=4,
marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0,
render_axes=True, axes_font_name='sans-serif', axes_font_size=10,
axes_font_style='normal', axes_font_weight='normal', axes_font_size=0.0,
axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6),
render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the cost function evolution at each fitting iteration.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None, optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•line_style ({ '-', '--', '-.', ': '}, optional) – The style of the lines.

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) – If True, the markers will be rendered.

•marker_style (marker, optional) – The style of the markers. Example marker options

{'.', ',', 'o', 'v', '^', '<', '>', '+', 'x', 'D', 'd', 's', 'p', '*', 'h', 'H', '1', '2', '3', '4', '8'}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (See below, optional) - The font of the axes. Example options

{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({'normal', 'italic', 'oblique'}, optional) - The font style of the axes.

•axes_font_weight (See below, optional) - The font weight of the axes. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
    'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
    'extra bold', 'black'}
```

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

Plot of a statistical metric of the displacement between the shape of each iteration and the shape of the previous one.

Parameters

•**stat_type** ({mean, median, min, max}, optional) – Specifies a statistic metric to be extracted from the displacements (see also *displacements_stats(*) method).

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

{r, g, b, c, m, k, w}
or
(3,) ndarray

•line_style (*str* (See below), optional) – The style of the lines. Example options:

```
\{-, --, -., :\}
```

•line_width (*float*, optional) – The width of the lines.

•render_markers (bool, optional) - If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are {r, g, b, c, m, k, w}
or
(3,) ndarray

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

```
{normal, italic, oblique}
```

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (*menpo.visualize.GraphPlotter*) – The renderer object.

plot_errors (compute_error=None, figure_id=None, *new_figure=False*, render_lines=True, line colour='b'. *line_style='-'*, *line_width=2*, render_markers=True, marker_style='o', marker_size=4, marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0, render axes=True, axes_font_name='sans-serif', axes_font_style='normal', axes_font_size=10, axes_font_weight='normal', axes_x_limits=0.0, axes_y_limits=None, axes_x_ticks=None, axes_y_ticks=None, figure_size=(10, 6), render_grid=True, grid_line_style='-', grid_line_width=0.5)

Plot of the error evolution at each fitting iteration.

Parameters

•compute_error (*callable*, optional) – Callable that computes the error between the shape at each iteration and the ground truth shape.

•figure_id (*object*, optional) – The id of the figure to be used.

•**new_figure** (*bool*, optional) – If True, a new figure is created.

•render_lines (bool, optional) – If True, the line will be rendered.

•line_colour (*colour* or None (See below), optional) – The colour of the line. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•line_style (str (See below), optional) – The style of the lines. Example options:

```
\{-, --, -., :\}
```

•line_width (float, optional) – The width of the lines.

•render_markers (bool, optional) - If True, the markers will be rendered.

•marker_style (*str* (See below), optional) – The style of the markers. Example *marker* options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (int, optional) – The size of the markers in points.

•marker_face_colour (*colour* or None, optional) – The face (filling) colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or None, optional) – The edge colour of the markers. If None, the colour is sampled from the jet colormap. Example *colour* options are

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (float, optional) – The width of the markers' edge.

•render_axes (bool, optional) - If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•**axes_font_style** (*str* (See below), optional) – The font style of the axes. Example options

```
{normal, italic, oblique}
```

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves' height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (bool, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Returnsrenderer (menpo.visualize.GraphPlotter) – The renderer object.

reconstructed_initial_error(compute_error=None)

Returns the error of the reconstructed initial shape of the fitting process, if the ground truth shape exists. This is the error computed based on the *reconstructed_initial_shapes[0]*.

- **Parameterscompute_error** (*callable*, optional) Callable that computes the error between the reconstructed initial and ground truth shapes.
- **Returnsreconstructed_initial_error** (*float*) The error that corresponds to the initial shape's reconstruction.
- **Raises**ValueError Ground truth shape has not been set, so the reconstructed initial error cannot be computed

to_result (pass_image=True, pass_initial_shape=True, pass_gt_shape=True)

Returns a *Result* instance of the object, i.e. a fitting result object that does not store the iterations. This can be useful for reducing the size of saved fitting results.

Parameters

•pass_image (bool, optional) - If True, then the image will get passed (if it exists).

•**pass_initial_shape** (*bool*, optional) – If True, then the initial shape will get passed (if it exists).

•**pass_gt_shape** (*bool*, optional) – If True, then the ground truth shape will get passed (if it exists).

Returnsresult (*Result*) – The final "lightweight" fitting result.

view (figure id=None, new figure=False, render image=True, render final shape=True, render_initial_shape=False, render_gt_shape=False, subplots enabled=True, channels=None, interpolation='bilinear', cmap name=None, alpha=1.0, masked=True, final_marker_face_colour='r', final_marker_edge_colour='k', final_line_colour='r', initial marker face colour='b', initial marker edge colour='k', initial line colour='b', gt marker face colour='y', gt marker edge colour='k', gt line colour='y', render lines=True, line style='-', line_width=2, render_markers=True, marker_style='o', marker edge width=1.0, render numbering=False, marker size=4, numbers_horizontal_align='center', numbers_vertical_align='bottom', numbers_font_name='sansserif', numbers_font_size=10, numbers_font_style='normal', numbers_font_weight='normal', numbers_font_colour='k', render_legend=True, legend_title='', legend_font_name='sanslegend font style='normal', legend font size=10, legend_font_weight='normal', serif'. legend_marker_scale=None, legend_location=2, legend_bbox_to_anchor=(1.05, 1.0), legend_border_axes_pad=None, *legend_horizontal_spacing=None*, *legend_n_columns=1*, *legend_vertical_spacing=None*, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sansaxes_font_size=10, axes_font_style='normal', axes_font_weight='normal', serif', axes x limits=None, axes y limits=None, axes x ticks=None, axes v ticks=None, figure size=(7, 7))

Visualize the fitting result. The method renders the final fitted shape and optionally the initial shape, ground truth shape and the image, id they were provided.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) - If True, a new figure is created.

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

- •render_final_shape (*bool*, optional) If True, then the final fitting shape gets rendered.
- •render_initial_shape (*bool*, optional) If True and the initial fitting shape exists, then it gets rendered.
- •**render_gt_shape** (*bool*, optional) If True and the ground truth shape exists, then it gets rendered.
- •**subplots_enabled** (*bool*, optional) If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.
- •channels (*int* or *list* of *int* or all or None) If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.
- •interpolation (See Below, optional) The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

{none, nearest, bilinear, bicubic, spline16, spline36, hanning, hamming, hermite, kaiser, quadric, catrom, gaussian, bessel, mitchell, sinc, lanczos}

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

•final_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_marker_edge_colour (See Below, optional) – The edge colour of the markers of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•final_line_colour (See Below, optional) – The line colour of the final fitting shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_marker_edge_colour (See Below, optional) - The edge colour of the markers of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•initial_line_colour (See Below, optional) – The line colour of the initial shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_face_colour (See Below, optional) – The face (filling) colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_marker_edge_colour (See Below, optional) – The edge colour of the markers of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•gt_line_colour (See Below, optional) – The line colour of the ground truth shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_lines (*bool* or *list* of *bool*, optional) – If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•line_style (*str* or *list* of *str*, optional) – The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{'-', '--', '-.', ':'}

•line_width (*float* or *list* of *float*, optional) – The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•marker_style (*str* or *list* of *str*, optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final, initial, groundtruth*) order. Example options:

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per shape in (*final*, *initial*, *groundtruth*) order.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align ({center, right, left}, optional) - The horizontal alignment of the numbers' texts.

•numbers_vertical_align ({center, top, bottom, baseline}, optional) – The vertical alignment of the numbers' texts.

•numbers_font_name (See Below, optional) – The font of the numbers. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (See Below, optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style ({normal, italic, oblique}, optional) - The font style of the legend.

•legend_font_size (int, optional) – The font size of the legend.

•legend_font_weight (See Below, optional) – The font weight of the legend. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (*int*, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

- •legend_border (bool, optional) If True, a frame will be drawn around the legend.
- •legend_border_padding (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.
- •legend_rounded_corners (*bool*, optional) If True, the frame's corners will be rounded (fancybox).
- •render_axes (bool, optional) If True, the axes will be rendered.
- •axes_font_name (See Below, optional) The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- •axes_font_size (*int*, optional) The font size of the axes.
- •axes_font_style ({normal, italic, oblique}, optional) The font style of the axes.
- •axes_font_weight (See Below, optional) The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

- •axes_x_limits (float or (float, float) or None, optional) The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.
- •axes_y_limits ((*float*, *float*) tuple or None, optional) The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.
- •axes_x_ticks (list or tuple or None, optional) The ticks of the x axis.
- •axes_y_ticks (list or tuple or None, optional) The ticks of the y axis.
- •figure_size ((float, float) tuple or None optional) The size of the figure in inches.

Returnsrenderer (*class*) – The renderer object.

view iterations (figure id=None, new figure=False, iters=None, render image=True, channels=None. subplots_enabled=False, interpolation='bilinear', render lines=True, cmap name=None, alpha=1.0, masked=True, line_style='-', *line_width=2*, *line_colour=None*, render_markers=True, marker edge colour=None, marker face colour=None, marker_style='o', marker_size=4. marker edge width=1.0, render numbering=False, numbers_horizontal_align='center'. numbers vertical align='bottom', numbers font name='sans-serif', numbers font size=10, numbers font style='normal', numbers font weight='normal', numrender_legend=True, *bers_font_colour='k'*, legend_title='', legend_font_name='sans-serif', legend_font_style='normal', legend_font_size=10, legend_font_weight='normal', legend_marker_scale=None, *legend location=2*, legend_bbox_to_anchor=(1.05, 1.0). legend_border_axes_pad=None, *legend_n_columns=1*, legend_horizontal_spacing=None, legend_vertical_spacing=None, legend_border=True, legend_border_padding=None, legend_shadow=False, legend_rounded_corners=False, render_axes=False, axes_font_name='sans-serif', axes font size=10, axes font style='normal', axes font weight='normal', axes_x_limits=None, axes y limits=None, axes x ticks=None, axes y ticks=None, figure size=(7, 7))

Visualize the iterations of the fitting process.

Parameters

•figure_id (*object*, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•iters (*int* or *list* of *int* or None, optional) – The iterations to be visualized. If None, then all the iterations are rendered.

No.	Visualised shape	Description
0	self.initial_shape	Initial shape
1	self.reconstructed_initial_shape	Reconstructed initial
2	self.shapes[2]	Iteration 1
i	self.shapes[i]	Iteration i-1
n_iters+1	self.final_shape	Final shape

•render_image (bool, optional) – If True and the image exists, then it gets rendered.

•**subplots_enabled** (*bool*, optional) – If True, then the requested final, initial and ground truth shapes get rendered on separate subplots.

•channels (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.

•interpolation (*str* (See Below), optional) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

{none, nearest, bilinear, bicubic, spline16, spline36, hanning, hamming, hermite, kaiser, quadric, catrom, gaussian, bessel, mitchell, sinc, lanczos}

•**cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

•alpha (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).

•masked (bool, optional) – If True, then the image is rendered as masked.

- •**render_lines** (*bool* or *list* of *bool*, optional) If True, the lines will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_style (*str* or *list* of *str* (See below), optional) The style of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options:

```
{-, --, -., :}
```

- •line_width (*float* or *list* of *float*, optional) The width of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.
- •line_colour (*colour* or *list* of *colour* (See Below), optional) The colour of the lines. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•**render_markers** (*bool* or *list* of *bool*, optional) – If True, the markers will be rendered. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_style (*str or 'list* of *str* (See below), optional) – The style of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•marker_edge_colour (*colour* or *list* of *colour* (See Below), optional) – The edge colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_face_colour (*colour* or *list* of *colour* (See Below), optional) – The face (filling) colour of the markers. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. You can either provide a single value that will be used for all shapes or a list with a different value per iteration shape.

•render_numbering (bool, optional) – If True, the landmarks will be numbered.

•numbers_horizontal_align (*str* (See below), optional) – The horizontal alignment of the numbers' texts. Example options

```
{center, right, left}
```

•numbers_vertical_align (*str* (See below), optional) – The vertical alignment of the numbers' texts. Example options

```
{center, top, bottom, baseline}
```

•numbers_font_name (*str* (See below), optional) – The font of the numbers. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

•numbers_font_size (*int*, optional) – The font size of the numbers.

•numbers_font_style ({normal, italic, oblique}, optional) - The font style of the numbers.

•numbers_font_weight (*str* (See below), optional) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•numbers_font_colour (See Below, optional) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

•render_legend (bool, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•legend_font_style (*str* (See below), optional) – The font style of the legend. Example options

{normal, italic, oblique}

•legend_font_size (*int*, optional) – The font size of the legend.

•legend_font_weight (*str* (See below), optional) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

•legend_bbox_to_anchor ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.

•legend_border_axes_pad (*float*, optional) – The pad between the axes and legend border.

•legend_n_columns (int, optional) – The number of the legend's columns.

•legend_horizontal_spacing (*float*, optional) – The spacing between the columns.

•legend_vertical_spacing (*float*, optional) – The vertical space between the legend entries.

•legend_border (bool, optional) – If True, a frame will be drawn around the legend.

• **legend_border_padding** (*float*, optional) – The fractional whitespace inside the legend border.

•legend_shadow (bool, optional) – If True, a shadow will be drawn behind legend.

•legend_rounded_corners (*bool*, optional) – If True, the frame's corners will be rounded (fancybox).

•render_axes (bool, optional) – If True, the axes will be rendered.

•axes_font_name (str (See below), optional) – The font of the axes. Example options

{serif, sans-serif, cursive, fantasy, monospace}

•axes_font_size (*int*, optional) – The font size of the axes.

•axes_font_style ({normal, italic, oblique}, optional) - The font style of the axes.

•axes_font_weight (*str* (See below), optional) – The font weight of the axes. Example options

{ultralight, light, normal, regular, book, medium, roman, semibold, demibold, demi, bold, heavy, extra bold, black}

•axes_x_limits (float or (float, float) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the Image as a percentage of the Image's width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_y_limits ((*float*, *float*) tuple or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the Image as a percentage of the Image's height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set automatically.

•axes_x_ticks (list or tuple or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) tuple or None optional) – The size of the figure in inches.

Returnsrenderer (class) – The renderer object.

view_widget (figure_size=(7, 7))

Visualizes the result object using an interactive widget.

Parametersfigure_size ((*int*, *int*), optional) – The initial size of the rendered figure.

costs

Returns a *list* with the cost per iteration. It returns None if the costs are not computed.

Typelist of float or None

final_shape

Returns the final shape of the fitting process.

Typemenpo.shape.PointCloud

gt_shape

Returns the ground truth shape associated with the image. In case there is not an attached ground truth shape, then None is returned.

Typemenpo.shape.PointCloud or None

image

Returns the image that the fitting was applied on, if it was provided. Otherwise, it returns None.

Typemenpo.shape.Image or subclass or None

initial_shape

Returns the initial shape that was provided to the fitting method to initialise the fitting process. In case the initial shape does not exist, then None is returned.

Typemenpo.shape.PointCloud or None

is_iterative

Flag whether the object is an iterative fitting result.

Typebool

n_iters

Returns the total number of iterations of the fitting process.

Typeint

n_iters_per_scale

Returns the number of iterations per scale of the fitting process.

Typelist of int

n_scales

Returns the number of scales used during the fitting process.

Type*int*

reconstructed_initial_shapes

Returns the result of the reconstruction step that takes place at each scale before applying the iterative optimisation.

Typelist of menpo.shape.PointCloud

shape_parameters

Returns the *list* of shape parameters obtained at each iteration of the fitting process. The *list* includes the parameters of the *initial_shape* (if it exists) and *final_shape*.

Typelist of (n_params,) ndarray

shapes

Returns the *list* of shapes obtained at each iteration of the fitting process. The *list* includes the *initial_shape* (if it exists) and *final_shape*.

Typelist of menpo.shape.PointCloud

menpofit.transform

Model Driven Transforms

OrthoMDTransform

class menpofit.transform.OrthoMDTransform (model, transform_cls, source=None)
Bases: GlobalMDTransform

A transform that couples an alignment transform to a statistical model together with a global similarity transform, such that the weights of the transform are fully specified by both the weights of statistical model and the weights of the similarity transform. The model is assumed to generate an instance which is then transformed by the similarity transform; the result defines the target landmarks of the transform. If no source is provided, the mean of the model is defined as the source landmarks of the transform.

This transform (in contrast to the GlobalMDTransform) additionally orthonormalises both the global and the model basis against each other, ensuring that orthogonality and normalization is enforced across the unified bases.

Parameters

•model (*OrthoPDM* or *subclass*) – A linear statistical shape model (Point Distribution Model) that also has a global similarity transform that is orthonormalised with the shape bases.

•transform_cls (subclass of menpo.transform.Alignment) – A class of menpo.transform.Alignment. The align constructor will be called on this with the source and target landmarks. The target is set to the points generated from the model using the provide weights - the source is either given or set to the model's mean.

•**source** (*menpo.shape.PointCloud* or None, optional) – The source landmarks of the transform. If None, the mean of the model is used.

 $\mathbf{Jp}\left(\cdot \right)$

Compute the parameters' Jacobian, as shown in [1].

ReturnsJp ((n_params, n_params) ndarray) – The parameters' Jacobian.

References

apply (*x*, *batch_size=None*, ***kwargs*) Applies this transform to x.

If x is **Transformable**, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply() method.

Parameters

•**x** (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.

•**batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.

•kwargs (*dict*) – Passed through to _apply().

Returnstransformed (type (x)) – The transformed object or array

apply_inplace(*args, **kwargs)

Deprecated as public supported API, use the non-mutating *apply()* instead.

For internal performance-specific uses, see _apply_inplace().

as_vector(**kwargs)

Returns a flattened representation of the object as a single vector.

Returnsvector ((N, ndarray) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(transform)

Returns a TransformChain that represents this transform composed after the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, o.

Parameterstransform (Transform) - Transform to be applied before self

Returnstransform (TransformChain) – The resulting transform chain.

compose_after_from_vector_inplace(delta)

Composes two transforms together based on the first order approximation proposed in [1].

Parametersdelta ((N,) *ndarray*) – Vectorized *ModelDrivenTransform* to be applied **before** self.

Returnstransform (*self*) – self, updated to the result of the composition

References

compose_before(transform)

Returns a **TransformChain** that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

Parameterstransform (Transform) – Transform to be applied after self

Returnstransform (TransformChain) - The resulting transform chain.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other **Copyable** objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returnstype (self) – A copy of this object

d_dp (points)

The derivative of this *ModelDrivenTransform* with respect to the parametrisation changes evaluated at points.

This is done by chaining the derivative of points wrt the source landmarks on the transform (dW/dL) together with the Jacobian of the linear model wrt its weights (dX/dp).

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

```
Returnsd_dp((n_points, n_parameters, n_dims) ndarray) – The Jacobian with respect to the parametrisation.
```

from_vector(vector)

Build a new instance of the object from it's vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returnsobject (type(self)) – An new instance of this class.

from_vector_inplace(vector)

Deprecated. Use the non-mutating API, from_vector.

For internal usage in performance-sensitive spots, see _from_vector_inplace()

Parametersvector ((n_parameters,) ndarray) - Flattened representation of this object

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returnshas_nan_values (*bool*) – If the vectorized object contains nan values.

pseudoinverse_vector(vector)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for *self.from_vector(vector).pseudoinverse.as_vector()*. On *ModelDrivenTransform* this is especially fast - we just negate the vector provided.

Parametersvector ((P,) *ndarray*) – A vectorized version of self

Returnspseudoinverse_vector ((N,) ndarray) – The pseudoinverse of the vector provided

set_target (new_target)

Update this object so that it attempts to recreate the new_target.

Parametersnew_target (**PointCloud**) – The new target that this object should try and regenerate.

has_true_inverse

Whether the transform has true inverse.

Typebool

n_dims

The number of dimensions that the transform supports.

Type*int*

n_dims_output

The output of the data from the transform.

None if the output of the transform is not dimension specific.

Typeint or None

n_parameters

The total number of parameters.

Type*int*

n_points

The number of points on the *target*.

Type*int*

target

The current menpo.shape.PointCloud that this object produces.

Typemenpo.shape.PointCloud

LinearOrthoMDTransform

class menpofit.transform.LinearOrthoMDTransform(model, sparse_instance)

Bases: OrthoPDM, Transform

A transform that couples an alignment transform to a statistical model together with a global similarity transform, such that the weights of the transform are fully specified by both the weights of statistical model and the weights of the similarity transform. The model is assumed to generate an instance which is then transformed by the similarity transform; the result defines the target landmarks of the transform. If no source is provided, the mean of the model is defined as the source landmarks of the transform.

This transform (in contrast to the GlobalMDTransform) additionally orthonormalises both the global and the model basis against each other, ensuring that orthogonality and normalization is enforced across the unified bases.

This transform (in contrast to the *OrthoMDTransform*) should be used with linear statistical models of dense shapes.

Parameters

•model (menpo.model.LinearModel) – A linear statistical shape model.

•sparse_instance (menpo.shape.PointCloud) – The source landmarks of the transform.

apply (*x*, *batch_size=None*, ***kwargs*) Applies this transform to x.

If x is **Transformable**, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply () method.

Parameters

•**x** (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.

•**batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.

•kwargs (*dict*) – Passed through to _apply().

Returnstransformed (type (x)) – The transformed object or array

apply_inplace(*args, **kwargs)

Deprecated as public supported API, use the non-mutating *apply()* instead.

For internal performance-specific uses, see _apply_inplace().

as_vector(**kwargs)

Returns a flattened representation of the object as a single vector.

Returnsvector ((N, ndarray) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(transform)

Returns a TransformChain that represents this transform composed after the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, o.

Parameterstransform (Transform) - Transform to be applied before self

Returnstransform (TransformChain) – The resulting transform chain.

compose_before(transform)

Returns a **TransformChain** that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

Parameterstransform (Transform) – Transform to be applied after self

Returnstransform (TransformChain) – The resulting transform chain.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other **Copyable** objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returnstype (self) – A copy of this object

$d_dp (_)$

The derivative with respect to the parametrisation changes evaluated at points.

- **Parameterspoints** ((n_points, n_dims) *ndarray*) The spatial points at which the derivative should be evaluated.
- **Returnsd_dp**((n_points, n_parameters, n_dims) *ndarray*) The Jacobian with respect to the parametrisation.

from_vector(vector)

Build a new instance of the object from it's vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returnsobject (type(self)) – An new instance of this class.

from_vector_inplace(vector)

Deprecated. Use the non-mutating API, from_vector.

For internal usage in performance-sensitive spots, see _from_vector_inplace()

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of this object

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returnshas_nan_values (*bool*) – If the vectorized object contains nan values.

increment (shapes, n_shapes=None, forgetting_factor=1.0, max_n_components=None, ver-

bose=False) Update the eigenvectors, eigenvalues and mean vector of this model by performing incremental PCA on the given samples.

Parameters

•**shapes** (*list* of *menpo.shape.PointCloud*) – List of new shapes to update the model from.

•**n_shapes** (*int* or None, optional) – If *int*, then *shapes* must be an iterator that yields n_{shapes} . If None, then *shapes* has to be a list (so we know how large the data matrix needs to be).

•forgetting_factor ([0.0, 1.0] *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples. If 1.0, all samples are weighted equally and, hence, the results is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples. See [1] for details.

•max_n_components (*int* or None, optional) – The maximum number of components that the model will keep. If None, then all the components will be kept.

•verbose (bool, optional) – If True, then information about the progress will be printed.

References

set_target (target)

Update this object so that it attempts to recreate the new_target.

Parametersnew_target (*menpo.shape.PointCloud*) – The new target that this object should try and regenerate.

dense_target

The current dense menpo.shape.PointCloud that this object produces.

Typemenpo.shape.PointCloud

global_parameters

The parameters for the global transform.

Type(n_global_parameters,) ndarray

n_active_components

The number of components currently in use on this model.

Type*int*

n_dims

The number of dimensions of the spatial instance of the model

Type*int*

n_dims_output

The output of the data from the transform.

None if the output of the transform is not dimension specific.

Typeint or None

n_global_parameters

The number of parameters in the global_transform

Type*int*

n_landmarks

The number of sparse landmarks.

Type*int*

n_parameters

The length of the vector that this object produces.

Type*int*

n_points

The number of points on the *target*.

Type*int*

n_weights

The number of parameters in the linear model.

Typeint

sparse_target

The current sparse *menpo.shape.PointCloud* that this object produces.

Typemenpo.shape.PointCloud

target

The current *menpo.shape.PointCloud* that this object produces.

Typemenpo.shape.PointCloud

weights

The weights of the model.

Type(n_weights,) ndarray

Homogeneous Transforms

DifferentiableAffine

```
class menpofit.transform.DifferentiableAffine (h_matrix, copy=True, skip_checks=False)
Bases: Affine, DP, DX
```

Base class for an affine transformation that can compute its own derivative with respect to spatial changes, as well as its parametrisation.

apply (*x*, *batch_size=None*, ***kwargs*) Applies this transform to x.

If x is **Transformable**, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply() method.

Parameters

•**x** (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.

•**batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.

•kwargs (dict) - Passed through to _apply().

Returnstransformed (type (x)) – The transformed object or array

apply_inplace(*args, **kwargs)

Deprecated as public supported API, use the non-mutating apply() instead.

For internal performance-specific uses, see _apply_inplace().

as_vector(**kwargs)

Returns a flattened representation of the object as a single vector.

Returnsvector ((N) *ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(transform)

A Transform that represents this transform composed after the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, \circ .

An attempt is made to perform native composition, but will fall back to a **TransformChain** as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameterstransform (Transform) – Transform to be applied before self

Returnstransform (Transform or TransformChain) – If the composition was native, a single new Transform will be returned. If not, a TransformChain is returned instead.

compose_after_inplace(transform)

Update self so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameterstransform (composes_inplace_with) - Transform to be applied before
 self

RaisesValueError – If transform isn't an instance of composes_inplace_with

compose_before(transform)

A Transform that represents this transform composed before the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

An attempt is made to perform native composition, but will fall back to a **TransformChain** as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameterstransform (Transform) – Transform to be applied after self

Returnstransform (Transform or TransformChain) – If the composition was native, a single new Transform will be returned. If not, a TransformChain is returned instead.

compose_before_inplace(transform)

Update self so that it represents this transform composed before the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

```
Parameterstransform (composes_inplace_with) - Transform to be applied after
    self
```

RaisesValueError - If transform isn't an instance of composes_inplace_with

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other **Copyable** objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returnstype(self) - A copy of this object

d_dp (points)

The derivative with respect to the parametrisation changes evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dp((n_points, n_parameters, n_dims) *ndarray*) – The Jacobian with respect to the parametrisation.

 $d_dp[i, j, k]$ is the scalar differential change that the k'th dimension of the i'th point experiences due to a first order change in the j'th scalar in the parametrisation vector.

d_dx (*points*)

The first order derivative with respect to spatial changes evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dx ((n_points, n_dims, n_dims) *ndarray*) – The Jacobian wrt spatial changes.

 $d_dx[i, j, k]$ is the scalar differential change that the j'th dimension of the i'th point experiences due to a first order change in the k'th dimension.

It may be the case that the Jacobian is constant across space - in this case axis zero may have length 1 to allow for broadcasting.

decompose()

Decompose this transform into discrete Affine Transforms.

Useful for understanding the effect of a complex composite transform.

Returns

transforms (list of DiscreteAffine) - Equivalent to this affine transform, such that

reduce(lambda x, y: x.chain(y), self.decompose()) == self

from_vector (vector)

Build a new instance of the object from its vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a deepcopy of the object followed by a call to from_vector_inplace(). This method can be overridden for a performance benefit if desired.

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returnstransform (Homogeneous) – An new instance of this class.

from_vector_inplace(vector)

Deprecated. Use the non-mutating API, from_vector.

For internal usage in performance-sensitive spots, see _from_vector_inplace()

Parametersvector ((n_parameters,) ndarray) - Flattened representation of this object

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returnshas_nan_values (*bool*) – If the vectorized object contains nan values.

init_from_2d_shear (phi, psi, degrees=True)

Convenience constructor for 2D shear transformations about the origin.

Parameters

•phi (float) – The angle of shearing in the X direction.

•**psi** (*float*) – The angle of shearing in the Y direction.

•degrees (*bool*, optional) – If True phi and psi are interpreted as degrees. If False, phi and psi are interpreted as radians.

Returnsshear_transform (Affine) – A 2D shear transform.

init_identity (n_dims)

Creates an identity matrix Affine transform.

Parametersn_dims (*int*) – The number of dimensions.

Returnsidentity (Affine) – The identity matrix transform.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping *source* and *target*, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

TypeHomogeneous

pseudoinverse_vector(vector)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

self.from_vector(vector).pseudoinverse().as_vector()

Can be much faster than the explicit call as object creation can be entirely avoided in some cases.

Parametersvector ((n_parameters,) *ndarray*) - A vectorized version of self

Returnspseudoinverse_vector ((n_parameters,) *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix (value, copy=True, skip_checks=False)

Deprecated Deprecated - do not use this method - you are better off just creating a new transform!

Updates h_matrix, optionally performing sanity checks.

Note that it won't always be possible to manually specify the h_matrix through this method, specifically if changing the h_matrix could change the nature of the transform. See h_matrix_is_mutable for how you can discover if the h_matrix is allowed to be set for a given class.

Parameters

•value (*ndarray*) – The new homogeneous matrix to set.

•copy (*bool*, optional) – If False, do not copy the h_matrix. Useful for performance.

•skip_checks (bool, optional) - If True, skip checking. Useful for performance.

RaisesNotImplementedError - If h_matrix_is_mutable returns False.

composes_inplace_with

Affine can swallow composition with any other Affine.

composes_with

Any Homogeneous can compose with any other Homogeneous.

h_matrix

The homogeneous matrix defining this transform.

Type (n_dims + 1, n_dims + 1) ndarray

h_matrix_is_mutable

Deprecated True iff set_h_matrix() is permitted on this type of transform.

If this returns False calls to set_h_matrix () will raise a NotImplementedError.

Typebool

has_true_inverse

The pseudoinverse is an exact inverse.

TypeTrue

linear_component

The linear component of this affine transform.

Type(n_dims, n_dims) ndarray

n_dims

The dimensionality of the data the transform operates on.

Type*int*

n_dims_output

The output of the data from the transform.

Type*int*

n_parameters

n_dims * (n_dims + 1) parameters - every element of the matrix but the homogeneous part.

Typeint

Examples

2D Affine: 6 parameters:

[p1, p3, p5] [p2, p4, p6]

3D Affine: 12 parameters:

[p1, p4, p7, p10] [p2, p5, p8, p11] [p3, p6, p9, p12]

translation_component

The translation component of this affine transform.

Type(n_dims,) ndarray

DifferentiableSimilarity

class menpofit.transform.DifferentiableSimilarity(h_matrix,

skip_checks=False)

copy=True,

Bases: Similarity, DP, DX

Base class for a similarity transformation that can compute its own derivative with respect to spatial changes, as well as its parametrisation.

apply (x, batch_size=None, **kwargs)

Applies this transform to x.

If x is **Transformable**, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply() method.

Parameters

•**x** (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.

•**batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.

•kwargs (dict) – Passed through to _apply().

Returnstransformed (type (x)) – The transformed object or array

apply_inplace(*args, **kwargs)

Deprecated as public supported API, use the non-mutating *apply()* instead.

For internal performance-specific uses, see _apply_inplace().

as_vector(**kwargs)

Returns a flattened representation of the object as a single vector.

Returnsvector ((N, ndarray) - The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(transform)

A Transform that represents this transform composed after the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, \circ .

An attempt is made to perform native composition, but will fall back to a **TransformChain** as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameterstransform (Transform) - Transform to be applied before self

Returnstransform (Transform or TransformChain) – If the composition was native, a single new Transform will be returned. If not, a TransformChain is returned instead.

compose_after_inplace(transform)

Update self so that it represents this transform composed after the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameterstransform (composes_inplace_with) - Transform to be applied before
 self

RaisesValueError - If transform isn't an instance of composes_inplace_with

compose_before(transform)

A Transform that represents this transform composed before the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

An attempt is made to perform native composition, but will fall back to a **TransformChain** as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameterstransform (Transform) - Transform to be applied after self

Returnstransform (Transform or TransformChain) – If the composition was native, a single new Transform will be returned. If not, a TransformChain is returned instead.

compose_before_inplace(transform)

Update self so that it represents this transform composed before the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

```
Parameterstransform (composes_inplace_with) - Transform to be applied after
    self
```

RaisesValueError – If transform isn't an instance of composes_inplace_with

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other **Copyable** objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returnstype(self) – A copy of this object

d_dp (*points*)

The derivative with respect to the parametrisation changes evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dp((n_points, n_parameters, n_dims) *ndarray*) – The Jacobian with respect to the parametrisation.

 $d_dp[i, j, k]$ is the scalar differential change that the k'th dimension of the i'th point experiences due to a first order change in the j'th scalar in the parametrisation vector.

d_dx (points)

The first order derivative with respect to spatial changes evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dx ((n_points, n_dims, n_dims) *ndarray*) – The Jacobian wrt spatial changes.

 $d_dx[i, j, k]$ is the scalar differential change that the j'th dimension of the i'th point experiences due to a first order change in the k'th dimension.

It may be the case that the Jacobian is constant across space - in this case axis zero may have length 1 to allow for broadcasting.

decompose()

Decompose this transform into discrete Affine Transforms.

Useful for understanding the effect of a complex composite transform.

Returns

transforms (list of DiscreteAffine) - Equivalent to this affine transform, such that

reduce(lambda x, y: x.chain(y), self.decompose()) == self

from_vector(vector)

Build a new instance of the object from its vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returnstransform (Homogeneous) – An new instance of this class.

from_vector_inplace(vector)

Deprecated. Use the non-mutating API, from_vector.

For internal usage in performance-sensitive spots, see _from_vector_inplace()

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of this object

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returnshas_nan_values (*bool*) – If the vectorized object contains nan values.

init_from_2d_shear (phi, psi, degrees=True)

Convenience constructor for 2D shear transformations about the origin.

Parameters

•phi (*float*) – The angle of shearing in the X direction.

•**psi** (*float*) – The angle of shearing in the Y direction.

•degrees (*bool*, optional) – If True phi and psi are interpreted as degrees. If False, phi and psi are interpreted as radians.

Returnsshear_transform (Affine) – A 2D shear transform.

init_identity(n_dims)

Creates an identity transform.

Parametersn_dims (*int*) – The number of dimensions.

Returnsidentity (Similarity) – The identity matrix transform.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping *source* and *target*, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

TypeHomogeneous

pseudoinverse_vector(vector)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

self.from_vector(vector).pseudoinverse().as_vector()

Can be much faster than the explicit call as object creation can be entirely avoided in some cases.

Parametersvector ((n_parameters,) ndarray) - A vectorized version of self

Returnspseudoinverse_vector((n_parameters,) *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix (value, copy=True, skip_checks=False)

Deprecated Deprecated - do not use this method - you are better off just creating a new transform!

Updates h_matrix, optionally performing sanity checks.

Note that it won't always be possible to manually specify the h_matrix through this method, specifically if changing the h_matrix could change the nature of the transform. See h_matrix_is_mutable for how you can discover if the h_matrix is allowed to be set for a given class.

Parameters

•value (*ndarray*) – The new homogeneous matrix to set.

•copy (*bool*, optional) – If False, do not copy the h_matrix. Useful for performance.

•skip_checks (bool, optional) – If True, skip checking. Useful for performance.

RaisesNotImplementedError - If h_matrix_is_mutable returns False.

composes_inplace_with

Affine can swallow composition with any other Affine.

composes_with

Any Homogeneous can compose with any other Homogeneous.

h_matrix

The homogeneous matrix defining this transform.

Type(n_dims + 1, n_dims + 1) ndarray

h_matrix_is_mutable

Deprecated True iff set_h_matrix() is permitted on this type of transform.

If this returns False calls to *set_h_matrix()* will raise a NotImplementedError.

Typebool

has_true_inverse

The pseudoinverse is an exact inverse.

TypeTrue

linear_component

The linear component of this affine transform.

Type(n_dims, n_dims) ndarray

n_dims

The dimensionality of the data the transform operates on.

Type*int*

n_dims_output

The output of the data from the transform.

Type*int*

n_parameters

Number of parameters of Similarity

2D Similarity - 4 parameters

[(1 + a), -b, tx] [b, (1 + a), ty]

3D Similarity: Currently not supported

Returnsn_parameters (int) – The transform parameters

RaisesDimensionalityError, NotImplementedError - Only 2D transforms are supported.

translation_component

The translation component of this affine transform.

Type(n_dims,) ndarray

DifferentiableAlignmentSimilarity

class menpofit.transform.DifferentiableAlignmentSimilari	ty (source,	target,	ro-
	tation=Tr	ue,	al-
	low_mirr	or=False)	
Bases: AlignmentSimilarity, DP, DX			

Base class that constructs a similarity transformation that is the optimal transform to align the *source* to the *target*. It can compute its own derivative with respect to spatial changes, as well as its parametrisation.

```
aligned_source()
```

The result of applying self to source

TypePointCloud

alignment_error()

The Frobenius Norm of the difference between the target and the aligned source.

Typefloat

```
apply (x, batch_size=None, **kwargs)
Applies this transform to x.
```

If x is **Transformable**, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply() method.

Parameters

•**x** (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.

•**batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.

•kwargs (dict) – Passed through to _apply().

Returnstransformed (type (x)) – The transformed object or array

apply_inplace(*args, **kwargs)

Deprecated as public supported API, use the non-mutating *apply()* instead.

For internal performance-specific uses, see _apply_inplace().

as_non_alignment()

Returns the non-alignment version of the transform.

TypeDifferentiableSimilarity

as_vector(**kwargs)

Returns a flattened representation of the object as a single vector.

Returnsvector ((N, ndarray) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(transform)

A Transform that represents this transform composed after the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, o.

An attempt is made to perform native composition, but will fall back to a **TransformChain** as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameterstransform (Transform) – Transform to be applied before self

Returnstransform (Transform or TransformChain) – If the composition was native, a single new Transform will be returned. If not, a TransformChain is returned instead.

compose_after_inplace(transform)

Update self so that it represents this transform composed after the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameterstransform (composes_inplace_with) - Transform to be applied before
 self

RaisesValueError - If transform isn't an instance of composes_inplace_with

compose_before(transform)

A **Transform** that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```
a and b are left unchanged.

An attempt is made to perform native composition, but will fall back to a **TransformChain** as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameterstransform (Transform) - Transform to be applied after self

Returnstransform (Transform or TransformChain) – If the composition was native, a single new Transform will be returned. If not, a TransformChain is returned instead.

compose_before_inplace(transform)

Update self so that it represents this transform composed before the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameterstransform (composes_inplace_with) - Transform to be applied after self

RaisesValueError – If transform isn't an instance of composes_inplace_with

copy()

Generate an efficient copy of this HomogFamilyAlignment.

Returnsnew_transform (type(self)) – A copy of this object

d_dp (points)

The derivative with respect to the parametrisation changes evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dp((n_points, n_parameters, n_dims) *ndarray*) – The Jacobian with respect to the parametrisation.

 $d_dp[i, j, k]$ is the scalar differential change that the k'th dimension of the i'th point experiences due to a first order change in the j'th scalar in the parametrisation vector.

d_dx (points)

The first order derivative with respect to spatial changes evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dx((n_points, n_dims, n_dims) *ndarray*) – The Jacobian wrt spatial changes.

 $d_dx[i, j, k]$ is the scalar differential change that the j'th dimension of the i'th point experiences due to a first order change in the k'th dimension.

It may be the case that the Jacobian is constant across space - in this case axis zero may have length 1 to allow for broadcasting.

decompose()

Decompose this transform into discrete Affine Transforms.

Useful for understanding the effect of a complex composite transform.

Returns

transforms (list of DiscreteAffine) - Equivalent to this affine transform, such that

reduce(lambda x, y: x.chain(y), self.decompose()) == self

from_vector (vector)

Build a new instance of the object from its vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returnstransform (Homogeneous) – An new instance of this class.

from_vector_inplace(vector)

Deprecated. Use the non-mutating API, from_vector.

For internal usage in performance-sensitive spots, see _from_vector_inplace()

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of this object

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returnshas_nan_values (bool) – If the vectorized object contains nan values.

init_from_2d_shear (phi, psi, degrees=True)

Convenience constructor for 2D shear transformations about the origin.

Parameters

•phi (float) – The angle of shearing in the X direction.

•**psi** (*float*) – The angle of shearing in the Y direction.

•degrees (*bool*, optional) – If True phi and psi are interpreted as degrees. If False, phi and psi are interpreted as radians.

Returnsshear_transform (Affine) – A 2D shear transform.

init_identity (n_dims)

Creates an identity transform.

Parametersn_dims (*int*) – The number of dimensions.

Returnsidentity (Similarity) – The identity matrix transform.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping source and target, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Returnstransform (type(self)) – The inverse of this transform.

pseudoinverse_vector(vector)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

self.from_vector(vector).pseudoinverse().as_vector()

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parametersvector ((n_parameters,) ndarray) - A vectorized version of self

Returnspseudoinverse_vector ((n_parameters,) *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix (value, copy=True, skip_checks=False)

Deprecated Deprecated - do not use this method - you are better off just creating a new transform!

Updates h_matrix, optionally performing sanity checks.

Note that it won't always be possible to manually specify the h_matrix through this method, specifically if changing the h_matrix could change the nature of the transform. See h_matrix_is_mutable for how you can discover if the h_matrix is allowed to be set for a given class.

Parameters

•value (*ndarray*) – The new homogeneous matrix to set.

•copy (bool, optional) – If False, do not copy the h_matrix. Useful for performance.

•skip_checks (bool, optional) – If True, skip checking. Useful for performance.

RaisesNotImplementedError - If h_matrix_is_mutable returns False.

set_target (new_target)

Update this object so that it attempts to recreate the new_target.

Parametersnew_target (**PointCloud**) – The new target that this object should try and regenerate.

composes_inplace_with

Affine can swallow composition with any other Affine.

composes_with

Any Homogeneous can compose with any other Homogeneous.

h_matrix

The homogeneous matrix defining this transform.

Type (n_dims + 1, n_dims + 1) ndarray

h_matrix_is_mutable

Deprecated True iff set_h_matrix() is permitted on this type of transform.

If this returns False calls to *set_h_matrix()* will raise a NotImplementedError.

Typebool

has_true_inverse

The pseudoinverse is an exact inverse.

TypeTrue

linear_component

The linear component of this affine transform.

Type(n_dims, n_dims) ndarray

n_dims

The number of dimensions of the *target*.

Type*int*

n_dims_output

The output of the data from the transform.

Type*int*

n_parameters

Number of parameters of Similarity

2D Similarity - 4 parameters

[(1 + a), -b, tx] [b, (1 + a), ty]

3D Similarity: Currently not supported

Returnsn_parameters (*int*) – The transform parameters

RaisesDimensionalityError, NotImplementedError - Only 2D transforms are supported.

n_points

The number of points on the *target*.

Type*int*

source

The source **PointCloud** that is used in the alignment.

The source is not mutable.

TypePointCloud

target

The current **PointCloud** that this object produces.

To change the target, use set_target().

TypePointCloud

translation_component

The translation component of this affine transform.

Type (n_dims,) ndarray

DifferentiableAlignmentAffine

```
class menpofit.transform.DifferentiableAlignmentAffine (source, target)
```

Bases: AlignmentAffine, DP, DX

Base class that constructs an affine transformation that is the optimal transform to align the *source* to the *target*. It can compute its own derivative with respect to spatial changes, as well as its parametrisation.

aligned_source() The result of applying self to *source*

TypePointCloud

```
alignment_error()
The Frobenius Norm of the difference between the target and the aligned source.
```

Typefloat

apply (*x*, *batch_size=None*, ***kwargs*) Applies this transform to x.

If x is **Transformable**, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply() method.

Parameters

•**x** (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.

•**batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.

•kwargs (*dict*) – Passed through to _apply().

Returnstransformed (type (x)) – The transformed object or array

apply_inplace(**args*, ***kwargs*)

Deprecated as public supported API, use the non-mutating apply() instead.

For internal performance-specific uses, see _apply_inplace().

as_non_alignment()

Returns the non-alignment version of the transform.

TypeDifferentiableAffine

as_vector(**kwargs)

Returns a flattened representation of the object as a single vector.

Returnsvector ((N,) ndarray) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(transform)

A Transform that represents this transform composed after the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, o.

An attempt is made to perform native composition, but will fall back to a **TransformChain** as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameterstransform (Transform) – Transform to be applied before self

Returnstransform (Transform or TransformChain) – If the composition was native, a single new Transform will be returned. If not, a TransformChain is returned instead.

compose_after_inplace(transform)

Update self so that it represents this transform composed after the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameterstransform (composes_inplace_with) - Transform to be applied before
 self

RaisesValueError – If transform isn't an instance of composes_inplace_with

compose_before(transform)

A Transform that represents this transform composed before the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

An attempt is made to perform native composition, but will fall back to a **TransformChain** as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameterstransform (Transform) - Transform to be applied after self

Returnstransform (Transform or TransformChain) – If the composition was native, a single new Transform will be returned. If not, a TransformChain is returned instead.

compose_before_inplace(transform)

Update self so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameterstransform (composes_inplace_with) - Transform to be applied after
 self

RaisesValueError - If transform isn't an instance of composes_inplace_with

copy()

Generate an efficient copy of this **HomogFamilyAlignment**.

Returnsnew_transform (type(self)) – A copy of this object

d_dp (points)

The derivative with respect to the parametrisation changes evaluated at points.

```
Parameterspoints ((n_points, n_dims) ndarray) – The spatial points at which the derivative should be evaluated.
```

Returns

d_dp((n_points, n_parameters, n_dims) *ndarray*) – The Jacobian with respect to the parametrisation.

 $d_dp[i, j, k]$ is the scalar differential change that the k'th dimension of the i'th point experiences due to a first order change in the j'th scalar in the parametrisation vector.

d_dx (points)

The first order derivative with respect to spatial changes evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dx ((n_points, n_dims, n_dims) *ndarray*) – The Jacobian wrt spatial changes.

 $d_dx[i, j, k]$ is the scalar differential change that the j'th dimension of the i'th point experiences due to a first order change in the k'th dimension.

It may be the case that the Jacobian is constant across space - in this case axis zero may have length 1 to allow for broadcasting.

decompose()

Decompose this transform into discrete Affine Transforms.

Useful for understanding the effect of a complex composite transform.

Returns

transforms (list of DiscreteAffine) – Equivalent to this affine transform, such that

reduce(lambda x, y: x.chain(y), self.decompose()) == self

from_vector (vector)

Build a new instance of the object from its vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returnstransform (Homogeneous) – An new instance of this class.

from_vector_inplace(vector)

Deprecated. Use the non-mutating API, from_vector.

For internal usage in performance-sensitive spots, see _from_vector_inplace()

Parametersvector ((n_parameters,) *ndarray*) – Flattened representation of this object

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returnshas_nan_values (*bool*) – If the vectorized object contains nan values.

init_from_2d_shear (phi, psi, degrees=True)

Convenience constructor for 2D shear transformations about the origin.

Parameters

•phi (*float*) – The angle of shearing in the X direction.

•**psi** (*float*) – The angle of shearing in the Y direction.

•degrees (*bool*, optional) – If True phi and psi are interpreted as degrees. If False, phi and psi are interpreted as radians.

Returnsshear_transform (Affine) – A 2D shear transform.

init_identity (n_dims)

Creates an identity matrix Affine transform.

Parametersn_dims (*int*) – The number of dimensions.

Returnsidentity (Affine) – The identity matrix transform.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping source and target, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Returnstransform (type(self)) – The inverse of this transform.

pseudoinverse_vector(vector)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

self.from_vector(vector).pseudoinverse().as_vector()

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parametersvector ((n_parameters,) ndarray) - A vectorized version of self

Returnspseudoinverse_vector ((n_parameters,) *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix (value, copy=True, skip_checks=False)

Deprecated Deprecated - do not use this method - you are better off just creating a new transform!

Updates h_matrix, optionally performing sanity checks.

Note that it won't always be possible to manually specify the h_matrix through this method, specifically if changing the h_matrix could change the nature of the transform. See h_matrix_is_mutable for how you can discover if the h_matrix is allowed to be set for a given class.

Parameters

•value (*ndarray*) – The new homogeneous matrix to set.

•copy (*bool*, optional) – If False, do not copy the h_matrix. Useful for performance.

•skip_checks (bool, optional) – If True, skip checking. Useful for performance.

RaisesNotImplementedError - If h_matrix_is_mutable returns False.

set_target (new_target)

Update this object so that it attempts to recreate the new_target.

Parametersnew_target (PointCloud) - The new target that this object should try and regenerate.

composes_inplace_with

Affine can swallow composition with any other Affine.

composes_with

Any Homogeneous can compose with any other Homogeneous.

h_matrix

The homogeneous matrix defining this transform.

Type (n_dims + 1, n_dims + 1) *ndarray*

h_matrix_is_mutable

Deprecated True iff set_h_matrix() is permitted on this type of transform.

If this returns False calls to set_h_matrix() will raise a NotImplementedError.

Typebool

has_true_inverse

The pseudoinverse is an exact inverse.

TypeTrue

linear_component

The linear component of this affine transform.

Type(n_dims, n_dims) ndarray

n_dims

The number of dimensions of the *target*.

Type*int*

n_dims_output

The output of the data from the transform.

Type*int*

```
n parameters
```

 $n_dims \star (n_dims + 1)$ parameters - every element of the matrix but the homogeneous part.

Typeint

Examples

2D Affine: 6 parameters:

[p1, p3, p5] [p2, p4, p6]

3D Affine: 12 parameters:

[p1, p4, p7, p10] [p2, p5, p8, p11] [p3, p6, p9, p12]

n_points

The number of points on the *target*.

Type*int*

source

The source **PointCloud** that is used in the alignment.

The source is not mutable.

TypePointCloud

target

The current **PointCloud** that this object produces.

To change the target, use *set_target()*.

TypePointCloud

translation_component

The translation component of this affine transform.

Type(n_dims,) ndarray

Alignments

DifferentiablePiecewiseAffine

class menpofit.transform.DifferentiablePiecewiseAffine (source, target)
Bases: CachedPWA, DL, DX

A differentiable Piecewise Affine Transformation.

This is composed of a number of triangles defined be a set of *source* and *target* vertices. These vertices are related by a common triangle *list*. No limitations on the nature of the triangle *list* are imposed. Points can then be mapped via barycentric coordinates from the *source* to the *target* space. Trying to map points that are not contained by any source triangle throws a *TriangleContainmentError*, which contains diagnostic information.

The transform can compute its own derivative with respect to spatial changes, as well as anchor landmark changes.

```
aligned_source()
```

The result of applying self to source

TypePointCloud

alignment_error()

The Frobenius Norm of the difference between the target and the aligned source.

Typefloat

```
apply (x, batch_size=None, **kwargs)
```

Applies this transform to x.

If x is **Transformable**, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply() method.

Parameters

•x (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.

•**batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.

•kwargs (dict) – Passed through to _apply().

Returnstransformed (type (x)) – The transformed object or array

apply_inplace(*args, **kwargs)

Deprecated as public supported API, use the non-mutating *apply()* instead.

For internal performance-specific uses, see _apply_inplace().

compose_after(transform)

Returns a TransformChain that represents this transform composed after the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, o.

Parameterstransform (Transform) – Transform to be applied before self

Returnstransform (TransformChain) – The resulting transform chain.

compose_before(transform)

Returns a TransformChain that represents this transform composed before the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

Parameterstransform (Transform) - Transform to be applied after self

Returnstransform (TransformChain) – The resulting transform chain.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other **Copyable** objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returnstype(self) – A copy of this object

d_dl (points)

The derivative of the warp with respect to spatial changes in anchor landmark points or centres, evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dl ((n_points, n_centres, n_dims) *ndarray*) - The Jacobian wrt landmark changes.

 $d_dl[i, k, m]$ is the scalar differential change that the any dimension of the i'th point experiences due to a first order change in the m'th dimension of the k'th landmark point.

Note that at present this assumes that the change in every dimension is equal.

d_dx (points)

The first order derivative of the warp with respect to spatial changes evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dx((n_points, n_dims, n_dims) *ndarray*) – The Jacobian wrt spatial changes.

 $d_dx[i, j, k]$ is the scalar differential change that the j'th dimension of the i'th point experiences due to a first order change in the k'th dimension.

It may be the case that the Jacobian is constant across space - in this case axis zero may have length 1 to allow for broadcasting.

RaisesTriangleContainmentError: - If any point is outside any triangle of this PWA.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping *source* and *target*, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Typetype (self)

```
set_target (new_target)
```

Update this object so that it attempts to recreate the new_target.

Parametersnew_target (PointCloud) - The new target that this object should try and regenerate.

has_true_inverse

The inverse is true.

TypeTrue

n_dims

The number of dimensions of the *target*.

Type*int*

n_dims_output

The output of the data from the transform.

None if the output of the transform is not dimension specific.

Typeint or None

n_points

The number of points on the *target*.

Type*int*

n_tris

The number of triangles in the triangle list.

Type*int*

source

The source **PointCloud** that is used in the alignment.

The source is not mutable.

TypePointCloud

target

The current **PointCloud** that this object produces.

To change the target, use *set_target()*.

TypePointCloud

trilist

The triangle list.

Type (n_tris, 3) ndarray

DifferentiableThinPlateSplines

class menpofit.transform.DifferentiableThinPlateSplines (source, target, kernel=None)
Bases: ThinPlateSplines, DL, DX

The Thin Plate Splines (TPS) alignment between 2D *source* and *target* landmarks. The transform can compute its own derivative with respect to spatial changes, as well as anchor landmark changes.

Parameters

•source ((N, 2) ndarray) – The source points to apply the tps from

•target ((N, 2) *ndarray*) – The target points to apply the tps to

•kernel (*class* or None, optional) – The differentiable kernel to apply. Possible options are *DifferentiableR2LogRRBF* and *DifferentiableR2LogR2RBF*. If None, then *DifferentiableR2LogR2RBF* is used.

aligned_source()

The result of applying self to source

TypePointCloud

alignment_error()

The Frobenius Norm of the difference between the target and the aligned source.

Typefloat

```
apply (x, batch_size=None, **kwargs)
```

Applies this transform to x.

If x is **Transformable**, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply() method.

Parameters

•**x** (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.

•**batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.

•kwargs (dict) - Passed through to _apply().

Returnstransformed (type (x)) – The transformed object or array

apply_inplace(*args, **kwargs)

Deprecated as public supported API, use the non-mutating *apply()* instead.

For internal performance-specific uses, see _apply_inplace().

compose_after(transform)

Returns a TransformChain that represents this transform composed after the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, o.

Parameterstransform (Transform) – Transform to be applied before self

Returnstransform (TransformChain) – The resulting transform chain.

compose_before(transform)

Returns a TransformChain that represents this transform composed before the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

Parameterstransform (Transform) – Transform to be applied after self

Returnstransform (TransformChain) – The resulting transform chain.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other **Copyable** objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returnstype (self) - A copy of this object

d_dl (points)

Calculates the Jacobian of the TPS warp wrt to the source landmarks assuming that he target is equal to the source. This is a special case of the Jacobian wrt to the source landmarks that is used in AAMs to weight the relative importance of each pixel in the reference frame wrt to each one of the source landmarks.

 $dW_dl = dOmega_dl * k(points) = T * d_L**-1_dl * k(points) = T * -L**-1 dL_dl L**-1 * k(points)$

per point (c, d) = (d, c+3) (c+3, c+3) (c+3, c+3, c, d) (c+3, c+3) (c+3) (c, d) = (d, c+3) (c+3, c+3, c, d) (c+3) (c+3) (c, d) = (d, c+3) (c+3, c+3, c, d) (c+3) (c+3

- **Parameterspoints** ((n_points, n_dims) *ndarray*) The spatial points at which the derivative should be evaluated.
- **ReturnsdW/dl** ((*n_points, n_params, n_dims*) *ndarray*) The Jacobian of the transform wrt to the source landmarks evaluated at the previous points and assuming that the target is equal to the source.

d_dx (points)

The first order derivative of this TPS warp wrt spatial changes evaluated at points.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returns

d_dx((n_points, n_dims, n_dims) *ndarray*) – The Jacobian wrt spatial changes.

 $d_dx[i, j, k]$ is the scalar differential change that the j'th dimension of the i'th point experiences due to a first order change in the k'th dimension.

It may be the case that the Jacobian is constant across space - in this case axis zero may have length 1 to allow for broadcasting.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping *source* and *target*, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Typetype(self)

set_target (new_target)

Update this object so that it attempts to recreate the new_target.

Parametersnew_target (**PointCloud**) – The new target that this object should try and regenerate.

has_true_inverse

type-False

n_dims

The number of dimensions of the *target*.

Type*int*

n_dims_output

The output of the data from the transform.

None if the output of the transform is not dimension specific.

Typeint or None

n_points

The number of points on the *target*.

Type*int*

source

The source **PointCloud** that is used in the alignment.

The source is not mutable.

TypePointCloud

target

The current **PointCloud** that this object produces.

To change the target, use set_target().

TypePointCloud

RBF

DifferentiableR2LogR2RBF

```
class menpofit.transform.DifferentiableR2LogR2RBF(c)
Bases: R2LogR2RBF, DL
```

Dases. Relogicenci, Di

The $r^2 \log r^2$ basis function.

The derivative of this function is $2r(\log r^2 + 1)$, where r = ||x - c||.

It can compute its own derivative with respect to landmark changes.

```
apply (x, batch_size=None, **kwargs)
Applies this transform to x.
```

If x is **Transformable**, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply() method.

Parameters

•**x** (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.

•**batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.

•kwargs (dict) – Passed through to _apply().

Returnstransformed (type (x)) – The transformed object or array

apply_inplace (*args, **kwargs)

Deprecated as public supported API, use the non-mutating *apply()* instead.

For internal performance-specific uses, see _apply_inplace().

compose_after(transform)

Returns a **TransformChain** that represents **this** transform composed **after** the given transform:

c = a.compose_after(b) c.apply(p) == a.apply(b.apply(p))

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, o.

Parameterstransform (Transform) – Transform to be applied before self

Returnstransform (TransformChain) – The resulting transform chain.

compose_before(transform)

Returns a TransformChain that represents this transform composed before the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

Parameterstransform (Transform) – Transform to be applied after self

Returnstransform (TransformChain) – The resulting transform chain.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other **Copyable** objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returnstype(self) – A copy of this object

d_dl (points)

Apply the derivative of the basis function with the centres and the points given by *points*. Let *points* be x, then $2(x-c)^T (\log r_{x,l}^2 + 1) = 2(x-c)^T (2\log r_{x,l} + 1)$ where $r_{x,l} = ||x-c||$.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returnsd_dl ((n_points, n_centres, n_dims) *ndarray*) – The jacobian tensor representing the first order derivative of the radius from each centre wrt the centre's position, evaluated at each point.

n_centres

The number of centres.

Type*int*

n_dims

The RBF can only be applied on points with the same dimensionality as the centres.

Type*int*

n_dims_output

The result of the transform has a dimension (weight) for every centre.

Type*int*

DifferentiableR2LogRRBF

```
class menpofit.transform.DifferentiableR2LogRRBF(c)
```

Bases: R2LogRRBF, DL

Calculates the $r^2 \log r$ basis function.

The derivative of this function is $r(1 + 2\log r)$, where r = ||x - c||.

It can compute its own derivative with respect to landmark changes.

apply (*x*, *batch_size=None*, ***kwargs*) Applies this transform to x.

If x is **Transformable**, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply() method.

Parameters

•**x** (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.

•**batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.

•kwargs (*dict*) – Passed through to _apply().

Returnstransformed (type (x)) – The transformed object or array

apply_inplace(*args, **kwargs)

Deprecated as public supported API, use the non-mutating apply() instead.

For internal performance-specific uses, see _apply_inplace().

compose_after(transform)

Returns a TransformChain that represents this transform composed after the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, o.

Parameterstransform (Transform) – Transform to be applied before self

Returnstransform (TransformChain) – The resulting transform chain.

compose_before(transform)

Returns a TransformChain that represents this transform composed before the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

Parameterstransform (Transform) – Transform to be applied after self

Returnstransform (TransformChain) – The resulting transform chain.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other **Copyable** objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returnstype (self) – A copy of this object

d_dl (points)

The derivative of the basis function with the coordinate system evaluated at *points*. Let *points* be x, then $(x-c)^T(1+2\log r_{x,l})$, where $r_{x,l} = ||x-c||$.

Parameterspoints ((n_points, n_dims) *ndarray*) – The spatial points at which the derivative should be evaluated.

Returnsd_dl ((n_points, n_centres, n_dims) ndarray) - The Jacobian wrt landmark changes.

n_centres

The number of centres.

Type*int*

n_dims

The RBF can only be applied on points with the same dimensionality as the centres.

Type*int*

n_dims_output

The result of the transform has a dimension (weight) for every centre.

Type*int*

menpofit.visualize

Print Utilities

print_progress

Print the remaining time needed to compute over an iterable.

To use, wrap an existing iterable with this function before processing in a for loop (see example).

The estimate of the remaining time is based on a moving average of the last 100 items completed in the loop.

This method is identical to *menpo.visualize.print_progress*, but adds a *verbose* flag which allows the printing to be skipped if necessary.

Parameters

•iterable (*iterable*) – An iterable that will be processed. The iterable is passed through by this function, with the time taken for each complete iteration logged.

•**prefix** (*str*, optional) – If provided a string that will be prepended to the progress report at each level.

- •**n_items** (*int*, optional) Allows for iterator to be a generator whose length will be assumed to be *n_items*. If not provided, then iterator needs to be *Sizable*.
- •offset (*int*, optional) Useful in combination with n_items report back the progress as if *offset* items have already been handled. n_items will be left unchanged.
- •**show_bar** (*bool*, optional) If False, The progress bar (e.g. [=======]) will be hidden.
- •show_count (bool, optional) If False, The item count (e.g. (4/25)) will be hidden.
- •**show_eta** (*bool*, optional) If False, The estimated time to finish (e.g. 00:00:03 remaining) will be hidden.
- •end_with_newline (*bool*, optional) If False, there will be no new line added at the end of the dynamic printing. This means the next print statement will overwrite the dynamic report presented here. Useful if you want to follow up a print_progress with a second print_progress, where the second overwrites the first on the same line.

•verbose (bool, optional) – Printing is performed only if set to True.

RaisesValueError - offset provided without n_items

Examples

This for loop:

```
from time import sleep
for i in print_progress(range(100)):
        sleep(1)
```

prints a progress report of the form:

```
[========= ] 70% (7/10) - 00:00:03 remaining
```

Errors Visualization

statistics_table

Function that generates a table with statistical measures on the fitting results of various methods using pandas. It supports multiple types of statistical measures.

Note that the returned object is a pandas table which can be further converted to Latex tabular or simply a string. See the examples for more details.

Parameters

•errors (list of list of float) – A list that contains lists of float with the errors per method.

•method_names (*list* of *str*) – The *list* with the names that will appear for each method. Note that it must have the same length as *errors*.

•auc_max_error (*float*) – The maximum error value for computing the area under the curve.

•auc_error_step (*float*) – The sampling step of the error bins for computing the area under the curve.

•auc_min_error (*float*, optional) – The minimum error value for computing the area under the curve.

•**stats_types** (*list* of *str* or None, optional) – The types of statistical measures to compute. Possible options are:

Value	Description
mean	The mean value of the errors.
std	The standard deviation of the errors.
median	The median value of the errors.
mad	The median absolute deviation of the errors.
max	The max value of the errors.
аис	The area under the curve based on the CED of the errors.
fr	The failure rate (percentage of images that failed).

If None, then all of them will be used with the above order.

- •**stats_names** (*list* of *str*, optional) The *list* with the names that will appear for each statistical measure type selected in *stats_types*. Note that it must have the same length as *stats_types*.
- •**sort_by** (*str* or None, optional) The column to use for sorting the methods. If None, then no sorting is performed and the methods will appear in the provided order of *method_names*. Possible options are:

Value	Description
mean	The mean value of the errors.
std	The standard deviation of the errors.
median	The median value of the errors.
mad	The median absolute deviation of the errors.
max	The max value of the errors.
аис	The area under the curve based on the CED of the errors.
fr	The failure rate (percentage of images that failed).

•**precision** (*int*, optional) – The precision of the reported values, i.e. the number of decimals.

Raises

•ValueError - stat_type must be selected from [mean, std, median, mad, max, auc, fr]

•ValueError - sort_by must be selected from [mean, std, median, mad, max, auc, fr]

•ValueError - stats_types and stats_names must have the same length

Returnstable (*pandas.DataFrame*) – The pandas table. It can be further converted to various format, such as Latex tabular or *str*.

Examples

Let us create some errors for 3 methods sampled from Normal distributions with different mean and standard deviations:

```
import numpy as np
from menpofit.visualize import statistics_table
method_names = ['Method_1', 'Method_2', 'Method_3']
```

We can create a pandas *DataFrame* as:

tab

Pandas offers excellent functionalities. For example, the table can be converted to an *str* as:

print(tab.to_string())

or to a Latex tabular as:

print(tab.to_latex())

plot_cumulative_error_distribution

menpofit.visualize.plot_cumulative_error_distribution	(errors, error_range=None,
	figure_id=None,
	new_figure=False, ti-
	tle='Cumulative Error Distri-
	<i>bution'</i> , <i>x_label='Normalized</i>
	Point-to-Point Error',
	y_label='Images Propor-
	tion', legend_entries=None,
	render_lines=True,
	line_colour=None,
	<i>line_style='-', line_width=2,</i>
	render_markers=True,
	marker_style='s',
	marker_size=7,
	marker_face_colour='w',
	marker_edge_colour=None,
	marker_edge_width=2,
	render_legend=True,
	legend_title=None,
	legend_font_name='sans-
	serif', leg-
	end_font_style='normal',
	legend_font_size=10, leg-
	end_font_weight='normal',
	legend_marker_scale=1.0,
	<i>legend_location=2, leg-</i>
	end_bbox_to_anchor=(1.05,
	1.0), leg-
	end_border_axes_pad=1.0,
	legend_n_columns=1, leg-
	end_horizontal_spacing=1.0,
	legend_vertical_spacing=1.0,
	legend_border=True, leg-
	end_border_padding=0.5,
	legend_shadow=False, leg-
	end_rounded_corners=False,
	render_axes=True,
	axes_font_name=`sans-
	serif, axes_font_size=10,
	axes_font_style= normal,
	axes_font_weight= normal,
	axes_x_limits=None,
	axes_y_limits=None,
	$axes_x_ncks=None,$
	$axes_y_ncks=none,$
	jigure_size=(/, /),
	arid line style=' '
	$g_{iii} une_{siyle} = -$, arid line width = 0.5
Dist the sumulative error distribution (CED) of the provided fitting errors	gria_une_wiain=0.5)

Plot the cumulative error distribution (CED) of the provided fitting errors.

Parameters

•errors (*list* of *lists*) – A *list* with *lists* of fitting errors. A separate CED curve will be rendered for each errors *list*.

•error_range (*list* of *float* with length 3, optional) – Specifies the horizontal axis range, i.e.

```
error_range[0] = min_error
error_range[1] = max_error
error_range[2] = error_step
```

If None, then 'error_range = [0., 0.101, 0.005]'.

•figure_id (object, optional) – The id of the figure to be used.

•new_figure (bool, optional) – If True, a new figure is created.

•title (*str*, optional) – The figure's title.

•x_label (*str*, optional) – The label of the horizontal axis.

•y_label (str, optional) – The label of the vertical axis.

•legend_entries (*list of 'str* or None, optional) – If *list* of *str*, it must have the same length as *errors list* and each *str* will be used to name each curve. If None, the CED curves will be named as '*Curve* %d'.

•render_lines (*bool* or *list* of *bool*, optional) – If True, the line will be rendered. If *bool*, this value will be used for all curves. If *list*, a value must be specified for each fitting errors curve, thus it must have the same length as *errors*.

•line_colour (*colour* or *list* of *colour* or None, optional) – The colour of the lines. If not a *list*, this value will be used for all curves. If *list*, a value must be specified for each curve, thus it must have the same length as *y_axis*. If None, the colours will be linearly sampled from jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

- •line_style ({ '-', '--', '-.', ':'} or *list* of those, optional) The style of the lines. If not a *list*, this value will be used for all curves. If *list*, a value must be specified for each curve, thus it must have the same length as *errors*.
- •line_width (*float* or *list* of *float*, optional) The width of the lines. If *float*, this value will be used for all curves. If *list*, a value must be specified for each curve, thus it must have the same length as *errors*.
- •render_markers (*bool* or *list* of *bool*, optional) If True, the markers will be rendered. If *bool*, this value will be used for all curves. If *list*, a value must be specified for each curve, thus it must have the same length as *errors*.

•marker_style (marker or list of markers, optional) – The style of the markers. If not a *list*, this value will be used for all curves. If *list*, a value must be specified for each curve, thus it must have the same length as *errors*. Example *marker* options

{'.', ',', 'o', 'v', '^', '<', '>', '+', 'x', 'D', 'd', 's', 'p', '*', 'h', 'H', '1', '2', '3', '4', '8'}

•marker_size (*int* or *list* of *int*, optional) – The size of the markers in points. If *int*, this value will be used for all curves. If *list*, a value must be specified for each curve, thus it must have the same length as *errors*.

•marker_face_colour (*colour* or *list* of *colour* or None, optional) – The face (filling) colour of the markers. If not a *list*, this value will be used for all curves. If *list*, a value must be specified for each curve, thus it must have the same length as *errors*. If None, the colours will be linearly sampled from jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_colour (*colour* or *list* of *colour* or None, optional) – The edge colour of the markers. If not a *list*, this value will be used for all curves. If *list*, a value must be specified for each curve, thus it must have the same length as *errors*. If None, the colours will be linearly sampled from jet colormap. Example *colour* options are

```
{'r', 'g', 'b', 'c', 'm', 'k', 'w'}
or
(3, ) ndarray
```

•marker_edge_width (*float* or *list* of *float*, optional) – The width of the markers' edge. If *float*, this value will be used for all curves. If *list*, a value must be specified for each curve, thus it must have the same length as *errors*.

•render_legend (*bool*, optional) – If True, the legend will be rendered.

•legend_title (*str*, optional) – The title of the legend.

•legend_font_name (See below, optional) - The font of the legend. Example options

{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}

•legend_font_style ({'normal', 'italic', 'oblique'}, optional) - The font style of the legend.

•legend_font_size (*int*, optional) – The font size of the legend.

•legend_font_weight (See below, optional) – The font weight of the legend. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
'extra bold', 'black'}
```

•legend_marker_scale (*float*, optional) – The relative size of the legend markers with respect to the original

•legend_location (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- •legend_bbox_to_anchor ((*float*, *float*), optional) The bbox that the legend will be anchored.
- •legend_border_axes_pad (*float*, optional) The pad between the axes and legend border.
- •legend_n_columns (int, optional) The number of the legend's columns.
- •legend_horizontal_spacing (float, optional) The spacing between the columns.
- •legend_vertical_spacing (*float*, optional) The vertical space between the legend entries.
- •legend_border (bool, optional) If True, a frame will be drawn around the legend.
- •legend_border_padding (*float*, optional) The fractional whitespace inside the legend border.
- •legend_shadow (bool, optional) If True, a shadow will be drawn behind legend.
- •legend_rounded_corners (*bool*, optional) If True, the frame's corners will be rounded (fancybox).
- •render_axes (bool, optional) If True, the axes will be rendered.
- •axes_font_name (See below, optional) The font of the axes. Example options

{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace'}

•axes_font_size (*int*, optional) – The font size of the axes.

- •axes_font_style({'normal', 'italic', 'oblique'}, optional) The font style of the axes.
- •axes_font_weight (See below, optional) The font weight of the axes. Example options

•axes_x_limits (*float* or (*float*, *float*) or None, optional) – The limits of the x axis. If *float*, then it sets padding on the right and left of the graph as a percentage of the curves' width. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set to (0., error_range[1]).

•axes_y_limits (*float* or (*float*, *float*) or None, optional) – The limits of the y axis. If *float*, then it sets padding on the top and bottom of the graph as a percentage of the curves'

height. If *tuple* or *list*, then it defines the axis limits. If None, then the limits are set to (0., 1.).

•axes_x_ticks (*list* or *tuple* or None, optional) – The ticks of the x axis.

•axes_y_ticks (list or tuple or None, optional) – The ticks of the y axis.

•figure_size ((float, float) or None, optional) – The size of the figure in inches.

•render_grid (*bool*, optional) – If True, the grid will be rendered.

•grid_line_style ({ '-', '--', '-.', ':'}, optional) – The style of the grid lines.

•grid_line_width (*float*, optional) – The width of the grid lines.

Raises ValueError - legend_entries list has different length than errors list

Returnsviewer (*menpo.visualize.GraphPlotter*) – The viewer object.

Index

A

AAM (class in menpofit.aam.base), 11 aam (menpofit.aam.LucasKanadeAAMFitter attribute), 130 31 AAMAlgorithmResult (class in menpofit.aam.result), 70 AAMResult (class in menpofit.aam.result), 53 ActiveShapeModel (class in menpofit.clm), 153 align shape with bounding box() (in module menpofit.fitter), 316 align_shapes() (in module menpofit.builder), 291 aligned_source() (menpofit.transform.DifferentiableAlignmentAffine method), 432 aligned_source() (menpofit.transform.DifferentiableAlignmentSimilarity method), 427 aligned_source() (menpofit.transform.DifferentiablePiecewiseAffine method), 438 aligned source() (menpofit.transform.DifferentiableThinPlateSplines method), 440alignment_error() (menpofit.transform.DifferentiableAlignmentAffine method), 432 alignment_error() (men $pofit.transform.DifferentiableAlignmentSimilarity^{appearance_model}$ method), 427 alignment_error() (menpofit.transform.DifferentiablePiecewiseAffine method), 438 alignment_error() (menpofit.transform.DifferentiableThinPlateSplines method), 440 52 AlternatingForwardCompositional (class in menpofit.aam), 34 AlternatingInverseCompositional (class in menpofit.aam), 35 AlternatingRegularisedLandmarkMeanShift (class in

menpofit.unified aam clm), 166 appearance costs (menpofit.aps.result.APSAlgorithmResult attribute), appearance_costs (menpofit.aps.result.APSResult attribute), 113 appearance_model (menpofit.aam.AlternatingForwardCompositional attribute), 35 appearance_model (menpofit.aam.AlternatingInverseCompositional attribute), 36 appearance model (menpofit.aam.AppearanceWeightsGaussNewton attribute), 46 appearance_model (menpofit.aam.AppearanceWeightsNewton attribute), 44 appearance model (menpofit.aam.MeanTemplateGaussNewton attribute), 49 appearance_model (menpofit.aam.MeanTemplateNewton attribute), 47 appearance_model (menpofit.aam.ModifiedAlternatingForwardCompositional attribute), 36 (menpofit.aam.ModifiedAlternatingInverseCompositional attribute), 37 appearance_model (menpofit.aam.ProjectOutForwardCompositional attribute), 38 appearance_model (menpofit.aam.ProjectOutGaussNewton attribute), appearance model (menpofit.aam.ProjectOutInverseCompositional attribute), 39 appearance_model (menpofit.aam.ProjectOutNewton attribute), 51

appearance_model (men-	apply() (menpofit.transform.DifferentiablePiecewiseAffine method) 438
attribute), 40	apply() (menpofit.transform.DifferentiableR2LogR2RBF
appearance_model (men-	method), 443
pofit.aam.SimultaneousInverseCompositional	apply() (menpofit.transform.DifferentiableR2LogRRBF
attribute), 41	method), 445
appearance_model (men-	apply() (menpofit.transform.DifferentiableSimilarity
pofit.aam.WibergForwardCompositional	method), 423
attribute), 41	apply() (menpofit.transform.Differentiable I hinPlateSplines
appearance_model (men-	apply() (manpofit transform LinearOrthoMDTransform
tribute) 42	method) 414
appearance model (mennofit ans Forward attribute) 97	apply() (menpofit transform OrthoMDTransform
appearance_model (menpofit.aps.Inverse attribute), 96	method), 411
appearance parameters (men-	apply inplace() (menpofit.transform.DifferentiableAffine
pofit.aam.result.AAMAlgorithmResult at-	method), 418
tribute), 86	apply_inplace() (menpofit.transform.DifferentiableAlignmentAffine
appearance_parameters (men-	method), 433
pofit.aam.result.AAMResult attribute), 69	apply_inplace() (menpofit.transform.DifferentiableAlignmentSimilarity
appearance_parameters (men-	method), 428
pofit.unified_aam_clm.result.UnifiedAAMCLM	AbgenityhinResault) (menpofit.transform.DifferentiablePiecewiseAffine
attribute), 201	method), 438
appearance_parameters (men-	apply_inplace() (menpofit.transform.DifferentiableR2LogR2RBF
pofit.unified_aam_clm.result.UnifiedAAMCLMI	Result method), 443
attribute), 184	apply_inplace() (menpofit.transform.DifferentiableR2LogRRBF
appearance_reconstructions() (menpofit.aam.base.AAM	method), 445
method), 12	apply_inplace() (menpofit.transform.DifferentiableSimilarity
appearance_reconstructions() (menpofit.aam.LinearAAM	method), 423
method), 20	apply_inplace() (menpoint.transform.Differentiable I hinPlateSplines
appearance_reconstructions() (men-	method), 441
23	method) 415
appearance reconstructions() (men-	apply inplace() (menofit transform OrthoMDTransform
pofit.aam.LucasKanadeAAMFitter method).	method), 412
29	aps (menpofit.aps.GaussNewtonAPSFitter attribute), 95
appearance reconstructions() (men-	APSAlgorithmResult (class in menpofit.aps.result), 114
pofit.aam.MaskedAAM method), 16	APSResult (class in menpofit.aps.result), 97
appearance_reconstructions() (menpofit.aam.PatchAAM	area_under_curve_and_failure_rate() (in module men-
method), 25	pofit.error), 307
appearance_reconstructions() (men-	as_non_alignment() (men-
pofit.unified_aam_clm.base.UnifiedAAMCLM	pofit.transform.DifferentiableAlignmentAffine
method), 160	method), 433
appearance_reconstructions() (men-	as_non_alignment() (men-
pofit.unified_aam_clm.UnifiedAAMCLMFitter	pofit.transform.DifferentiableAlignmentSimilarity
method), 164	method), 428
AppearanceWeightsGaussNewton (class in men-	as_vector() (menpofit.modelinstance.GlobalPDM
pofit.aam), 44	method), 332
AppearanceWeightsNewton (class in menpofit.aam), 43	as_vector() (menpofit.modelinstance.GlobalSimilarityModel
apply() (menpofit.transform.DifferentiableAffine	method), 329
method), 418	as_vector() (menpont.modelinstance.Niodelinstance
appry() (inclipoint.transform.DifferentiableAlignmentAffine method) 432	as vector() (mennofit modelingtance OrthoDDM
apply() (menpofit transform Differentiable A lignment Simil	arity method) 335
method), 427	as vector() (menpofit.modelinstance.PDM method). 330
	,,, _,

- as_vector() (menpofit.transform.DifferentiableAffine C method), 418 ch
- as_vector() (menpofit.transform.DifferentiableAlignmentAffineck_callable() (in module menpofit.checks), 297 method), 433 check_diagonal() (in module menpofit.checks), 294
- as_vector() (menpofit.transform.DifferentiableAlignmentSi method), 428
- as_vector() (menpofit.transform.DifferentiableSimilarity method), 423
- as_vector() (menpofit.transform.LinearOrthoMDTransform method), 415
- as_vector() (menpofit.transform.OrthoMDTransform method), 412
- ATM (class in menpofit.atm.base), 131
- atm (menpofit.atm.LucasKanadeATMFitter attribute), 145

В

bb area() (in module menpofit.error), 301 bb_avg_edge_length() (in module menpofit.error), 301 bb_avg_edge_length_49_euclidean_error() (in module menpofit.error), 309 bb_avg_edge_length_68_euclidean_error() (in module menpofit.error), 308 bb diagonal() (in module menpofit.error), 301 bb perimeter() (in module menpofit.error), 301 build fitter interfaces() (menpofit.aam.base.AAM method), 13 build fitter interfaces() (menpofit.aam.LinearAAM method), 20 build_fitter_interfaces() (menpofit.aam.LinearMaskedAAM method), 23 build_fitter_interfaces() (menpofit.aam.MaskedAAM method), 16 build fitter interfaces() (menpofit.aam.PatchAAM method), 26 build_fitter_interfaces() (menpofit.atm.base.ATM method), 132 build_fitter_interfaces() (menpofit.atm.LinearATM method), 138 build fitter interfaces() (menpofit.atm.LinearMaskedATM method), 140 build fitter interfaces() (menpofit.atm.MaskedATM method), 135 build_fitter_interfaces() (menpofit.atm.PatchATM method), 142 build_fitter_interfaces() (menpofit.unified aam clm.base.UnifiedAAMCLM method), 161 build_patch_reference_frame() (in module menpofit.builder), 291 build_reference_frame() (in module menpofit.builder), 291

С check_algorithm_cls() (in module menpofit.checks), 298 check_diagonal() (in module menpofit.checks), 295 milacitygraph() (in module menpofit.checks), 299 check_landmark_trilist() (in module menpofit.checks), 295 check_max_components() (in module menpofit.checks), 298 check max iters() (in module menpofit.checks), 297 check_model() (in module menpofit.checks), 296 check multi scale param() (in module menpofit.checks), 296 check patch shape() (in module menpofit.checks), 297 check sampling() (in module menpofit.checks), 298 check scales() (in module menpofit.checks), 296 check trilist() (in module menpofit.checks), 296 CLM (class in menpofit.clm), 148 clm (menpofit.clm.GradientDescentCLMFitter attribute), 152 compose_after() (menpofit.transform.DifferentiableAffine method), 418 compose_after() (menpofit.transform.DifferentiableAlignmentAffine method), 433 compose_after() (menpofit.transform.DifferentiableAlignmentSimilarity method), 428 compose after() (menpofit.transform.DifferentiablePiecewiseAffine method), 438 compose after() (menpofit.transform.DifferentiableR2LogR2RBF method), 443 compose after()(menpofit.transform.DifferentiableR2LogRRBF method), 445 compose after() (menpofit.transform.DifferentiableSimilarity method), 423 compose after() (menpofit.transform.DifferentiableThinPlateSplines method), 441 compose_after() (menpofit.transform.LinearOrthoMDTransform method), 415 compose_after() (menpofit.transform.OrthoMDTransform method), 412 compose_after_from_vector_inplace() (menpofit.transform.OrthoMDTransform method), 412 compose after inplace() (menpofit.transform.DifferentiableAffine method). 419 compose_after_inplace() (menpofit.transform.DifferentiableAlignmentAffine method), 433 compose after inplace() (menpofit.transform.DifferentiableAlignmentSimilarity method), 428

compose_after_inplace() (menpofit.transform.DifferentiableSimilarity

	method), 423	tribute), 426
compose_	_before() (men-	composes_with (menpofit.transform.DifferentiableAffine
	pofit.transform.DifferentiableAffine method),	attribute), 421
	419	$composes_with\ (menpofit.transform.DifferentiableAlignmentAffine$
compose_	_before() (men-	attribute), 436
	pofit.transform.DifferentiableAlignmentAffine	$composes_with\ (menpofit.transform.DifferentiableAlignmentSimilarity$
	method), 433	attribute), 431
compose_	_before() (men-	composes_with (menpofit.transform.DifferentiableSimilarity
	pofit.transform.DifferentiableAlignmentSimilarit	y attribute), 426
	method), 428	compute_cumulative_error() (in module menpofit.error),
compose_	_before() (men-	306
	pofit.transform.DifferentiablePiecewiseAffine	compute_features() (in module menpofit.builder), 292
	method), 438	compute_reference_shape() (in module men-
compose_	_before() (men-	pofit.builder), 292
	pofit.transform.DifferentiableR2LogR2RBF	compute_statistical_measures() (in module men-
	method), 444	pofit.error), 307
compose_	_before() (men-	copy() (menpofit.modelinstance.GlobalPDM method),
	pofit.transform.DifferentiableR2LogRRBF	
	method), 445	copy() (menpoht.modelinstance.GlobalSimilarityModel
compose_	_before() (men-	method), 329
	polit.transform.DifferentiableSimilarity	copy() (menpolit.modelinstance.Modelinstance method),
	method), 424	$\frac{321}{2}$
compose_	_Delore() (men-	copy() (menpoint.modelinstance.OrthoPDM method), 555
	mothed) 441	copy() (menpoint.modelinstance.PDM method), 550
2000000	hefera() (man	(inenpoint transform. Differentiable Affine method),
compose_	_Defore() (Incli-	419 conv() (mennofit transform Differentiable Alignment Affine
	method) 415	method) 434
compose	hefore() (men-	copy() (menpofit transform Differentiable A lignment Similarity
compose_	pofit transform OrthoMDTransform method)	method) 429
	412	copy() (mennofit transform DifferentiablePiecewiseAffine
compose	before inplace() (men-	method) 439
c ompose <u>-</u>	pofit transform DifferentiableAffine method).	copy() (menpofit transform DifferentiableR2LogR2RBF
	419	method). 444
compose	before inplace() (men-	copy() (menpofit.transform.DifferentiableR2LogRRBF
·····	pofit.transform.DifferentiableAlignmentAffine	method), 445
	method), 434	copy() (menpofit.transform.DifferentiableSimilarity
compose	_before_inplace() (men-	method), 424
	pofit.transform.DifferentiableAlignmentSimilarit	ycopy() (menpofit.transform.DifferentiableThinPlateSplines
	method), 429	method), 441
compose_	_before_inplace() (men-	copy() (menpofit.transform.LinearOrthoMDTransform
	pofit.transform.DifferentiableSimilarity	method), 415
	method), 424	copy() (menpofit.transform.OrthoMDTransform method),
composes	s_inplace_with (men-	413
	pofit.transform.DifferentiableAffine attribute),	CorrelationFilterExpertEnsemble (class in menpofit.clm),
	421	154
composes	s_inplace_with (men-	cost_closure() (menpofit.lk.ECC method), 214
	pofit.transform.DifferentiableAlignmentAffine	cost_closure() (menpofit.lk.FourierSSD method), 212
	attribute), 436	cost_closure() (menpofit.lk.GradientCorrelation method),
composes	s_inplace_with (men-	217
	pofit.transform.DifferentiableAlignmentSimilarit	ycost_closure() (menpofit.lk.GradientImages method), 215
	attribute), 431	cost_closure() (menpofit.lk.SSD method), 211
composes	s_inplace_with (men-	costs (menpoht.aam.result.AAMAlgorithmResult at-
	pofit.transform.DifferentiableSimilarity at-	tribute), 86

costs (1 costs	nenpofit.aam.result.AAMResult attribute), 69 (menpofit.aps.result.APSAlgorithmResult at-	d_dx() (menpofit.transform.DifferentiableAffine method), 420
costs (1	tribute), 130	d_dx() (menpofit.transform.DifferentiableAlignmentAffine
costs	(menpofit.lk.result.LucasKanadeAlgorithmResult attribute), 251	d_dx() (menpofit.transform.DifferentiableAlignmentSimilarity method), 429
costs	(menpofit.lk.result.LucasKanadeResult attribute), 234	d_dx() (menpofit.transform.DifferentiablePiecewiseAffine method), 439
costs (r	nenpofit.result.MultiScaleNonParametricIterativeRe attribute), 393	sdltdx() (menpofit.transform.DifferentiableSimilarity method), 424
costs (r	nenpofit.result.MultiScaleParametricIterativeResult attribute), 410	d_dx() (menpofit.transform.DifferentiableThinPlateSplines method), 442
costs	(menpofit.result.NonParametricIterativeResult at- tribute), 359	decompose() (menpofit.transform.DifferentiableAffine method), 420
costs	(menpofit.result.ParametricIterativeResult at- tribute), 376	decompose() (menpofit.transform.DifferentiableAlignmentAffine method), 434
costs (r	nenpofit.unified_aam_clm.result.UnifiedAAMCLM/ attribute), 201	AlgcoithpoRe()(Inenpofit.transform.DifferentiableAlignmentSimilarity method), 429
costs (r	nenpofit.unified_aam_clm.result.UnifiedAAMCLMI attribute), 184	Rescotmpose() (menpofit.transform.DifferentiableSimilarity method), 425
D		deformation_costs (men-
d dl()	(menpofit.differentiable.DL method), 299	130
d_dl() ((menpofit.transform.DifferentiablePiecewiseAffine method), 439	deformation_costs (menpofit.aps.result.APSResult attribute), 113
d_dl()	(menpofit.transform.DifferentiableR2LogR2RBF method), 444	deformation_model (menpofit.aps.Forward attribute), 97 deformation_model (menpofit.aps.Inverse attribute), 96
d_dl()	(menpofit.transform.DifferentiableR2LogRRBF method), 446	dense_target (menpofit.transform.LinearOrthoMDTransform attribute), 417
d_dl() ((menpofit.transform.DifferentiableThinPlateSplines method) 442	densify_shapes() (in module menpofit.builder), 292 DifferentiableAffine (class in menpofit transform), 418
d dp()	(menpofit.differentiable.DP method), 300	DifferentiableAlignmentAffine (class in men-
d_dp()	(menpofit.modelinstance.GlobalPDM method), 333	pofit.transform), 432 DifferentiableAlignmentSimilarity (class in men-
d_dp()	(menpofit.modelinstance.GlobalSimilarityModel method), 329	pofit.transform), 427 DifferentiablePiecewiseAffine (class in men-
d_dp()	(menpofit.modelinstance.ModelInstance method), 327	pofit.transform), 437 DifferentiableR2LogR2RBF (class in men-
d_dp()	(menpofit.modelinstance.OrthoPDM method), 335	pofit.transform), 443 DifferentiableR2LogRRBF (class in menpofit.transform),
d_dp()	(menpofit.modelinstance.PDM method), 331	445 DifferentiableSimilarity (class in manpafit transform)
d_dp()	(menpolit.transform.DifferentiableAffine method), 420	422
d_dp()	(menpofit.transform.DifferentiableAlignmentAffine method), 434	DifferentiableThinPlateSplines (class in men- pofit.transform), 440
d_dp()	(menpofit.transform.DifferentiableAlignmentSimilar method), 429	rflisplacements() (menpofit.aam.result.AAMAlgorithmResult method), 71
d_dp()	(menpofit.transform.DifferentiableSimilarity method), 424	displacements() (menpofit.aam.result.AAMResult method), 53
d_dp()	(menpofit.transform.LinearOrthoMDTransform method), 416	displacements() (menpofit.aps.result.APSAlgorithmResult method), 115
d_dp()	(menpofit.transform.OrthoMDTransform method), 413	displacements() (menpofit.aps.result.APSResult method), 98
d_dx()	(menpofit.differentiable.DX method), 300	$displacements () \ (menpofit.lk.result.LucasKanadeAlgorithmResult$

method), 235	DX (class in menpofit.differentiable), 300
displacements () (menpofit.lk.result.LucasKanadeResult	F
method), 218	E
displacements() (menpofit.result.MultiScaleNonParametric	IECCOVERSSUIT menpofit.lk), 214
method), 377	errors() (menpofit.aam.result.AAMAlgorithmResult
displacements() (menpofit.result.MultiScaleParametricItera	tiveResult method), 71
method), 394	errors() (menpofit.aam.result.AAMResult method), 53
displacements() (menpofit.result.NonParametricIterativeRe	selfors() (menpofit.aps.result.APSAlgorithmResult
method), 343	method), 115
displacements() (menpofit.result.ParametricIterativeResult	errors() (menpofit.aps.result.APSResult method), 98
method), 360	errors() (menpofit.lk.result.LucasKanadeAlgorithmResult
displacements() (menpofit.unified_aam_clm.result.Unified/	AAMCLMAleonathmesesult
method), 186	errors() (menpofit.lk.result.LucasKanadeResult method),
displacements() (menpofit.unified_aam_clm.result.Unified/	AAMCLMIgesult
method), 168	errors() (menpofit.result.MultiScaleNonParametricIterativeResult
displacements_stats() (men-	method), 377
pofit.aam.result.AAMAIgorithmResult	errors() (menpofit.result.MultiScaleParametricIterativeResult
method), /1	method), 394
displacements_stats() (menpofit.aam.result.AAMResult	errors() (menpofit.result.NonParametricIterativeResult
method), 53	method), 344
displacements_stats() (men-	errors() (menpofit.result.ParametricIterativeResult
pofit.aps.result.APSAlgorithmResult method),	method), 360
	errors() (menpofit.unified_aam_clm.result.UnifiedAAMCLMAlgorithmRes
(menpoint.aps.resuit.APSResuit	method), 186
method), 98	errors() (menpofit.unified_aam_clm.result.UnifiedAAMCLMResult
displacements_stats() (men-	method), 169
mothed) 225	euclidean_bb_normalised_error() (in module men-
method), 255	pofit.error), 305
noft lk recult L uces Kenede Desult method)	euclidean_distance_indexed_normalised_error() (in mod-
218	ule menpoht.error), 306
displacements stats() (man	euclidean_distance_normalised_error() (in module men-
nofit result MultiScaleNonDarametricIterativeDec	pofit.error), 305
method) 377	"euclidean_error() (in module menpofit.error), 304
displacements_stats() (man	extract_patches() (in module menpolit.builder), 293
nofit result MultiScaleParametricIterativeResult	F
method) 304	1
displacements_stats() (men-	final_error() (menpofit.aam.result.AAMAlgorithmResult
nofit result NonParametricIterativeResult	method), 71
method) 344	final_error() (menpofit.aam.result.AAMResult method),
displacements_stats() (men-	53
pofit result ParametricIterativeResult method)	final_error() (menpofit.aps.result.APSAlgorithmResult
360	method), 115
displacements stats() (men-	final_error() (menpofit.aps.result.APSResult method), 98
pofit unified aam clm result UnifiedAAMCLM	final_error() (menpofit.lk.result.LucasKanadeAlgorithmResult
method). 186	method), 236
displacements stats() (men-	final_error() (menpofit.lk.result.LucasKanadeResult
pofit.unified aam clm.result.UnifiedAAMCLM	method), 219
method). 168	Timal_error() (menpoht.result.MultiScaleNonParametricIterativeResult
distance two indices() (in module menpofit.error). 302	method), 3/8
DL (class in menpofit.differentiable). 299	inal_error() (menpont.result.MultiScaleParametricIterativeResult
DlibERT (class in menpofit.dlib), 202	method), 595
DlibWrapper (class in menpofit.dlib). 205	inal_error() (menpont.result.NonParametriciterativeResult
DP (class in menpofit.differentiable), 300	memou), 544

final_error() (menpofit.result.ParametricIterativeResult method), 360	fit_from_bb() (menpofit.sdm.SupervisedDescentFitter method), 254
final_error() (menpofit.result.Result method), 337	fit_from_bb() (menpofit.unified_aam_clm.UnifiedAAMCLMFitter
final_error() (menpofit.unified_aam_clm.result.UnifiedAAM method) 186	MCLMAlg onithnoR estate fit_from_shape() (menpofit aam LucasKanadeAAMFitter
final error() (menpofit unified aam clm result UnifiedAA)	MCL MResmbethod) 30
method), 169	fit_from_shape() (men-
final_shape (menpofit.aam.result.AAMAlgorithmResult attribute), 86	pofit.aam.SupervisedDescentAAMFitter method), 33
final_shape (menpofit.aam.result.AAMResult attribute), 69	fit_from_shape() (menpofit.aps.GaussNewtonAPSFitter method), 94
final_shape (menpofit.aps.result.APSAlgorithmResult at- tribute), 130	fit_from_shape() (menpofit.atm.LucasKanadeATMFitter method), 145
final_shape (menpofit.aps.result.APSResult attribute), 113	fit_from_shape() (men- pofit.clm.GradientDescentCLMFitter method),
final_shape (menpofit.lk.result.LucasKanadeAlgorithmResu attribute), 251	ult 152 fit from shape() (menpofit.dlib.DlibERT method), 204
final_shape (menpofit.lk.result.LucasKanadeResult at- tribute), 234	fit_from_shape() (menpofit.dlib.DlibWrapper method), 205
final_shape (menpofit.result.MultiScaleNonParametricItera attribute), 393	t íve<u>Ræsml</u> shape() (men- pofit.fitter.MultiScaleNonParametricFitter
$final_shape\ (menpofit.result.MultiScaleParametricIterativeParametri$	Result method), 313
attribute), 410	fit_from_shape() (men-
final_shape (menpofit.result.NonParametricIterativeResult attribute), 359	pofit.fitter.MultiScaleParametricFitter method), 315
final_shape (menpofit.result.ParametricIterativeResult at- tribute), 376	fit_from_shape() (menpofit.io.PickleWrappedFitter method), 320
final_shape (menpofit.result.Result attribute), 342	fit_from_shape() (menpofit.lk.LucasKanadeFitter
final_shape (menpofit.unified_aam_clm.result.UnifiedAAM	ICLMAlgonitettinRiðsúllø7
attribute), 201	fit_from_shape() (menpofit.sdm.RegularizedSDM
final_shape (menpofit.unified_aam_clm.result.UnifiedAAM	ICLMResulmethod), 259
attribute), 184	fit_from_shape() (menpofit.sdm.SupervisedDescentFitter
fit_from_bb() (menpofit.aam.LucasKanadeAAMFitter	method), 254
method), 29	fit_from_shape() (men-
fit_from_bb() (menpofit.aam.SupervisedDescentAAMFitter method), 32	r pofit.unified_aam_clm.UnifiedAAMCLMFitter method), 165
fit_from_bb() (menpofit.aps.GaussNewtonAPSFitter	Forward (class in menpofit.aps), 96
method), 94	ForwardAdditive (class in menpofit.lk), 208
fit_from_bb() (menpofit.atm.LucasKanadeATMFitter	ForwardCompositional (class in menpofit.atm), 146
method), 144	ForwardCompositional (class in menpofit.lk), 209
fit_from_bb() (menpofit.clm.GradientDescentCLMFitter	FourierSSD (class in menpofit.lk), 212
method), 151	frequency_filter_images (men-
fit_from_bb() (menpofit.dlib.DlibERT method), 204	pofit.clm.CorrelationFilterExpertEnsemble
fit_from_bb() (menpofit.dlib.DlibWrapper method), 205	attribute), 156
fit_from_bb() (menpofit.fitter.MultiScaleNonParametricFitt	efrom_vector() (menpofit.modelinstance.GlobalPDM
method), 312	method), 333
fit_from_bb() (menpofit.fitter.MultiScaleParametricFitter method), 314	from_vector() (menpofit.modelinstance.GlobalSimilarityModel method), 329
fit_from_bb() (menpofit.io.PickleWrappedFitter method), 320	from_vector() (menpofit.modelinstance.ModelInstance method), 327
fit_from_bb() (menpofit.lk.LucasKanadeFitter method), 206	from_vector() (menpofit.modelinstance.OrthoPDM method), 335
fit_from_bb() (menpofit.sdm.RegularizedSDM method), 258	from_vector() (menpofit.modelinstance.PDM method), 331

from_vector() (menpofit.transform.DifferentiableAffine	G
method), 420	GaussNewtonAPSFitter (class in menpofit.aps), 93
from_vector() (menpofit.transform.DifferentiableAlignmer	nt affine
method), 435	pofit.fitter), 316
from_vector() (menpofit.transform.DifferentiableAlignmer	tenerative APS (class in menpofit.aps), 88
method), 430	global_parameters (menpofit.modelinstance.GlobalPDM
method) 425	attribute), 334
from vector() (mennofit transform LinearOrthoMDTransfo	global_parameters (menpofit.modelinstance.OrthoPDM
method) 416	attribute), 336
from vector() (menpofit.transform.OrthoMDTransform	global_parameters (men-
method), 413	polit.transform.LinearOrtnowiDTransform
from_vector_inplace() (men-	GlobalPDM (class in mennofit modelinstance) 332
pofit.modelinstance.GlobalPDM method),	GlobalSimilarityModel (class in men-
333	nofit modelinstance) 329
from_vector_inplace() (men-	gradient() (menpofit.lk.ECC method), 214
pofit.modelinstance.GlobalSimilarityModel	gradient() (menpofit.lk.FourierSSD method), 213
method), 329	gradient() (menpofit.lk.GradientCorrelation method), 217
from_vector_inplace() (men-	gradient() (menpofit.lk.GradientImages method), 215
pofit.modelinstance.ModelInstance method),	gradient() (menpofit.lk.SSD method), 211
328	GradientCorrelation (class in menpofit.lk), 217
trom_vector_inplace() (men-	GradientDescentCLMFitter (class in menpofit.clm), 151
polit.modelinstance.OrthoPDM method),	GradientImages (class in menpofit.lk), 215
555 from vector inplace() (manpafit modelingtones DDM	gt_shape (menpofit.aam.result.AAMAlgorithmResult at-
method) 331	tribute), 86
from vector inplace() (men-	gt_shape (menpofit.aam.result.AAMResult attribute), 69
pofit transform DifferentiableAffine method).	gt_shape (menpofit.aps.result.APSAlgorithmResult at-
420	tribute), 130
from vector inplace() (men-	gt_shape (menpofit lk result Lucas Kanade Algorithm Pesult
pofit.transform.DifferentiableAlignmentAffine	attribute) 251
method), 435	of shape (menpofit lk result LucasKanadeResult at-
from_vector_inplace() (men-	tribute). 234
pofit.transform.DifferentiableAlignmentSimilari	^{ty} gt shape (menpofit.result.MultiScaleNonParametricIterativeResult
method), 430	attribute), 393
from_vector_inplace() (men-	gt_shape (menpofit.result.MultiScaleParametricIterativeResult
pofit.transform.DifferentiableSimilarity	attribute), 410
method), 425	gt_shape (menpofit.result.NonParametricIterativeResult
from_vector_inplace() (men-	attribute), 359
method) 416	gt_shape (menpofit.result.ParametricIterativeResult at-
from vector inplace() (men-	tribute), 376
nofit transform OrthoMDTransform method)	gt_shape (menpoht.result.Result attribute), 343
413	gt_snape (menpont.unined_aam_cim.resuit.UninedAAMCLMAigorithmRe
FullyParametricMeanTemplateNewton (class in men-	attribute), 201
pofit.sdm), 286	attribute) 184
FullyParametricProjectOutGaussNewton (class in men-	
pofit.sdm), 284	Н
FullyParametricProjectOutNewton (class in men-	h matrix (menpofit transform Differentiable Affine
pofit.sdm), 283	attribute), 421
FullyParametricProjectOutOPP (class in menpofit.sdm),	h_matrix (menpofit.transform.DifferentiableAlignmentAffine
289	attribute), 436
FullyParametricWeightsNewton (class in menpofit.sdm),	h_matrix (menpofit.transform.DifferentiableAlignmentSimilarity
200	attribute), 431

h_matrix (menpofit.transform.DifferentiableSimilarity at- tribute), 426	pofit.transform.DifferentiablePiecewiseAffine attribute), 439
h_matrix_is_mutable (men-	has_true_inverse (men-
pofit.transform.DifferentiableAffine attribute),	pofit.transform.DifferentiableSimilarity at-
422	tribute), 426
h_matrix_is_mutable (men-	has_true_inverse (men-
pofit.transform.DifferentiableAlignmentAffine	pofit.transform.DifferentiableThinPlateSplines
attribute), 436	attribute). 442
h matrix is mutable (men-	has true inverse (men-
pofit.transform.DifferentiableAlignmentSimilarit	v pofit.transform.OrthoMDTransform attribute).
attribute), 431	414
h matrix is mutable (men-	hessian() (menpofit.lk.ECC method), 214
pofit transform DifferentiableSimilarity at-	hessian() (menpofit lk FourierSSD method) 213
tribute) 426	hessian() (menpoint lk GradientCorrelation method) 217
has nan values() (mennofit modelinstance GlobalPDM	hessian() (menpolit lk GradientImages method) 215
method) 333	hessian() (menpofit lk SSD method) 211
has nan values() (men	holistic features (menpofit aam Lucas Kanade A AMEitter
nas_nan_values() (Incli-	attribute) 31
method) 320	holistic features (mennofit and Supervised Descent & AMEitter
has non values() (mon	nonstic_reatures (inclipont.aam.superviseuDescentAAMirfitter
nds_ndn_values() (nen-	holistic features (mannafit and Gauss Newton ADSEitter
228	attribute) 95
has nan values() (mennofit modelinstance OrthoPDM	holistic features (mennofit atm Lucas Kanade ATMFitter
method) 335	attribute) 146
has non values() (mennofit modelinstance PDM	holistic features (manpafit alm GradiantDescentCI MEitter
mathod) 231	attribute) 152
hes nen values() (men	holistic features (monpofit dlib DlibEPT attribute) 204
nas_nan_values() (nen-	holistic_leatures (menpolit.dito.DitoEK1 attribute), 204
120	nonsuc_reatures (menpont.nuer.MutuScaleNonParametricFitter
420 (mar	auribule), 515
nas_nan_values() (men-	noistic_features (menpont.ntter.MultiScaleParametricFitter
pont.transform.DifferentiableAlignmentAffine	attribute), 315
method), 435	holistic_features (menpofit.lk.LucasKanadeFitter at-
has_nan_values() (men-	tribute), 208
pofit.transform.DifferentiableAlignmentSimilarit	yholistic_features (menpofit.sdm.RegularizedSDM at-
method), 430	tribute), 259
has_nan_values() (men-	holistic_features (menpofit.sdm.SupervisedDescentFitter
pofit.transform.DifferentiableSimilarity	attribute), 255
method), 425	holistic_features (menpofit.unified_aam_clm.UnifiedAAMCLMFitter
has_nan_values() (men-	attribute), 165
pofit.transform.LinearOrthoMDTransform	HolisticAAM (in module menpofit.aam), 15
method), 416	HolisticATM (in module menpofit.atm), 134
has_nan_values() (men-	homogeneous_parameters (men-
pofit.transform.OrthoMDTransform method),	pofit.lk.result.LucasKanadeAlgorithmResult
413	attribute), 251
has_true_inverse (men-	homogeneous_parameters (men-
pofit.transform.DifferentiableAffine attribute),	pofit.lk.result.LucasKanadeResult attribute),
422	234
has_true_inverse (men-	
pofit.transform.DifferentiableAlignmentAffine	
attribute), 436	IIRLRegression (class in menpofit.math), 321
has_true_inverse (men-	image (menpofit.aam.result.AAMAlgorithmResult
pofit.transform.DifferentiableAlignmentSimilarit	y attribute), 86
attribute), 431	image (menpofit.aam.result.AAMResult attribute). 69
has_true_inverse (men-	

image (menpofit.aps.result.APSAlgorithmResult at- tribute), 130	increment() (menpofit.math.IIRLRegression method), 322
image (menpofit.aps.result.APSResult attribute), 113 image (menpofit.lk.result.LucasKanadeAlgorithmResult attribute), 251	increment() (menpofit.math.IRLRegression method), 321 increment() (menpofit.math.OPPRegression method), 323 increment() (menpofit.math.OptimalLinearRegression
image (menpofit.lk.result.LucasKanadeResult attribute), 234	method), 323 increment() (menpofit.math.PCRRegression method),
image (menpofit.result.MultiScaleNonParametricIterativeR attribute), 393	esult 322 increment() (menpofit.modelinstance.GlobalPDM
image (menpofit.result.MultiScaleParametricIterativeResult attribute), 410	method), 333 increment() (menpofit.modelinstance.OrthoPDM
image (menpofit.result.NonParametricIterativeResult at- tribute), 359	method), 335 increment() (menpofit.modelinstance.PDM method), 331
image (menpofit.result.ParametricIterativeResult at- tribute), 376	increment() (menpofit.sdm.FullyParametricMeanTemplateNewton method), 286
image (menpofit.result.Result attribute), 343	increment() (menpofit.sdm.FullyParametricProjectOutGaussNewton
image (menpofit.unified_aam_clm.result.UnifiedAAMCLM	[AlgorithmuReshudd]), 285
attribute), 201 image (menpofit.unified_aam_clm.result.UnifiedAAMCLM	Increment() (menpofit.sdm.FullyParametricProjectOutNewton IResult method), 283
attribute), 184	increment() (menpofit.sdm.FullyParametricProjectOutOPP
imccf() (in module menpolit.math), 325	method), 290
imosse() (in module menpont.matn), 326	increment() (menpoint.sdm.rullyParametric weightsiNewton
method) 45	increment() (mennefit sdm NonDeremetricGoussNewton
increment() (mennofit aam AppearanceWeightsNewton	method) 262
method) 43	increment() (mennofit sdm NonParametricNewton
increment() (menpofit aam base AAM method) 13	method) 260
increment() (menpofit aam LinearAAM method) 20	increment() (mennofit sdm NonParametricOPPRegression
increment() (menpofit.aam.LinearMaskedAAM method).	method). 266
23	increment() (menpofit.sdm.NonParametricOptimalRegression
increment() (menpofit.aam.MaskedAAM method), 17	method). 265
increment() (menpofit.aam.MeanTemplateGaussNewton method), 48	increment() (menpofit.sdm.NonParametricPCRRegression method), 263
increment() (menpofit.aam.MeanTemplateNewton method), 46	increment() (menpofit.sdm.ParametricAppearanceMeanTemplateGuassNew method), 279
increment() (menpofit.aam.PatchAAM method), 26	increment() (menpofit.sdm.ParametricAppearanceMeanTemplateNewton
increment() (menpofit.aam.ProjectOutGaussNewton	method), 278
method), 51	$increment () \ (menpofit.sdm.ParametricAppearanceProjectOutGuassNewton$
increment() (menpofit.aam.ProjectOutNewton method),	method), 276
50	increment() (menpofit.sdm.ParametricAppearanceProjectOutNewton
increment() (menpofit.aam.SupervisedDescentAAMFitter	method), 275
method), 33	increment() (menpofit.sdm.ParametricAppearanceWeightsGuassNewton
increment() (menpofit.aps.GenerativeAPS method), 89	method), 281
increment() (menpofit.atm.base.ATM method), 132	increment() (menpofit.sdm.ParametricAppearanceWeightsNewton
increment() (menpont.atm.LinearAI M method), 138	method), 280
140	method), 269
increment() (menpofit.atm.MaskedATM method), 135	increment() (menpofit.sdm.ParametricShapeNewton
increment() (menpofit.atm.PatchATM method), 142	method), 267
increment() (menpont.clm.CLM method), 149	increment() (menpofit.sdm.ParametricShapeOPPRegression
increment() (menpoint.cim.CorrelationFilterExpertEnsemble	e method), 2/4
method), 155	nCremen() (menpoint.sum.rarametricSnapeOptimalKegression
method), 157	increment() (menpofit.sdm.ParametricShapePCRRegression
method), 271	initial_shape (menpofit.aam.result.AAMAlgorithmResult
--	--
increment() (menpofit.sdm.RegularizedSDM method),	attribute), 86
259	initial_shape (menpofit.aam.result.AAMResult attribute),
increment() (menpofit.sdm.SupervisedDescentFitter	69
increment() (mennefit transform LinearOrtheMDTransform	attributo) 121
method) 416	initial shape (mennofit and result APSResult attribute)
IncrementalCorrelationFilterThinWrapper (class in men-	113
pofit.clm). 157	initial shape (menpofit.lk.result.LucasKanadeAlgorithmResult
init_from_2d_shear() (men-	attribute), 251
pofit.transform.DifferentiableAffine method),	initial_shape (menpofit.lk.result.LucasKanadeResult at-
421	tribute), 234
init_from_2d_shear() (men-	$initial_shape\ (menpofit.result.MultiScaleNonParametricIterativeResult$
pofit.transform.DifferentiableAlignmentAffine	attribute), 393
method), 435	initial_shape (menpofit.result.MultiScaleParametricIterativeResult
init_from_2d_shear() (men-	attribute), 410
pofit.transform.DifferentiableAlignmentSimilarit	yinitial_shape (menpofit.result.NonParametricIterativeResult
init from 2d sheer() (mon	attribute), 359
nofit transform DifferentiableSimilarity	attribute) 376
method) 425	initial shape (mennofit result Result attribute) 343
init identity() (menpofit transform DifferentiableAffine	initial shape (menpolitunified aam clm.result Unified AMCLMAlgorith
method), 421	attribute), 201
init_identity() (menpofit.transform.DifferentiableAlignmen	taufifinae_shape (menpofit.unified_aam_clm.result.UnifiedAAMCLMResult
method), 435	attribute), 184
init_identity() (menpofit.transform.DifferentiableAlignmen method), 430	tsinstalactety) (menpofit.aam.base.AAM method), 13 instance() (menpofit.aam.LinearAAM method), 21
init_identity() (menpofit.transform.DifferentiableSimilarity	instance() (menpofit.aam.LinearMaskedAAM method),
method), 425	24
initial_error() (menpofit.aam.result.AAMAlgorithmResult	instance() (menpofit.aam.MaskedAAM method), 17
method), 71	instance() (menpofit.aam.PatchAAM method), 26
initial_error() (menpofit.aam.result.AAMResult method),	instance() (menpofit.aps.GenerativeAPS method), 90
54	instance() (menpofit.atm.base.ATM method), 133
initial_error() (menpofit.aps.result.APSAlgorithmResult	instance() (menpofit.atm.LinearATM method), 138
method), 115	instance() (menpofit.atm.LinearMaskedATM method),
initial_error() (menpoin.aps.resuit.APSResuit method),	141 instance() (manpafit atm Maskad ATM mathad) 126
initial error() (mennofit lk result Lucas Kanade AlgorithmP.	aimitance() (menpofit atm Patch ATM method), 143
method) 236	instance() (menpofit unified aam clm hase Unified AAMCLM
initial error() (menpofit.lk.result.LucasKanadeResult	method). 161
method), 219	Inverse (class in menpofit.aps), 95
initial_error() (menpofit.result.MultiScaleNonParametricIte	rlativerRessolmpositional (class in menpofit.atm), 147
method), 378	InverseCompositional (class in menpofit.lk), 210
initial_error() (menpofit.result.MultiScaleParametricIterativ	dResklegression (class in menpofit.math), 321
method), 395	is_iterative (menpofit.aam.result.AAMAlgorithmResult
initial_error() (menpofit.result.NonParametricIterativeResu	lt attribute), 86
method), 344	is_iterative (menpofit.aam.result.AAMResult attribute),
initial_error() (menpofit.result.ParametricIterativeResult	69
method), 361	is_iterative (menpofit.aps.result.APSAlgorithmResult at-
initial_error() (menpofit.result.Result method), 337	tribute), 131
iniual_error() (menpont.unined_aam_cim.result.UnifiedAA	in <u>unerative</u> (memorial la result Luces Venede Algorithm Desult
initial error() (mennofit unified som alm result Unified AA	MCI MReatthibute) 251
method) 169	is iterative (mennofit lk result LucasKanadeResult
moulou), 102	is_actuative (interportativesuitebucasivaliadertesuit

attribute), 234	MeanTemplateGaussNewton (class in menpofit.aam), 48
is_iterative (menpofit.result.MultiScaleNonParametricIteration)	ti MeRasTiemplateNewton (class in menpofit.aam), 46
attribute), 393	MenpoFitBuilderWarning (class in menpofit.builder), 295
$is_iterative\ (menpofit.result.MultiScaleParametricIterativeForm) \\ \label{eq:menpofit.result}$	RevenpoFitModelBuilderWarning (class in men-
attribute), 410	pofit.builder), 295
is_iterative (menpofit.result.NonParametricIterativeResult	ModelInstance (class in menpofit.modelinstance), 327
attribute), 359	ModifiedAlternatingForwardCompositional (class in
is_iterative (menpofit.result.ParametricIterativeResult at-	menpofit.aam), 36
tribute), 376	ModifiedAlternatingInverseCompositional (class in men-
is_iterative (menpofit.result.Result attribute), 343	pofit.aam), 37
is_iterative (menpofit.unified_aam_clm.result.UnifiedAAM	GilowkA(g(inithmRekultenpofit.math), 325
attribute), 201	MultiScaleNonParametricFitter (class in menpofit.fitter),
is_iterative (menpofit.unified_aam_clm.result.UnifiedAAM	ICLMResult12
attribute), 184	MultiScaleNonParametricIterativeResult (class in men-
	pofit.result), 377
J	MultiScaleParametricFitter (class in menpofit.fitter), 314
Jp() (menpofit.transform.OrthoMDTransform method),	MultiScaleParametricIterativeResult (class in men-
411	pofit.result), 394

L

linear_component (men-	n
pofit.transform.DifferentiableAffine attribute),	
422	
linear_component (men-	n
pofit.transform.DifferentiableAlignmentAffine	
attribute), 436	
linear_component (men-	n
pofit.transform.DifferentiableAlignmentSimilarit	y
attribute), 431	n
linear_component (men-	
pofit.transform.DifferentiableSimilarity at-	
tribute), 426	n
LinearAAM (class in menpofit.aam), 19	
LinearATM (class in menpofit.atm), 137	n
LinearMaskedAAM (class in menpofit.aam), 22	
LinearMaskedATM (class in menpofit.atm), 139	n
LinearOrthoMDTransform (class in menpofit.transform),	
414	n
load_balanced_frontal_face_fitter() (in module men-	
pofit.aam), 87	n
LucasKanadeAAMFitter (class in menpofit.aam), 28	
LucasKanadeAlgorithmResult (class in men-	n
pofit.lk.result), 235	
LucasKanadeATMFitter (class in menpofit.atm), 144	n
LucasKanadeFitter (class in menpofit.lk), 206	n
LucasKanadeResult (class in menpofit.lk.result), 218	
NA	n
141	

mad() (in module menpofit.error), 307 MaskedAAM (class in menpofit.aam), 15 MaskedATM (class in menpofit.atm), 134 mccf() (in module menpofit.math), 324 mean_pupil_49_error() (in module menpofit.error), 310 mean_pupil_68_error() (in module menpofit.error), 309

N

n_active_components (men- pofit.modelinstance.GlobalPDM attribute), 334 n_active_components (menpofit.modelinstance.PDM attribute), 336 n_active_components (menpofit.modelinstance.PDM at- tribute), 332 n_active_components (men- pofit.transform.LinearOrthoMDTransform attribute), 417 n_centres (menpofit.transform.DifferentiableR2LogR2RBF attribute), 444 n_centres (menpofit.transform.DifferentiableR2LogRRBF attribute), 446 n_dims (menpofit.modelinstance.GlobalPDM attribute), 334 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 336 n_dims (menpofit.transform.DifferentiableAffine at- tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 430	IN
pofit.modelinstance.GlobalPDM attribute), 334 n_active_components (menpofit.modelinstance.PDM attribute), 336 n_active_components (menpofit.modelinstance.PDM at- tribute), 332 n_active_components (men- pofit.transform.LinearOrthoMDTransform attribute), 417 n_centres (menpofit.transform.DifferentiableR2LogR2RBF attribute), 444 n_centres (menpofit.transform.DifferentiableR2LogRRBF attribute), 446 n_dims (menpofit.modelinstance.GlobalPDM attribute), 334 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.ModelInstance at- tribute), 328 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 336 n_dims (menpofit.transform.DifferentiableAffine at- tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 430	n_active_components (men-
<pre>n_active_components (men- pofit.modelinstance.OrthoPDM attribute), 336 n_active_components (menpofit.modelinstance.PDM at- tribute), 332 n_active_components (men- pofit.transform.LinearOrthoMDTransform attribute), 417 n_centres (menpofit.transform.DifferentiableR2LogR2RBF attribute), 444 n_centres (menpofit.transform.DifferentiableR2LogRRBF attribute), 444 n_centres (menpofit.modelinstance.GlobalPDM attribute), 334 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.ModelInstance at- tribute), 328 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 336 n_dims (menpofit.transform.DifferentiableAffine at- tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 430</pre>	pofit.modelinstance.GlobalPDM attribute), 334
pofit.modelinstance.OrthoPDM attribute), 336 n_active_components (menpofit.modelinstance.PDM at- tribute), 332 n_active_components (men- pofit.transform.LinearOrthoMDTransform attribute), 417 n_centres (menpofit.transform.DifferentiableR2LogR2RBF attribute), 444 n_centres (menpofit.transform.DifferentiableR2LogRRBF attribute), 446 n_dims (menpofit.modelinstance.GlobalPDM attribute), 334 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 336 n_dims (menpofit.transform.DifferentiableAffine at- tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 430	n_active_components (men-
 n_active_components (menpofit.modelinstance.PDM attribute), 332 n_active_components (menpofit.transform.LinearOrthoMDTransform attribute), 417 n_centres (menpofit.transform.DifferentiableR2LogR2RBF attribute), 444 n_centres (menpofit.transform.DifferentiableR2LogRRBF attribute), 446 n_dims (menpofit.modelinstance.GlobalPDM attribute), 334 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.transform.DifferentiableAffine attribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 430 	pofit.modelinstance.OrthoPDM attribute), 336
 n_active_components (men- pofit.transform.LinearOrthoMDTransform attribute), 417 n_centres (menpofit.transform.DifferentiableR2LogR2RBF attribute), 444 n_centres (menpofit.transform.DifferentiableR2LogRRBF attribute), 446 n_dims (menpofit.modelinstance.GlobalPDM attribute), 334 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.ModelInstance at- tribute), 328 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.transform.DifferentiableAffine at- tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439 	n_active_components (menpofit.modelinstance.PDM at-
 n_active_components (men- pofit.transform.LinearOrthoMDTransform attribute), 417 n_centres (menpofit.transform.DifferentiableR2LogR2RBF attribute), 444 n_centres (menpofit.transform.DifferentiableR2LogRRBF attribute), 446 n_dims (menpofit.modelinstance.GlobalPDM attribute), 334 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.ModelInstance at- tribute), 328 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.transform.DifferentiableAffine at- tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439 	tribute), 332
pofit.transform.LinearOrthoMDTransform attribute), 417 n_centres (menpofit.transform.DifferentiableR2LogR2RBF attribute), 444 n_centres (menpofit.transform.DifferentiableR2LogRRBF attribute), 446 n_dims (menpofit.modelinstance.GlobalPDM attribute), 334 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.ModelInstance at- tribute), 328 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 336 n_dims (menpofit.transform.DifferentiableAffine at- tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 431 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439	n_active_components (men-
 n_centres (menpofit.transform.DifferentiableR2LogR2RBF attribute), 444 n_centres (menpofit.transform.DifferentiableR2LogRRBF attribute), 446 n_dims (menpofit.modelinstance.GlobalPDM attribute), 334 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.ModelInstance at- tribute), 328 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.transform.DifferentiableAffine at- tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439 	pofit.transform.LinearOrthoMDTransform
 n_centres (menpolit.transform.DifferentiableR2LogRRBF attribute), 444 n_centres (menpofit.transform.DifferentiableR2LogRRBF attribute), 446 n_dims (menpofit.modelinstance.GlobalPDM attribute), 334 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.ModelInstance attribute), 328 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.transform.DifferentiableAffine attribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439 	n contros (monpofit transform DifferentichleD21 ogD2DDE
 n_centres (menpofit.transform.DifferentiableR2LogRRBF attribute), 446 n_dims (menpofit.modelinstance.GlobalPDM attribute), 334 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.ModelInstance at- tribute), 328 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.transform.DifferentiableAffine at- tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439 	attribute), 444
 attribute), 446 n_dims (menpofit.modelinstance.GlobalPDM attribute), 334 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.ModelInstance attribute), 328 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.transform.DifferentiableAffine attribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439 	n centres (menpofit.transform.DifferentiableR2LogRRBF
 n_dims (menpofit.modelinstance.GlobalPDM attribute), 334 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.ModelInstance attribute), 328 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.transform.DifferentiableAffine attribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439 	attribute), 446
 n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329 n_dims (menpofit.modelinstance.ModelInstance at- tribute), 328 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.transform.DifferentiableAffine at- tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439 	n_dims (menpofit.modelinstance.GlobalPDM attribute), 334
n_dims (menpofit.modelinstance.ModelInstance at- tribute), 328 n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.transform.DifferentiableAffine at- tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439	n_dims (menpofit.modelinstance.GlobalSimilarityModel attribute), 329
n_dims (menpofit.modelinstance.OrthoPDM attribute), 336 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.transform.DifferentiableAffine at- tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439	n_dims (menpofit.modelinstance.ModelInstance at- tribute), 328
 n_dims (menpofit.modelinstance.PDM attribute), 332 n_dims (menpofit.transform.DifferentiableAffine attribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439 	n_dims (menpofit.modelinstance.OrthoPDM attribute), 336
n_dims (menpofit.transform.DifferentiableAffine at- tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439	n_dims (menpofit.modelinstance.PDM attribute), 332
tribute), 422 n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439	n_dims (menpofit.transform.DifferentiableAffine at-
n_dims (menpofit.transform.DifferentiableAlignmentAffine attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439	tribute), 422
attribute), 436 n_dims (menpofit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute), 439	n_dims (menpofit.transform.DifferentiableAlignmentAffine
n_dims (menpolit.transform.DifferentiableAlignmentSimilarity attribute), 431 n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute) 439	attribute), 436
n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute) 439	n_dims (menpofit.transform.DifferentiableAlignmentSimilarity
n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute) 439	attribute), 431
	n_dims (menpofit.transform.DifferentiablePiecewiseAffine attribute) 439
n dims (menpofit transform DifferentiableR2LogR2RBF	n dims (menpofit transform DifferentiableR2LogR2RBF

attribute), 444

n_dims	(menpofit.transform.DifferentiableR2LogRRBF attribute) 446	n iters (r	attribute), 410
n_dims	(menpofit.transform.DifferentiableSimilarity at-		tribute), 359
n dims (tribute), 42/ menpofit.transform.DifferentiableThinPlateSplines	n_iters	(menpolit.result.ParametriciterativeResult at- tribute), 376
_	attribute), 442	n_iters (n	enpofit.unified_aam_clm.result.UnifiedAAMCLMAlgorithmResult
n_dims	(menpofit.transform.LinearOrthoMDTransform	n itana (n	attribute), 202
n dims	(menpofit.transform.OrthoMDTransform at-	II_ILEIS (II	attribute), 184
	tribute), 414	n_iters_p	er_scale (menpofit.aam.result.AAMResult at-
n_dims_	output (menpofit.transform.DifferentiableAffine		tribute), 69
n dims	output (menpofit.transform.DifferentiableAlignme	n_ners_p ntAffine	tribute), 114
<u></u>	attribute), 436	n_iters_p	er_scale (menpofit.lk.result.LucasKanadeResult
n_dims_	output (menpofit.transform.DifferentiableAlignme	ntSimilarit	attribute), 234
n dima	attribute), 431	n_iters_p	er_scale (men-
II_uIIIIS_	attribute), 440	cAnnie	attribute), 393
n_dims_	output (menpofit.transform.DifferentiableR2LogR2	2RBters_p	er_scale (men-
1.	attribute), 444	DDE	pofit.result.MultiScaleParametricIterativeResult
n_aims_	attribute) 446	кыг n iters n	auribule), 410 er scale (men-
n_dims_	output (menpofit.transform.DifferentiableSimilarit	и_ненз_р у	pofit.unified_aam_clm.result.UnifiedAAMCLMResult
	attribute), 427	~	attribute), 184
n_dims_	output (menpofit.transform.DifferentiableThinPlate	els <u>p</u> lanælma	rks (menpofit.transform.LinearOrthoMDTransform attribute) 417
n_dims_	output (menpofit.transform.LinearOrthoMDTransf	ommonarame	ters (menpofit.modelinstance.GlobalPDM at-
	attribute), 417	-1	tribute), 334
n_dims_	output (menpofit.transform.OrthoMDTransform attribute), 414	n_parame	ters (menpofit.modelinstance.GlobalSimilarityModel attribute), 330
n_expert	s (menpofit.clm.CorrelationFilterExpertEnsemble	n_parame	ters (menpofit.modelinstance.ModelInstance at-
n global	attribute), 156	n narame	tribute), 328
n_5100a	pofit.modelinstance.GlobalPDM attribute),	n_parame	attribute), 336
	334	n_parame	ters (menpofit.modelinstance.PDM attribute),
n_global	_parameters (men-	n noroma	332 tars (manpafit transform Differentiable Affine
	336	n_parame	attribute), 422
n_global	_parameters (men-	n_parame	ters (menpofit.transform.DifferentiableAlignmentAffine
	pofit.transform.LinearOrthoMDTransform		attribute), 437
n iters	(menpofit.aam.result.AAMAlgorithmResult_at-	n_parame	attribute), 431
	tribute), 87	n_parame	ters (menpofit.transform.DifferentiableSimilarity
n_iters (menpofit.aam.result.AAMResult attribute), 69		attribute), 427
n_iters	(menpofit.aps.result.APSAlgorithmResult at- tribute), 131	n_parame	ters (menpofit.transform.LinearOrthoMDTransform attribute), 417
n_iters (menpofit.aps.result.APSResult attribute), 114	n_parame	ters (menpofit.transform.OrthoMDTransform
n_iters (menpont.lk.result.LucasKanadeAlgorithmResult	n nointe	attribute), 414 (menpofit modelinstance GlobalPDM attribute)
n_iters (menpofit.lk.result.LucasKanadeResult attribute),	n_points	334
	234	n_points	menpofit.modelinstance.GlobalSimilarityModel
n_iters (1	menpofit.result.MultiScaleNonParametricIterativeF	Result	attribute), 330
n iters (aurioue), 393 nenpofit.result.MultiScaleParametricIterativeResul	n_points lt	(menpoint.modelinstance.wodelinstance at- tribute), 328

n_points (menpofit.modelinstance.OrthoPDM attribute), 336	n_scales (menpofit.result.MultiScaleParametricIterativeResult attribute), 410
n_points (menpofit.modelinstance.PDM attribute), 332	n_scales (menpofit.sdm.RegularizedSDM attribute), 260
n_points (menpofit.transform.DifferentiableAlignmentAffin attribute), 437	næ_scales (menpofit.sdm.SupervisedDescentFitter at- tribute), 255
n_points (menpofit.transform.DifferentiableAlignmentSimi attribute), 432	laritycales (menpofit.unified_aam_clm.base.UnifiedAAMCLM attribute), 163
n_points (menpofit.transform.DifferentiablePiecewiseAffin attribute), 440	en_scales (menpofit.unified_aam_clm.result.UnifiedAAMCLMResult attribute), 184
n_points (menpofit.transform.DifferentiableThinPlateSplin attribute), 442	<pre>scales (menpofit.unified_aam_clm.UnifiedAAMCLMFitter attribute), 166</pre>
n_points (menpofit.transform.LinearOrthoMDTransform attribute), 417	n_tris (menpofit.transform.DifferentiablePiecewiseAffine attribute), 440
n_points (menpofit.transform.OrthoMDTransform	n_weights (menpofit.modelinstance.GlobalPDM at-
attribute), 414	tribute), 334
n_sample_offsets (men-	n_weights (menpofit.modelinstance.GlobalSimilarityModel
pofit.clm.CorrelationFilterExpertEnsemble	attribute), 330
attribute), 156	n_weights (menpofit.modelinstance.ModelInstance at-
n_scales (menpofit.aam.base.AAM attribute), 15	tribute), 328
n_scales (menpofit.aam.LinearAAM attribute), 21 n_scales (menpofit.aam.LinearMaskedAAM attribute),	n_weights (menpofit.modelinstance.OrthoPDM at- tribute), 336
24	n_weights (menpofit.modelinstance.PDM attribute), 332
n_scales (menpofit.aam.LucasKanadeAAMFitter at- tribute), 31	n_weights (menpofit.transform.LinearOrthoMDTransform attribute), 417
n_scales (menpofit.aam.MaskedAAM attribute), 19	noisy_alignment_similarity_transform() (in module men-
n_scales (menpofit.aam.PatchAAM attribute), 28	pofit.fitter), 316
n_scales (menpofit.aam.result.AAMResult attribute), 69	noisy_shape_from_bounding_box() (in module men-
n_scales (menpofit.aam.SupervisedDescentAAMFitter	pofit.fitter), 317
attribute), 34	noisy_shape_from_shape() (in module menpofit.fitter),
n_scales (menpofit.aps.GaussNewtonAPSFitter attribute),	317
95	noisy_target_alignment_transform() (in module men-
n_scales (menpofit.aps.GenerativeAPS attribute), 93	pofit.htter), 318
n_scales (menpofit.aps.result.APSResult attribute), 114	NonParametricGaussNewton (class in menpolit.sdm),
n_scales (menpofit.atm.base.ATM attribute), 134	$\frac{261}{1000}$
n_scales (menpoil.alm.LinearAl M altribute), 159	NonParametriciterativeResult (class in menpolit.result),
1/1	NonParametricNewton (class in mennofit sdm) 260
n scales (mennofit atm LucasKanade ATMFitter at-	NonParametricOPPRegression (class in menpolit.sum), 200
tribute), 146	266
n_scales (menpofit.atm.MaskedATM attribute), 137	NonParametricOptimalRegression (class in men-
n_scales (menpofit.atm.PatchATM attribute), 144	poht.sdm), 264
n_scales (menpofit.clm.CLM attribute), 150	NonParametricPCRRegression (class in menpofit.sdm),
n_scales (menpofit.clm.GradientDescentCLMFitter at-	
tribute), 152	normalization_wrt_reference_snape() (in module men-
n_scales (menpolit.dilb.DilbERT attribute), 204	point.builder), 295
attribute), 313	0
n_scales (menpofit.fitter.MultiScaleParametricFitter at-	OPPRegression (class in menpofit.math), 323
tribute), 315	OptimalLinearRegression (class in menpofit.math), 323
n_scales (menpotit.lk.LucasKanadeFitter attribute), 208	OrthoMDTransform (class in menpofit.transform), 411
n_scales (menpofit.IK.result.LucasKanadeResult at-	OrthoPDM (class in menpofit.modelinstance), 334
IIIUUUC), 204 n. scales (mennefit result MultiScaleNonDeremetricIterativ	outer_eye_corner_49_euclidean_error() (in module men-
attribute), 393	pofit.error), 311

- outer eye corner 51 euclidean error() (in module menpofit.error), 311
- outer eye corner 68 euclidean error() (in module menpofit.error), 310

Ρ

attribute), 156 ParametricAppearanceMeanTemplateGuassNewton (class in menpofit.sdm), 279 ParametricAppearanceMeanTemplateNewton (class in menpofit.sdm), 277 ParametricAppearanceProjectOutGuassNewton (class in menpofit.sdm), 276 ParametricAppearanceProjectOutNewton (class in menpofit.sdm), 275 ParametricAppearanceWeightsGuassNewton (class in menpofit.sdm), 281 ParametricAppearanceWeightsNewton (class in menpofit.sdm), 280 ParametricIterativeResult (class in menpofit.result), 359 ParametricShapeGaussNewton (class in menpofit.sdm), 269 ParametricShapeNewton (class in menpofit.sdm), 267 ParametricShapeOPPRegression (class in menpofit.sdm), 273 ParametricShapeOptimalRegression (class in menpofit.sdm), 272 ParametricShapePCRRegression (class in menpofit.sdm), 270 PatchAAM (class in menpofit.aam), 24 PatchATM (class in menpofit.atm), 141 PCRRegression (class in menpofit.math), 322 PDM (class in menpofit.modelinstance), 330 PickleWrappedFitter (class in menpofit.io), 318 plot_costs() (menpofit.aam.result.AAMAlgorithmResult method), 71 plot_costs() (menpofit.aam.result.AAMResult method), 54 plot_costs() (menpofit.aps.result.APSAlgorithmResult method), 116plot_costs() (menpofit.aps.result.APSResult method), 99 plot_costs() (menpofit.lk.result.LucasKanadeAlgorithmResultot_errors() (menpofit.aam.result.AAMResult method), method), 236 $(menpofit.lk.result.LucasKanadeResult \ \ plot_errors()$ plot_costs() method), 219 $plot_costs() (menpofit.result.MultiScaleNonParametricIterative Restors() (menpofit.aps.result.APSResult method), (method), ($ method), 378 method), 395 plot_costs() (menpofit.result.NonParametricIterativeResult plot_errors() method), 344

plot costs() (menpofit.unified aam clm.result.UnifiedAAMCLMAlgorithm method). 187 plot costs() (menpofit.unified aam clm.result.UnifiedAAMCLMResult method), 169 plot cumulative error distribution() (in module menpofit.visualize), 450 (menpofit.aam.result.AAMAlgorithmResult method), 73 plot_displacements() (menpofit.aam.result.AAMResult method), 55 plot_displacements() (menpofit.aps.result.APSAlgorithmResult method), 117 plot_displacements() (menpofit.aps.result.APSResult method), 100plot_displacements() (menpofit.lk.result.LucasKanadeAlgorithmResult method), 238 plot displacements() (menpofit.lk.result.LucasKanadeResult method), 221 plot_displacements() (menpofit.result.MultiScaleNonParametricIterativeResult method), 380 plot displacements() (menpofit.result.MultiScaleParametricIterativeResult method), 397 plot_displacements() (menpofit.result.NonParametricIterativeResult method), 346 plot_displacements() (menpofit.result.ParametricIterativeResult method), 362 plot displacements() (menpofit.unified_aam_clm.result.UnifiedAAMCLMAlgorithmResult method), 188 plot displacements() (menpofit.unified aam clm.result.UnifiedAAMCLMResult method), 171 plot errors() (menpofit.aam.result.AAMAlgorithmResult method), 75 57 (menpofit.aps.result.APSAlgorithmResult method), 119 102 $plot_costs() (menpofit.result.MultiScaleParametricIterative {\it Relative} result. and {\it Relati$ method), 239 (menpofit.lk.result.LucasKanadeResult method), 223

 $(menpofit.result.ParametricIterativeResult \quad plot_errors() \ (menpofit.result.MultiScaleNonParametricIterativeResult \ NotParametricIterativeResult \ Not$ method), 381 method), 361

plot_costs()

plot_errors() (menpofit.result.MultiScaleParametricIterativ	eResult method), 442
method), 398	pseudoinverse_vector() (men-
plot_errors() (menpofit.result.NonParametricIterativeResul method), 348	t pofit.transform.DifferentiableAffine method), 421
plot_errors() (menpofit.result.ParametricIterativeResult	pseudoinverse_vector() (men-
method), 364	pofit.transform.DifferentiableAlignmentAffine
plot_errors() (menpofit.unified_aam_clm.result.UnifiedAA method) 100	MCLMAIgnethonlycsuli
notion), 190	MCI MP acentifit transform Differentiable Alignment Similarity
method), 173	method), 430
predict() (menpofit.math.IIRLRegression method), 322	pseudoinverse_vector() (men-
predict() (menpofit.math.IRLRegression method), 321	pofit.transform.DifferentiableSimilarity
predict() (menpofit.math.OPPRegression method), 324	method), 426
predict() (menpofit.math.OptimalLinearRegression	pseudoinverse vector() (men-
method) 323	pofit transform OrthoMDTransform method)
predict() (mennofit math PCRRegression method) 322	413
predict, probability() (men	715
noft alm CorrelationFilterEvportEnsemble	R
point.cometationFinterExpertEnsemble	
method), 155	random_instance() (menpofit.aam.base.AAM method),
predict_response() (men-	14
pofit.clm.CorrelationFilterExpertEnsemble method), 155	random_instance() (menpofit.aam.LinearAAM method), 21
print_progress() (in module menpofit.visualize), 446	random_instance() (menpofit.aam.LinearMaskedAAM
project() (menpofit.aam.AppearanceWeightsGaussNewton	method), 24
method), 45	random instance() (menpofit.aam.MaskedAAM
project() (menpofit.aam.AppearanceWeightsNewton	method), 17
method), 43	random instance() (mennofit aam PatchAAM method)
project out() (menpofit.aam.ProjectOutForwardComposition	onal 27
method) 38	random instance() (mennofit and Generative ΔPS
project out() (mennofit aam ProjectOutGaussNewton	method) 00
method) 52	method), 50
meinet out() (manaft aam Draiaat()utInvariaCompositie	random_instance() (inenpoint.auii.base.ATM inethod),
project_out() (menpoint.aam.r10jectOutinverseCompositio	
method), 38	random_instance() (menpofit.atm.LinearATM method),
project_out() (menpofit.aam.ProjectOutNewton method),	138
50	random_instance() (menpofit.atm.LinearMaskedATM
ProjectOutForwardCompositional (class in men-	method), 141
pofit.aam), 38	random_instance() (menpofit.atm.MaskedATM method),
ProjectOutGaussNewton (class in menpofit.aam), 51	136
ProjectOutInverseCompositional (class in menpofit.aam),	random_instance() (menpofit.atm.PatchATM method),
ProjectOutNewton (class in mennofit sam) 40	rendom instance() (mon
ProjectOutRegularisedLandmarkMaanShift (class in	random_instance() (incli-
menpofit.unified aam clm), 167	method), 161
pseudoinverse() (menpofit.transform.DifferentiableAffine	reconstructed initial error() (men-
method), 421	pofit aam result AAMAlgorithmResult
pseudoinverse() (menpofit transform DifferentiableAlignm	entAffine method) 76
method) 435	reconstructed initial error() (men
neurou), 455	entSimilaritable com result A AMPosult method) 50
method) 420	magnetizated initial amore)
neurod) (mannaft transform DifforentiableDiagoui	reconstructed_initial_error() (inen-
method) 420	iseAnnie pont.aps.result.APSAlgorithmKesult method),
method), 459	121
pseudoinverse() (menpont.transform.DifferentiableSimilar)	uyeconstructed_initial_error() (men-
method), 426	pofit.aps.result.APSResult method), 103
pseudoinverse() (menpotit.transform.DifferentiableThinPla	teSplines

- reconstructed initial error() (menpofit.lk.result.LucasKanadeAlgorithmResult method), 241 reconstructed_initial_error() (menpofit.lk.result.LucasKanadeResult method), 224 reconstructed initial error() (menpofit.result.MultiScaleParametricIterativeResult method), 400 reconstructed_initial_error() (menpofit.result.ParametricIterativeResult method), 366 reconstructed initial error() (menmethod), 191 reconstructed_initial_error() (menpofit.unified_aam_clm.result.UnifiedAAMCLMResult method), 174 reconstructed initial shape (menpofit.aam.result.AAMAlgorithmResult attribute), 87 reconstructed initial shape (menpofit.aps.result.APSAlgorithmResult attribute), 131 reconstructed initial shape (menpofit.lk.result.LucasKanadeAlgorithmResult attribute), 251 reconstructed_initial_shape (menpofit.result.ParametricIterativeResult attribute), 376 reconstructed initial shape (menpofit.unified_aam_clm.result.UnifiedAAMCLMAlgorithmRasalt attribute), 202 run() reconstructed_initial_shapes (menpofit.aam.result.AAMResult attribute), 70 run() reconstructed initial shapes (menpofit.aps.result.APSResult attribute), 114 run() reconstructed initial shapes (menpofit.lk.result.LucasKanadeResult attribute), run() 235 reconstructed initial shapes (menrun() pofit.result.MultiScaleParametricIterativeResult attribute), 410 reconstructed_initial_shapes (menpofit.unified_aam_clm.result.UnifiedAAMCLMResult attribute), 185 reference shape (menpofit.aam.LucasKanadeAAMFitter attribute), 31 run() reference_shape (menpofit.aam.SupervisedDescentAAMFitter attribute), 34 reference_shape (menpofit.aps.GaussNewtonAPSFitter attribute), 95 run() reference shape (menpofit.atm.LucasKanadeATMFitter
- reference shape (menpofit.clm.GradientDescentCLMFitter attribute), 152 reference shape (menpofit.dlib.DlibERT attribute), 205 reference shape (menpofit.fitter.MultiScaleNonParametricFitter attribute), 313 reference shape (menpofit.fitter.MultiScaleParametricFitter attribute). 315 reference shape (menpofit.lk.LucasKanadeFitter attribute). 208 reference_shape (menpofit.sdm.RegularizedSDM attribute), 260 reference_shape (menpofit.sdm.SupervisedDescentFitter attribute), 255 pofit.unified_aam_clm.result.UnifiedAAMCLMAlgforieIncrReshafte (menpofit.unified_aam_clm.UnifiedAAMCLMFitter attribute), 166 RegularisedLandmarkMeanShift (class in menpofit.clm), 153 RegularizedSDM (class in menpofit.sdm), 257 rescale images to reference shape() (in module menpofit.builder), 294 response covariance (menpofit.unified aam clm.UnifiedAAMCLMFitter attribute), 166 Result (class in menpofit.result), 337 root mean square bb normalised error() (in module menpofit.error), 302 root_mean_square_distance_indexed_normalised_error() (in module menpofit.error), 304 root_mean_square_distance_normalised_error() (in module menpofit.error), 303 root_mean_square_error() (in module menpofit.error), (menpofit.aam.AlternatingForwardCompositional method), 34 (menpofit.aam.AlternatingInverseCompositional method), 35 (menpofit.aam.AppearanceWeightsGaussNewton method), 45 (menpofit.aam.AppearanceWeightsNewton method), 43 (menpofit.aam.MeanTemplateGaussNewton method), 48 run() (menpofit.aam.MeanTemplateNewton method), 47 run() (menpofit.aam.ModifiedAlternatingForwardCompositional method), 36 run() (menpofit.aam.ModifiedAlternatingInverseCompositional method), 37 (menpofit.aam.ProjectOutForwardCompositional method), 38 run() (menpofit.aam.ProjectOutGaussNewton method), 52 (menpofit.aam.ProjectOutInverseCompositional method), 39 run() (menpofit.aam.ProjectOutNewton method), 50

attribute), 146

run()	(menpofit.aam.SimultaneousForwardCompositional		method), 274
	method), 39	run() (n	nenpofit.sdm.ParametricShapeOptimalRegression
run()	(menpofit.aam.SimultaneousInverseCompositional		method), 272
	method), 40	run()	(menpofit.sdm.ParametricShapePCRRegression
run()	(menpofit.aam.WibergForwardCompositional		method), 271
	method), 41	run() (m	enpofit.unified_aam_clm.AlternatingRegularisedLandmarkMeanSh
run()	(menpofit.aam.WibergInverseCompositional		method), 166
	method), 42	run() (m	enpofit.unified_aam_clm.ProjectOutRegularisedLandmarkMeanSh
run()	(menpofit.aps.Forward method), 96		method), 167
run()	(menpofit.aps.Inverse method), 95	-	
run()	(menpofit.atm.ForwardCompositional method), 146	S	
run()	(menpofit.atm.InverseCompositional method), 147	scale in	nages() (in module mennofit builder) 294
run()	(menpofit.clm.ActiveShapeModel method), 153	scales (mennofit aam LucasKanadeAAMFitter attribute)
run()	(menpofit.clm.RegularisedLandmarkMeanShift	seules (I	31
0	method), 154	scales (mennofit aam SupervisedDescent A AMFitter at-
run()	(menpofit.lk.ForwardAdditive method), 208	seules (tribute) 34
run()	(menpofit.lk.ForwardCompositional method), 209	scales ((mennofit ans GaussNewtonAPSFitter_attribute)
run()	(menpofit.lk.InverseCompositional method), 210	seales (
run()	(menpofit.sdm.FullyParametricMeanTemplateNewtor	l scales (mennofit atm LucasKanadeATMFitter_attribute)
	method), 287	seales (146
run()	(menpofit.sdm.FullyParametricProjectOutGaussNewt	Officiales	(mennofit clm GradientDescentCI MFitter at-
0	method). 285	seares	tribute) 152
run()	(menpofit.sdm.FullyParametricProjectOutNewton	scales (r	nennofit dlib DlibERT attribute) 205
	method). 283	scales (1	nenpolit fitter MultiScaleNonParametricFitter at
run()	(menpofit.sdm.FullyParametricProjectOutOPP	scales (I	tribute) 314
1411()	method). 290	scales	(mennofit fitter MultiScaleParametricFitter at
run()	(menpofit.sdm.FullyParametricWeightsNewton	scales	(menpoint.inter.intuitiscaler alametrici inter at-
1411()	method). 288	scolas (r	nannafit lk Lucas Kanada Fittar attributa) 208
run()	(menpofit sdm NonParametricGaussNewton	scales (I	nenpolit.ik.LucasKalladeFiller attribute), 208
run()	method) 262		mempolit.sum.RegularizedSDW attribute), 200
run()	(mennofit sdm NonParametricNewton method) 261	scales (255
run()	(menpofit sdm NonParametricOPPRegression	caolac (r	255
run()	method) 266	scales (1	attribute) 1((
run()	(mennofit sdm NonParametricOntimalRegression	CDMO	auribule), 100
run()	method) 265	SDM()	In module menpolit.sum), 250
run()	(mennofit sdm NonParametricPCRRegression	search_s	attribute) 156
run()	method) 263		aufibule), 150
run()	(mennofit sdm Parametric AppearanceMeanTemplate(set_n_m SuassNev	(atrix() (menpoint.transform.DifferentiableAffine
Tun()	method) 279		• method), 421
run()	(mennofit sdm Parametric Appearance Mean Template)	set_n_m	atrix() (menpoint transform. Differentiable Alignment Alline
Tun()	method) 278		method), 430
run()	(mennofit sdm Parametric AppearanceProjectOutGuas	set_n_m	atrix() (menpoint transform. Differentiable Alignments imitarity
Tun()	method) 277	sat h m	method), 431
run()	(mennofit sdm Parametric AppearanceProjectOutNew	set_n_n	mathad) 426
Tun()	method) 275		method), 426
run()	(mennofit sdm Parametric Annearance Weights Guass)	set_mod	els_components() (in module menpont.cnecks),
Tun()	method) 282	cwion	
run()	(mennofit sdm Parametric Appearance Weights Newtor	set_targ	et() (menpont.modelinstance.GlobalPDM
Tun()	method) 280		method), 334
run()	(menpofit sdm ParametricShapeGaussNewton	set_targ	et() (menpolit.modelinstance.GlobalSimilarityModel
iun()	method) 269		method), 329
run()	(mennofit sdm ParametricShaneNewton method)	set_targ	et() (menpofit.modelinstance.Modelinstance
run()	268		$\frac{1}{2} \frac{1}{2} \frac{1}$
mm	(mennofit sdm Parametric Shana ODD Dagrassion	set_targ	et() (menpofit.modelinstance.OrthoPDM
Tun()	(menpoint.sum.i arametricshapeor r Kegression		method), 530

set target() (menpofit.modelinstance.PDM method), 331 shapes (menpofit.result.MultiScaleParametricIterativeResult set target() (menpofit.transform.DifferentiableAlignmentAffine attribute), 411 method), 436 shapes (menpofit.result.NonParametricIterativeResult atset target() (menpofit.transform.DifferentiableAlignmentSimilarity tribute), 359 method), 431 (menpofit.result.ParametricIterativeResult shapes atset target() (menpofit.transform.DifferentiablePiecewiseAffine tribute), 376 method), 439 shapes (menpofit.unified aam clm.result.UnifiedAAMCLMAlgorithmResu set target() (menpofit.transform.DifferentiableThinPlateSplines attribute), 202 method), 442 shapes (menpofit.unified aam clm.result.UnifiedAAMCLMResult set_target() (menpofit.transform.LinearOrthoMDTransform attribute), 185 method), 417 similarity_2d_instance_model() (in module men-(menpofit.transform.OrthoMDTransform pofit.modelinstance), 328 set_target() method), 414 SimultaneousForwardCompositional (class in menpofit.aam), 39 shape_instance() (menpofit.clm.CLM method), 149 shape_instance() (men-SimultaneousInverseCompositional (class in menpofit.unified_aam_clm.base.UnifiedAAMCLM pofit.aam), 40 method), 161 source (menpofit.transform.DifferentiableAlignmentAffine attribute), 437 shape_parameters (mensource (menpofit.transform.DifferentiableAlignmentSimilarity pofit.aam.result.AAMAlgorithmResult atattribute), 432 tribute). 87 shape_parameters (menpofit.aam.result.AAMResult atsource (menpofit.transform.DifferentiablePiecewiseAffine tribute), 70 attribute), 440 source (menpofit.transform.DifferentiableThinPlateSplines shape_parameters (menpofit.aps.result.APSAlgorithmResult attribute), attribute), 443 sparse target (menpofit.transform.LinearOrthoMDTransform 131 shape_parameters (menpofit.aps.result.APSResult atattribute), 417 tribute), 114 spatial_filter_images (menshape_parameters (menpofit.clm.CorrelationFilterExpertEnsemble pofit.lk.result.LucasKanadeAlgorithmResult attribute), 157 attribute), 251 SSD (class in menpofit.lk), 211 statistics_table() (in module menpofit.visualize), 447 shape_parameters (menpofit.result.MultiScaleParametricIterativeResult steepest_descent_images() (menpofit.lk.ECC method), attribute), 411 214 shape_parameters (mensteepest_descent_images() (menpofit.lk.FourierSSD pofit.result.ParametricIterativeResult attribute), method), 213 376 steepest descent images() (menshape parameters (menpofit.lk.GradientCorrelation method), 217 pofit.unified_aam_clm.result.UnifiedAAMCLMAkgerithtnResultnt_images() (menpofit.lk.GradientImages attribute), 202 method), 216 shape_parameters steepest_descent_images() (menpofit.lk.SSD method), (menpofit.unified aam clm.result.UnifiedAAMCLMResult 212 attribute), 185 steepest descent update() (menpofit.lk.ECC method), (menpofit.aam.result.AAMAlgorithmResult at-215 shapes tribute), 87 steepest_descent_update() (menpofit.lk.FourierSSD shapes (menpofit.aam.result.AAMResult attribute), 70 method), 213 shapes (menpofit.aps.result.APSAlgorithmResult atsteepest_descent_update() (mentribute), 131 pofit.lk.GradientCorrelation method), 218 shapes (menpofit.aps.result.APSResult attribute), 114 steepest_descent_update() (menpofit.lk.GradientImages shapes (menpofit.lk.result.LucasKanadeAlgorithmResult method), 216 attribute), 252 steepest_descent_update() (menpofit.lk.SSD method), shapes (menpofit.lk.result.LucasKanadeResult attribute), 212235 SupervisedDescentAAMFitter (class in menpofit.aam), shapes (menpofit.result.MultiScaleNonParametricIterativeResult 31 attribute), 393 SupervisedDescentFitter (class in menpofit.sdm), 252

Т	method), 241
target (menpofit.modelinstance.GlobalPDM attribute), 334	to_result() (menpofit.lk.result.LucasKanadeResult method), 224
target (menpofit.modelinstance.GlobalSimilarityModel attribute), 330	to_result() (menpofit.result.MultiScaleNonParametricIterativeResult method), 383
target (menpofit.modelinstance.ModelInstance attribute), 328	to_result() (menpofit.result.MultiScaleParametricIterativeResult method), 400
target (menpofit.modelinstance.OrthoPDM attribute), 337	to_result() (menpofit.result.NonParametricIterativeResult method), 349
target (menpolit.inodefinistance.i Diff attribute), 552 target (menpolit.transform.DifferentiableAlignmentAffine attribute), 437	to_result() (menpofit.result.ParametricIterativeResult method), 366
target (menpofit.transform.DifferentiableAlignmentSimilar attribute), 432	ito_result() (menpofit.unified_aam_clm.result.UnifiedAAMCLMAlgorithmI method), 192
target (menpofit.transform.DifferentiablePiecewiseAffine attribute), 440	to_result() (menpofit.unified_aam_clm.result.UnifiedAAMCLMResult method), 174
target (menpofit.transform.DifferentiableThinPlateSplines attribute), 443	train() (menpofit.aam.AppearanceWeightsGaussNewton method), 45
target (menpofit.transform.LinearOrthoMDTransform at- tribute), 417	train() (menpofit.aam.AppearanceWeightsNewton method), 44
target (menpofit.transform.OrthoMDTransform attribute), 414	train() (menpofit.aam.MeanTemplateGaussNewton method), 49
template (menpofit.aam.AlternatingForwardCompositional attribute), 35	train() (menpofit.aam.MeanTemplateNewton method), 47 train() (menpofit.aam.ProjectOutGaussNewton method),
template (menpofit.aam.AlternatingInverseCompositional attribute), 36	52 train() (menpofit.aam.ProjectOutNewton method), 50
template (menpofit.aam.ModifiedAlternatingForwardComp attribute), 36	method), 158
template (menpofit.aam.ModifiedAlternatingInverseCompo attribute), 37	train() (menpofit.math.IIRLRegression method), 322 train() (menpofit.math.IRLRegression method), 321
template (menpofit.aam.ProjectOutForwardCompositional attribute), 38	train() (menpofit.math.OPPRegression method), 324 train() (menpofit.math.OptimalLinearRegression
template (menpofit.aam.ProjectOutInverseCompositional attribute), 39	method), 323 train() (menpofit.math.PCRRegression method), 322
template (menpofit.aam.SimultaneousForwardComposition attribute), 40	natrain() (menpofit.sdm.FullyParametricMeanTemplateNewton method), 287
template (menpofit.aam.SimultaneousInverseCompositiona attribute), 41	al train() (menpofit.sdm.FullyParametricProjectOutGaussNewton method), 285
template (menpofit.aam.WibergForwardCompositional attribute), 42	train() (menpofit.sdm.FullyParametricProjectOutNewton method), 284
template (menpofit.aam.WibergInverseCompositional at- tribute), 42	train() (menpofit.sdm.FullyParametricProjectOutOPP method), 290
template (menpofit.aps.Forward attribute), 97 template (menpofit.aps.Inverse attribute), 96	train() (menpofit.sdm.FullyParametricWeightsNewton method), 289
template (menpointapointverse attribute), 75 147	train() (menpofit.sdm.NonParametricGaussNewton method), 262
template (menpofit.atm.InverseCompositional attribute), 147	train() (menpofit.sdm.NonParametricNewton method), 261
to_result() (menpofit.aam.result.AAMAlgorithmResult method), 77	train() (menpofit.sdm.NonParametricOPPRegression method), 267
to_result() (menpofit.aam.result.AAMResult method), 59	train() (menpofit.sdm.NonParametricOptimalRegression method), 265
method), 121	train() (menpofit.sdm.NonParametricPCRRegression method) 264
to_result() (menpofit.aps.result.APSResult method), 104 to_result() (menpofit.lk.result.LucasKanadeAlgorithmResu	altrain() (menpofit.sdm.ParametricAppearanceMeanTemplateGuassNewton

method) 200	transform	(mannaft atm ForwardCompositional	at
melnou), 280	Newton	tribute) 147	at-
method) 278	transform	(manpafit atm Inverse Compositional attribut	ta)
train() (mennofit sdm Parametric AppearanceProjectOutGus	seNewton		(C),
method) 277	translatio	n component (m	en-
train() (mennofit sdm Parametric AppearanceProjectOutNey	vton	nofit transform Differentiable Affine attribut	te)
method) 276	vion	422	(c),
train() (mennofit sdm Parametric Appearance Weights Guass	Newnsdatio	n component (m	en-
method). 282	i thuistiitio	pofit transform Differentiable Alignment Affi	ne
train() (menpofit.sdm.ParametricAppearanceWeightsNewto	n	attribute), 437	
method), 281	translatio	n component (me	en-
train() (menpofit.sdm.ParametricShapeGaussNewton		pofit.transform.DifferentiableAlignmentSimi	ilarity
method), 270		attribute), 432	•
train() (menpofit.sdm.ParametricShapeNewton method),	translatio	n_component (me	en-
268		pofit.transform.DifferentiableSimilarity	at-
train() (menpofit.sdm.ParametricShapeOPPRegression		tribute), 427	
method), 274	trilist (m	enpofit.transform.DifferentiablePiecewiseAff	ine
train() (menpofit.sdm.ParametricShapeOptimalRegression method), 273		attribute), 440	
train() (menpofit.sdm.ParametricShapePCRRegression	U		
method), 271	unified a	am clm (mo	en-
transform (menpofit.aam.AlternatingForwardCompositiona	1	pofit.unified aam clm.UnifiedAAMCLMFit	ter
attribute), 35		attribute), 166	
transform (menpofit.aam. Alternating Inverse Compositional	UnifiedA	AMCLM (class in me	en-
attribute), 36		pofit.unified_aam_clm.base), 159	
transform (menpofit.aam.AppearanceWeightsGaussNewton	UnifiedA	AMCLMAlgorithmResult (class in me	en-
attribute), 46		pofit.unified_aam_clm.result), 185	
transform (menpofit.aam.AppearanceWeightsNewton at-	UnifiedA	AMCLMFitter (class in me	en-
tribute), 44		pofit.unified_aam_clm), 163	
transform (menpofit.aam.MeanTemplateGaussNewton at-	UnifiedA	AMCLMResult (class in me	en-
tribute), 49		pofit.unified_aam_clm.result), 168	
transform (menpolit.aam.MeanTemplateNewton at-	V		
tribute), 47	V		
attribute), 36	Postuonai	(menpofit.aam.result.AAMAlgorithmRes	sult
transform (menpofit.aam.ModifiedAlternatingInverseComp	ositional	enpofit aam result AAMResult method) 59	
attribute), 37	view() (II	(menpofit aps result APSAlgorithmRes	sult
$transform \ (menpofit.aam. Project OutForward Compositional Composition and Compositin and Compositin and Composition and Composition and Co$	view()	method) 121	
attribute), 38	view() (m	henpofit.aps.result.APSResult method), 104	
transform (menpofit.aam.ProjectOutGaussNewton	view() (1	nenpofit.lk.result.LucasKanadeAlgorithmRes	sult
attribute), 52		method), 242	
transform (menpofit.aam.ProjectOutInverseCompositional attribute), 39	view() (r	nenpofit.lk.result.LucasKanadeResult metho	d),
transform (menpofit.aam.ProjectOutNewton attribute), 51	view() (m	ennofit result MultiScaleNonParametricIterat	iveResult
$transform \ (menpofit.aam. Simultaneous Forward Composition) \ (menpofit.aam. Simultaneous Forward Composi$	nal	method). 383	il voi cosult
attribute), 40	view() (m	enpofit.result.MultiScaleParametricIterativeR	Result
transform (menpofit.aam.SimultaneousInverseComposition	al	method), 400	
attribute), 41	view()	(menpofit.result.NonParametricIterativeRes	sult
transform (menpofit.aam.WibergForwardCompositional	~	method), 350	
attribute), 42	view()	(menpofit.result.ParametricIterativeRes	sult
transform (menpofit.aam.WibergInverseCompositional		method), 366	
attribute), 42	view() (m	nenpofit.result.Result method), 338	
transform (menpolit.aps.ForWard attribute), 9/	view() (m	enpofit.unified_aam_clm.result.UnifiedAAM	CLMAlgorithmResu
transform (menpoint.aps.inverse attribute), 90		method), 192	

view() (menpofit.unified_aam_clm.result.UnifiedAAMCL2 method), 175	MResultterations() (men- pofit.lk.result.LucasKanadeAlgorithmResult
view_aam_widget() (menpofit.aam.base.AAM method),	method), 246
view_aam_widget() (menpofit.aam.MaskedAAM	method), 229
method), 17	view_iterations() (men-
view_aam_widget() (menpofit.aam.PatchAAM method), 27	pofit.result.MultiScaleNonParametricIterativeResult method), 388
view_aam_widget() (men-	view_iterations() (men-
pofit.unified_aam_clm.base.UnifiedAAMCLM method), 161	pofit.result.MultiScaleParametricIterativeResult method), 405
view_appearance_graph_widget() (men-	view_iterations() (men-
polit.aps.GenerativeAPS method), 90	point result non parametric nerative Result
view_appearance_models_widget() (men-	method), 554
polit.aam.base.AAM method), 14	view_iterations() (men-
view_appearance_models_widget() (men-	pont.result.ParametriciterativeResult method),
pofit.aam.MaskedAAM method), 18	3/1
view_appearance_models_widget() (men-	view_iterations() (men-
pofit.aam.PatchAAM method), 27	poht.unified_aam_clm.result.UnifiedAAMCLMAlgorithmResult
view_appearance_models_widget() (men-	method), 197
pofit.unified_aam_clm.base.UnifiedAAMCLM	view_iterations() (men-
method), 162	pofit.unified_aam_clm.result.UnifiedAAMCLMResult
view_atm_widget() (menpofit.atm.base.ATM method),	method), 179
133	view_shape_graph_widget() (men-
view_atm_widget() (menpoht.atm.MaskedATM method),	pofit.aps.GenerativeAPS method), 92
136	view_shape_models_widget() (menpofit.aam.base.AAM
view_atm_widget() (menpofit.atm.PatchATM method),	method), 14
143	view_shape_models_widget() (men-
view_clm_widget() (menpofit.clm.CLM method), 150	pofit.aam.LinearAAM method), 21
view_clm_widget() (men-	view_shape_models_widget() (men-
pofit.unified_aam_clm.base.UnifiedAAMCLM method), 162	pofit.aam.LinearMaskedAAM method), 24
view_deformation_graph_widget() (men-	view_shape_models_widget() (men-
pofit.aps.GenerativeAPS method), 90	pofit.aam.MaskedAAM method), 18
view_deformation_model() (men- pofit.aps.GenerativeAPS method), 90	view_shape_models_widget() (menpofit.aam.PatchAAM method), 28
view_expert_ensemble_widget() (menpofit.clm.CLM	view_shape_models_widget() (men-
method), 150	pofit.aps.GenerativeAPS method), 92
view_expert_ensemble_widget() (men-	view_shape_models_widget() (menpofit.atm.base.ATM
pofit.unified_aam_clm.base.UnifiedAAMCLM	method), 134
method), 163	view_shape_models_widget() (menpofit.atm.LinearATM
view_frequency_filter_images_widget() (men-	method), 139
pofit.clm.CorrelationFilterExpertEnsemble	view_shape_models_widget() (men-
method), 156	pofit.atm.LinearMaskedATM method), 141
view_iterations() (men-	view_shape_models_widget() (men-
pofit.aam.result.AAMAlgorithmResult	pofit.atm.MaskedATM method), 136
method), 82	view_shape_models_widget() (menpofit.atm.PatchATM
view_iterations() (menpofit.aam.result.AAMResult	method), 143
method), 64	view_shape_models_widget() (menpofit.clm.CLM
view_iterations() (men-	method), 150
pofit.aps.result.APSAlgorithmResult method),	view_shape_models_widget() (men-
126	pofit.unified_aam_clm.base.UnifiedAAMCLM
view_iterations() (menpofit.aps.result.APSResult	method), 163
method), 109	view_spatial_filter_images_widget() (men-

pofit.clm.CorrelationFilterExpertEnsemble method) 156	weights (menpofit.modelinstance.GlobalSimilarityModel attribute) 330
view_widget() (menpofit.aam.result.AAMAlgorithmResult method), 86	weights (menpofit.modelinstance.ModelInstance at- tribute), 328
view_widget() (menpofit.aam.result.AAMResult method), 69	weights (menpofit.modelinstance.OrthoPDM attribute), 337
view_widget() (menpofit.aps.result.APSAlgorithmResult method), 130	weights (menpofit.modelinstance.PDM attribute), 332 weights (menpofit.transform.LinearOrthoMDTransform
view_widget() (menpofit.aps.result.APSResult method), 113	attribute), 418 WibergForwardCompositional (class in menpofit.aam),
view_widget() (menpofit.lk.result.LucasKanadeAlgorithmF	Result 41
method), 251	WibergInverseCompositional (class in menpofit.aam), 42
view_widget() (menpofit.lk.result.LucasKanadeResult method), 234	
view_widget() (menpofit.result.MultiScaleNonParametricIt method), 393	erativeResult
view_widget() (menpofit.result.MultiScaleParametricIterati method), 410	veResult
view_widget() (menpofit.result.NonParametricIterativeResumethod), 359	ılt
view_widget() (menpofit.result.ParametricIterativeResult method), 376	
view_widget() (menpofit.result.Result method), 342	
view_widget() (menpofit.unified_aam_clm.result.UnifiedA. method), 201	AMCLMAlgorithmResult
view_widget() (menpofit.unified_aam_clm.result.UnifiedA. method), 184	AMCLMResult
W	
warn images() (in module mennofit builder) 294	

warp_iniages() (in module menpone.ounder), 291
warped_images() (men-
pofit.aam.LucasKanadeAAMFitter method),
30
warped_images() (men-
pofit.aam.SupervisedDescentAAMFitter
method), 34
warped_images() (menpofit.aps.GaussNewtonAPSFitter
method), 95
warped_images() (menpofit.atm.LucasKanadeATMFitter
method), 145
<pre>warped_images() (menpofit.lk.ForwardAdditive method),</pre>
208
warped_images() (menpofit.lk.ForwardCompositional
method), 210
warped_images() (menpofit.lk.InverseCompositional
method), 211
warped_images() (menpofit.lk.LucasKanadeFitter
method), 207
warped_images() (men-
pofit.unified aam clm.UnifiedAAMCLMFitter
method). 165
weights (menpofit.modelinstance.GlobalPDM attribute).
334